TDP-Reasoner: Timing-Dependent Plasticity Along the Recursion

Anonymous Author(s)
Affiliation
email

Abstract

Small recursive models trained from scratch are the strongest non-LLM approach to puzzle benchmarks such as Sudoku-Extreme and ARC-AGI. These models, HRM and TRM among them, re-apply a Transformer block many times. Seen as a modern Hopfield network, each step's attention is a Hebbian memory of the current state, so recursion reinforces the model's current answer, and accuracy falls once it runs past its training horizon. We propose TDP-Reasoner (timing-dependent plasticity reasoner), which keeps a fast-weight memory along the recursion itself: keys and values from different steps are paired under a learned two-sided timing window, borrowed from spike-timing-dependent plasticity, so the memory tracks how the state moves rather than where it is. Demonstrations of a task reach the query only through a per-task linear rule fitted in context, so unseen tasks need no retraining. Trained for 256 recursion blocks and run for 10,000, it raises held-out Sudoku-Extreme accuracy from 59.8% to 82.0% and never loses a solved puzzle. On unseen ARC-AGI-1 tasks with small grids it matches the public TRM checkpoint (43.2% vs. 45.5%) after about 3% of its training; at full scale it reaches 18.8% pass@2 on ARC-AGI-1 (TRM: 41.8% under the same evaluation) and 0% on ARC-AGI-2.

1 Introduction

[To be written.]

2 Related work

[To be written.]

3 TDP-Reasoner

Block. One block with shared weights is applied at recursion steps $n = 1, 2, \ldots$. Each head reads

$$\text{read}_n = \left(\sum_\tau v_{n,\tau} \tilde{k}_{n,\tau}^\top + W_n \right) \tilde{q}_n \tag{1}$$

with unit-length, rotary-encoded queries and keys (QK-norm); the attention and a SwiGLU feed-forward layer each add a residual followed by a parameter-free RMSNorm. Without W_n this is recurrent linear attention over the tokens τ, which keeps nothing across steps but the state.

Memory across the recursion. W_n is a fast weight carried across steps. Each token keeps decaying traces of its keys and values, $\bar{k}_r \leftarrow z_r \bar{k}_r + \gamma_r \tilde{k}$ and $\bar{v}_r \leftarrow z_r \bar{v}_r + \gamma_r v$, over $R = 4$ bands with learned complex poles $z_r = \exp(-e^{\nu_r} + i\theta_r)$ and $\gamma_r = \sqrt{1-|z_r|^2}$, which keeps them bounded. Each step pairs the new value with the key traces and the new key with the earlier value traces,

$$W_n = (1-\eta)\, W_{n-1} + \eta \sum_{\tau} \sum_{r} \mathrm{Re}\big(a_r\, v_n \bar{k}_{r,n}^{\top} + b_r\, z_r \bar{v}_{r,n-1}\, \tilde{k}_n^{\top}\big), \tag{2}$$

with learned complex a_r, b_r and rate $\eta \le 1/8$. Unrolled, exactly,

$$W_n = \sum_{\tau} \sum_{s,t \le n} \eta (1-\eta)^{n-\max(s,t)}\, L(t-s)\; v_{t,\tau}\, \tilde{k}_{s,\tau}^{\top}, \qquad L(\Delta) = \begin{cases} \sum_r \gamma_r \mathrm{Re}(a_r z_r^{\Delta}) & \Delta \ge 0, \\ \sum_r \gamma_r \mathrm{Re}(b_r z_r^{|\Delta|}) & \Delta < 0. \end{cases} \tag{3}$$

With the key as presynaptic and the value as postsynaptic activity, this is the pair-based STDP integral: every pair of events is added once, when the later one arrives, weighted by a window of their lag whose two sides separate key-first from value-first pairs. The exponential STDP window is the case $R = 1$, $\theta = 0$, $a > 0$, $b < 0$. No spikes are needed: in a recursion like this, spiking itself carries no information of substance, and the window uses only the order and lag of two events, which the step index supplies. At a fixed point all pairs are equal, and W reduces to a Hebbian term scaled by the area of the window. *[Figure: windows learned on Sudoku.]*

This is the Sudoku model: recurrent linear attention with QK-norm, plus traces and a timing window.

Reading demonstrations. For ARC, each example is a lane processed on its own, with its output grid hidden; the lanes of a task form a group. A rule head reads the demonstrations through one per-task linear map from learned cell features $\phi = W_\phi h / \|W_\phi h\|$ to colours y,

$$\Theta = \arg\min_{\Theta} \sum_{o \in \text{demos}} \big\| y(o) - \Theta\, \phi(o) \big\|^2 + \lambda \|\Theta\|_1, \qquad r(o) = \Theta\, \phi(o), \tag{4}$$

and feeds r into the next block on the output canvas. Prior knowledge about ARC lives only in the slow features ϕ. The rule is chosen by a fixed principle that does not depend on the task: the sparsest linear map that fits the demonstrations. The task itself is held only in the fast Θ. No task is stored in the weights, so an unseen task needs no puzzle embedding and no test-time training. Queries never enter (4), and each demonstration is fitted on the others. Each block takes one proximal-gradient step on (4), so the rule is refined along the recursion together with the state.

Training and inference. A segment runs a fixed number of blocks and backpropagates through the last few. State, traces, W and Θ carry over to the next segment without gradient, with a stablemax cross-entropy loss after every segment (TRM's deep supervision, without halting). At inference each task runs in several dihedral and colour-permuted versions whose answers are voted; ties are broken by how well each version predicts its own demonstrations.

4 Experiments

[To be written.]

5 Limitations and future work

[To be written.]