

## 比较

```
1 1、创建文件到本地
2 $ echo aaaa >test.txt
3 $ echo bbbb > test.txt
4 2、添加在缓存区
5 $ git add test.txt
6 3、添加到本地库
7 $ git commit -m "添加文件到本地库" test.txt
8 4、修改文件
9 echo cccc >> test.txt
10 5、比对工作区和暂存区的文件 git idiff 文件；比较单个文件的差异
11 $ git diff test.txt
12     warning: LF will be replaced by CRLF in test.txt.
13     The file will have its original line endings in your working directory
14     diff --git a/test.txt b/test.txt
15     index be4e668..9235b42 100644
16     --- a/test.txt
17     +++ b/test.txt
18     @@ -1,2 +1,3 @@
19     aaaaa
20     bbbbb
21     +ccccc
22 6、多个文件的比较,比较工作区和暂存区中的所有文件差异
23 $ git diff
24     warning: LF will be replaced by CRLF in test.txt.
25     The file will have its original line endings in your working directory
26     warning: LF will be replaced by CRLF in test1.txt.
27     The file will have its original line endings in your working directory
28     diff --git a/test.txt b/test.txt
29     index be4e668..9235b42 100644
30     --- a/test.txt
31     +++ b/test.txt
32     @@ -1,2 +1,3 @@
33     aaaaa
34     bbbbb
35     +ccccc
36     diff --git a/test1.txt b/test1.txt
37     index 8baef1b..5f5521f 100644
```

```
38      --- a/test1.txt
39      +++ b/test1.txt
40      @@ -1 +1,2 @@
41          abc
42      +def
43
```

## HEAD比较

## 索引比较

```
1      $ git diff 8988efb test1.txt
2      diff --git a/test1.txt b/test1.txt
3      index 8baef1b..f5bc74f 100644
4      --- a/test1.txt
5      +++ b/test1.txt
6      @@ -1 +1,3 @@
7          abc
8      +def
9      +ghi
10     \ No newline at end of file
11
```