


I implemented the topology below:



A is localhost:8000

B is localhost:8001

C is localhost:8002

D is localhost:8003

E is localhost:8004

Here are the converging screenshots:

A

`./jrip34 -p 8000 localhost:8001:10 localhost:8002:4 localhost:8003:8`

```

xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jrip34 -p 8000 localhost:8001:10 localhost:8002:4
localhost:8003:8
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001      10      127.0.0.1:8001
127.0.0.1:8003      8       127.0.0.1:8003
127.0.0.1:8002      4       127.0.0.1:8002
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001      10      127.0.0.1:8001
127.0.0.1:8003      8       127.0.0.1:8003
127.0.0.1:8002      4       127.0.0.1:8002
127.0.0.1:8004     12       127.0.0.1:8001
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001      10      127.0.0.1:8001
127.0.0.1:8003      8       127.0.0.1:8003
127.0.0.1:8002      4       127.0.0.1:8002
127.0.0.1:8004     12       127.0.0.1:8001
  
```

B

`./jrip34 -p 8001 localhost:8000:6 localhost:8003:2 localhost:8004:2`

```

xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jrip34 -p 8001 localhost:8000:6 localhost:8003:2
localhost:8004:2
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8000      6       127.0.0.1:8000
127.0.0.1:8003      2       127.0.0.1:8003
127.0.0.1:8002     10       127.0.0.1:8000
127.0.0.1:8004      2       127.0.0.1:8004
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8000      6       127.0.0.1:8000
127.0.0.1:8003      2       127.0.0.1:8003
127.0.0.1:8002     10       127.0.0.1:8000
127.0.0.1:8004      2       127.0.0.1:8004
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8000      6       127.0.0.1:8000
127.0.0.1:8003      2       127.0.0.1:8003
127.0.0.1:8002     10       127.0.0.1:8000
127.0.0.1:8004      2       127.0.0.1:8004
  
```

C

./jrip34 -p 8002 localhost:8000:4

```
xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jrip34 -p 8002 localhost:8000:4
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001        14      127.0.0.1:8000
127.0.0.1:8000         4      127.0.0.1:8000
127.0.0.1:8003        12      127.0.0.1:8000
127.0.0.1:8004        19      127.0.0.1:8000
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001        14      127.0.0.1:8000
127.0.0.1:8000         4      127.0.0.1:8000
127.0.0.1:8003        12      127.0.0.1:8000
127.0.0.1:8004        16      127.0.0.1:8000
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001        14      127.0.0.1:8000
127.0.0.1:8000         4      127.0.0.1:8000
127.0.0.1:8003        12      127.0.0.1:8000
127.0.0.1:8004        16      127.0.0.1:8000
```

D

./jrip34 -p 8003 localhost:8000:5 localhost:8001:3 localhost:8004:7

```
xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jrip34 -p 8003 localhost:8000:5 localhost:8001:3
localhost:8004:7
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001         3      127.0.0.1:8001
127.0.0.1:8000         5      127.0.0.1:8000
127.0.0.1:8002         9      127.0.0.1:8000
127.0.0.1:8004         5      127.0.0.1:8001
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001         3      127.0.0.1:8001
127.0.0.1:8000         5      127.0.0.1:8000
127.0.0.1:8002         9      127.0.0.1:8000
127.0.0.1:8004         5      127.0.0.1:8001
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001         3      127.0.0.1:8001
127.0.0.1:8000         5      127.0.0.1:8000
127.0.0.1:8002         9      127.0.0.1:8000
127.0.0.1:8004         5      127.0.0.1:8001
```

E

./jrip34 -p 8004 localhost:8001:1 localhost:8003:5

```
xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jrip34 -p 8004 localhost:8001:1 localhost:8003:5
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001         1      127.0.0.1:8001
127.0.0.1:8000         7      127.0.0.1:8001
127.0.0.1:8003         3      127.0.0.1:8001
127.0.0.1:8002        11      127.0.0.1:8001
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001         1      127.0.0.1:8001
127.0.0.1:8000         7      127.0.0.1:8001
127.0.0.1:8003         3      127.0.0.1:8001
127.0.0.1:8002        11      127.0.0.1:8001
[IP/PORT DESTINATION] [DISTANCE] [NEXT_HOP]
127.0.0.1:8001         1      127.0.0.1:8001
127.0.0.1:8000         7      127.0.0.1:8001
127.0.0.1:8003         3      127.0.0.1:8001
127.0.0.1:8002        11      127.0.0.1:8001
```

Traceroute is shown as below:

```
xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jtraceroute -p 7999 localhost:8000 localhost:8002
127.0.0.1:8000
127.0.0.1:8002
xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jtraceroute -p 7999 localhost:8000 localhost:8003
127.0.0.1:8000
127.0.0.1:8003
xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jtraceroute -p 7999 localhost:8000 localhost:8004
127.0.0.1:8000
127.0.0.1:8001
127.0.0.1:8004
xinwei@Xinweis-MacBook-Pro:~/Documents/GitHub/jrip/step3$ ./jtraceroute -p 7999 localhost:8001 localhost:8002
127.0.0.1:8001
127.0.0.1:8000
127.0.0.1:8002
```