创建连接

接口概述

创建SSE长连接，用于接收TrekAgent的实时推送消息（如思考过程、工具调用、文本输出等）。调用顺序第2步：建立SSE连接，channelId使用随机UUID。

前提条件

此接口为SSE流式接口，返回Content-Type为text/event-stream；channelId参数必填，需传入随机UUID。

接口调用地址

```
POST http://10.128.203.200:80/sfm-agent-studio/sfm-api-gateway/gateway/agent/auto/new/open/createNewChannel
```

入参描述

Header传参

字段	数据类型	是否必填	描述	示例
Authorization	String	是	APP_KEY	Bearer YOUR_APP_KEY
Content-Type	String	是	Content-Type	application/json

Body传参

字段	数据类型	是否必填	描述	示例
channelId	string	是	通道ID	4bcaa882-9c54-4b78-9057-54db58591b5b

出参描述

字段	数据类型	描述	示例
data	string	SSE数据内容	{"RESULT": "Connection successful"}

请求示例

curl命令示例

```
curl -X 'POST' http://10.128.203.200:80/sfm-agent-studio/sfm-api-gateway/gateway/agent/auto/new/open/createNewChannel \
-H 'Authorization: Bearer YOUR_APP_KEY' \
-H 'Content-Type: application/json' \
-H 'Accept: text/event-stream' \
-d '{
"channelId": "4bcaa882-9c54-4b78-9057-54db58591b5b"
}'
```

响应示例

SSE流式输出

```
data: {"RESULT": "Connection successful"}

data: {"action":"思考","actionParam":{"type":"thought","position":"pop","content":"..."}}

data: {"RESULT": ""}
```

状态码说明

Http状态返回码	错误描述	错误释义
401	GATEWAY APP_KEY MISSING!	网关必填参数缺失
401	GATEWAY APP_KEY WRONG!	鉴权失败,无效 APP_KEY
401	GATEWAY APP_KEY ALREADY EXPIRED!	鉴权失败,APP_KEY 已过期
401	GATEWAY ROLE NOT MATCH!	鉴权失败,当前 APP_KEY 归属用户对应的角色不匹配
401	GATEWAY ROLE HAS EXPIRED!	鉴权失败,当前 APP_KEY 归属用户对应的角色已过期
403	GATEWAY APP_PATH NOT FOUND!	无效的服务调用路径
403	GATEWAY APP_PATH NOT REGISTER!	当前服务调用路径未注册
429	GATEWAY LIMIT !	服务触发限流,请稍后再试
429	GATEWAY LIMIT CURRENT CALL TYPE !	服务触发限流,请稍后再试
403	GATEWAY HEADER PARAMETER MISSING!	业务所需必填参数缺失
403	GATEWAY PARAMETER WORKSPACE NO MATCH!	传递的工作空间编码与APP_KEY归属用户关联的工作空间编码不匹配
401	GATEWAY AUTH_TYPE WRONG!	鉴权失败,不支持的鉴权方式
401	GATEWAY AUTH_USER NOT MATCH WRONG!	鉴权失败,AK用户信息不匹配
401	GATEWAY AUTH_USER_ROLE WRONG!	鉴权失败,用户角色不匹配
404	GATEWAY ROUTE URL NOT FOUND!	无效的目标服务地址
401	GATEWAY LIMIT !	服务链接已达上限,请稍后再试
500	TARGET_SERVICE_ERROR_CONNECTION_REFUSE_EXCEPTION	目标服务拒绝连接
500	TARGET_SERVICE_ERROR_NO_RESPONSE_EXCEPTION	目标服务无响应