DNS (Domain Name System) Client

User Guide

Express Logic, Inc.

858.613.6640
Toll Free 888.THREADX
FAX 858.521.4259

www.expresslogic.com

Contents

Chapter 1

Introduction to the NetX DNS Client

The DNS provides a distributed database that contains mapping between domain names and physical IP addresses. The database is referred to as *distributed* because there is no single entity on the Internet that contains the complete mapping. An entity that maintains a portion of the mapping is called a DNS Server. The Internet is composed of numerous DNS Servers, each of which contains a subset of the database. DNS Servers also respond to DNS Client requests for domain name mapping information, only if the server has the requested mapping.

The DNS Client protocol for NetX provides the application with services to request mapping information from one or more DNS Servers.

DNS Client Setup

In order to function properly, the DNS Client package requires that a NetX IP instance has already been created.

After creating the DNS Client, the application must add one or more DNS servers to the server list maintained by the DNS Client. To add DNS servers, the application uses the *nx_dns_server_add* service.

If the NX_DNS_IP_GATEWAY_SERVER option is enabled, and the IP instance gateway address is non zero, the IP instance gateway is automatically added as the primary DNS server. If DNS server information is not statically known, it may also be derived through the Dynamic Host Configuration Protocol (DHCP) for NetX. Please refer to the NetX DHCP User Guide for more information.

The DNS Client requires a packet pool for transmitting DNS messages. By default, the DNS Client creates this packet pool when the *nx_dns_create* service is called. The configuration options NX_DNS_PACKET_PAYLOAD and NX_DNS_PACKET_POOL_SIZE allow the application to determine the packet payload and packet pool size (e.g. number of packets) of this packet pool respectively. These options are described in section "Configuration Options" in Chapter Two.

An alternative to the DNS Client creating its own packet pool is for the application to create the packet pool and set it as the DNS Client's packet pool using the *nx_dns_packet_pool_set* service. To do so, the NX_DNS_CLIENT_USER_CREATE_PACKET_POOL option must be defined. This option also requires a previously created packet pool using *nx_packet_pool_create* as the packet pool pointer input to *nx_dns_packet_pool_set*. When the DNS Client instance is deleted, the application is responsible for deleting the DNS Client packet pool if NX_DNS_CLIENT_USER_CREATE_PACKET_POOL is enabled if it is no longer needed.

Note: For applications choosing to provide its own packet pool using the NX_DNS_CLIENT_USER_CREATE_PACKET_POOL option, the packet size needs to be able to hold the DNS maximum massage size (512 bytes) plus rooms for UDP header, IPv4 header, and the MAC header.

DNS Messages

The DNS has a very simple mechanism for obtaining mapping between host names and IP addresses. To obtain a mapping, the DNS Client prepares a DNS query message containing the name or the IP address that needs to be resolved. The message is then sent to the first DNS server in the server list. If the server has such a mapping, it replies to the DNS Client using a DNS response message that contains the requested mapping information. If the server does not respond, the DNS Client queries the next server on its list until all its DNS servers have been queried. If no response from all its DNS servers is received, the DNS Client has retry logic to retransmit the DNS message. On resending a DNS query, the retransmission timeout is doubled. This process continues until the maximum transmission timeout (defined as NX_DNS_MAX_RETRANS_TIMEOUT in *nxd_dns.h*) is reached or until a successful response is received from that server is obtained.

NetX DNS Client can perform IPv4 address lookups (type A) by calling *nx_dns_host_by_name_get or nx_dns_ipv4_address_by_name_get*. The DNS Client can perform reverse lookups of IP addresses (type PTR queries) to obtain web host names using *nx_dns_host_by_address_get*.

DNS messaging utilizes the UDP protocol to send requests and field responses.   A DNS Server listens on port number 53 for queries from clients. Therefore UDP services must be enabled in NetX using the ***nx_udp_enable*** service on a previously created IP instance (***nx_ip_create***).

At this point, the DNS Client is ready to accept requests from the application and send out DNS queries.

Extended DNS Resource Record Types

If NX_DNS_ENABLE_EXTENDED_RR_TYPES is enabled, NetX DNS Client also supports the following record type queries:

CNAME	contains the canonical name for an alias
TXT	contains a text string
NS	contains an authoritative name server
SOA	contains the start of a zone of authority
MX	used for mail exchange
SRV	contains information on the service offered by the domain

With the exception of CNAME and TXT record types, the application must supply a 4-byte aligned buffer to receive the DNS data record.

In NetX DNS Client, record data is stored in such a way to make most efficient use of buffer space.

For those queries whose record types have variable data length, such as NS records whose host names are of variable length, NetX DNS Client saves the data as follows. The buffer supplied in the DNS Client query is organized into an area of fixed length data and an area of unstructured memory. The top of the memory buffer is organized into 4-byte aligned record entries. Each record entry contains the IP address and a pointer to the variable length data for that IP address. The variable length data for each IP address are stored in the unstructured area memory starting at the end of the memory buffer. The variable length data for each successive record entry is saved in the next area memory adjacent to the previous record entries variable data. Hence, the variable data 'grows' towards the structured area of memory containing the record entries until there is insufficient memory to store another record entry and variable data.

This is shown in the figure below:

```
beginning of record
buffer memory

        ↓
        0                                              64 bits

entry 0  | XX.XX.XX.XX    Pointer to host name string  |
entry 1  | XX.XX.XX.XX    Pointer to host name string  |
entry 2  | XX.XX.XX.XX    Pointer to host name string  |
....
         | XX.XX.XX.XX    Pointer to host name string  |
entry n


         |                               host name n |
         | ....                          host name 2 |
         | host name 1                   hostname  0 |

                              end of record ↑
                              buffer memory
```

The example of the DNS domain name (NS) data storage is shown above.

NetX DNS Client queries using the record storage format return the number of records saved to the record buffer. This information enables the application to extract NS records from the record buffer.

An example of a DNS Client query that stores variable length DNS data using this record storage format is shown below:

```
UINT  _nx_dns_domain_name_server_get(NX_DNS *dns_ptr,
                    UCHAR *host_name, VOID *record_buffer,
                    UINT buffer_size, UINT *record_count,
                    ULONG wait_option)
```

More details are available in Chapter 3, "Description of DNS Client Services".

DNS Cache

If NX_DNS_CACHE_ENABLE is enabled, NetX DNS Client supports the DNS Cache feature. After creating the DNS Client, the application can call the API *nx_dns_cache_initialize()* to set the special DNS Cache. If enable DNS Cache feature, DNS Client will find the available answer from DNS Cache

before starts to send DNS query, if find the available answer, directly return the answer to application, otherwise DNS Client sends out query message to DNS server and waits for the reply. When DNS Client gets the response message and there is free cache available, DNS Client returns the answer to the application and also adds the answer as resource record into DNS cache.

Each answer a data structure *NX_DNS_RR* (Resource Record) in the cache. Strings (resource record name and data) in Records are variable length, therefore are not stored in the NX_DNS_RR structure. The Record contains pointers to the actual memory location where the strings are stored. The string table and the Records share the cache. Records are stored from the beginning of the cache, and grow towards the end of the cache. The string table starts from the end of the cache and grows towards the beginning of the cache. Each string in the string table has a length field and a counter field. When a string is added to the string table, if the same string is already present in the table, the counter value is incremented and no memory is allocated for the string. The cache is considered full if no more resource records or new strings can be added to the cache.

DNS Client Limitations

The DNS Client supports one DNS request at a time. Threads attempting to make another DNS request are temporarily blocked until the previous DNS request is complete.

The NetX DNS Client does not use data from authoritative answers to forward additional DNS queries to other DNS servers.

DNS RFCs

NetX DNS is compliant with the following RFCs:

RFC1034 DOMAIN NAMES - CONCEPTS AND FACILITIES
RFC1035 DOMAIN NAMES - IMPLEMENTATION AND SPECIFICATION
RFC1480 The US Domain
RFC 2782 A DNS RR for specifying the location of services (DNS SRV)

Chapter 2

Installation and Use of NetX DNS Client

This chapter contains a description of various issues related to installation, setup, and usage of the NetX DNS Client.

Product Distribution

NetX DNS Client is shipped on a single CD-ROM compatible disk. The package includes two source files and a PDF file that contains this document, as follows:

nx_dns.h	Header file for NetX DNS Client
nx_dns.c	C Source file for NetX DNS Client
nx_dns.pdf	PDF description of NetX DNS Client

DNS Client Installation

To use NetX DNS Client, copy the source code files *nx_dns.c* and *nx_dns.h* to the same directory where NetX is installed. For example, if NetX is installed in the directory "*\threadx\arm7\green*" then the *nx_dns.h* and *nx_dns.c* files should be copied into this directory.

Using the DNS Client

Using NetX DNS Client is easy. Basically, the application code must include *nx_dns.h* after it includes *tx_api.h* and *nx_api.h*, in order to use ThreadX and NetX, respectively. Once *nx_dns.h* is included, the application code is then able to make the DNS function calls specified later in this guide. The application must also add *nx_dns.c* to the build process. This file must be compiled in the same manner as other application files and its object form must be linked along with the files of the application. This is all that is required to use NetX DNS.

Note that since DNS utilizes NetX UDP services, UDP must be enabled with the *nx_udp_enable* call prior to using DNS.

Small Example System for DNS Client

In the example DNS application program provided in this section, *nx_dns.h* is included at line 6.   NX_DNS_CLIENT_USER_CREATE_PACKET_POOL, which allows the DNS Client application to create the packet pool for the DNS Client, is declared on lines 21-23. This packet pool is used for allocating packets for sending DNS messages. If NX_DNS_CLIENT_USER_CREATE_PACKET_POOL is defined, a packet pool is created in lines 71-91.   If this option is not enabled, the DNS Client creates its own packet pool as per the packet payload and pool size set by configuration parameters in *nx_dns.h* and described elsewhere in this chapter.

Another packet pool is created in lines 93-105 for the Client IP instance which is used for internal NetX operations. Next the IP instance is created using the *nx_ip_create* call in line 107-119.   It is possible for the IP task and the DNS Client to share the same packet pool, but since the DNS Client typically sends out larger messages than the control packets sent by the IP task, using separate packet pools makes more efficient use of memory.

ARP and UDP (which is used by IPv4 networks) are enabled in lines 122 and 134 respectively.

Note this demo uses the 'ram' driver declared on line 37 and used in the *nx_ip_create* call. This ram driver is distributed with the NetX source code. To actually run the DNS Client the application must supply an actual physical network driver to transmit and receive packets from the DNS server.

The Client thread entry function *thread_client_entry* is defined below the *tx_application_define* function. It initially relinquishes control to the system to allow the IP task thread to be initialized by the network driver.

It then creates the DNS Client on lines 176-187, initializes the cache on lines 189-200, and sets the packet pool previously created to the DNS Client instance on lines 202-217. It then adds an IPv4 DNS server on lines 220-229.

The remainder of the example program uses the DNS Client services to make DNS queries.   Host IP address lookups are performed on lines 240 and 262. The difference between these two services, *nx_dns_host_by_name_get* and *nx_dns_ipv4_address_by_name_get*, is that the former only saves one IP address, while the latter saves multiple addresses if DNS Server replied.

Reverse lookups (host name from IP address) are performed on lines 354 (*nx_dns_host_by_address_get*).

Two more services for DNS lookups, CNAME and TXT, are demonstrated on lines 375 and 420 respectively, to discover CNAME and TXT for the input domain name. NetX DNS Client as similar services for other record types, e.g. NS, MX, SRV and SOA. See Chapter 3 for detailed descriptions of all record type lookups available in NetX DNS Client.

When the DNS Client is deleted on line 594, using the *nx_dns_delete* service, the packet pool for the DNS Client is not deleted unless the DNS Client created its own packet pool. Otherwise, it is up to the application to delete the packet pool if it has no further use for it.

```
1 /* This is a small demo of DNS Client for the high-performance NetX TCP/IP stack.
*/
 2
 3 #include    "tx_api.h"
 4 #include    "nx_api.h"
 5 #include    "nx_udp.h"
 6 #include    "nx_dns.h"
 7
 8
 9 #define     DEMO_STACK_SIZE         4096
10
11 #define     NX_PACKET_PAYLOAD       1536
12 #define     NX_PACKET_POOL_SIZE     30 * NX_PACKET_PAYLOAD
13 #define     LOCAL_CACHE_SIZE        2048
14
15 /* Define the ThreadX and NetX object control blocks...  */
16
17 NX_DNS                  client_dns;
18 TX_THREAD               client_thread;
19 NX_IP                   client_ip;
20 NX_PACKET_POOL          main_pool;
21 #ifdef NX_DNS_CLIENT_USER_CREATE_PACKET_POOL
22 NX_PACKET_POOL          client_pool;
23 #endif
24 UCHAR                   local_cache[LOCAL_CACHE_SIZE];
25
26 UINT                    error_counter = 0;
27
28
29 #define CLIENT_ADDRESS       IP_ADDRESS(192,168,0,11)
30 #define DNS_SERVER_ADDRESS   IP_ADDRESS(192,168,0,1)
31
32 /* Define thread prototypes.  */
33
34 void    thread_client_entry(ULONG thread_input);
35
36 /***** Substitute your ethernet driver entry function here *********/
37 extern  VOID _nx_ram_network_driver(NX_IP_DRIVER *driver_req_ptr);
38
39
40 /* Define main entry point.  */
41
42 int main()
43 {
44
45     /* Enter the ThreadX kernel.  */
46     tx_kernel_enter();
47 }
48
49
50 /* Define what the initial system looks like.  */
51
52 void    tx_application_define(void *first_unused_memory)
53 {
54
55 CHAR    *pointer;
56 UINT    status;
57
58
59     /* Setup the working pointer.  */
60     pointer =  (CHAR *) first_unused_memory;
61
```

```
62      /* Create the main thread.  */
63      tx_thread_create(&client_thread, "Client thread", thread_client_entry, 0,
64              pointer, DEMO_STACK_SIZE, 4, 4, TX_NO_TIME_SLICE, TX_AUTO_START);
65
66      pointer =  pointer + DEMO_STACK_SIZE;
67
68      /* Initialize the NetX system.  */
69      nx_system_initialize();
70
71 #ifdef NX_DNS_CLIENT_USER_CREATE_PACKET_POOL
72
73      /* Create the packet pool for the DNS Client to send packets.
74
75          If the DNS Client is configured for letting the host application create
76          the DNS packet pool, (see NX_DNS_CLIENT_USER_CREATE_PACKET_POOL option),
see
77          nx_dns_create() for guidelines on packet payload size and pool size.
78          packet traffic for NetX processes.
79      */
80      status =  nx_packet_pool_create(&client_pool, "DNS Client Packet Pool",
NX_DNS_PACKET_PAYLOAD, pointer, NX_DNS_PACKET_POOL_SIZE);
81
82      pointer = pointer + NX_DNS_PACKET_POOL_SIZE;
83
84      /* Check for pool creation error.  */
85      if (status)
86      {
87
88          error_counter++;
89          return;
90      }
91 #endif
92
93      /* Create the packet pool which the IP task will use to send packets. Also
available to the host
94          application to send packet. */
95      status =  nx_packet_pool_create(&main_pool, "Main Packet Pool",
NX_PACKET_PAYLOAD, pointer, NX_PACKET_POOL_SIZE);
96
97      pointer = pointer + NX_PACKET_POOL_SIZE;
98
99      /* Check for pool creation error.  */
100     if (status)
101     {
102
103         error_counter++;
104         return;
105     }
106
107     /* Create an IP instance for the DNS Client.  */
108     status = nx_ip_create(&client_ip, "DNS Client IP Instance", CLIENT_ADDRESS,
0xFFFFFF00UL,
109                         &main_pool, _nx_ram_network_driver, pointer, 2048, 1);
110
111     pointer =  pointer + 2048;
112
113     /* Check for IP create errors.  */
114     if (status)
115     {
116
117         error_counter++;
118         return;
119     }
120
121     /* Enable ARP and supply ARP cache memory for the DNS Client IP.  */
122     status =  nx_arp_enable(&client_ip, (void *) pointer, 1024);
123     pointer = pointer + 1024;
124
125     /* Check for ARP enable errors.  */
126     if (status)
127     {
128
129         error_counter++;
130         return;
131     }
132
133     /* Enable UDP traffic because DNS is a UDP based protocol.  */
134     status =  nx_udp_enable(&client_ip);
135
136     /* Check for UDP enable errors.  */
137     if (status)
```

```
138       {
139
140           error_counter++;
141           return;
142       }
143 }
144
145 #define BUFFER_SIZE      200
146 #define RECORD_COUNT     10
147
148 /* Define the Client thread.  */
149
150 void    thread_client_entry(ULONG thread_input)
151 {
152
153 UCHAR             record_buffer[200];
154 UINT              record_count;
155 UINT              status;
156 ULONG             host_ip_address;
157 UINT              i;
158 ULONG             *ipv4_address_ptr[RECORD_COUNT];
159 #ifdef NX_DNS_ENABLE_EXTENDED_RR_TYPES
160 NX_DNS_NS_ENTRY
161                   *nx_dns_ns_entry_ptr[RECORD_COUNT];
162 NX_DNS_MX_ENTRY
163                   *nx_dns_mx_entry_ptr[RECORD_COUNT];
164 NX_DNS_SRV_ENTRY
165                   *nx_dns_srv_entry_ptr[RECORD_COUNT];
166 NX_DNS_SOA_ENTRY
167                   *nx_dns_soa_entry_ptr;
168 ULONG             host_address;
169 USHORT            host_port;
170 #endif
171
172     /* Give NetX IP task a chance to get initialized . */
173     tx_thread_sleep(100);
174
175
176     /* Create a DNS instance for the Client.  Note this function will create
177        the DNS Client packet pool for creating DNS message packets intended
178        for querying its DNS server. */
179     status =  nx_dns_create(&client_dns, &client_ip, (UCHAR *)"DNS Client");
180
181     /* Check for DNS create error.  */
182     if (status)
183     {
184
185         error_counter++;
186         return;
187     }
188
189 #ifdef NX_DNS_CACHE_ENABLE
190     /* Initialize the cache.  */
191     status = nx_dns_cache_initialize(&client_dns, local_cache, LOCAL_CACHE_SIZE);
192
193     /* Check for DNS cache error.  */
194     if (status)
195     {
196
197         error_counter++;
198         return;
199     }
200 #endif
201
202     /* Is the DNS client configured for the host application to create the pecket
pool? */
203 #ifdef NX_DNS_CLIENT_USER_CREATE_PACKET_POOL
204
205     /* Yes, use the packet pool created above which has appropriate payload size
206        for DNS messages. */
207      status = nx_dns_packet_pool_set(&client_dns, &client_pool);
208
209     /* Check for set DNS packet pool error.  */
210     if (status)
211     {
212
213         error_counter++;
214         return;
215     }
216
217 #endif /* NX_DNS_CLIENT_USER_CREATE_PACKET_POOL */
```

```
218
219
220      /* Add an IPv4 server address to the Client list. */
221      status = nx_dns_server_add(&client_dns, DNS_SERVER_ADDRESS);
222
223      /* Check for DNS add server error.  */
224      if (status)
225      {
226
227          error_counter++;
228          return;
229       }
230
231
232
233
234
/***************************************************************************/
235 /*                             Type A
*/
236 /*        Send A type DNS Query to its DNS server and get the IPv4 address.
*/
237
/***************************************************************************/
238
239      /* Look up an IPv4 address over IPv4. */
240      status = nx_dns_host_by_name_get(&client_dns, (UCHAR *)"www.my_example.com",
&host_ip_address, 400);
241
242      /* Check for DNS query error.  */
243      if (status != NX_SUCCESS)
244      {
245          error_counter++;
246      }
247
248      else
249      {
250
251          printf("--------------------------------------------------------\n");
252          printf("Test A: \n");
253          printf("IP address: %lu.%lu.%lu.%lu\n",
254          host_ip_address >> 24,
255          host_ip_address >> 16 & 0xFF,
256          host_ip_address >> 8 & 0xFF,
257          host_ip_address & 0xFF);
258      }
259
260
261      /* Look up IPv4 addresses to record multiple IPv4 addresses in record_buffer
and return the IPv4 address count.   */
262      status = nx_dns_ipv4_address_by_name_get(&client_dns, (UCHAR
*)"www.my_example.com", &record_buffer[0], BUFFER_SIZE, &record_count, 400);
263
264      /* Check for DNS query error.  */
265      if (status != NX_SUCCESS)
266      {
267          error_counter++;
268      }
269
270      else
271      {
272
273          printf("--------------------------------------------------------\n");
274          printf("Test A: ");
275          printf("record_count = %d \n", record_count);
276      }
277
278      /* Get the IPv4 addresses of host.   */
279      for(i =0; i< record_count; i++)
280      {
281          ipv4_address_ptr[i] = (ULONG *)(record_buffer + i * sizeof(ULONG));
282          printf("record %d: IP address: %lu.%lu.%lu.%lu\n", i,
283                  *ipv4_address_ptr[i] >> 24,
284                  *ipv4_address_ptr[i] >> 16 & 0xFF,
285                  *ipv4_address_ptr[i] >> 8 & 0xFF,
286                  *ipv4_address_ptr[i] & 0xFF);
287      }
288
289
290
/***************************************************************************/
```

```
291 /*                                  Type A + CNAME response
*/
292 /*        Send A type DNS Query to its DNS server and get the IPv4 address.
*/
293
/*******************************************************************************/
294     /* Look up an IPv4 address over IPv4. */
295     status = nx_dns_host_by_name_get(&client_dns, (UCHAR *)"www.my_example.com",
&host_ip_address, 400);
296
297     /* Check for DNS query error.  */
298     if (status != NX_SUCCESS)
299     {
300         error_counter++;
301     }
302
303     else
304     {
305
306         printf("-------------------------------------------------------\n");
307         printf("Test A + CNAME response: \n");
308         printf("IP address: %lu.%lu.%lu.%lu\n",
309         host_ip_address >> 24,
310         host_ip_address >> 16 & 0xFF,
311         host_ip_address >> 8 & 0xFF,
312         host_ip_address & 0xFF);
313     }
314
315
316     /* Look up IPv4 addresses to record multiple IPv4 addresses in record_buffer
and return the IPv4 address count.  */
317     status = nx_dns_ipv4_address_by_name_get(&client_dns, (UCHAR
*)"www.my_example.com", &record_buffer[0], BUFFER_SIZE, &record_count, 400);
318
319     /* Check for DNS query error.  */
320     if (status != NX_SUCCESS)
321     {
322         error_counter++;
323     }
324
325     else
326     {
327
328         printf("-------------------------------------------------------\n");
329         printf("Test Test A + CNAME response: ");
330         printf("record_count = %d \n", record_count);
331     }
332
333     /* Get the IPv4 addresses of host.  */
334     for(i =0; i< record_count; i++)
335     {
336         ipv4_address_ptr[i] = (ULONG *)(record_buffer + i * sizeof(ULONG));
337         printf("record %d: IP address: %lu.%lu.%lu.%lu\n", i,
338                 *ipv4_address_ptr[i] >> 24,
339                 *ipv4_address_ptr[i] >> 16 & 0xFF,
340                 *ipv4_address_ptr[i] >> 8 & 0xFF,
341                 *ipv4_address_ptr[i] & 0xFF);
342     }
343
344
345
/*******************************************************************************/
346 /*                                  Type PTR
*/
347 /*        Send PTR type DNS Query to its DNS server and get the host name.
*/
348
/*******************************************************************************/
349
350
351
352     /* Look up host name over IPv4. */
353     host_ip_address = IP_ADDRESS(74, 125, 71, 106);
354     status = nx_dns_host_by_address_get(&client_dns, host_ip_address,
&record_buffer[0], BUFFER_SIZE, 450);
355
356     /* Check for DNS query error.  */
357     if (status != NX_SUCCESS)
358     {
359         error_counter++;
360     }
```

```
361
362     else
363     {
364         printf("--------------------------------------------------------\n");
365         printf("Test PTR: %s\n", record_buffer);
366     }
367
368 #ifdef NX_DNS_ENABLE_EXTENDED_RR_TYPES
369
/*****************************************************************************/
370 /*                              Type CNAME
*/
371 /*   Send CNAME type DNS Query to its DNS server and get the canonical name .
*/
372
/*****************************************************************************/
373
374     /* Send CNAME type to record the canonical name of host in record_buffer.
*/
375     status = nx_dns_cname_get(&client_dns, (UCHAR *)"www.my_example.com",
&record_buffer[0], BUFFER_SIZE, 400);
376
377     /* Check for DNS query error.  */
378     if (status != NX_SUCCESS)
379     {
380         error_counter++;
381     }
382
383     else
384     {
385
386         printf("-------------------------------------------------------\n");
387         printf("Test CNAME: %s\n", record_buffer);
388     }
389
390
391
/*****************************************************************************/
392 /*                              Type TXT
*/
393 /*     Send TXT type DNS Query to its DNS server and get descriptive text.
*/
394
/*****************************************************************************/
395
396     /* Send TXT type to record the descriptive test of host in record_buffer.
*/
397     status = nx_dns_host_text_get(&client_dns, (UCHAR *)"www.my_example.com",
&record_buffer[0], BUFFER_SIZE, 400);
398
399     /* Check for DNS query error.  */
400     if (status != NX_SUCCESS)
401     {
402         error_counter++;
403     }
404
405     else
406     {
407
408         printf("-------------------------------------------------------\n");
409         printf("Test TXT: %s\n", record_buffer);
410     }
411
412
413
/*****************************************************************************/
414 /*                              Type NS
*/
415 /*   Send NS type DNS Query to its DNS server and get the domain name server.
*/
416
/*****************************************************************************/
417
418     /* Send NS type to record multiple name servers in record_buffer and return
the name server count.
419         If the DNS response includes the IPv4 addresses of name server, record it
similarly in record_buffer.  */
420     status = nx_dns_domain_name_server_get(&client_dns, (UCHAR
*)"www.my_example.com", &record_buffer[0], BUFFER_SIZE, &record_count, 400);
421
422     /* Check for DNS query error.  */
```

```
423        if (status != NX_SUCCESS)
424        {
425            error_counter++;
426        }
427
428        else
429        {
430
431            printf("--------------------------------------------------------\n");
432            printf("Test NS: ");
433            printf("record_count = %d \n", record_count);
434        }
435
436        /* Get the name server.  */
437        for(i =0; i< record_count; i++)
438        {
439            nx_dns_ns_entry_ptr[i] = (NX_DNS_NS_ENTRY *)(record_buffer + i *
sizeof(NX_DNS_NS_ENTRY));
440
441            printf("record %d: IP address: %d.%d.%d.%d\n", i,
442                    nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address  >> 24,
443                    nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address >> 16 & 0xFF,
444                    nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address >> 8 & 0xFF,
445                    nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address & 0xFF);
446            if(nx_dns_ns_entry_ptr[i] -> nx_dns_ns_hostname_ptr)
447                printf("hostname = %s\n", nx_dns_ns_entry_ptr[i] ->
nx_dns_ns_hostname_ptr);
448            else
449                printf("hostname is not set\n");
450        }
451
452
/*****************************************************************************/
453 /*                              Type MX
*/
454 /*    Send MX type DNS Query to its DNS server and get the domain mail exchange.
*/
455
/*****************************************************************************/
456
457        /* Send MX DNS query type to record multiple mail exchanges in record_buffer
and return the mail exchange count.
458            If the DNS response includes the IPv4 addresses of mail exchange, record
it similarly in record_buffer.  */
459        status = nx_dns_domain_mail_exchange_get(&client_dns, (UCHAR
*)"www.my_example.com", &record_buffer[0], BUFFER_SIZE, &record_count, 400);
460
461        /* Check for DNS query error.  */
462        if (status != NX_SUCCESS)
463        {
464            error_counter++;
465        }
466
467        else
468        {
469
470            printf("--------------------------------------------------------\n");
471            printf("Test MX: ");
472            printf("record_count = %d \n", record_count);
473        }
474
475        /* Get the mail exchange.  */
476        for(i =0; i< record_count; i++)
477        {
478            nx_dns_mx_entry_ptr[i] = (NX_DNS_MX_ENTRY *)(record_buffer + i *
sizeof(NX_DNS_MX_ENTRY));
479
480            printf("record %d: IP address: %d.%d.%d.%d\n", i,
481                    nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address >> 24,
482                    nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address >> 16 & 0xFF,
483                    nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address >> 8 & 0xFF,
484                    nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address & 0xFF);
485            printf("preference = %d \n ", nx_dns_mx_entry_ptr[i] ->
nx_dns_mx_preference);
486            if(nx_dns_mx_entry_ptr[i] -> nx_dns_mx_hostname_ptr)
487                printf("hostname = %s\n", nx_dns_mx_entry_ptr[i] ->
nx_dns_mx_hostname_ptr);
488            else
489                printf("hostname is not set\n");
490        }
491
```

```
492
/****************************************************************************/
493 /*                              Type SRV
*/
494 /*  Send SRV type DNS Query to its DNS server and get the location of services.
*/
495
/****************************************************************************/
496
497      /* Send SRV DNS query type to record the location of services in
record_buffer and return count.
498         If the DNS response includes the IPv4 addresses of service name, record
it similarly in record_buffer.  */
499      status = nx_dns_domain_service_get(&client_dns, (UCHAR
*)"www.my_example.com", &record_buffer[0], BUFFER_SIZE, &record_count, 400);
500
501      /* Check for DNS query error.  */
502      if (status != NX_SUCCESS)
503      {
504          error_counter++;
505      }
506
507      else
508      {
509
510          printf("--------------------------------------------------------\n");
511          printf("Test SRV: ");
512          printf("record_count = %d \n", record_count);
513      }
514
515      /* Get the location of services.  */
516      for(i =0; i< record_count; i++)
517      {
518          nx_dns_srv_entry_ptr[i] = (NX_DNS_SRV_ENTRY *)(record_buffer + i *
sizeof(NX_DNS_SRV_ENTRY));
519
520          printf("record %d: IP address: %d.%d.%d.%d\n", i,
521                  nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address >> 24,
522                  nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address >> 16 & 0xFF,
523                  nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address >> 8 & 0xFF,
524                  nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address & 0xFF);
525          printf("port number = %d\n", nx_dns_srv_entry_ptr[i] ->
nx_dns_srv_port_number );
526          printf("priority = %d\n", nx_dns_srv_entry_ptr[i] ->
nx_dns_srv_priority );
527          printf("weight = %d\n", nx_dns_srv_entry_ptr[i] -> nx_dns_srv_weight );
528          if(nx_dns_srv_entry_ptr[i] -> nx_dns_srv_hostname_ptr)
529              printf("hostname = %s\n", nx_dns_srv_entry_ptr[i] ->
nx_dns_srv_hostname_ptr);
530          else
531              printf("hostname is not set\n");
532      }
533
534      /* Get the service info, NetX old API.*/
535      status = nx_dns_info_by_name_get(&client_dns, (UCHAR *)"www.my_example.com",
&host_address, &host_port, 200);
536
537      /* Check for DNS add server error.  */
538      if (status != NX_SUCCESS)
539      {
540          error_counter++;
541      }
542
543      else
544      {
545
546          printf("--------------------------------------------------------\n");
547          printf("Test SRV: ");
548          printf("IP address: %d.%d.%d.%d\n",
549                  host_address >> 24,
550                  host_address >> 16 & 0xFF,
551                  host_address >> 8 & 0xFF,
552                  host_address & 0xFF);
553          printf("port number = %d\n", host_port);
554      }
555
556
/****************************************************************************/
557 /*                              Type SOA
*/
```

```
558 /* Send SOA type DNS Query to its DNS server and get zone of start of
authority.*/
559
/*****************************************************************************/
560
561      /* Send SOA DNS query type to record the zone of start of authority in
record_buffer.   */
562      status = nx_dns_authority_zone_start_get(&client_dns, (UCHAR
*)"www.my_example.com", &record_buffer[0], BUFFER_SIZE, 400);
563
564      /* Check for DNS query error.   */
565      if (status != NX_SUCCESS)
566      {
567          error_counter++;
568      }
569
570      /* Get the loc*/
571      nx_dns_soa_entry_ptr = (NX_DNS_SOA_ENTRY *) record_buffer;
572      printf("-----------------------------------------------------\n");
573      printf("Test SOA: \n");
574      printf("serial = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_serial );
575      printf("refresh = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_refresh );
576      printf("retry = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_retry );
577      printf("expire = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_expire );
578      printf("minmum = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_minmum );
579      if(nx_dns_soa_entry_ptr -> nx_dns_soa_host_mname_ptr)
580          printf("host mname = %s\n", nx_dns_soa_entry_ptr ->
nx_dns_soa_host_mname_ptr);
581      else
582          printf("host mame is not set\n");
583      if(nx_dns_soa_entry_ptr -> nx_dns_soa_host_rname_ptr)
584          printf("host rname = %s\n", nx_dns_soa_entry_ptr ->
nx_dns_soa_host_rname_ptr);
585      else
586          printf("host rname is not set\n");
587
588
589 #endif
590
591      /* Shutting down...*/
592
593      /* Terminate the DNS Client thread. */
594      status = nx_dns_delete(&client_dns);
595
596      return;
597 }
598
599
```

Configuration Options

There are several configuration options for building DNS for NetX. These options can be redefined in *nx_dns.h.* The following list describes each in detail:

Define	Meaning
NX_DNS_TYPE_OF_SERVICE	Type of service required for the DNS UDP requests. By default, this value is defined as NX_IP_NORMAL for normal IP packet service.
NX_DNS_TIME_TO_LIVE	Specifies the maximum number of routers a packet can pass before it is discarded. The default value is 0x80.
NX_DNS_FRAGMENT_OPTION	Sets the socket property to allow or disallow fragmentation of outgoing packets. The default value is NX_DONT_FRAGMENT.
NX_DNS_QUEUE_DEPTH	Sets the maximum number of packets to store on the socket receive queue. The default value is 5.
NX_DNS_MAX_SERVERS	Specifies the maximum number of DNS Servers in the Client server list.
NX_DNS_MESSAGE_MAX	The maximum DNS message size for sending DNS queries. The default value is 512, which is also the maximum size specified in RFC 1035 Section 2.3.4.
NX_DNS_PACKET_PAYLOAD_UNALIGNED	If not defined, the size of the Client packet payload which includes the Ethernet, IP (or IPv6), and UDP headers plus the maximum DNS message size specified by

NX_DNS_MESSAGE_MAX. Regardless if defined, the packet payload is the 4-byte aligned and stored in NX_DNS_PACKET_PAYLOAD.

NX_DNS_PACKET_POOL_SIZE   Size of the Client packet pool for sending DNS queries if NX_DNS_CLIENT_USER_CREATE_PACKET_POOL is not defined. The default value is large enough for 16 packets of payload size defined by NX_DNS_PACKET_PAYLOAD, and is 4-byte aligned.

NX_DNS_MAX_RETRIES   The maximum number of times the DNS Client will query the current DNS server before trying another server or aborting the DNS query.

NX_ DNS_MAX_RETRANS_TIMEOUT The maximum retransmission timeout on a DNS query to a specific DNS server. The default value is 64 seconds (64 *NX_IP_PERIODIC_RATE).

NX_DNS_IP_GATEWAY_AND_DNS_SERVER
If defined and the Client IPv4 gateway address is non zero, the DNS Client sets the IPv4 gateway as the Client's primary DNS server. The default value is disabled.

NX_ DNS_PACKET_ALLOCATE_TIMEOUT
This sets the timeout option for allocating a packet from the DNS client packet pool. The default value is 1 second (1*NX_IP_PERIODIC_RATE).

NX_DNS_CLIENT_USER_CREATE_PACKET_POOL
This enables the DNS Client to let the application create and set the DNS Client packet pool. By default this option is disabled, and the DNS Client creates its own packet pool in *nx_dns_create*.

NX_ DNS_CLIENT_CLEAR_QUEUE   This enables the DNS Client to clear old DNS messages off the receive queue before sending a new query. Removing these packets from previous DNS queries prevents the DNS Client socket queue from overflowing and dropping valid packets.

NX_DNS_ENABLE_EXTENDED_RR_TYPES

This enables the DNS Client to query on additional DNS record types in (e.g. CNAME, NS, MX, SOA, SRV and TXT).

NX_DNS_CACHE_ENABLE

This enables the DNS Client to store the answer records into DNS cache.

Chapter 3

Description of NetX DNS Client Services

This chapter contains a description of all NetX DNS services (listed below) in alphabetic order.

In the "Return Values" section in the following API descriptions, values in **BOLD** are not affected by the **NX_DISABLE_ERROR_CHECKING** define that is used to disable API error checking, while non-bold values are completely disabled.

nx_dns_authority_zone_start_get
Look up the start of a zone of authority associated with the specified host name

nx_dns_cache_initialize
Initialize a DNS Cache.

nx_dns_cache_notify_clear
Clear the cache full notify function.

nx_dns_cache_notify_set
Set the cache full notify function.

nx_dns_cname_get
Look up the canonical domain name for the input domain name alias

nx_dns_create
Create a DNS Client instance

nx_dns_delete
Delete a DNS Client instance

nx_dns_domain_name_server_get
Look up the authoritative name servers for the input domain zone

nx_dns_domain_mail_exchange_get
Look up the mail exchange associated the specified host name.

nx_dns_domain_service_get

*Look up the service(s) associated with
the specified host name*

nx_dns_get_serverlist_size
Return the size of the DNS Client server list

nx_dns_info_by_name_get
Return IP address, port querying on input host name

nx_dns_ipv4_address_by_name_get
Look up the IPv4 address from the specified host name

nx_dns_host_by_address_get
Look up a host name from a specified IP address

nx_dns_host_by_name_get
Look up the IPv4 address from the specified host name

nx_dns_host_text_get
Look up the text data for the input domain name

nx_dns_packet_pool_set
Set the DNS Client packet pool

nx_dns_server_add
*Add a DNS Server at the specified address
to the Client list*

nx_dns_server_get
Return the DNS Server in the Client list

nx_dns_server_remove
Remove a DNS Server from the Client list

nx_dns_server_remove_all
Remove all DNS Servers from the Client list

nx_dns_authority_zone_start_get

Look up the start of the zone of authority for the input host

Prototype

```
UINT nx_dns_authority_zone_start_get (NX_DNS *dns_ptr, UCHAR *host_name,
                                      VOID *record_buffer,
                                      UINT buffer_size,
                                      UINT *record_count,
                                      ULONG wait_option);
```

Description

If NX_DNS_ENABLE_EXTENDED_RR_TYPES is defined, this service sends a query of type SOA with the specified domain name to obtain the start of the zone of authority for the input domain name.   The DNS Client copies the SOA record(s) returned in the DNS Server response into the *record_buffer* memory location. Note that *record_buffer* must be 4-byte aligned to receive the data.

In NetX DNS Client, the SOA record type, NX_DNS_SOA_ENTRY, is saved as seven 4 byte parameters, totaling 28 bytes:

nx_dns_soa_host_mname_ptr   Pointer to primary source of
                                    data for this zone
nx_dns_soa_host_rname_ptr   Pointer to mailbox responsible for this zone
nx_dns_soa_serial   Zone version number
nx_dns_soa_refresh   Refresh interval
 nx_dns_soa_retry   Interval between SOA query retries
 nx_dns_soa_expire   Time duration when SOA expires
 nx_dns_soa_minmum   Minimum TTL field in SOA
                                    hostname DNS reply messages

The storage of a two SOA records is shown below. The SOA records containing fixed length data are entered starting at the top of the buffer. The pointers MNAME and RNAME point to the variable length data (host names) which are stored at the bottom of the buffer. Additional SOA records are entered after the first record ("additional SOA records…") and their variable length data is stored above the last entry's variable length data ("additional SOA variable length data"):

```
0                                                          32 bits
|----------------------------------------------------------- |
|                        MNAME 0                            |
|----------------------------------------------------------- |
|                        RNAME 0                            |
|----------------------------------------------------------- |
|                        SERIAL 0                           |
|----------------------------------------------------------- |
|                        REFRESH 0                          |
|----------------------------------------------------------- |
|                        RETRY 0                            |
|----------------------------------------------------------- |
|                        EXPIRE 0                           |
|----------------------------------------------------------- |
|                        MINMUM 0                           |
|----------------------------------------------------------- |
|                        MNAME 1                            |
|----------------------------------------------------------- |
|                        RNAME 1                            |
|----------------------------------------------------------- |
|                        SERIAL 1                           |
|----------------------------------------------------------- |
|                        REFRESH 1                          |
|----------------------------------------------------------- |
|                        RETRY 1                            |
|----------------------------------------------------------- |
|                        EXPIRE 1                           |
|----------------------------------------------------------- |
|                        MINMUM 1                           |
|----------------------------------------------------------- |
|                  (additional SOA records)                 |
|----------------------------------------------------------- |
|            (additional SOA variable length data)          |
|----------------------------------------------------------- |
|                 mailbox host name string 1                |
|----------------------------------------------------------- |
|              primary source host name string 1            |
|----------------------------------------------------------- |
|                 mailbox host name string 0                |
|----------------------------------------------------------- |
|              primary source host name string 0            |
|----------------------------------------------------------- |
```

If the input *record_buffer* cannot hold all the SOA data in the server reply, the the *record_buffer* holds as many records as will fit and returns the number of records in the buffer.

With the number of SOA records returned in *record_count,* the application can parse the data from *record_buffer* and extract the start of zone authority host name strings.

Input Parameters

dns_ptr   Pointer to DNS Client.
host_name   Pointer to host name to obtain SOA data for
record_buffer   Pointer to location to extract SOA data into
buffer_size   Size of buffer to hold SOA data
record_count   Pointer to the number of SOA records retrieved
wait_option   Wait option to receive DNS Server response

Return Values

NX_SUCCESS	(0x00)	Successfully obtained SOA data
NX_DNS_NO_SERVER	(0xA1)	Client server list is empty
NX_DNS_QUERY_FAILED		
	(0xA3)	No valid DNS response received
NX_PTR_ERROR	(0x07)	Invalid IP or DNS pointer
NX_CALLER_ERROR	(0x11)	Invalid caller of this service
NX_DNS_PARAM_ERROR	(0xA8)	Invalid non pointer input

Allowed From

Threads

Example

```
UCHAR   record_buffer[50];
UINT    record_count;
NX_DNS_SOA_ENTRY *nx_dns_soa_entry_ptr;

/* Request the start of authority zone(s) for the specified host.  */
status = nx_dns_authority_zone_start_get(&client_dns, (UCHAR *)"www.my_example.com",
                                         record _buffer, sizeof(record_buffer),
                                         &record_count, 500);

/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
        error_counter++;
}
else
{
    /* If status is NX_SUCCESS a DNS query was successfully completed and SOA data is
    returned in soa_buffer.  */

    /* Set a local pointer to the SOA buffer. */
    nx_dns_soa_entry_ptr = (NX_DNS_SOA_ENTRY *) record_buffer;

    printf("-------------------------------------------------------\n");
    printf("Test SOA: \n");
    printf("serial = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_serial );
    printf("refresh = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_refresh );
    printf("retry = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_retry );
    printf("expire = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_expire );
    printf("minmum = %d\n", nx_dns_soa_entry_ptr -> nx_dns_soa_minmum );
```

```
        if(nx_dns_soa_entry_ptr -> nx_dns_soa_host_mname_ptr)
        {
            printf("host mname = %s\n",
                    nx_dns_soa_entry_ptr -> nx_dns_soa_host_mname_ptr);
        }
        else
        {
            printf("host mame is not set\n");
        }

        if(nx_dns_soa_entry_ptr -> nx_dns_soa_host_rname_ptr)
        {
            printf("host rname = %s\n",
                    nx_dns_soa_entry_ptr -> nx_dns_soa_host_rname_ptr);
        }
        else
        {

            printf("host rname is not set\n");
        }
}

[Output]
--------------------------------------------------
Test SOA:
serial = 2012111212
refresh = 7200
retry = 1800
expire = 1209600
minmum = 300
host mname = ns1.www.my_example.com
host rname = dns-admin.www.my_example.com
```

nx_dns_cache_initialize

Initialize the DNS Cache

Prototype

```
UINT nx_dns_cache_initialize(NX_DNS *dns_ptr,
                        VOID *cache_ptr, UINT cache_size);
```

Description

This service creates and initializes a DNS Cache.

Input Parameters

dns_ptr   Pointer to DNS control block.

cache_ptr   Pointer to DNS Cache.

cache_size   Size of DNS Cache, in bytes.

Return Values

NX_SUCCESS   (0x00)   DNS Cache successfully
                                     initialized
NX_DNS_ERROR   (0xA0)   Cache is not 4-byte aligned.
NX_DNS_PARAM_ERROR   (0xA8)   Invalid DNS ID.
NX_PTR_ERROR   (0x07)   Invalid DNS pointer.
NX_CALLER_ERROR   (0x11)   Invalid caller of this service

Allowed From

Threads

Example

```
UCHAR  dns_cache [2048];

/* Initialize the DNS Cache.  */
status =  nx_dns_cache_initialize(&my_dns, dns_cache, 2048);

/* If status is NX_SUCCESS DNS Cache was successfully initialized.  */
```

nx_dns_cache_notify_clear

Clear the DNS Cache full notify function

Prototype

```
UINT nx_dns_cache_notify_clear(NX_DNS *dns_ptr);
```

Description

This service clears the cache full notify function.

Input Parameters

dns_ptr   Pointer to DNS control block.

Return Values

NX_SUCCESS	(0x00)	DNS cache notify successfully set
NX_DNS_PARAM_ERROR	(0xA8)	Invalid DNS ID.
NX_PTR_ERROR	(0x07)	Invalid DNS pointer.

Allowed From

Threads

Example

```
/* Clear the DNS Cache full notify function.  */
status =  nx_dns_cache_notify_clear(&my_dns);

/* If status is NX_SUCCESS DNS Cache full notify function was successfully cleared. */
```

nx_dns_cache_notify_set

Set the DNS Cache full notify function

Prototype

```
UINT nx_dns_cache_notify_set(NX_DNS *dns_ptr,
                             VOID (*cache_full_notify_cb)(NX_DNS *dns_ptr));
```

Description

This service sets the cache full notify function.

Input Parameters

dns_ptr   Pointer to DNS control block.

cache_full_notify_cb   The callback function to be invoked
                                when cache become full.

Return Values

NX_SUCCESS   (0x00)   DNS cache notify successfully
                                    set
NX_DNS_PARAM_ERROR   (0xA8)   Invalid DNS ID.
NX_PTR_ERROR   (0x07)   Invalid DNS pointer.

Allowed From

Threads

Example

```
/* Set the DNS Cache full notify function.  */
status = nx_dns_cache_notify_set(&my_dns, cache_full_notify_cb);

/* If status is NX_SUCCESS DNS Cache full notify function was successfully set.  */
```

nx_dns_cname_get

Look up the canonical name for the input hostname

Prototype

```
UINT nx_dns_cname_get(NX_DNS *dns_ptr, UCHAR *host_name,
                      UCHAR *record_buffer, UINT buffer_size,
                      ULONG wait_option);
```

Description

If NX_DNS_ENABLE_EXTENDED_RR_TYPES is defined in *nx_dns.h*, this service sends a query of type CNAME with the specified domain name to obtain the canonical domain name. The DNS Client copies the CNAME string returned in the DNS Server response into the *record_buffer* memory location.

Input Parameters

dns_ptr	Pointer to DNS Client.
host_name	Pointer to host name to obtain CNAME data for
record_buffer	Pointer to location to extract CNAME data into
buffer_size	Size of buffer to hold CNAME data
wait_option	Wait option to receive DNS Server response

Return Values

NX_SUCCESS	(0x00)	Successfully obtained CNAME data
NX_DNS_NO_SERVER	(0xA1)	Client server list is empty
NX_DNS_QUERY_FAILED		
	(0xA3)	No valid DNS response received
NX_PTR_ERROR	(0x07)	Invalid IP or DNS pointer
NX_CALLER_ERROR	(0x11)	Invalid caller of this service
NX_DNS_PARAM_ERROR	(0xA8)	Invalid non-pointer input

Allowed From

Threads

Example

```
CHAR            record _buffer[50];

/* Request the canonical name for the specified host.  */
status = nx_dns_cname_get(&client_dns, (UCHAR *)"www.my_example.com ",
                          record_buffer, sizeof(record_buffer), 500);

/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
    error_counter++;
```

```
}
else
{
    /* If status is NX_SUCCESS a DNS query was successfully completed and the
       canonical host name is returned in record_buffer.  */

    printf("-------------------------------------------------------\n");
    printf("Test CNAME: %s\n", record_buffer);
}
```

[Output]

Test CNAME: my_example.com

nx_dns_create

Create a DNS Client instance

Prototype

```
UINT nx_dns_create(NX_DNS *dns_ptr, NX_IP *ip_ptr, CHAR *domain_name);
```

Description

This service creates a DNS Client instance for the previously created IP instance.

Important Note: The application must ensure that the packet payload of the packet pool used by the DNS Client is large enough for the maximum 512 byte DNS message, plus UDP, IP and Ethernet headers. If the DNS Client creates its own packet pool, this is defined by NX_DNS_PACKET_POOL_SIZE and NX_DNS_PACKET_PAYLOAD. If the DNS Client application prefers to supply a previously created packet pool, the payload for IPv4 DNS Client should be 512 bytes for the maximum DNS plus 20 bytes for the IP header, 8 bytes for the UDP header and 14 bytes for the Ethernet header.

Input Parameters

dns_ptr	Pointer to DNS Client.
ip_ptr	Pointer to previously created IP instance.
domain_name	Pointer to domain name for DNS instance.

Return Values

NX_SUCCESS	(0x00)	Successful DNS create
NX_DNS_ERROR	(0xA0)	DNS create error
NX_PTR_ERROR	(0x07)	Invalid IP or DNS pointer
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Create a DNS Client instance.  */
status = nx_dns_create(&my_dns, &my_ip, "My DNS");

/* If status is NX_SUCCESS a DNS Client instance was successfully
   created.  */
```

nx_dns_delete

Delete a DNS Client instance

Prototype

```
UINT nx_dns_delete(NX_DNS *dns_ptr);
```

Description

This service deletes a previously created DNS Client instance and frees up its resources. Note that if NX_DNS_CLIENT_USER_CREATE_PACKET_POOL is defined and the DNS Client was assigned a user defined packet pool, it is up to the application to delete the DNS Client packet pool if it no longer needs it.

Input Parameters

dns_ptr   Pointer to previously created DNS Client instance.

Return Values

NX_SUCCESS   (0x00)   Successful DNS Client delete.
NX_PTR_ERROR   (0x07)   Invalid IP or DNS Client pointer.
NX_CALLER_ERROR   (0x11)   Invalid caller of this service.

Allowed From

Threads

Example

```
/* Delete a DNS Client instance.  */
status =  nx_dns_delete(&my_dns);

/* If status is NX_SUCCESS the DNS Client  instance was successfully
   deleted.  */
```

nx_dns_domain_name_server_get

Look up the authoritative name servers for the input domain zone

Prototype

```
UINT nx_dns_domain_name_server_get(NX_DNS *dns_ptr, UCHAR *host_name,
                                   VOID *record_buffer, UINT buffer_size,
                                   UINT *record_count, ULONG wait_option);
```

Description

If NX_DNS_ENABLE_EXTENDED_RR_TYPES is defined, this service sends a query of type NS with the specified domain name to obtain the name servers for the input domain name.   The DNS Client copies the NS record(s) returned in the DNS Server response into the *record_buffer* memory location. Note that *record_buffer* must be 4-byte aligned to receive the data.

In NetX DNS Client the NS data type, NX_DNS_NS_ENTRY, is saved as two 4-byte parameters:

nx_dns_ns_ipv4_address	Name server's IPv4 address
nx_dns_ns_hostname_ptr	Pointer to the name server's hostname

The buffer shown below contains four NX_DNS_NS_ENTRY records. The pointer to host name string in each entry points to the corresponding host name string in the bottom half of the buffer:

```
         |----------------------------------------------------------|
Record 0 |      ip_address 0            |    Pointer to host name 0 |
         |----------------------------------------------------------|
Record 1 |      ip_address 1            |    Pointer to host name 1 |
         |----------------------------------------------------------|
Record 2 |      ip_address 2            |    Pointer to host name 2 |
         |----------------------------------------------------------|
Record 3 |      ip_address 3            |    Pointer to host name 3 |
         |----------------------------------------------------------|
         |            (room for additional record entries )         |
         |                                                          |
         |            (room for additional host names )             |
         |----------------------------------------------------------|
         | host name 3       |                host name 2           |
         |----------------------------------------------------------|
         | host name 1             |      ns_hostname 0             |
         |----------------------------------------------------------|
```

If the input *record_buffer* cannot hold all the NS data in the server reply, the the *record_buffer* holds as many records as will fit and returns the number of records in the buffer.

With the number of NS records returned in *record_count,* the application can parse the IP address and host name of each record in the *record_buffer*.

Input Parameters

dns_ptr	Pointer to DNS Client.
host_name	Pointer to host name to obtain NS data for
record_buffer	Pointer to location to extract NS data into
buffer_size	Size of buffer to hold NS data
record_count	Pointer to the number of NS records retrieved
wait_option	Wait option to receive DNS Server response

Return Values

NX_SUCCESS	(0x00)	Successfully obtained NS data
NX_DNS_NO_SERVER	(0xA1)	Client server list is empty
NX_DNS_QUERY_FAILED		
	(0xA3)	No valid DNS response received
NX_DNS_PARAM_ERROR	(0xA8)	Invalid DNS ID.
NX_PTR_ERROR	(0x07)	Invalid IP or DNS pointer
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
#define RECORD_COUNT    10

ULONG  record_buffer[50];
UINT   record_count;
NX_DNS_NS_ENTRY  *nx_dns_ns_entry_ptr[RECORD_COUNT];

/* Request the name server(s) for the specified host.  */
status = nx_dns_domain_name_server_get(&client_dns, (UCHAR *)" www.my_example.com ",
                                    record_buffer, sizeof(record_buffer),
                                    &record_count, 500);

/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
    error_counter++;
}

else
{
    /* If status is NX_SUCCESS a DNS query was successfully completed and NS data is
       returned in record_buffer.  */

    printf("----------------------------------------------------\n");
    printf("Test NS: ");
    printf("record_count = %d \n", record_count);
```

```
    /* Get the name server.  */
    for(i =0; i< record_count; i++)
    {
        nx_dns_ns_entry_ptr[i] = (NX_DNS_NS_ENTRY *)
                            (record_buffer + i * sizeof(NX_DNS_NS_ENTRY));

        printf("record %d: IP address: %d.%d.%d.%d\n", i,
                        nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address  >> 24,
                        nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address >> 16 & 0xFF,
                        nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address >> 8 & 0xFF,
                      nx_dns_ns_entry_ptr[i] -> nx_dns_ns_ipv4_address & 0xFF);
        if(nx_dns_ns_entry_ptr[i] -> nx_dns_ns_hostname_ptr)
        {
            printf("hostname = %s\n",
                    nx_dns_ns_entry_ptr[i] -> nx_dns_ns_hostname_ptr);
         }
        else
            printf("hostname is not set\n");
    }
}

[Output]
------------------------------------------------------
Test NS: record_count = 4
record 0: IP address: 192.2.2.10
hostname = ns2.www.my_example.com
record 1: IP address: 192.2.2.11
hostname = ns1.www.my_example.com
record 2: IP address: 192.2.2.12
hostname = ns3.www.my_example.com
record 3: IP address: 192.2.2.13
hostname = ns4.www.my_example.com
```

nx_dns_domain_mail_exchange_get

Look up the mail exchange(s) for the input host name

Prototype

```
UINT nx_dns_domain_mail_exchange_get(NX_DNS *dns_ptr, UCHAR *host_name,
                                     VOID *record_buffer,
                                     UINT buffer_size,
                                     UINT *record_count,
                                     ULONG wait_option);
```

Description

If NX_DNS_ENABLE_EXTENDED_RR_TYPES is defined, this service sends a query of type MX with the specified domain name to obtain the mail exchange for the input domain name.   The DNS Client copies the MX record(s) returned in the DNS Server response into the *record_buffer* memory location. Note that *record_buffer* must be 4-byte aligned to receive the data.

In NetX DNS Client, the mail exchange record type, NX_DNS_MAIL_EXCHANGE_ENTRY, is saved as four parameters, totaling 12 bytes:

nx_dns_mx_ipv4_address	Mail exchange IPv4 address	4 bytes
nx_dns_mx_preference	Preference	2 bytes
nx_dns_mx_reserved0	Reserved	2 bytes
nx_dns_mx_hostname_ptr	Pointer to mail exchange server host name	4 bytes

A buffer containing four MX records is shown below. Each record contains the fixed length data from the list above. The pointer to the mail exchange server host name points to the corresponding host name at the bottom of the buffer.

```
|---------------------------------------------------------------|
|ip address 0 | preference | res  | pointer to host name        |
|---------------------------------------------------------------|
|ip address 1 | preference | res  | pointer to host name        |
|---------------------------------------------------------------|
|ip address 2 | preference | res  | pointer to host name        |
|---------------------------------------------------------------|
|ip address 3 | preference | res  | pointer to host name        |
|---------------------------------------------------------------|
|          (room for additional MX record entries)              |
|                                                               |
|          (room for additional MX host name data)              |
|---------------------------------------------------------------|
| mx_host name 3               |      mx_host name 2            |
|---------------------------------------------------------------|
| mx_host name 1               |      mx_host name 0            |
|---------------------------------------------------------------|
```

If the input *record_buffer* cannot hold all the MX data in the server reply, the the *record_buffer* holds as many records as will fit and returns the number of records in the buffer.

With the number of MX records returned in *record_count,* the application can parse the MX parameters, including the mail host name of each record in the *record_buffer*.

Input Parameters

dns_ptr   Pointer to DNS Client.
host_name   Pointer to host name to obtain MX data for
record_buffer   Pointer to location to extract MX data into
buffer_size   Size of buffer to hold MX data
record_count   Pointer to the number of MX records retrieved
wait_option   Wait option to receive DNS Server response

Return Values

NX_SUCCESS   (0x00)   Successfully obtained MX data
NX_DNS_NO_SERVER   (0xA1)   Client server list is empty
NX_DNS_QUERY_FAILED
                       (0xA3)   No valid DNS response received
NX_DNS_PARAM_ERROR(0xA8)   Invalid DNS ID.
NX_PTR_ERROR   (0x07)   Invalid IP or DNS pointer
NX_CALLER_ERROR   (0x11)   Invalid caller of this service

Allowed From

Threads

Example

```
#define MAX_RECORD_COUNT 10

ULONG  record_buffer[50];
UINT   record_count;
NX_DNS_MX_ENTRY  *nx_dns_mx_entry_ptr[MAX_RECORD_COUNT];

/* Request the mail exchange data for the specified host.  */
status = nx_dns_domain_mail_exchange_get(&client_dns, (UCHAR *)" www.my_example.com
",
                                        record_buffer, sizeof(record_buffer),
                                        &record_count, 500);

/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
    error_counter++;
```

```
}

else
{
    /* If status is NX_SUCCESS a DNS query was successfully completed and MX data
       is returned in record_buffer.  */

    printf("----------------------------------------------------\n");
    printf("Test MX: ");
    printf("record_count = %d \n", record_count);


    /* Get the mail exchange.  */
    for(i =0; i< record_count; i++)
    {
        nx_dns_mx_entry_ptr[i] = (NX_DNS_MX_ENTRY *)
                (record_buffer + i * sizeof(NX_DNS_MX_ENTRY));

        printf("record %d: IP address: %d.%d.%d.%d\n", i,
                nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address >> 24,
                nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address >> 16 & 0xFF,
                nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address >> 8 & 0xFF,
                nx_dns_mx_entry_ptr[i] -> nx_dns_mx_ipv4_address & 0xFF);

        printf("preference = %d \n ",
                nx_dns_mx_entry_ptr[i] -> nx_dns_mx_preference);

        if(nx_dns_mx_entry_ptr[i] -> nx_dns_mx_hostname_ptr)
                printf("hostname = %s\n",
                        nx_dns_mx_entry_ptr[i] -> nx_dns_mx_hostname_ptr);
        else
                printf("hostname is not set\n");
    }
}


[Output]

----------------------------------------------------
Test MX: record_count = 5
record 0: IP address: 192.2.2.10
preference = 40
hostname = alt3.aspmx.l.www.my_example.com
record 1: IP address: 192.2.2.11
preference = 50
hostname = alt4.aspmx.l.www.my_example.com
record 2: IP address: 192.2.2.12
preference = 10
hostname = aspmx.l.www.my_example.com
record 3: IP address: 192.2.2.13
preference = 20
hostname = alt1.aspmx.l.www.my_example.com
record 4: IP address: 192.2.2.14
preference = 30
hostname = alt2.aspmx.l.www.my_example.com
```

nx_dns_domain_service_get

Look up the service(s) provided by the input host name

Prototype

```
UINT nx_dns_domain_service_get (NX_DNS *dns_ptr, UCHAR *host_name,
                                VOID *record_buffer, UINT buffer_size,
                                UINT *record_count, ULONG wait_option);
```

Description

If NX_DNS_ENABLE_EXTENDED_RR_TYPES is defined, this service sends a query of type SRV with the specified domain name to look up the service(s) and their port number associated with the specified domain. The DNS Client copies the SRV record(s) returned in the DNS Server response into the *record_buffer* memory location. Note that *record_buffer* must be 4-byte aligned to receive the data.

In NetX DNS Client, the service record type, NX_DNS_SRV_ ENTRY, is saved as six parameters, totaling 16 bytes. This enables variable length SRV data to be stored in a memory efficient manner:

Server IPv4 address	nx_dns_srv_ipv4_address	4 bytes
Server priority	nx_dns_srv_priority	2 bytes
Server weight	nx_dns_srv_weight	2 bytes
Service port number	nx_dns_srv_port_number	2 bytes
Reserved for 4-byte alignment	nx_dns_srv_reserved0	2 bytes
Pointer to server host name	*nx_dns_srv_hostname_ptr	4 bytes

Four SRV records are stored in the supplied buffer. Each NX_DNS_SRV_ENTRY record contains a pointer, *nx_dns_srv_hostname_ptr*, that points to the corresponding host name string in the bottom of the record buffer:

```
|------------------------------------------------------------------ |
|IPv4 address 0 | priority | weight | port | res | host name ptr   |
|------------------------------------------------------------------ |
|IPv4 address 1 | priority | weight | port | res | host name ptr   |
|------------------------------------------------------------------ |
|IPv4 address 2 | priority | weight | port | res | host name ptr   |
|------------------------------------------------------------------ |
|                    (room for additional records)                 |
|------------------------------------------------------------------ |
|              (room for additional host name strings)             |
|------------------------------------------------------------------ |
|srv_hostname 3                      | srv_hostname 2              |
|------------------------------------------------------------------ |
|srv_hostname 1                      | srv_hostname 0              |
|------------------------------------------------------------------ |
```

If the input *record_buffer* cannot hold all the SRV data in the server reply, the the *record_buffer* holds as many records as will fit and returns the number of records in the buffer.

With the number of SRV records returned in *record_count,* the application can parse the SRV parameters, including the server host name of each record in the *record_buffer*.

Input Parameters

dns_ptr   Pointer to DNS Client.
host_name   Pointer to host name to obtain SRV data for
record_buffer   Pointer to location to extract SRV data into
buffer_size   Size of buffer to hold SRV data
record_count   Pointer to the number of SRV records retrieved
wait_option   Wait option to receive DNS Server response

Return Values

NX_SUCCESS   (0x00)   Successfully obtained SRV data
NX_DNS_NO_SERVER   (0xA1)   Client server list is empty
NX_DNS_QUERY_FAILED
                         (0xA3)   No valid DNS response received
NX_DNS_PARAM_ERROR(0xA8)   Invalid DNS ID.
NX_PTR_ERROR   (0x07)   Invalid IP or DNS pointer
NX_CALLER_ERROR   (0x11)   Invalid caller of this service

Allowed From

Threads

Example

```
#define MAX_RECORD_COUNT  10

UCHAR  record_buffer[50];
UINT   record_count;
NX_DNS_SRV_ENTRY *nx_dns_srv_entry_ptr[MAX_RECORD_COUNT];

/* Request the service(s) provided by the specified host.  */
status =  nx_dns_domain_service_get(&client_dns, (UCHAR *)"www.my_example.com ",
                               record_buffer, sizeof(record_buffer),
                               &record_count, 500);

/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
    error_counter++;
}

else
```

```
{
    /* If status is NX_SUCCESS a DNS query was successfully completed and SRV data is
         returned in record_buffer.  */

    printf("----------------------------------------------------\n");
    printf("Test SRV: ");
    printf("record_count = %d \n", record_count);


    /* Get the location of services.  */
    for(i =0; i< record_count; i++)
    {
        nx_dns_srv_entry_ptr[i] = (NX_DNS_SRV_ENTRY *)
                            (record_buffer + i * sizeof(NX_DNS_SRV_ENTRY));

        printf("record %d: IP address: %d.%d.%d.%d\n", i,
                nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address >> 24,
                nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address >> 16 & 0xFF,
                nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address >> 8 & 0xFF,
                nx_dns_srv_entry_ptr[i] -> nx_dns_srv_ipv4_address & 0xFF);

        printf("port number = %d\n",
                nx_dns_srv_entry_ptr[i] -> nx_dns_srv_port_number );
        printf("priority = %d\n", nx_dns_srv_entry_ptr[i] -> nx_dns_srv_priority );
        printf("weight = %d\n", nx_dns_srv_entry_ptr[i] -> nx_dns_srv_weight );

        if(nx_dns_srv_entry_ptr[i] -> nx_dns_srv_hostname_ptr)
        {
            printf("hostname = %s\n",
                    nx_dns_srv_entry_ptr[i] -> nx_dns_srv_hostname_ptr);
        }
        else
            printf("hostname is not set\n");
    }
}

[Output]
-------------------------------------------------
Test SRV: record_count = 3
record 0: IP address: 192.2.2.10
port number = 5222
priority = 20
weight = 0
hostname = alt4.xmpp.l.www.my_example.com
record 1: IP address: 192.2.2.11
port number = 5222
priority = 5
weight = 0
hostname = xmpp.l.www.my_example.com
record 2: IP address: 192.2.2.12
port number = 5222
priority = 20
weight = 0
hostname = alt1.xmpp.l.www.my_example.com
```

nx_dns_get_serverlist_size

Return the size of the DNS Client's Server list

Prototype

```
UINT nx_dns_get_serverlist_size (NX_DNS *dns_ptr, UINT *size);
```

Description

This service returns the number of valid DNS Servers in the Client list.

Input Parameters

dns_ptr   Pointer to DNS control block
size   Returns the number of servers in the list

Return Values

NX_SUCCESS   (0x00)   DNS Server list size
                                        successfully returned
NX_PTR_ERROR   (0x07)   Invalid IP or DNS pointer.
NX_CALLER_ERROR   (0x11)   Invalid caller of this
                                        service

Allowed From

Threads

Example

```
UINT my_listsize;

/* Get the number of non null DNS Servers in the Client list.  */
status = nx_dns_get_serverlist_size (&my_dns, 5, &my_listsize);

/* If status is NX_SUCCESS the size of the DNS Server list was successfully
   returned.  */
```

nx_dns_info_by_name_get

Return ip address and port of DNS server by host name

Prototype

```
UINT nx_dns_info_by_name_get(NX_DNS *dns_ptr, UCHAR *host_name,
                             ULONG *host_address_ptr,
                             USHORT *host_port_ptr, ULONG wait_option);
```

Description

This service returns the Server IP and port (service record) based on the input host name by DNS query. If a service record is not found, this routine returns a zero IP address in the input address pointer and a non-zero error status return to signal an error.

Input Parameters

dns_ptr   Pointer to DNS control block
host_name   Pointer to host name buffer
host_address_ptr   Pointer to address to return
host_port_ptr   Pointer to port to return
wait_option   Wait option for the DNS response

Return Values

NX_SUCCESS   (0x00)   DNS Server record
                                         successfully returned

NX_DNS_NO_SERVER   (0xA1)   No DNS Server registered
                                         with Client to send query on
                                         hostname

NX_DNS_QUERY_FAILED   (0xA3)   DNS query failed; no
                                         response from any DNS
                                         servers in Client list or no
                                         service record is available for
                                         the input hostname.

NX_PTR_ERROR   (0x07)   Invalid IP or DNS pointer
NX_CALLER_ERROR   (0x11)   Invalid caller of this
                                         service

Allowed From

Threads

Example

```
ULONG ip_address
USHORT port;

/* Attempt to resolve the IP address and ports for this host name.  */
status = nx_dns_info_by_name_get(&my_dns, "www.abc1234.com", &ip_address, &port,
200);

/* If status is NX_SUCCESS the DNS query was successful and the IP address and
   report for the hostname are returned.  */
```

nx_dns_ipv4_address_by_name_get

Look up the IPv4 address for the input host name

Prototype

```
UINT nx_ dns_ipv4_address_by_name_get (NX_DNS *dns_ptr,
                                       UCHAR *host_name_ptr, VOID *buffer,
                                       UINT buffer_size,
                                       UINT *record_count,
                                       ULONG wait_option);
```

Description

This service sends a query of Type A with the specified host name to obtain the IP addresses for the input host name. The DNS Client copies the IPv4 address from the A record(s) returned in the DNS Server response into the *record_buffer* memory location. Note that *record_buffer* must be 4-byte aligned to receive the data.

Multiple IPv4 addresses are stored in the 4-byte aligned buffer as shown below:

```
|----------------------------------------------------------------- |
| Address 0 | Address 1 | Address 2 |  .  . . . . . |  Address n    |
|----------------------------------------------------------------- |
```

If the supplied buffer cannot hold all the IP address data, the remaining A records are not stored in *record_buffer*. This enables the application to retrieve one, some or all of the available IP address data in the server reply.

With the number of A records returned in *record_count the application can parse the IPv4 address data from the *record_buffer*.

Input Parameters

dns_ptr   Pointer to DNS Client.
host_name_ptr   Pointer to host name to obtain IPv4 address
buffer   Pointer to location to extract IPv4 data into
buffer_size   Size of buffer to hold IPv4 data
wait_option   Wait option to receive DNS Server response

Return Values

NX_SUCCESS   (0x00)   Successfully obtained IPv4 data
NX_DNS_NO_SERVER   (0xA1)   Client server list is empty
NX_DNS_QUERY_FAILED

	(0xA3)	No valid DNS response received
NX_DNS_PARAM_ERROR	(0xA8)	Invalid input parameter.
NX_PTR_ERROR	(0x07)	Invalid IP or DNS pointer
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
#define MAX_RECORD_COUNT  20


ULONG          record_buffer[50];
UINT           record_count;
ULONG          *ipv4_address_ptr[MAX_RECORD_COUNT];

/* Request the IPv4 address for the specified host.  */
status = nx_dns_ipv4_address_by_name_get(&client_dns,
                                        (UCHAR *)"www.my_example.com",
                                        record_buffer,
                                        sizeof(record_buffer),&record_count,
                                        500);

/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
        error_counter++;
}
else
{
        /* If status is NX_SUCCESS a DNS query was successfully completed the IPv4
           address(es) is returned in record_buffer.  */


        printf("-----------------------------------------------------\n");
        printf("Test A: ");
        printf("record_count = %d \n", record_count);


        /* Get the IPv4 addresses of host.  */
        for(i =0; i< record_count; i++)
        {
            ipv4_address_ptr[i] = (ULONG *)(record_buffer + i * sizeof(ULONG));
            printf("record %d: IP address: %d.%d.%d.%d\n", i,
                *ipv4_address_ptr[i] >> 24,
                *ipv4_address_ptr[i] >> 16 & 0xFF,
                *ipv4_address_ptr[i] >> 8 & 0xFF,
                *ipv4_address_ptr[i] & 0xFF);
        }

}

[Output]

-----------------------------------------------------
Test A: record_count = 5
record 0: IP address: 192.2.2.10
record 1: IP address: 192.2.2.11
record 2: IP address: 192.2.2.12
record 3: IP address: 192.2.2.13
record 4: IP address: 192.2.2.14
```

nx_dns_host_by_address_get

Look up a host name from an IP address

Prototype

```
UINT nx_dns_host_by_address_get(NX_DNS *dns_ptr, ULONG ip_address,
                                ULONG *host_name_ptr,
                                ULONG max_host_name_size,
                                ULONG wait_option);
```

Description

This service requests name resolution of the supplied IP address from one or more DNS Servers previously specified by the application. If successful, the NULL-terminated host name is returned in the string specified by *host_name_ptr*.

Input Parameters

dns_ptr   Pointer to previously created DNS instance.
ip_address   IP address to resolve into a name
host_name_ptr   Pointer to destination area for host name
max_host_name_size   Size of destination area for host name
wait_option   Defines how long the service will wait in timer ticks for a DNS server response after each DNS query and query retry. The wait options are defined as follows:

timeout value   (0x00000001–0xFFFFFFFE)
TX_WAIT_FOREVER (0xFFFFFFFF)

Selecting TX_WAIT_FOREVER causes the calling thread to suspend indefinitely until a DNS server responds to the request.

Selecting a numeric value (1-0xFFFFFFFE) specifies the maximum number of timer-ticks to stay suspended while waiting for the DNS resolution.

Return Values

NX_SUCCESS   (0x00)   Successful DNS resolution
NX_DNS_TIMEOUT   (0xA2)   Timed out on obtaining DNS mutex
NX_DNS_NO_SERVER   (0xA1)   No DNS Server address specified
NX_DNS_QUERY_FAILED

	(0xA3)	Received no response to query
NX_DNS_BAD_ADDRESS_ERROR		
	(0xA4)	Null input address
NX_DNS_INVALID_ADDRESS_TYPE		Index points to invalid
	(0xB2)	address type (e.g. IPv6)
NX_DNS_PARAM_ERROR		
	(0xA8)	Invalid non pointer input
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
#define BUFFER_SIZE   200

UCHAR   resolved_name[200];

/* Get the name associated with IP address 192.2.2.10.  */
status =  nx_dns_host_by_address_get(&my_dns, IP_ADDRESS(192.2.2.10),
                                &resolved_name[0], BUFFER_SIZE, 450);

/* If status is NX_SUCCESS the name associated with the IP address
   can be found in the resolved_name variable.  */
```

nx_dns_host_by_name_get

Look up an IP address from the host name

Prototype

```
UINT nx_dns_host_by_name_get(NX_DNS *dns_ptr, ULONG *host_name,
                             ULONG *host_address_ptr, ULONG wait_option);
```

Description

This service requests name resolution of the supplied name from one or more DNS Servers previously specified by the application. If successful, the associated IP address is returned in the destination pointed to by *host_address_ptr*.

Input Parameters

dns_ptr   Pointer to previously created DNS instance.
host_name_ptr   Pointer to host name
host_address_ptr   Pointer to destination for IP address
wait_option   Defines how long the service will wait for the DNS resolution. The wait options are defined as follows:

timeout value   (0x00000001 through 0xFFFFFFFE)
TX_WAIT_FOREVER (0xFFFFFFFF)

Selecting TX_WAIT_FOREVER causes the calling thread to suspend indefinitely until a DNS server responds to the request.

Selecting a numeric value (1-0xFFFFFFFE) specifies the maximum number of timer-ticks to stay suspended while waiting for the DNS resolution.

Return Values

NX_SUCCESS   (0x00)   Successful DNS resolution.
NX_DNS_NO_SERVER   (0xA1)   No DNS Server address specified
NX_DNS_QUERY_FAILED
                        (0xA3) Received no response to query
NX_DNS_PARAM_ERROR
                        (0xA8)   Invalid non pointer input
NX_PTR_ERROR   (0x07)   Invalid pointer input
NX_CALLER_ERROR   (0x11)   Invalid caller of this service

Allowed From

Threads

Example

```
ULONG ip_address;

/* Get the IP address for the name "www.my_example.com".  */
status =  nx_dns_host_by_name_get(&my_dns, "www.my_example.com", &ip_address, 4000);

/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
    error_counter++;
}

else
{

    /* If status is NX_SUCCESS the IP address for "www.my_example.com" can be found
       in the "ip_address" variable.  */

    printf("----------------------------------------------------\n");
    printf("Test A: \n");
    printf("IP address: %d.%d.%d.%d\n",
    host_ip_address >> 24,
    host_ip_address >> 16 & 0xFF,
    host_ip_address >> 8 & 0xFF,
    host_ip_address & 0xFF);
}


[Output]
 ----------------------------------------------------
Test A:
IP address: 192.2.2.10
```

nx_dns_host_text_get

Look up the text string for the input domain name

Prototype

```
UINT nx_dns_host_text_get(NX_DNS *dns_ptr, UCHAR *host_name,
                          UCHAR *record_buffer,
                          UINT buffer_size, ULONG wait_option);
```

Description

This service sends a query of type TXT with the specified domain name and buffer to obtain the arbitrary string data.

The DNS Client copies the text string in the TXT record in the DNS Server response into the *record_buffer* memory location. Note that `record_buffer` does not need to be 4-byte aligned to receive the data.

Input Parameters

dns_ptr   Pointer to DNS Client.
host_name   Pointer to name of host to search on
record_buffer   Pointer to location to extract TXT data into
buffer_size   Size of buffer to hold TXT data
wait_option   Wait option to receive DNS Server response

Return Values

NX_SUCCESS   (0x00)   Successfully TXT string obtained
NX_DNS_NO_SERVER   (0xA1)   Client server list is empty
NX_DNS_QUERY_FAILED
                        (0xA3)   No valid DNS response received
NX_PTR_ERROR   (0x07)   Invalid pointer input
NX_CALLER_ERROR   (0x11)   Invalid caller of this service
NX_DNS_PARAM_ERROR
                        (0xA8)   Invalid non pointer input

Allowed From

Threads

Example

```
CHAR            record_buffer[50];

/* Request the text string for the specified host.  */
status =  nx_dns_host_text_get(&client_dns, (UCHAR *)"www.my_example.com",
                                record_buffer,
                                sizeof(record_buffer), 500);


/* Check for DNS query error.  */
if (status != NX_SUCCESS)
{
    error_counter++;
}
else
{
    /* If status is NX_SUCCESS a DNS query was successfully completed and the text
       string is returned in record_buffer.  */

    printf("-----------------------------------------------------\n");
    printf("Test TXT:\n %s\n", record_buffer);
}


[Output]


-----------------------------------------------------
Test TXT:
v=spf1 include:_www.my_example.com ip4:192.2.2.10/31 ip4:192.2.2.11/31 ~all
```

nx_dns_packet_pool_set

Set the DNS Client packet pool

Prototype

```
UINT nx_dns_packet_pool_set(NX_DNS *dns_ptr, NX_PACKET_POOL *pool_ptr);
```

Description

This service sets a previously created packet pool as the DNS Client packet pool. The DNS Client will use this packet pool to send DNS queries, so the packet payload should not be less than NX_DNS_PACKET_PAYLOAD_UNALIGNED which includes the Ethernet frame, IP and UDP headers and is defined in *nx_dns.h.* Note that *w*hen the DNS Client is deleted, the packet pool is not deleted with it and it is the responsibility of the application to delete the packet pool when it no longer needs it.

Note: this service is only available if the configuration option NX_DNS_CLIENT_USER_CREATE_PACKET_POOL is defined in *nx_dns.h*

Input Parameters

dns_ptr   Pointer to previously created DNS Client instance.
pool_ptr   Pointer to previously created packet pool

Return Values

NX_SUCCESS   (0x00)   Successful completion.
NX_NOT_ENABLED   (0x14)   Client not configured for this option
NX_PTR_ERROR   (0x07)   Invalid IP or DNS Client pointer.
NX_CALLER_ERROR   (0x11)   Invalid caller of this service.

Allowed From

Threads

Example

```
NX_DNS my_dns;
NX_PACKET_POOL client_pool;
NX_IP *ip_ptr;


/* Create the DNS Client.  */
status =  nx_dns_create(&my_dns, ip_ptr, "My DNS Client");

/* Create a  packet pool for the DNS Client.  */
status =  nx_packet_pool_create(&client_pool, "DNS Client Packet Pool",
                                NX_DNS_PACKET_PAYLOAD, free_mem_pointer,
                                NX_DNS_PACKET_POOL_SIZE);

/* Set the DNS Client  packet pool.  */
status =  nx_dns_packet_pool_set(&my_dns, &client_pool);

/* If status is NX_SUCCESS the DNS Client  packet pool was successfully set.  */
```

nx_dns_server_add

Add DNS Server IP Address

Prototype

```
UINT nx_dns_server_add(NX_DNS *dns_ptr, ULONG server_address);
```

Description

This service adds an IPv4 DNS Server to the server list.

Input Parameters

dns_ptr	Pointer to DNS control block.
server_address	IP address of DNS Server

Return Values

NX_SUCCESS	(0x00)	Server successfully added
NX_DNS_DUPLICATE_ENTRY		
NX_NO_MORE_ENTRIES	(0x17)	No more DNS Servers Allowed (list is full)
NX_DNS_PARAM_ERROR	(0xA8)	Invalid non pointer input
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service
NX_DNS_BAD_ADDRESS_ERROR		
	(0xA4)	Null server address input

Allowed From

Threads

Example

```
/* Add a DNS Server at IP address 202.2.2.13.  */
status =  nx_dns_server_add(&my_dns, IP_ADDRESS(202,2,2,13));

/* If status is NX_SUCCESS a DNS Server was successfully added.  */
```

nx_dns_server_get

Return an IPv4 DNS Server from the Client list

Prototype

```
UINT nx_dns_server_get(NX_DNS *dns_ptr, UINT index,
                       ULONG *dns_server_address);
```

Description

This service returns the IPv4 DNS Server address from the server list at the specified index.   Note that the index is zero based. If the input index exceeds the size of the DNS Client list, an error is returned. The *nx_dns_get_serverlist_size* service may be called first obtain the number of DNS servers in the Client list.

Input Parameters

dns_ptr   Pointer to DNS control block
index   Index into DNS Client's list of servers
dns_server_address   Pointer to IP address of DNS Server

Return Values

NX_SUCCESS   (0x00)   Successful server returned
NX_DNS_SERVER_NOT_FOUND
                                              (0xA9)   Index points to empty slot
NX_DNS_BAD_ADDRESS_ERROR
                                              (0xA4)   Index points to Null address
NX_DNS_PARAM_ERROR   (0xA8)   Index exceeds size of list
NX_PTR_ERROR   (0x07)   Invalid IP or DNS pointer.
NX_CALLER_ERROR   (0x11)   Invalid caller of this
                                                                    service

Allowed From

Threads

Example

```
ULONG my_server_address;

/* Get the DNS Server at index 5 (zero based) into the Client list.  */
status =  nx_dns_server_get(&my_dns, 5, &my_server_addres);

/* If status is NX_SUCCESS a DNS Server was successfully
   returned.  */
```

nx_dns_server_remove

Remove an IPv4 DNS Server from the Client list

Prototype

```
UINT nx_dns_server_remove(NX_DNS *dns_ptr, ULONG server_address);
```

Description

This service removes an IPv4 DNS Server from the Client list.

Input Parameters

dns_ptr   Pointer to DNS control block.

server_address   IP address of DNS Server.

Return Values

NX_SUCCESS	(0x00)	DNS Server successfully removed
NX_DNS_SERVER_NOT_FOUND	(0xA9)	Server not in Client list
NX_DNS_BAD_ADDRESS_ERROR	(0xA4)	Null server address input
NX_PTR_ERROR	(0x07)	Invalid IP or DNS pointer.
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Remove the DNS Server at IP address is 202.2.2.13.  */
status =  nx_dns_server_remove(&my_dns, IP_ADDRESS(202,2,2,13));

/* If status is NX_SUCCESS a DNS Server was successfully
   removed.  */
```

nx_dns_server_remove_all

Remove all DNS Servers from the Client list

Prototype

```
UINT nx_dns_server_remove_all(NX_DNS *dns_ptr);
```

Description

This service removes all DNS Servers from the Client list.

Input Parameters

dns_ptr   Pointer to DNS control block.

Return Values

NX_SUCCESS	(0x00)	DNS Servers successfully removed
NX_DNS_ERROR	(0xA0)	Unable to obtain protection mutex
NX_PTR_ERROR	(0x07)	Invalid IP or DNS pointer.
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Remove all DNS Servers from the Client list.  */
status =  nx_dns_server_remove_all(&my_dns);

/* If status is NX_SUCCESS all DNS Servers were successfully removed.  */
```