



Amlogic Hailstorm V5.2.0 Release Note

AMLOGIC, Inc.

2518 Mission College Blvd
Santa Clara, CA 95054
U.S.A.
www.amlogic.com

AMLOGIC reserves the right to change any information described herein at any time without notice.
AMLOGIC assumes no responsibility or liability from use of such information.

Amlogic Openlinux Release Note

Content

1. Basic Information	3
1.1. INTRODUCTION	3
1.2. CHIP INFORMATION	5
1.3. REFERENCE PLATFORM	6
1.4. HOW TO GET CODE	7
1.5. HOW TO INTEGRATE THE CODE	8
1.6. DYNAMIC FINGERPRINT	9
1.7. HOW TO CONFIG DDP MS12 DTS DOLBY VISION AND HDCP	10
1.8. HOW TO BUILD CODE	11
1.9. DEVICE VENDOR SCS(SECURE BOOT v3)	14
1.10. SECURE MODE	15
1.11. FASTBOOT	16
1.12. HOW TO UPGRADE	17
1.12.1. all partitions	17
1.12.2. physical partitions	18
1.12.3. logical partitions	19
2. Test Report	20
2.1. AUTO REBOOT IN NORMAL TEMPERATURE	20
2.2. AUTO SHUTDOWN/SUSPEND IN NORMAL TEMPERATURE	20
2.3. 3D GAME BURNING TEST REPORT	20
2.4. MONKEY TEST TEST REPORT	21
2.5. FACTORYRESET TEST REPORT	21
2.6. A/V BURN TEST REPORT	22
2.7. DVB STRESS TEST	22
2.8. VIDEO FORMAT TEST REPORT	23
3. Tools version	26
4. NTS Known Issues	27
5. License version	29
6. License path	31

1. Basic Information

1.1. Introduction

This document is the release notes of Amlogic reference source codes aligned with Android S running on Amlogic S905X4/S905C2/S905Y4/S905C3/S805X2 reference hardware.

S905X4/S905C2/S905Y4/S905C3/S805X2 released the GTVS clean version.

S905X4/S905C2/S905Y4/S905C3 has Dolby MS12, DDP passthrough, and non-Dolby config.

S805X2 has non-Dolby config.

The purpose of this release is:

1. GTVS Clean.
 - (1) CTS(12.0 R6)
 - (2) GTS(10.0 R2)
 - (3) VTS(12.0 R6)
 - (4) CTS-verify(12.0 R6)
 - (5) CTS-on-gsi(12.0 R6)
 - (6) STS(2022-12)
 - (7) TVTS(2.5 R1)
 - (8) Android TV smoking(Youtube testing)
2. NTS cert (validation ninja 9)
3. Pre-certification
 - (1) VMX-IPTV Client E2E
 - (2) VMX-WEB Client E2E
 - (3) VMX-DVB Client E2E(DTVKit)
 - (4) Nagra TKL Simbad for S905X4(DTVKit)
 - (5) Nagra NOCS Simbad for S905C2(DTVKit)
 - (6) Nagra TKL for S905X4(CBS)
 - (7) Nagra NOCS for S905C2(CBS)
 - (8) Irdeto for S905C2/S905C3(Irdeto middleware)
 - (9) Irdeto for S905C3(DTVKit)
 - (10) DDP V4.8 for DVB
 - (11) MS12 V2 for DVB
 - (12) MS12 V1 DVB for S905X4
 - (13) Dolby vision v2.6
 - (14) DTS-HD
 - (15) ART
4. Full function ready:
 - (1) Component compatibility
 - (1) HDMI
 - (2) CVBS
 - (3) WIFI
 - (4) BT
 - (5) Ethernet
 - (6) Bluetooth
 - (7) USB
 - (8) Remote
 - (9) Spdif
 - (2) Suspend/Resume
 - (3) Multi-media functionality.
 - (4) Multi-instance.
 - (5) Widevine CAS.
 - (6) Display functionality.

Amlogic Openlinux Release Note

- (7) PQ/DI.
- (8) HDR10.
- (9) Dolby Vision.
- (10) System functionality.
- (11) Audio-output.
- (12) Secure boot V3.
- (13) Fastboot
- (14) A/B update
- (15) AVB Anti-roll back
- (16) HDMI CTS 2.0
- (17) HDMI CEC
- (18) HDR10+
- (19) HDCP 1.4/2.3
- (20) CBS

5. Performance

- (1) Benchmark
- (2) UX
- (3) APP launch speed
- (4) Video start/Switch speed
- (5) Memory usage

6. DTVKit

- (1) DVB-C Program search
- (2) DVB-S/DVB-S2 Program search
- (3) DVB-T/DVB-T2 Program search
- (4) Channel auto search
- (5) Channel manual search
- (6) NIT search
- (7) MHEG5
- (8) Teletext
- (9) PVR
- (10) TimeShift
- (11) subtitle
- (12) Program Edit
- (13) LCN
- (14) EPG
- (15) Channels Lock
- (16) Parental Lock
- (17) AD
- (18) Info Banner
- (19) Aspect Ratio
- (20) update channel
- (21) Date、Time
- (22) Audio language
- (23) Switch Channel
- (24) FCC/PIP

Amlogic Openlinux Release Note

1.2. Chip Information

S905X4/S905C2/S905Y4/S905C3/S805X2 :

We choose **S905X4/S905Y4/S805X2** reference platform as our major developing and testing platforms for this release. **S905X4/S905Y4/S805X2** OTT and VMX ultra w/ DTVkit Hybrid have been verified and certified, **S905C2/S905C3** are the family chip and use the same codebase.

Item	S905X4/S905C2	S805X2
CPU	Quad-core ARM Cortex-A55	Quad-core ARM Cortex-A35
GPU	ARM Mali-G31 MP2	ARM Mali-G31 MP2
Memory	32-bit DDR3/4/3L, LPDDR3/4	32-bit DDR3/4/3L, LPDDR4
Video decoding	AV1/H.265/VP9/AVS2-P2 to 4k@60fps	AV1/H.265/VP9/AVS2-P2 to 1080p@60fps
Video Encoding	H.265/JPEG to 1080p@60fps	SW encoder
HDMI-TX	4k60hz	1080p60hz
AV output	CVBS	CVBS
Ethernet	10M/100M/1000M	10M/100M
IP License	Dolby Audio/DTS/Dolby Vision	Dolby Audio/DTS
Demux	Support	Support

Item	S905Y4/S905C3
CPU	Quad-core ARM Cortex-A35
GPU	ARM Mali-G31 MP2
Memory	32-bit DDR3/4/3L, LPDDR4
Video decoding	AV1/H.265/VP9/AVS2-P2 to 4k@60fps
Video Encoding	SW encoder
HDMI-TX	4k60hz
AV output	CVBS
Ethernet	10M/100M
IP License	Dolby Audio/DTS/Dolby Vision
Demux	Support

Amlogic Hailstorm V5.2.0 Release Note

1.3. Reference Platform

Mbox:

Ohm(S905X4)
EMMC,WIFI QCA6174 ,DDR4 2GB

Ohmcas(S905C2)
EMMC,WIFI QCA6174 ,DDR4 2GB

Oppen(S905Y4)
EMMC,WIFI QCA6174 ,DDR4 2GB

Oppencas(S905C3)
EMMC,WIFI QCA6174 ,DDR4 2GB

Planck(S805X2)
EMMC,WIFI QCA6174 ,DDR4 1GB

Planck_gtv(S805X2)
EMMC,WIFI QCA6174 ,DDR4 1.5GB

Amlogic Openlinux Release Note

1.4. How to Get Code

You can download Android S source code by running the following repo commands:

ODM or OEM

Note: Permission for downloading code

1. Google server(Whole code that can build the final firmware, Kernel/uboot are the binary)
2. Amlogic Openlinux server(Kernel/uboot source code)

1. use below command to get the code in google server(apply the license from Google):

```
$cd~/<your-google-repo-dir>/  
$repo init -u  
https://partner-android.googlesource.com/platform/vendor/pdk/ohm/ohm-userdebug/manifest  
-b builds/s-tv-amlogic-hybrid-release/STTC.230104.002  
$repo sync
```

2. use below command to get the code in amlogic server(apply the license from Amlogic)

```
$cd~/<your-amlogic-repo-dir>/  
$repo init -u ssh://git@openlinux.amlogic.com/s-amlogic/platform/manifest.git -b s-amlogic -m  
openlinux/ott/amlogic/s-amlogic-source-20230106-gtvs.xml  
$repo sync
```

Notice: Oversea customer use below command:

```
$cd~/<your-amlogic-repo-dir>/  
$repo init -u ssh://git@openlinux2.amlogic.com/s-amlogic/platform/manifest.git -b s-amlogic  
-m openlinux/ott/amlogic/s-amlogic-source-20230106-gtvs.xml  
$repo sync
```

Needed storage space: need about 200G storage space.

Amlogic Openlinux Release Note

1.5. How to integrate the code

Some customers need to build the UBoot/kernel source code . Use the below commands to integrate the code:

```
$cd ~/<your-amlogic-repo-dir>/
$cp -rf bootloader <your-google-repo-dir>/
cp -rf build <your-google-repo-dir>/
cp -rf common/ <your-google-repo-dir>/
cp -rf device/amlogic/ohmcas <your-google-repo-dir>/device/amlogic/
cp -rf device/amlogic/ohmcas-kernel <your-google-repo-dir>/device/amlogic/
cp -rf device/amlogic/oppencas <your-google-repo-dir>/device/amlogic/
cp -rf device/amlogic/oppencas-kernel <your-google-repo-dir>/device/amlogic/
cp -rf device/amlogic/ohmcas2 <your-google-repo-dir>/device/amlogic/
cp -rf vendor/wifi_driver <your-google-repo-dir>/vendor/
cp -rf hardware/amlogic/media_modules/ <your-google-repo-dir>/hardware/amlogic/
cp -rf vendor/amlogic/common/gpu/ <your-google-repo-dir>/vendor/amlogic/common/
cp -rf vendor/amlogic/common/apps/Updater <your-google-repo-dir>/vendor/amlogic/common/apps/
cp -rf vendor/amlogic/common/tdk_linuxdriver/ <your-google-repo-dir>/vendor/amlogic/common/
cp -rf vendor/amlogic/common/pre_submit_for_google <your-google-repo-dir>/vendor/amlogic/common/
cp -rf vendor/amlogic/common/patches <your-google-repo-dir>/vendor/amlogic/common/
cp -rf vendor/amlogic/common/external/exfat <your-google-repo-dir>/vendor/amlogic/common/external/
cp -rf vendor/amlogic/common/external/ntfs-3g <your-google-repo-dir>/vendor/amlogic/common/external/
cp -rf vendor/amlogic/ohmcas/ <your-google-repo-dir>/vendor/amlogic/
cp -rf vendor/amlogic/ohmcas2/ <your-google-repo-dir>/vendor/amlogic/
cp -rf vendor/amlogic/oppencas/ <your-google-repo-dir>/vendor/amlogic/

cd <your-google-repo-dir>/build/make/; git checkout -f
```

Amlogic Openlinux Release Note

1.6. Dynamic fingerprint

Although Android TV devices are similar, their system properties can differ. To help reduce the build load, the Android TV OEM partition has been released for use with Android TV on Android 12.

```
1. Change device/amlogic/oppen/oem/oem.prop
. build/envsetup.sh
lunch oppen-user
make custom_images -j8

2. copy out/target/product/oppen/oem.img to device/amlogic/oppen/oem/

As ohm.
```

Amlogic Openlinux Release Note

1.7. How to config DDP MS12 DTS Dolby Vision and HDCP

Dolby Digital Plus, Dolby ms12, DTS or Dolby vision is stored in the oem partition.

1. Copy libHwAudio_dcvdec.so to vendor/amlogic/common/prebuilt/libstagefrighthw/lib/libHwAudio_dcvdec.so
2. Copy libdolbyps12.so to device/amlogic/common/dolby_ms12/install/encrypted_lib/libdolbyps12.so
3. Copy libdolbyps12.so(ms12v1) to device/amlogic/common/dolby_ms12/install/encrypted_lib/ms12v1/libdolbyps12.so
4. Copy libHwAudio_dtshd.so to vendor/amlogic/common/prebuilt/libstagefrighthw/lib/libHwAudio_dtshd.so
5. Copy dovi.ko to device/amlogic/ohm/files/dovi.ko , as ohmcas/oppen etc.
6. Copy dovi_fw.bin to device/amlogic/ohm/dovi_fw.bin , as ohmcas/oppen etc.
7. Copy hdcp_tx22 and firmware.le to vendor/amlogic/restricted_libs/hdcp_tx22/

Enable Dolby Digital Plus, Dolby ms12, DTS or Dolby vision Macro.

```
TARGET_BUILD_WITH_DOVI :=true
TARGET_DOLBY_VERSION := ms12_v2  #or set ddp_only
TARGET_DTS_VERSION :=dtshd
```

Generate OEM partition

```
. build/envsetup.sh
lunch ohm_hybrid-user
make custom_images -j8

copy out/target/product/ohm/oem.img to device/amlogic/ohm/oem/oem_hybrid/

As oppen etc.
```

Amlogic Openlinux Release Note

1.8. How to Build Code

Before building the code, you must execute this command at the code root directory for merge some important patches.

```
./vendor/amlogic/common/patches/detect.sh
```

Build Bootloader

1. ohm_hybrid(S905X4)

```
cd bootloader/u-boot-repo/  
./mk sc2_ah212 --avb2 --vab  
cp build/u-boot.bin.signed ../../device/amlogic/ohm/bootloader.img  
cp build/u-boot.bin.sd.bin.signed ../../device/amlogic/ohm/upgrade/  
cp build/u-boot.bin.usb.signed ../../device/amlogic/ohm/upgrade/
```

2. ohmcas(S905C2)

```
cd bootloader/u-boot-repo/  
./mk sc2_ah232 --avb2 --vab  
cp build/u-boot.bin.signed ../../device/amlogic/ohmcas/bootloader.img  
cp build/u-boot.bin.sd.bin.signed ../../device/amlogic/ohmcas/upgrade/  
cp build/u-boot.bin.usb.signed ../../device/amlogic/ohmcas/upgrade/
```

3. oppen_hybrid(S905Y4)

```
cd bootloader/u-boot-repo/  
./mk s4_ap222 --avb2 --vab  
cp build/u-boot.bin.signed ../../device/amlogic/oppen/bootloader.img  
cp build/u-boot.bin.sd.bin.signed ../../device/amlogic/oppen/upgrade/  
cp build/u-boot.bin.usb.signed ../../device/amlogic/oppen/upgrade/
```

4. oppencas(S905C3)

```
cd bootloader/u-boot-repo/  
./mk s4_ap232 --avb2 --vab  
cp build/u-boot.bin.signed ../../device/amlogic/oppencas/bootloader.img  
cp build/u-boot.bin.sd.bin.signed ../../device/amlogic/oppencas/upgrade/  
cp build/u-boot.bin.usb.signed ../../device/amlogic/oppencas/upgrade/
```

5. planck/planck_gtv(S805X2)

```
cd bootloader/u-boot-repo/  
./mk s4_aq222 --avb2 --vab  
cp build/u-boot.bin.signed ../../device/amlogic/planck/bootloader.img  
cp build/u-boot.bin.sd.bin.signed ../../device/amlogic/planck/upgrade/  
cp build/u-boot.bin.usb.signed ../../device/amlogic/planck/upgrade/
```

Noticed: Bootloader disabled fastboot unlock function by default. Android VTS/GSI or debug need enable fastboot unlock function through --fastboot-write. Like ./mk s4_ap222 --avb2 --vab --fastboot-write.

Build Kernel

Amlogic Openlinux Release Note

1. ohm_hybrid(S905X4)

```
./device/amlogic/common/kernelbuild/mk ohm -v 5.4 -t user
```

2. ohmcas(S905C2)

```
./device/amlogic/common/kernelbuild/mk ohmcas -v 5.4 -t user
```

3. oppen_hybrid(S905Y4)

```
./device/amlogic/common/kernelbuild/mk oppen -v 5.4 -t user
```

4. oppencas(S905C3)

```
./device/amlogic/common/kernelbuild/mk oppencas -v 5.4 -t user
```

5. planck_gtv(S805X2)

```
./device/amlogic/common/kernelbuild/mk planck -v 5.4 -t user
```

6. planck(S805X2)

```
export KERNEL_A32_SUPPORT=true  
./device/amlogic/common/kernelbuild/mk planck -v 5.4 -t user
```

Build Android

1. ohm_hybrid(S905X4)

```
. build/envsetup.sh  
lunch ohm_hybrid-user  
make -j8
```

2. ohmcas_gtv(S905C2)

```
. build/envsetup.sh  
lunch ohmcas_gtv-user  
make -j8
```

3. oppen_hybrid(S905Y4)

```
. build/envsetup.sh  
lunch oppen_hybrid-user  
make -j8
```

4. oppencas_gtv(S905C3)

```
. build/envsetup.sh  
lunch oppencas_gtv-user  
make -j8
```

5. planck_gtv(S805X2)

Amlogic Openlinux Release Note

```
. build/envsetup.sh
lunch planck_gtv-user
make -j8
```

6. planck(S805X2)

```
. build/envsetup.sh
export KERNEL_A32_SUPPORT=true
lunch planck-user
make -j8
```

Noticed: Android S will start to use kernel 5.4 and we setup a new kernel and modules build way named standalone build.

Standalone build is a standard kernel and modules build way. We need separate Android and Kernel builds. Android S has two UI: Waston UI(Android TV) and Amati UI(Google TV). For Hailstorm project, Please choose Amati UI for S905X4 and S905Y4. Waston UI for S805X2.

Lunch project name	Type
ohm	OTT ATV
ohm_gtv	OTT GTV
ohm_hybrid	DVB GTV
ohmcas	DVB ATV
ohmcas_gtv	DVB GTV
oppen	OTT ATV
oppen_gtv	OTT GTV
oppen_hybrid	DVB GTV
oppencas	DVB ATV
oppencas_gtv	DVB GTV
planck	OTT ATV
planck_gtv	OTT GTV

1.9. Device Vendor SCS(Secure boot v3)

Device Vendor SCS(Secure boot v3), please refer to the documents.

- <Amlogic S905X4 Series Secure Boot User Guide>
- <Amlogic S905Y4 Series Secure Boot User Guide>
- <Amlogic Linux SCS Signing ToolUserGuide>

Amlogic Hailstorm V5.2.0 Release Note

1.10. Secure Mode

This document provides required security mode configuration guidelines to prevent system data from being tampered with. Please refer the documents:

<Security Mode Configuration Guide>

Amlogic Hailstorm V5.2.0 Release Note

Amlogic Openlinux Release Note

1.11. Fastboot

We **MUST** update adb/fastboot version to 29.0.1-5644136 or 29.0.1-5644136+. Otherwise there are lots of adb/flash issues.

adb:

```
Android Debug Bridge version 1.0.41  
Version 29.0.1-5644136
```

fastboot

```
fastboot version 29.0.1-5644136
```

You can download latest SDK Platform-Tools from

<https://developer.android.com/studio/releases/platform-tools.html#downloads>

Amlogic Openlinux Release Note

1.12. How to Upgrade

There are 3 ways to update.

- Upgrade with USB burn tool
- Upgrade with OTA
- Upgrade with fastboot

1.12.1. all partitions

If you like to use our usb burn tool to update the images, it's the same as before. We have a fastboot flash-all script to update image, just like Android S. You need not care about the dynamic partitions.

Partition name	make command	image name	burning ways
all partitions	make otapackage	1.ohm-ota-xxxxxxx.zip 2.aml_upgrade_package.img 3.ohm-fastboot-xxxxxxx.zip	1.by OTA upgrade 2.by USB burning 3.by fastboot
	make	aml_upgrade_package.img	by USB burning

Amlogic Openlinux Release Note

1.12.2. physical partitions

In Android S, physical partitions are **bootloader**, **boot**, **logo**, **vendor_boot** etc.

Fastboot should be in **bootloader** mode when flashing these physical partitions.

Below is the way of burning each partitions:

Partition name	make command	image name	burning ways
boot	make bootimage	boot.img	fastboot flash boot boot.img
logo	make logoimg	logo.img	fastboot flash logo logo.img
uboot	./mk sc2_ah212 --avb2 --vab	u-boot.bin.signed	fastboot flash bootloader u-boot.bin.signed
odm_ext	make odm_ext_image	odm_ext.img	fastboot flash odm_ext odm_ext.img
vendor_boot	make vendorbootimage	vendor_boot.img	fastboot flash vendor_boot vendor_boot.img

Notes: execute 'fastboot flashing unlock' to unlock the device if you want to use fastboot commands.

Amlogic Openlinux Release Note

1.12.3. logical partitions

In Android S, logical partitions are **system**, **system_ext**, **vendor**, **odm**, **product**.
Fastboot should be in fastbootd mode when flashing these logical partitions.

Below is the way of burning each partitions:

Partition name	make command	image name	burning ways
system	make systemimage	system.img	fastboot flash system system.img
vendor	make vendorimage	vendor.img	fastboot flash vendor vendor.img
odm	make odmimage	odm.img	fastboot flash odm odm.img
product	make productimage	product.img	fastboot flash product product.img
system_ext	make systemextimage	system_ext.img	fastboot flash system_ext system_ext.img

Notes: execute 'fastboot flashing unlock' to unlock the device if you want to use fastboot commands.

2. Test Report

2.1. Auto Reboot in Normal Temperature

Test Platform	Test Case	Total test time	Test Result
AH212#175	Auto reboot	72H	Pass
AH212#186	Auto reboot	72H	Pass
AH212#197	Auto reboot	72H	Pass
AH212#237	Auto reboot	72H	Pass
AP222#200	Auto reboot	72H	Pass
AP222#224	Auto reboot	72H	Pass
AP222#228	Auto reboot	72H	Pass
AP222#231	Auto reboot	72H	Pass
AH212#200	uboot autoreboot	72H	Pass
AH212#238	uboot autoreboot	72H	Pass
AH212#248	uboot autoreboot	72H	Pass
AH212#249	uboot autoreboot	72H	Pass
AP222#146	uboot autoreboot	72H	Pass
AP222#164	uboot autoreboot	72H	Pass
AP222#313	uboot autoreboot	72H	Pass
AP222#319	uboot autoreboot	72H	Pass

2.2. Auto Shutdown/Suspend in Normal Temperature

Test Platform	Test Case	Total test time	Test Result
AH212#200	Auto shutdown	72H	Pass
AH212#238	Auto shutdown	72H	Pass
AH212#248	Auto shutdown	72H	Pass
AH212#249	Auto shutdown	72H	Pass
AP222#200	Auto shutdown	72H	Pass
AP222#224	Auto shutdown	72H	Pass
AP222#228	Auto shutdown	72H	Pass
AP222#231	Auto shutdown	72H	Pass
AH212#175	Auto suspend	72H	Pass
AH212#186	Auto suspend	72H	Pass
AH212#197	Auto suspend	72H	Pass
AH212#237	Auto suspend	72H	Pass
AP222#200	Auto suspend	72H	Pass
AP222#224	Auto suspend	72H	Pass
AP222#228	Auto suspend	72H	Pass
AP222#231	Auto suspend	72H	Pass

2.3. 3D Game burning Test Report

Test Platform	Test Case	Total test time	Test Result
AH212#175	3D Game	72H	Pass
AH212#186	3D Game	72H	Pass
AH212#197	3D Game	72H	Pass
AH212#237	3D Game	72H	Pass
AP222#200	3D Game	72H	Pass

Amlogic Openlinux Release Note

AP222#224	3D Game	72H	Pass
AP222#228	3D Game	72H	Pass
AP222#231	3D Game	72H	Pass

2.4. Monkey test Test Report

Test Platform	Test Case	Total test time	Test Result	Comments
AH212#200	Monkey test/300ms	72H	Pass	
AH212#238	Monkey test/300ms	72H	Pass	
AH212#248	Monkey test/300ms	72H	Pass	
AH212#249	Monkey test/300ms	72H	Pass	
AP222#146	Monkey test/300ms	72H	Pass	
AP222#164	Monkey test/300ms	72H	Pass	
AP222#313	Monkey test/300ms	72H	Pass	
AP222#319	Monkey test/300ms	72H	Pass	

Monkey Black list

com.droidlogic.PPPoEcom.droidlogic.PPPoE
com.droidlogic.miracast
com.droidlogic.mediacenter
com.droidlogic.otaupgrade
com.droidlogic.tvinput
com.hpplay.happyplay.aw
com.android.tv.settings
com.droidlogic.tv.settings
com.google.android.tungsten.setupwraith
com.google.android.gms
com.android.vending
com.google.android.youtube.tv
com.google.android.videos
com.google.android.tv.remote.service
com.google.android.tvrecommendations
com.google.android.gms.persistent
com.google.android.youtube.tv.recommendations
com.google.android.tv.frameworkpackagestubs
com.google.android.tvcom.droidlogic.videoplayer

2.5. FactoryReset Test Report

Test Platform	Test Case	Total test time	Test Result
AH212#200	Factory reset	72H	Pass
AH212#238	Factory reset	72H	Pass
AH212#248	Factory reset	72H	Pass
AH212#249	Factory reset	72H	Pass
AP222#200	Factory reset	72H	Pass
AP222#224	Factory reset	72H	Pass
AP222#228	Factory reset	72H	Pass
AP222#231	Factory reset	72H	Pass

Amlogic Openlinux Release Note

2.6. A/V Burn Test Report

Test Platform	Test Case	Total test time	Test Result
AH212#94	4K H265	72H	Pass
AH212#128	4K H265	72H	Pass
AH212#137	4K H265	72H	Pass
AH212#194	4K H265	72H	Pass
AP232#134	4K H265	72H	Pass
AH212#128	4K H264	72H	Pass
AH212#238	4K H264	72H	Pass
AP232#131	4K H264	72H	Pass
AH212#194	4K VP9	72H	Pass
AH212#249	4K VP9	72H	Pass
AP232#135	4K VP9	72H	Pass
AP232#130	4K AV1	72H	Pass
AH212#105	4K AV1	72H	Pass
AP222#176	4K AV1	72H	Pass
AP222#134	4K H265	72H	Pass
AP222#169	4K H264	72H	Pass
AP222#200	4K VP9	72H	Pass
AH212#120	Youtube	12H	Pass
AH212#194	Youtube	12H	Pass
AH212#120	Youtube	12H	Pass
AP222#99	Youtube	12H	Pass
AP222#188	full format	72H	Pass
AP222#159	full format	72H	Pass
AP222#169	full format	72H	Pass

2.7. DVB Stress Test

Test Platform	Test Case	Total test time	Test Result	Comments
AH212#637	Auto Search	72H	Pass	
AH212#640	Auto Search	72H	Pass	
AH212#126	Auto Search	72H	Pass	
AH212#169	Auto Search	72H	Pass	
AH212#166	4K Bitstream Longterm Playing	72H	Pass	
AH212#232	4K Bitstream Longterm Playing	72H	Pass	
AH212#126	4K Bitstream Longtime Playing	72H	Pass	
AH212#169	4K Bitstream Longtime Playing	72H	Pass	
AH212#166	Single freq. Channel Change	72H	Pass	
AH212#232	Single freq. Channel Change	72H	Pass	
AH212#126	Single freq. Channel Change	72H	Pass	
AH212#169	Single freq. Channel Change	72H	Pass	

Amlogic Openlinux Release Note

AH212#169	Multi freq. Channel Change	72H	Pass	
AH212#232	Multi freq. Channel Change	72H	Pass	
AH212#126	Multi freq. Channel Change	72H	Pass	
AH212#169	Subtitle Longterm Playing	72H	Pass	
AH212#166	Subtitle Longterm Playing	72H	Pass	
AH212#232	Subtitle Longterm Playing	72H	Pass	
AH212#126	Subtitle Longterm Playing	72H	Pass	
AH212#1	LongTime Playback(PIP)	72H	Pass	
AH212#2	LongTime Playback(PIP)	72H	Pass	
AH212#1	Program Switch(PIP)	72H	Pass	
AH212#2	Program Switch(PIP)	72H	Pass	
AH212#2	weak signal Longtime Playing	48H	Pass	

2.8. Video Format Test Report

Noticed: Please confirm the license before opening the multimedia format.

Extension	Codec Detail	Tested Resolution	Ohm/Ohmcas	Oppen/Oppencas	Planck
.3g2	H263	704x576	Support	Support	Support
.3gp	MPEG-4 Visual	640x480	Support	Support	Support
	MPEG-4	320x240	Support	Support	Support
	H263	320x276	Support	Support	Support
	H264	1920x1080	Support	Support	Support
.avi	AVC	1920x1080	Support	Support	Support
	M-JPEG	1024x576	Support	Support	Support
	RealMagic	720x480	Support	Support	Support
	MPEG-4	720x576	Support	Support	Support
	h264	1920x1080	Support	Support	Support
	FF mpeg MPEG4	640x480	Support	Support	Support
.dat	MPEG-1	352x288	Support	Support	Support
.evo	VC-1	1920x1080	Support	Support	Support
.f4v	AVC(H264)	1280x720	Support	Support	Support
.flv	Sorenson Spark	320x276	Support	Support	Support
	VP6	800x342	Support	Support	Support
.mp4	AVC(H264)	1920x1080	Support	Support	Support
	HEVC(H265)	1920x1080	Support	Support	Support
	4K HEVC(4K H265)	3840x2160	Support	Support	No support
	8K HEVC(8K H265)	8192x4320	Support	Support	No support

Amlogic Openlinux Release Note

	AV1	1920x1080	Support	Support	Support
	4K AV1	3840x2160	Support	Support	No support
	H263	176x144	Support	Support	Support
.m2ts	AVC	1920x1080	Support	Support	Support
	VC-1	1920x1080	Support	Support	Support
.m2v	MPEG-2	480x576	Support	Support	Support
.m4v	AVC	1280x720	Support	Support	Support
.mkv	WMV3	1280x720	Support	Support	Support
	MPEG-4 Visual	1920x1080	Support	Support	Support
	AVC	1920x1080	Support	Support	Support
	4K HEVC(4K H265)	3840x2160	Support	Support	No support
	8K HEVC(8K H265)	8192x4320	Support	Support	No support
	VP8	1920x1080	Support	Support	Support
	VP9	1920x1080	Support	Support	Support
.mov	MPEG-4 Visual	1280x720	Support	Support	Support
	mjpa	640x480	Support	Support	Support
	H263	320x240	Support	Support	Support
	M-JPEG	640x480	Support	Support	Support
	AVC(H264)	1920x1080	Support	Support	Support
	4K H264	3840x2160	Support	Support	No support
.mpeg	MPEG-2	1920x1080	Support	Support	Support
	VC-1	1920x1080	Support	Support	Support
	MPEG-1	720x576	Support	Support	Support
.mts	AVC	1440x1080	Support	Support	Support
.ogm	XVID	640x480	Support	Support	Support
.PMP	H264	480x272	Support	Support	Support
.tp	MPEG-2	1920x1088	Support	Support	Support
.ts	HEVC(H265)	1920x1080	Support	Support	Support
	4K HEVC(4K H265)	3840x2160	Support	Support	No support
	8K HEVC(8K H265)	8192x4320	Support	Support	No support
	MPEG-1	1920x1080	Support	Support	Support
	avs	720x576	Support	Support	Support
	avs+	1920x1080	Support	Support	Support
	avs2	3840x2160	Support	Support	No support
	AVC	1920x1080	Support	Support	Support
	MPEG-2	1920x1080	Support	Support	Support
.vob	MPEG-2	720x576	Support	Support	Support
.wmv	WMV1	640x480	Support	Support	Support
	WMV2	768x432	Support	Support	Support
	WMV3	1920x1080	Support	Support	Support
.webm	VP8	1920x1080	Support	Support	Support
	VP9	1920x1080	Support	Support	Support
	4K VP9	3840x2160	Support	Support	No support
	8K VP9	8192x4320	Support	Support	No support
	AV1	1920x1080	Support	Support	Support
4K	AVC(H264)	3840x2160	Support	Support	No support
	HEVC(H265)	3840x2160	Support	Support	No support

Amlogic Openlinux Release Note

	VP9	3840x2160	Support	Support	No support
	AV1	3840x2160	Support	Support	No support
8K	HEVC(H265)	8192x4320	Support	Support	No support
	VP9	8192x4320	Support	Support	No support
	AV1	7680x4320	Support	Support	No support

Amlogic Hailstorm V5.2.0 Release Note

3. Tools version

Tool name	version
USB burning tool	Aml_Burn_Tool_V3.2.6
Customization	Amlogic customization V.2.1.3
Linux Secure boot V3	Aml_Linux_SCS_SignTool V2.2.1
adb	1.0.41
fastboot	29.0.1
Kernel tool chain	gcc-linaro-6.3.1-2017.02-x86_64_arm-linux-gnueabi gcc-linaro-6.3.1-2017.02-x86_64_aarch64-linux-gnu

4. NTS Known Issues

Issue key	Summary	More info
AMCNM-159	vv_Ninja 9 FastPlayback performance does not meet requirements.	Case impacted: FPSTART-**, FPSTART-FRAME-LIMIT With the default value minVideoFramesForPlaybackStart=10, a few FPSTART-** test cases can't be passed. From Netflix's investigation, Amlogic needs to use set minVideoFramesForPlaybackStart=11 for Hailstorm SDK5.2 for downstream ODM scaling reference. If set the value to 11, FPSTART-FRAME-LIMIT would be failed. Need to file a ticket for the failure.
AMCNM-166	(AUDIO-LAT-UI-*) Ninja vv9 UI Audio latency doesn't meet Netflix requirements.	In Ninja vv9 Hailstorm 5.2 SDK, AUDIO UIAudio latency test result did improve from 200ms+ in Ninja 8 to pass/marginal fail with -35/175ms requirement depending on Sink device setup. However, it could not pass if it use more strict -40/40 with system offset using Golden EP reference or Eleven -40/40 with offset (range of 80ms) - NTS with Golden EP reference or Eleven fail -35/175 without offset (range of 210ms) - NTS with ANY EP Setup may pass without offset on the 175ms boundary depending on Sink device setup.
AMCNM-160	(DPI-201-TC6) Manual verification step for CVBS analog video output activeVideoOutput width/height are incorrect	This issue only impacts CVBS supported devices. In order to fix AMDFG-27 (CVBS output blurry), we modified the screen size to FHD when using CVBS output. The side effect is Netflix UI and stream resolution can't be limited to SD. It's a common issue with Android OS 12+ devices, awaiting a solution from Google.
AMDF-45	SWPLAYER-PLAYBACK-QUALITY* Inconsistent test result due to NRDP reporting frame drop or EP reporting frame drop/freeze	SWPLAYER-PLAYBACK-QUALITY tests for all resolutions 180 to 720p have inconsistent results if running the test multiple times. in low resolution: 180, the failure is mainly due to the NRDP SDK instrumentation showing that, at resolution 180, 1 dropped video frame at the beginning of playback while EP reported no frame drop during the playback. Usually, this 1 drop of the frame indicates the start is late, the video and audio are not synced and need to drop one video frame to sync up.
AMCNM-133	Ninja9 case SYSTEM-GLES32-ADDITIONAL-EXTENSIONS fail.	New features can't catch up with the current release, planned to be implemented from Android T. Partners need to file a ticket to add inheritable exemption for ATV S+ Ninja vv_9 for official submission.

Important Note:

- (1) If without MS12, Dolby Passthrough configuration is used, projects need to configure PDM, set "Dolby Digital Plus 5.1 Audio Support" to Passthrough.
- (2) For Non-Dolby devices, projects need to file a major ticket on AUDIO-023-TC12 SPDIF output silence when Netflix plays Dolby 5.1 audio track, due to lack of Dolby license.

Amlogic Openlinux Release Note

- (3) When long time tests EP sync with MS12 configuration, there might be an AVSync drifting issue caused by certain TVs. Usually, hotplug HDMI cable or reset audio output format manually will recover it from the bad state.
- (4) For AUDIO-MEDIAVOL-** test cases, when output MAT different sink devices the quality is different, AVR looks better than TV. If you don't have a good TV, suggest using AVR to test those test cases.
- (5) SONY TV doesn't support HDR10 (10bit) by default, users need to turn on "Enhanced 4K format" in "External inputs -> HDMI signal format" to enable HDR10. Reference: <https://www.sony.com/electronics/support/articles/00141961>
- (6) Netflix strongly recommended to use the "Always HDR" policy as REF does. If projects want to keep playback HDR, when Netflix foreground the device should still work on "Always HDR" mode and there should be no SDR<->HDR transition happens in Netflix APP.
- (7) With validation ninja_9, needs apply patch modify minVideoFramesForPlaybackStart=11 to pass all FPSTART-60FP-* case.
- (8) Need apply patch for MGKID v2 integration ,make sure case MGKID-VALIDATE-MGKDAT pass.
- (9) Launching Netflix from Remote Button,please refer link <https://docs.netflixpartners.com/docs/nrdp/dev/android-tv/ninja90/application-management/launching-netflix-from-remote-button/>
If your remote supports both BT and IR signal, make sure both are correct especially when BT is disconnected. A fail case with REF remote is IR sent "POWER" instead of "NETFLIX".
- (10) Sometimes there are changes in the test case during the test process, resulting in the test failing. Please keep communicating with Amlogic or Netflix.

Amlogic Openlinux Release Note

5. License version

Licensed Feature Name	Version	Document version
Dolby Digital Plus for Android	v20221010	In firmware Readme text
Dolby Digital for Android	v20200723	In firmware Readme text
Dolby MS12 V1.3.2 for android	v20220624	In firmware Readme text
Dolby MS12 V2.4 for android	v20220805	Amlogic_Dolby_MS12_v2_release_note_V0.5
DTS-HD for android	v20220614	In firmware Readme text
DRA Decoder for android	v20210728	In firmware Readme text
Secure OS TDK	TDK is included in the code	TDK Integration User Guide (3.3) S905X4 Secure Key Provision User Guide (3.3) S905Y4 Secure Key Provision User Guide (3.3)
Widevine	L1/L3	Amlogic WideVine Integration User Guide v0.9
Playready		Amlogic PlayReady Integrate User Guide v1.32
Dolby Vision 2.6 for Android kernel5.4.180 64bit	Ohm kernel5.4.180 64bit dovi.ko stb_release_20220607 dovi_fw_u2019.bin release-20210413 Oppen kernel5.4.180 64bit dovi.ko stb_release_20220607 dovi_fw_u2019.bin release-20210413	Amlogic DolbyVision Release (v0.5)
HDCP 1.4 for HDMI TX for Android	v20180408	Amlogic_HDCP1.4_Tx_Release_Note_V0.1
HDCP 2.X for HDMI TX for Android	v20201212	Amlogic_HDCP2.2_Tx_Release_Note_V1.0
Verimatrix	vendor/vmx/bootloader(m9x4/openlin ux-android-s: 0a27f9c891ebb2850a5a464c67f10d7 326b46968) vendor/vmx/bootloader(m9y4/openlin ux-android-s: c370e41552d88193b118f219757a5d 1b1a8f8467) vendor/amlogic/prebuild/verimatrix(r- amlogic: 66411743efaa0fe271aec7eed94d9c9 b43879670) vmx/sdk-rel(m9x4-rel: 7dbf941542b19e359dc63e9b5349c0 56e82507ab) vmx/sdk-rel(m9y4-rel: ea3f467a4f2c2d82b3449f6242e1346 18e1ad8f7) vendor/vmx/vmx-rel(master: a0fbf908c1a3f8019dae101395f217df 651f659a)	OHM S905X4 Verimatrix Android SDK Integration User Guide (2.7) S905X4 Verimatrix Android Client Integration User Guide (5.3) Amlogic CAS - Verimatrix Adaption API Guide-v1.0 Oppen S905Y4 Verimatrix Android Client Integration User Guide (8.1) S905Y4 Verimatrix Android SDK Integration User Guide (1.7) Amlogic CAS - Verimatrix Adaption API Guide-v1.0 Planck S805X2 Verimatrix Android Client Integration User Guide (8.3)
Nagra TKL/NOCS	nagra-sdk(projects/openlinux/v2.2: 2628334f3b0fe13457e2553971ea841 218eaa20b)	OHM S905X4 Nagra TKL Android MediaCasV2 Integration User Guide (1.1)

Amlogic Openlinux Release Note

	nagra-cashal(projects/openlinux/v3.0:d3c9098eeb782527370e57a369a27ab96cbb2efd)	S905X4 Nagra TKL Android SDK Integration User Guide (1.3)
	nagra-sdk(projects/openlinux/v3.4:26d62ec6cf8d50ad1a36a49420900377ea683e39)	S905C2 Nagra NOCS Android MediaCasV2 Integration User Guide (1.1)
		S905C2 Nagra NOCS Android SDK Integration User Guide (1.1)

Amlogic Hailstorm V5.2.0 Release Note

6. License path

Licensed Files	Path
HDCP TX firmware.le	/odm/etc/firmware/firmware.le
Dolby	/oem/lib/libHwAudio_dcvdec.so
MS12 V2	/oem/lib/ms12/libdolbys12.so
MS12 V1	/oem/lib/libdolbys12.so
Dolby vision	/oem/overlay/dovi.ko /oem/firmware/dovi_fw.bin