

# ***Experiment in Compiler Construction Parser design***

School of Information and Communication  
Technology  
Hanoi university of technology


# Content

---

- Overview
- KPL grammar
- Parser implementation

# Tasks of a parser


---




- Check the syntactic structure of a given program
  - Syntactic structure is given by Grammar
- Invoke semantic analysis and code generation
  - In an one-pass compiler, this module is very important since this forms the skeleton of the compiler

# Syntax diagram of KPL

program





block




# Syntax diagram of KPL


---




# Syntax diagram of KPL



# Syntax diagram of KPL




# Syntax diagram of KPL






# Syntax diagram of KPL



# Syntax diagram of KPL



## **KPL Grammar in BNF**

---

- Construct a grammar G based on syntax diagram
- Perform left recursive elimination (already)
- Perform left factoring

# KPL Grammar in BNF

---

01) Prog ::= KW\_PROGRAM TK\_IDENT SB\_SEMICOLON Block SB\_PERIOD

02) Block ::= KW\_CONST ConstDecl ConstDecls Block2

03) Block ::= Block2

04) Block2 ::= KW\_TYPE TypeDecl TypeDecls Block3

05) Block2 ::= Block3

06) Block3 ::= KW\_VAR VarDecl VarDecls Block4

07) Block3 ::= Block4

08) Block4 ::= SubDecls Block5 | Block5

09) Block5 ::= KW\_BEGIN Statements KW\_END

# KPL Grammar in BNF

---

- 10) `ConstDecls ::= ConstDecl ConstDecls`
- 11) `ConstDecls ::= ε`
- 12) `ConstDecl ::= TK_IDENT SB_EQUAL Constant SB_SEMICOLON`
- 13) `TypeDecls ::= TypeDecl TypeDecls`
- 14) `TypeDecls ::= ε`
- 15) `TypeDecl ::= TK_IDENT SB_EQUAL Type SB_SEMICOLON`
- 16) `VarDecls ::= VarDecl VarDecls`
- 17) `VarDecls ::= ε`
- 18) `VarDecl ::= TK_IDENT SB_COLON Type SB_SEMICOLON`
- 19) `SubDecls ::= FunDecl SubDecls`
- 20) `SubDecls ::= ProcDecl SubDecls`
- 21) `SubDecls ::= ε`

# KPL Grammar in BNF

---

- 22) FunDecl ::= KW\_FUNCTION TK\_IDENT Params SB\_COLON  
BasicType  
SB\_SEMICOLON Block SB\_SEMICOLON
- 23) ProcDecl ::= KW\_PROCEDURE TK\_IDENT Params SB\_SEMICOLON  
Block  
SB\_SEMICOLON
- 24) Params ::= SB\_LPAR Param Params2 SB\_RPAR
- 25) Params ::=  $\epsilon$
- 26) Params2 ::= SB\_SEMICOLON Param Params2
- 27) Params2 ::=  $\epsilon$
- 28) Param ::= TK\_IDENT SB\_COLON BasicType
- 29) Param ::= KW\_VAR TK\_IDENT SB\_COLON BasicType

# KPL Grammar in BNF

---

- 30) `Type ::= KW_INTEGER`
- 31) `Type ::= KW_CHAR`
- 32) `Type ::= TK_IDENT`
- 33) `Type ::= KW_ARRAY SB_LSEL TK_NUMBER SB_RSEL KW_OF Type`
  
- 34) `BasicType ::= KW_INTEGER`
- 35) `BasicType ::= KW_CHAR`
  
- 36) `UnsignedConstant ::= TK_NUMBER`
- 37) `UnsignedConstant ::= TK_IDENT`
- 38) `UnsignedConstant ::= TK_CHAR`
  
- 40) `Constant ::= SB_PLUS Constant2`
- 41) `Constant ::= SB_MINUS Constant2`
- 42) `Constant ::= Constant2`
- 43) `Constant ::= TK_CHAR`
  
- 44) `Constant2 ::= TK_IDENT`
- 45) `Constant2 ::= TK_NUMBER`

# KPL Grammar in BNF

---

46) `Statements ::= Statement Statements2`

47) `Statements2 ::= KW_SEMICOLON Statement Statements2`

48) `Statements2 ::=  $\epsilon$`

49) `Statement ::= AssignSt`

50) `Statement ::= CallSt`

51) `Statement ::= GroupSt`

52) `Statement ::= IfSt`

53) `Statement ::= WhileSt`

54) `Statement ::= ForSt`

55) `Statement ::=  $\epsilon$`



# KPL Grammar in BNF

---

- 56) AssignSt ::= Variable SB\_ASSIGN Expression
- 57) CallSt ::= KW\_CALL ProcedureIdent Arguments
- 58) GroupSt ::= KW\_BEGIN Statements KW\_END
- 59) IfSt ::= KW\_IF Condition KW\_THEN Statement ElseSt
- 60) ElseSt ::= KW\_ELSE Statement
- 61) ElseSt ::=  $\epsilon$
- 62) WhileSt ::= KW\_WHILE Condition KW\_DO Statement
- 63) ForSt ::= KW\_FOR TK\_IDENT SB\_ASSIGN Expression  
KW\_TO Expression KW\_DO Statement

# KPL Grammar in BNF

---

64) `Arguments ::= SB_LPAR Expression Arguments2 SB_RPAR`

65) `Arguments ::=  $\epsilon$`

66) `Arguments2 ::= SB_COMMA Expression Arguments2`

67) `Arguments2 ::=  $\epsilon$`

68) `Condition ::= Expression Condition2`

69) `Condition2 ::= SB_EQ Expression`

70) `Condition2 ::= SB_NEQ Expression`

71) `Condition2 ::= SB_LE Expression`

72) `Condition2 ::= SB_LT Expression`

73) `Condition2 ::= SB_GE Expression`

74) `Condition2 ::= SB_GT Expression`

# KPL Grammar in BNF

---

- 75) `Expression ::= SB_PLUS Expression2`
- 76) `Expression ::= SB_MINUS Expression2`
- 77) `Expression ::= Expression2`
  
- 78) `Expression2 ::= Term Expression3`
  
- 79) `Expression3 ::= SB_PLUS Term Expression3`
- 80) `Expression3 ::= SB_MINUS Term Expression3`
- 81) `Expression3 ::= ε`
  
- 82) `Term ::= Factor Term2`
  
- 83) `Term2 ::= SB_TIMES Factor Term2`
- 84) `Term2 ::= SB_SLASH Factor Term2`
- 85) `Term2 ::= ε`

# KPL Grammar in BNF

---

- 86) `Factor ::= TK_NUMBER`
- 87) `Factor ::= TK_CHAR`
- 88) `Factor ::= TK_IDENT Indexes`
- 89) `Factor ::= TK_IDENT Arguments`
- 90) `Factor ::= SB_LPAR Expression SB_RPAR`
  
- 91) `Variable ::= TK_IDENT Indexes`
- 92) `FunctionApplication ::= TK_IDENT Arguments`
  
- 93) `Indexes ::= SB_LSEL Expression SB_RSEL Indexes`
- 94) `Indexes ::= ε`

# Implemetation

---

- KPL is a LL(1) language
- design a top-down parser
  - *lookAhead* token
  - Parsing terminals
  - Parsing non-terminals
    - Constructing a parsing table
      - Computing FIRST() and FOLLOW()

# lookAhead token

---

- Look ahead the next token

```
Token *currentToken;    // Token vừa đọc  
Token *lookAhead;      // Token xem trước
```

```
void scan(void) {  
    Token* tmp = currentToken;  
    currentToken = lookAhead;  
    lookAhead = getValidToken();  
    free(tmp);  
}
```

# Parsing terminal symbol

---

```
void eat(TokenType tokenType) {  
    if (lookAhead->tokenType == tokenType) {  
        printToken(lookAhead);  
        scan();  
    } else  
        missingToken(tokenType, lookAhead->lineNo, lookAhead->colNo);  
}
```

# Invoking parser

---

```
int compile(char *fileName) {  
    if (openInputStream(fileName) == IO_ERROR)  
        return IO_ERROR;  
  
    currentToken = NULL;  
    lookAhead = getValidToken();  
  
    compileProgram();  
  
    free(currentToken);  
    free(lookAhead);  
    closeInputStream();  
    return IO_SUCCESS;  
}
```



# Parsing non-terminal symbol

---

Example: **Program**

**Prog ::= KW\_PROGRAM TK\_IDENT SB\_SEMICOLON Block SB\_PERIOD**

```
void compileProgram(void) {  
    assert("Parsing a Program ....");  
    eat(KW_PROGRAM);  
    eat(TK_IDENT);  
    eat(SB_SEMICOLON);  
    compileBlock();  
    eat(SB_PERIOD);  
    assert("Program parsed!");  
}
```

# Parsing non-terminal symbol

Example: **Statement**

FIRST(Statement) = {TK\_IDENT, KW\_CALL, KW\_BEGIN, KW\_IF, KW\_WHILE,  
KW\_FOR,  $\epsilon$ }

FOLLOW(Statement) = {SB\_SEMICOLON, KW\_END, KW\_ELSE}

/\* Predict parse table for Expression \*/

Input

Production

|          |                            |
|----------|----------------------------|
| TK_IDENT | 49) Statement ::= AssignSt |
| KW_CALL  | 50) Statement ::= CallSt   |
| KW_BEGIN | 51) Statement ::= GroupSt  |
| KW_IF    | 52) Statement ::= IfSt     |
| KW_WHILE | 53) Statement ::= WhileSt  |
| KW_FOR   | 54) Statement ::= ForSt    |

|              |                |
|--------------|----------------|
| SB_SEMICOLON | 55) $\epsilon$ |
| KW_END       | 55) $\epsilon$ |
| KW_ELSE      | 55) $\epsilon$ |

Others

Error

# Parsing non-terminal symbol (statement)

---

Example: **Statement**

```
void compileStatement(void) {
    switch (lookAhead->tokenType)
    {
        case TK_IDENT:
            compileAssignSt();
            break;
        case KW_CALL:
            compileCallSt();
            break;
        case KW_BEGIN:
            compileGroupSt();
            break;
        case KW_IF:
            compileIfSt();
            break;
        case KW_WHILE:
            compileWhileSt();
            break;
    }
```

```
        case KW_FOR:
            compileForSt();
            break;
            // check FOLLOW tokens
        case SB_SEMICOLON:
        case KW_END:
        case KW_ELSE:
            break;
            // Error occurs
        default:
            error(ERR_INVALIDSTATEMENT,
lookAhead->lineNo, lookAhead-
>colNo);
            break;
    }
}
```

# Assignment 1

---

- Parsing a program containing
  - Constant declaration
  - Type declaration
  - Variable declaration
  - Empty block

## Assignment 2

---

- Parsing a program containing
  - Constant declaration
  - Type declaration
  - Variable declaration
  - Statements

# LHS with more than 1 RHS

---

## Two alternatives for Basic Type

34) **BasicType** ::= **KW\_INTEGER**

35) **BasicType** ::= **KW\_CHAR**

```
void compileBasicType(void) {  
    switch (lookAhead->tokenType) {  
        case KW_INTEGER:  
            eat(KW_INTEGER);  
            break;  
        case KW_CHAR:  
            eat(KW_CHAR);  
            break;  
        default:  
            error(ERR_INVALIDBASICTYPE, lookAhead->lineNo, lookAhead->colNo);  
            break;  
    }  
}
```

# Loop processing

---

Loop for sequence of constant declarations

10) **ConstDecls ::= ConstDecl ConstDecls**

11) **ConstDecls ::=  $\epsilon$**

```
void compileConstDecls(void) {  
    while (lookAhead->tokenType == TK_IDENT)  
        compileConstDecl();  
}
```

# Sometimes you should refer to syntax diagrams

---

Syntax of Term (using BNF)


82)  $\text{Term} ::= \text{Factor Term2}$

83)  $\text{Term2} ::= \text{SB\_TIMES Factor Term2}$

84)  $\text{Term2} ::= \text{SB\_SLASH Factor Term2}$

85)  $\text{Term2} ::= \varepsilon$

Syntax of Term (using Syntax Diagram)





## Process rules for Term : 2 functions with Follow set

```
void compileTerm(void)
{ compileFactor();
  compileTerm2();
}
```


---

```
void compileTerm2(void) {
  switch (lookAhead->tokenType) {
    case SB_TIMES:
      eat(SB_TIMES);
      compileFactor();
      compileTerm2();
      break;
    case SB_SLASH:
      eat(SB_SLASH);
      compileFactor();
      compileTerm2();
      break;
    // check the FOLLOW set
    case SB_PLUS:
    case SB_MINUS:
    case KW_TO:
    case KW_DO:
```

```
    case SB_RPAR:
    case SB_COMMA:
    case SB_EQ:
    case SB_NEQ:
    case SB_LE:
    case SB_LT:
    case SB_GE:
    case SB_GT:
    case SB_RSEL:
    case SB_SEMICOLON:
    case KW_END:
    case KW_ELSE:
    case KW_THEN:
      break;
    default:
      error(ERR_INVALIDTERM, lookAhead->lineNo,
        lookAhead->colNo);
  }
}
```

# Process term with syntax diagram

```
void compileTerm(void)
{
    compileFactor();
    while(lookAhead->tokenType == SB_TIMES || lookAhead->tokenType == SB_SLASH)
    {
        switch (lookAhead->tokenType)
        {
            case SB_TIMES:
                eat(SB_TIMES);
                compileFactor();
                break;
            case SB_SLASH:
                eat(SB_SLASH);
                compileFactor();
                break;
        }
    }
}
```



## Assignment 3

---

- Parsing a program with full fledged grammar