

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Aether

Admin Basics

2026-08-29

Ports / access

Port	Service
5090	Dashboard + API

Auth

OIDC + SAML + LDAP as configured, or a static API key (`AETHER_API_KEY`) for non-interactive/CLI access. **If none of OIDC/SAML/LDAP/API-key is configured, Aether allows all requests (local-dev mode)** — the chart now auto-generates an API key by default so a fresh install isn't left open; retrieve it:

```
kubectl -n <namespace> get secret <release>-aether-secrets -o jsonpath='{.data.api-key}' | base64
```

Set your own at install time with `--set apiKey.value="a-real-key"`, or reference an existing Secret via `apiKey.existingSecret`.

Encryption key for stored secrets

`AETHER_SECRET_KEY` encrypts Aether's own on-disk secret store (stored credentials for the runtimes it manages — not just a login token). Also auto-generated by the chart by default now; **without it, the app derives a key from the pod's `HOSTNAME`, which is predictable and visible to anyone with pod-list RBAC in the namespace** — not a private seed in a Kubernetes deployment. Retrieve or set it the same way as the API key (`encryption-key` data key / `--set secretKey.value=...` / `secretKey.existingSecret`). Changing this key after secrets have been stored makes existing stored secrets unrecoverable — treat it like any other encryption key: set it once, back it up.

Install sketch

Follow the product README and deploy/Helm docs in the repository. Verify health endpoints or CLI status before opening the UI.

Related

- [Getting Started](#)

Operate from the console (UX)

1. Open this route from the nav or command palette and wait for live API data.
2. Use filters/search when present; drill into a row for detail.
3. For mutating actions: confirm role gates and impact before applying.
4. **Empty / fail:** Check service health, auth, and that required CRDs/backends for this domain are installed.
5. **Success:** Live data loads; created/updated objects appear without error toasts.