

ZYVORAI LABS · CUSTOMER DOCUMENTATION



## Admin Basics

2026-09-01

## Ports

| Port  | Service                                      |
|-------|----------------------------------------------|
| 5110  | REST + Storage Center UI ( ATLAS_BIND_ADDR ) |
| 5111  | gRPC ( ATLAS_GRPC_ADDR ; empty disables)     |
| 30511 | Common cluster REST/UI NodePort              |
| 30512 | Common gRPC NodePort                         |
| 30543 | Optional HTTPS NodePort                      |

Always document hosts as `<host>` — never paste lab IPs into customer runbooks.

# Auth

---

- Lab: `ATLAS_AUTH_REQUIRED=0` (open).
- Production: `ATLAS_AUTH_REQUIRED=1` + JWT secret ( `atlas-gateway-auth` ); weak defaults rejected at start.
- Mint tokens: `POST /api/atlas/v1/auth/tokens` , or paste into the rail **key** icon.
- Local users: **GOVERNANCE** → **Access** → **Create user**.
- CLI: `--token` / `ATLAS_TOKEN` ; API base `/api/atlas/v1/...`.
- Unauthenticated: `/health` , `/metrics` .

## Install sketch

---

```
make run # local gateway CLI  
tlasctl health  
tlasctl discover
```

Open `http://<host>:5110/` . Cluster: follow product deployment docs / Ceph gateway manifests.

## Operate from the console (admin)

---

1. Confirm `/health` and Command Deck health chip.
2. **Backends** registered → **Volumes** can provision.
3. Pause / cordon only from **Maintenance** when you mean to quiesce.
4. Mutations return `202` + job id — watch **Jobs** (UI or gRPC `WatchJob` ).

## Related

---

- [Getting Started](#)
- [Using the Dashboard](#)
- [Disaster Recovery](#)