

ZYVORAI LABS · CUSTOMER DOCUMENTATION



Getting Started

2026-09-01

What you need

Requirement	Notes
Atlas gateway	Default bind <code>:5110</code> (REST + Storage Center UI)
Optional gRPC	<code>:5111</code>
Backend	Ceph via Rook/driver, or lab fake driver
Auth	Lab often open (<code>ATLAS_AUTH_REQUIRED=0</code>); cluster uses JWT

1. Open Storage Center

- Console: `http://<host>:5110/`
- Cluster NodePort (common): `http://<host>:30511/` (HTTPS may be `:30543`)
- Health: `curl http://<host>:5110/health`

2. Sign in

Mode	What you do
Open (lab)	No token when <code>ATLAS_AUTH_REQUIRED=0</code>
JWT	Paste bearer token from the top-bar Account menu, or <code>POST /api/atlas/v1/auth/tokens</code>
Local user	GOVERNANCE → Access → Create user, then sign in on the login page
CLI	<code>atlasctl --token ...</code> or <code>ATLAS_TOKEN</code>

3. Orient yourself (UX)

1. **Command Deck** (/) — capacity sounding, pool tiles, protection gaps.
2. Left sidebar: six section groups with **collapsible headers** (chevron) and a **Filter navigation...** field at the top; collapse the whole rail to icons from the toggle at the bottom. Top bar: Spotlight (⌘K), Look & feel (Carbon / Apple Lite), running-jobs indicator, Alerts bell, health, and Account (clock, auth token, sign-out). **H** jumps to Command Deck.
3. Sidebar groups: **STORAGE** (always open), **DATA PROTECTION**, **DATABRIDGE**, **OBSERVABILITY**, **GOVERNANCE**, **INFRASTRUCTURE**. Admin/operator-only pages hide for lower roles.
4. Every mutation is a durable job (202 + id) — watch **Jobs**.

4. First workflows

A. Discover inventory

```
atlasctl health
atlasctl discover
atlasctl pools
atlasctl volumes
```

B. Provision from the console

1. **Volumes** → **Create volume** (policy/intent) → watch **Jobs**.
2. Optional: Snapshot / Schedule from the volume SlideOver.

C. Protect a volume

Snapshots / Schedules / Backups (needs a **Bucket**) — confirm job completion. Check **Protection Status**.

D. Check backend health

Backends → **Ceph** for day-2 OSD/pool/RGW signals. Investigate warn/crit before large provisions.

Next steps

- [Using the Dashboard](#)
 - [Admin basics](#)
 - [Page guides](#)
 - [Common workflows](#)
-

Storage Center is the Atlas operator console on the gateway (`http://<host>:5110/`).

Shell chrome

Navigation lives in a persistent **left sidebar**, grouped by six sections. Each section (except **Storage**) can be collapsed with the chevron on its header; the section containing your current page stays open. Use **Filter navigation...** at the top of the sidebar to narrow the list. Collapse the whole sidebar to an icon-only rail from the toggle at its base (state remembered per browser). Below ~900px the sidebar hides and the hamburger opens the same nav in a drawer — no duplicate shortcut list.

Role-aware nav: Viewer, Operator, and Admin sessions see different sidebar entries (governance and destructive ops require higher roles). Direct URLs to gated pages show an access message.

The top bar carries everything else:

Control	What it does
Sidebar	STORAGE · DATA PROTECTION · DATABRIDGE · OBSERVABILITY · GOVERNANCE · INFRASTRUCTURE — filter, section collapse, icon rail
Brand	Zyvor mark + Atlas — click to jump to Command Deck
Spotlight	⌘K / Ctrl+K — pools, volumes, modules (role-filtered)
Look & feel	Carbon (dark shop, default) or Apple Lite (light shop)
Jobs spinner	Shows while jobs are running → <code>/jobs</code>
Alerts bell	Open alert count → <code>/alerts</code> (also under OBSERVABILITY → Alerts)
Pause	Freeze auto-refresh
Health pill	Ceph/Atlas rollup (HEALTH_OK, DEGRADED, ...)
Account menu	Clock, paste/clear JWT, sign out

Keyboard: **H** jumps to Command Deck. **?** opens shortcut help.

Detail pages (pool drill-down, migration plan detail) show breadcrumbs above the page title.

Page grammar

Most screens share: **PageHead** (eyebrow + title + live state + ≤ 2 actions) → table/canvas → SlideOver or FormModal for mutations.

Empty states name the next action (Create volume, Create bucket, Register source, ...) — follow those CTAs rather than shrugging.

Operate tips

1. After any **Create** / **Backup** / **Failover**, open **Jobs** until `succeeded` .
2. Prefer console actions for day-2; use `atlasctl` for scripts and CI.
3. DataBridge: register **Cloud Databases** → **Migration Plans** → Plan Detail (CDC / cutover) → **Validation**.
4. Never paste lab IPs into runbooks — use `<host>` .

Related

- [Getting Started](#)
 - [Page index](#)
 - [Workflows](#)
-

Provision and snapshot a volume

1. [Command Deck](#) — confirm health
2. [Volumes](#) — **Create volume** from intent/policy
3. [Jobs](#) — wait for success
4. Volume SlideOver → **Snapshot**, or [Snapshots](#) / [Schedules](#)

Protect with backups

1. [Buckets](#) — **Create bucket**
2. [Backups](#) — **Backup** a volume
3. Confirm under [Protection Status](#) and [Jobs](#)

Run a DataBridge migration

1. [Cloud Databases](#) — **Register** source
2. [Migration Plans](#) — **Create** plan
3. [Plan Detail](#) — stages, CDC start/stop, cutover confirms
4. [Validation](#) / [Replication](#) / [Edge DB Clusters](#)

Day-2 Ceph / DR

1. [Backends / Ceph](#)
2. [Maintenance](#) — pause jobs or cordon before risky work
3. [Disaster Recovery](#) — peers, mirrors, promote/failover (confirm-gated)

Related

- [Getting Started](#)
- [Using the Dashboard](#)