

ZYVORAI LABS · CUSTOMER DOCUMENTATION



Page-by-Page Product Manual

2026-08-30

Page-by-page guides

Each guide follows: Purpose → When to use it → How to get there → Operate from the console (UX) → Related pages.

Every route is also listed in the [complete page index](#).

Data Protection

Page	What it covers
Backups	Volume backups into object buckets — create, restore, and retire copies.
Buckets	Object gateway buckets for exports and backup destinations.
Protection Status	Per-volume protection verdict — healthy / degraded / unprotected rollup.

Databridge

Page	What it covers
Edge DB Clusters	Edge database clusters provisioned as migration targets.
Plan Detail	Single migration plan — stages, CDC controls, cutover, and validation hooks.
Migration Plans	Create and list DataBridge migration plans from registered sources.
Replication	CDC replication streams for active migration plans.
Cloud Databases	Register external / cloud database sources for DataBridge migrations.
Validation	Validation runs and per-table results for migrated data.

Governance

Page	What it covers
Access	Local users for Storage Center sign-in — create and delete accounts.
API Docs	Curated REST + gRPC map for operators and integrators.
Policies	Built-in intent → placement catalog (atlas-policy) used when creating volumes.
Settings	Console settings — theme and session preferences for Storage Center.
Tenants	Tenant index — quotas and policy overrides.

Infrastructure

Page	What it covers
Backends	Registered storage backends — discovery and capacity summary.
Ceph	Day-2 Ceph signals — health rollup, df pools, OSD tree.
Cluster	Primary cluster inventory — health, pools, OSDs.
Disaster Recovery	Cross-cluster RBD mirroring — peers, mirrors, promote/demote/failover.
Kubernetes	Discovered StorageClasses from the attached cluster.

Page	What it covers
Maintenance	Pause the job engine, cordon backends, and clean orphan backups.
Pool Detail	Single pool sounding — volumes and OSD cells for one pool.

Observability

Page	What it covers
Activity	Recent operator and system activity stream.
Alerts	Open alert ledger — silence or resolve before capacity work.
Audit	Compliance trail of state-changing and sensitive actions.
Jobs	Durable async jobs for every mutation — progress, SSE live updates, failure detail.
Metrics	Ceph-native metric samples and OSD utilization averages.
Observatory	Estate telemetry canvas — capacity lenses and jump to Deck or Alerts.

Storage

Page	What it covers
Command Deck	Estate overview — capacity sounding, pool tiles, protection gaps, and quick jumps into volumes, snapshots, and backups.
RBD Images	Raw Ceph RBD images for machina/libvirt and bare VMs (bypassing CSI).
Schedules	Automate periodic snapshots or backups for a volume.
Snapshots	Point-in-time volume snapshots — clone or restore into new volumes.
Volumes	Intent-backed volume inventory — create, expand, snapshot, schedule, and delete across backends.

32 guides. Regenerate: `node scripts/customer-docs/generate-guide-index.mjs` .

Backups

Purpose

Volume backups into object buckets — create, restore, and retire copies.

When to use it

- Operate **Backups** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/backups`
- Nav: **DATA PROTECTION** → **Backups**

Operate from the console (UX)

1. Open `/backups` .
2. **Backup** — select volume + destination bucket; wait for the job.
3. Restore opens a modal (optional new volume name).
4. Bulk-delete selected backups when retiring.
5. **Empty / fail**: Create a bucket first under Buckets; ensure volume exists.
6. **Success**: Backup row with created time; restore job completes.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Buckets](#)
 - [Volumes](#)
 - [Jobs](#)
 - [Getting Started](#)
 - [Page index](#)
-

Buckets

Purpose

Object gateway buckets for exports and backup destinations.

When to use it

- Operate **Buckets** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/buckets`
- Nav: **DATA PROTECTION** → **Buckets**

Operate from the console (UX)

1. Open `/buckets` .
2. **Create bucket** — name + backend/RGW target.
3. Open a bucket to list/upload objects when the panel is wired.
4. **Empty / fail:** No RGW → check Ceph/RGW on Backends/Ceph pages.
5. **Success:** Bucket listed; usable as Backup destination.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Backups](#)
 - [Ceph](#)
 - [Getting Started](#)
 - [Page index](#)
-

Protection Status

Purpose

Per-volume protection verdict — healthy / degraded / unprotected rollup.

When to use it

- Operate **Protection Status** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/protection`
- Nav: **DATA PROTECTION** → **Protection Status**

Operate from the console (UX)

1. Open `/protection` .
2. Scan worst-case headline (healthy vs unprotected counts).
3. Drill volumes missing snaps/backups → Schedules or Backups.
4. **Empty / fail**: No volumes yet → provision first on Volumes.
5. **Success**: Every critical volume shows a healthy verdict.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Schedules](#)
 - [Backups](#)
 - [Volumes](#)
 - [Getting Started](#)
 - [Page index](#)
-

Edge DB Clusters

Purpose

Edge database clusters provisioned as migration targets.

When to use it

- Operate **Edge DB Clusters** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/databrbridge/edge-clusters`
- Nav: **DATABRIDGE** → **Edge DB Clusters**

Operate from the console (UX)

1. Open `/databrbridge/edge-clusters` .
2. Provision from a migration plan when empty.
3. Confirm cluster health before cutover.
4. **Empty / fail**: No clusters → complete plan provisioning stage first.
5. **Success**: Cluster listed and healthy for the plan.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Migration Plans](#)
 - [Getting Started](#)
 - [Page index](#)
-

Plan Detail

Purpose

Single migration plan — stages, CDC controls, cutover, and validation hooks.

When to use it

- Operate **Plan Detail** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/databridge/plans/:id`
- Nav: **DATABRIDGE** → **Migration Plans** → **plan row**

Operate from the console (UX)

1. Open a plan from `/databridge/plans` .
2. Read engine/CDC badges; start or advance stages per UI.
3. **Stop CDC / Restart CDC** when streaming; use confirm for destructive cutover actions.
4. Jump to Validation / Replication / Edge clusters as needed.
5. **Empty / fail**: Stage blocked → fix source connectivity or prior stage job.
6. **Success**: CDC live / cutover complete per badges; Jobs clean.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Validation](#)
 - [Replication](#)
 - [Jobs](#)
 - [Getting Started](#)
 - [Page index](#)
-

Migration Plans

Purpose

Create and list DataBridge migration plans from registered sources.

When to use it

- Operate **Migration Plans** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/databridge/plans`
- Nav: **DATABRIDGE** → **Migration Plans**

Operate from the console (UX)

1. Open `/databridge/plans` after registering a source.
2. **Create** New migration plan → open Plan Detail.
3. Track stages and CDC from the detail page.
4. **Empty / fail**: No plans → register a Cloud Database first.
5. **Success**: Plan row links to `/databridge/plans/:id`.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511`, HTTPS `:30543`). Health: `GET /health`. Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Cloud Databases](#)
 - [Plan Detail](#)
 - [Getting Started](#)
 - [Page index](#)
-

Replication

Purpose

CDC replication streams for active migration plans.

When to use it

- Operate **Replication** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/databridge/replication`
- Nav: **DATABRIDGE** → **Replication**

Operate from the console (UX)

1. Open `/databridge/replication` .
2. Confirm streams match plans with CDC started.
3. Restart CDC from Plan Detail if a stream stalls.
4. **Empty / fail**: No streams → Start CDC on a plan.
5. **Success**: Stream lag/state acceptable for cutover.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Plan Detail](#)
 - [Getting Started](#)
 - [Page index](#)
-

Cloud Databases

Purpose

Register external / cloud database sources for DataBridge migrations.

When to use it

- Operate **Cloud Databases** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/databridge/sources`
- Nav: **DATABRIDGE** → **Cloud Databases**

Operate from the console (UX)

1. Open `/databridge/sources` .
2. **Register** a source database (connection + engine).
3. Open a source → schema SlideOver (tables).
4. Then create a Migration Plan.
5. **Empty / fail:** Connection refused → network/creds; schema empty → privileges.
6. **Success:** Source listed with reachable schema.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Migration Plans](#)
 - [Getting Started](#)
 - [Page index](#)
-

Validation

Purpose

Validation runs and per-table results for migrated data.

When to use it

- Operate **Validation** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/databridge/validation`
- Nav: **DATABRIDGE** → **Validation**

Operate from the console (UX)

1. Open `/databridge/validation` after plan stages that emit checks.
2. Open a run → per-table SlideOver.
3. Fix failures before cutover.
4. **Empty / fail:** No runs → trigger validation from Plan Detail / workflow.
5. **Success:** Tables pass; ready for cutover.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Plan Detail](#)
 - [Getting Started](#)
 - [Page index](#)
-

Access

Purpose

Local users for Storage Center sign-in — create and delete accounts.

When to use it

- Operate **Access** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/access`
- Nav: **GOVERNANCE** → **Access**

Operate from the console (UX)

1. Open `/access` .
2. **Create user** with username/password; they sign in on the login page.
3. Delete users from the table when retiring access.
4. Paste service JWT via rail key icon for API automation.
5. **Empty / fail:** No users → create one; login fails → check `ATLAS_AUTH_REQUIRED` and token.
6. **Success:** New user can sign in; table lists accounts.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Settings](#)
 - [API Docs](#)
 - [Getting Started](#)
 - [Page index](#)
-

API Docs

Purpose

Curated REST + gRPC map for operators and integrators.

When to use it

- Operate **API Docs** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/api-docs`
- Nav: **GOVERNANCE** → **API Docs**

Operate from the console (UX)

1. Open `/api-docs` .
2. Scan Meta, Auth, Inventory, Write path (async jobs), Observability, DR, DataBridge.
3. Prefer `atlasctl` or REST with JWT; mutations return jobs.
4. **Empty / fail:** N/A — static reference; deep examples in product API docs.
5. **Success:** You can name the endpoint for the console action you just took.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Jobs](#)
 - [Access](#)
 - [Getting Started](#)
 - [Page index](#)
-

Policies

Purpose

Built-in intent → placement catalog (atlas-policy) used when creating volumes.

When to use it

- Operate **Policies** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/policies`
- Nav: **GOVERNANCE** → **Policies**

Operate from the console (UX)

1. Open `/policies` and review intent names (`production` , `database` , ...).
2. Use these intents in **Create volume**.
3. Tenant overrides live under Tenants → Policies.
4. **Empty / fail**: Catalog empty → gateway policy pack missing.
5. **Success**: Intents listed and selectable on create.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Volumes](#)
 - [Tenants](#)
 - [Getting Started](#)
 - [Page index](#)
-

Settings

Purpose

Console settings — theme and session preferences for Storage Center.

When to use it

- Operate **Settings** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/settings`
- Nav: **GOVERNANCE** → **Settings (sidebar Settings)**

Operate from the console (UX)

1. Open `/settings` .
2. Adjust Look & feel from the top-bar theme menu (Carbon, Apple Lite) if not on this page.
3. Confirm token/session via the Account menu (top-bar key icon).
4. **Empty / fail**: Changes not sticking → local storage blocked; re-auth.
5. **Success**: Theme/session match operator preference.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Access](#)
 - [Getting Started](#)
 - [Page index](#)
-

Tenants

Purpose

Tenant index — quotas and policy overrides.

When to use it

- Operate **Tenants** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/tenants`
- Nav: **GOVERNANCE** → **Tenants**

Operate from the console (UX)

1. Open `/tenants` .
2. Open a tenant → set Quota (Save) or review Policies slide-over.
3. Overrides fall back to built-in catalog when empty.
4. **Empty / fail:** No tenants → create via API/admin path your deploy uses; quotas block create if exceeded.
5. **Success:** Quota saved; volume creates respect limits.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Policies](#)
 - [Access](#)
 - [Getting Started](#)
 - [Page index](#)
-

Backends

Purpose

Registered storage backends — discovery and capacity summary.

When to use it

- Operate **Backends** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/backends`
- Nav: **INFRASTRUCTURE** → **Backends**

Operate from the console (UX)

1. Open `/backends` .
2. Confirm at least one backend is registered and healthy.
3. Cordon/uncordon from Maintenance when draining.
4. **Empty / fail:** None registered → install driver/Ceph and discover (`atlasctl discover`).
5. **Success:** Backend row with capacity; Volumes can provision.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Ceph](#)
 - [Maintenance](#)
 - [Getting Started](#)
 - [Page index](#)
-

Ceph

Purpose

Day-2 Ceph signals — health rollup, df pools, OSD tree.

When to use it

- Operate **Ceph** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: /ceph
- Nav: **INFRASTRUCTURE** → **Ceph** (sidebar Ceph)

Operate from the console (UX)

1. Open /ceph .
2. Read rollup + df pools; jump to Cluster if needed.
3. Investigate degraded/rebuilding before big provisions.
4. **Empty / fail**: No ceph df → driver/credentials; use lab fake driver only for demos.
5. **Success**: HEALTH_OK (or understood warn) with pools listed.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Cluster](#)
 - [Disaster Recovery](#)
 - [Getting Started](#)
 - [Page index](#)
-

Cluster

Purpose

Primary cluster inventory — health, pools, OSDs.

When to use it

- Operate **Cluster** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/cluster`
- Nav: **INFRASTRUCTURE** → **Cluster**

Operate from the console (UX)

1. Open `/cluster` .
2. Read primary name/health and pool/OSD counts.
3. Drill pools toward Ceph / Pool detail.
4. **Empty / fail:** Waiting on inventory → gateway↔Ceph connectivity.
5. **Success:** Health matches Command Deck rollup.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Ceph](#)
 - [Command Deck](#)
 - [Getting Started](#)
 - [Page index](#)
-

Disaster Recovery

Purpose

Cross-cluster RBD mirroring — peers, mirrors, promote/demote/failover.

When to use it

- Operate **Disaster Recovery** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/dr`
- Nav: **INFRASTRUCTURE** → **Disaster Recovery**

Operate from the console (UX)

1. Open `/dr` and read peers/mirrors + control-plane/dataplane readiness.
2. Add peer; enable mirroring on images; Promote / Demote / Failover with confirms.
3. Force promote only for split-brain recovery.
4. **Empty / fail:** Dataplane unverified → need second Ceph site; peers=0 → add peer first.
5. **Success:** Mirrors healthy; failover job succeeds when rehearsed.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511`, HTTPS `:30543`). Health: `GET /health`. Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Ceph](#)
 - [Jobs](#)
 - [Getting Started](#)
 - [Page index](#)
-

Kubernetes

Purpose

Discovered StorageClasses from the attached cluster.

When to use it

- Operate **Kubernetes** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/kubernetes`
- Nav: **INFRASTRUCTURE** → **Kubernetes**

Operate from the console (UX)

1. Open `/kubernetes` .
2. Verify StorageClasses expected by CSI consumers.
3. **Empty / fail:** No classes → check KUBECONFIG / RBAC for the gateway.
4. **Success:** Classes listed for the cluster Atlas manages.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Cluster](#)
 - [Backends](#)
 - [Getting Started](#)
 - [Page index](#)
-

Maintenance

Purpose

Pause the job engine, cordon backends, and clean orphan backups.

When to use it

- Operate **Maintenance** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/maintenance`
- Nav: **INFRASTRUCTURE** → **Maintenance**

Operate from the console (UX)

1. Open `/maintenance` .
2. Pause job engine only when you intend to quiesce (new jobs queue).
3. Cordon a backend to reject new provisioning.
4. Delete orphan backups carefully.
5. **Empty / fail:** Pause stuck → check API auth; cordon blocked → role.
6. **Success:** Desired pause/cordon state reflected; resume when done.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Backends](#)
 - [Jobs](#)
 - [Getting Started](#)
 - [Page index](#)
-

Pool Detail

Purpose

Single pool sounding — volumes and OSD cells for one pool.

When to use it

- Operate **Pool Detail** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/pools/:id`
- Nav: **Command Deck / Cluster** → **pool tile**

Operate from the console (UX)

1. Open `/pools/:id` from a Deck or Cluster pool link.
2. Review fill, volume list, OSD lattice.
3. Jump to Volumes or Command Deck from actions.
4. **Empty / fail:** Pool not found → stale id; return to Deck.
5. **Success:** Pool metrics match Ceph df.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Command Deck](#)
 - [Volumes](#)
 - [Getting Started](#)
 - [Page index](#)
-

Activity

Purpose

Recent operator and system activity stream.

When to use it

- Operate **Activity** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/activity`
- Nav: **OBSERVABILITY** → **Activity**

Operate from the console (UX)

1. Open `/activity` .
2. Scan recent events after provision/protect/migrate actions.
3. Correlate failures with Jobs and Audit.
4. **Empty / fail:** Quiet estate → trigger a volume op and refresh.
5. **Success:** Activity lines match your last mutations.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Jobs](#)
 - [Audit](#)
 - [Getting Started](#)
 - [Page index](#)
-

Alerts

Purpose

Open alert ledger — silence or resolve before capacity work.

When to use it

- Operate **Alerts** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/alerts`
- Nav: **OBSERVABILITY** → **Alerts** (sidebar Alerts, or the top-bar bell)

Operate from the console (UX)

1. Open `/alerts` (or top-bar bell → jump).
2. Filter by state; read critical vs open counts in PageHead.
3. **Silence** (1h) or **Resolve** with confirm.
4. **Empty / fail**: Filter too tight → clear filter; webhook paging may still need silence.
5. **Success**: Criticals cleared or deliberately silenced.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511`, HTTPS `:30543`). Health: `GET /health`. Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Jobs](#)
 - [Ceph](#)
 - [Getting Started](#)
 - [Page index](#)
-

Audit

Purpose

Compliance trail of state-changing and sensitive actions.

When to use it

- Operate **Audit** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/audit`
- Nav: **OBSERVABILITY** → **Audit**

Operate from the console (UX)

1. Open `/audit` .
2. Filter by actor and action.
3. Verify who created tokens, volumes, or DR failovers.
4. **Empty / fail**: No entries → auth/open mode may omit some events; confirm ATLAS auth mode.
5. **Success**: Expected mutations appear with actor + timestamp.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Access](#)
 - [Jobs](#)
 - [Getting Started](#)
 - [Page index](#)
-

Jobs

Purpose

Durable async jobs for every mutation — progress, SSE live updates, failure detail.

When to use it

- Operate **Jobs** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/jobs`
- Nav: **OBSERVABILITY** → **Jobs** (sidebar **Jobs**)

Operate from the console (UX)

1. Open `/jobs` after any create/backup/migrate/DR action.
2. Select a job for created time, state, and error detail.
3. Use rail Jobs chip for running count without leaving the page.
4. **Empty / fail:** No jobs → you have not mutated yet; failed jobs → fix cause and retry from source page.
5. **Success:** Job reaches succeeded; inventory refreshes.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511`, HTTPS `:30543`). Health: `GET /health`. Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Volumes](#)
 - [Activity](#)
 - [Getting Started](#)
 - [Page index](#)
-

Metrics

Purpose

Ceph-native metric samples and OSD utilization averages.

When to use it

- Operate **Metrics** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/metrics-dashboard`
- Nav: **OBSERVABILITY** → **Metrics**

Operate from the console (UX)

1. Open `/metrics-dashboard` .
2. Confirm samples arrive; note OSD average % when shown.
3. Cross-check spikes with Observatory and Ceph.
4. **Empty / fail:** Waiting on samples → backend/Ceph metrics not streaming.
5. **Success:** Sample count > 0 and averages look sane.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Observatory](#)
 - [Ceph](#)
 - [Getting Started](#)
 - [Page index](#)
-

Observatory

Purpose

Estate telemetry canvas — capacity lenses and jump to Deck or Alerts.

When to use it

- Operate **Observatory** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/observatory`
- Nav: **OBSERVABILITY** → **Observatory** (sidebar **Observatory**)

Operate from the console (UX)

1. Open `/observatory` and wait for estate samples.
2. Use lenses / panels for pool and OSD pressure.
3. Jump **Command Deck** or **Alerts** from PageHead actions.
4. **Empty / fail**: No samples → Ceph metrics path cold; check `/metrics-dashboard` and gateway.
5. **Success**: Live estate picture matches Deck health.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Command Deck](#)
 - [Alerts](#)
 - [Metrics](#)
 - [Getting Started](#)
 - [Page index](#)
-

Command Deck

Purpose

Estate overview — capacity sounding, pool tiles, protection gaps, and quick jumps into volumes, snapshots, and backups.

When to use it

- Operate **Command Deck** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: /
- Nav: **STORAGE** → **Command Deck (sidebar Deck, or the H shortcut)**

Operate from the console (UX)

1. Open / (Command Deck) after the gateway is reachable.
2. Read the health chip on the rail (HEALTH_OK / DEGRADED / ...) and live job/alert counts.
3. Use **New volume** to provision, or follow empty-state links (Create a volume →, Schedule nightly snapshots →, Create first bucket →).
4. Open a pool tile to drill into /pools/:id, or jump via Spotlight (⌘K / Ctrl+K).
5. Pause auto-refresh from the rail if you need a stable readout.
6. **Empty / fail:** No capacity → register a backend (INFRASTRUCTURE → Backends) and run discover; auth failures → paste JWT from the key icon.
7. **Success:** Sounding orb + pool/OSD lattice populate; jobs appear when you provision.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511`, HTTPS `:30543`). Health: `GET /health`. Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Volumes](#)
 - [Jobs](#)
 - [Ceph](#)
 - [Getting Started](#)
 - [Page index](#)
-

RBD Images

Purpose

Raw Ceph RBD images for machina/libvirt and bare VMs (bypassing CSI).

When to use it

- Operate **RBD Images** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/rbd`
- Nav: **STORAGE** → **RBD Images**

Operate from the console (UX)

1. Open `/rbd` and select the target pool (default often `rbd-nvme-prod`).
2. **Create image** with name + size; or Flatten / Clone / Resize / Snapshot from row actions.
3. Clone needs an existing snapshot — create under Snaps first if the hint says so.
4. Rollback is destructive — confirm before reverting to a snap.
5. **Empty / fail:** Wrong pool → switch pool; Ceph not ready → INFRASTRUCTURE → Ceph.
6. **Success:** Image listed in pool; jobs complete for flatten/clone/resize.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Ceph](#)
 - [Snapshots](#)
 - [Jobs](#)
 - [Getting Started](#)
 - [Page index](#)
-

Schedules

Purpose

Automate periodic snapshots or backups for a volume.

When to use it

- Operate **Schedules** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/schedules`
- Nav: **STORAGE** → **Schedules**

Operate from the console (UX)

1. Open `/schedules`.
2. Click **Schedule** — choose volume, cadence, retention, snapshot vs backup.
3. Confirm the schedule row appears; verify later runs under Snapshots / Backups / Jobs.
4. **Empty / fail**: Need at least one volume and (for backups) a bucket.
5. **Success**: Schedule listed; first fire shows as a job.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511`, HTTPS `:30543`). Health: `GET /health`. Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Volumes](#)
 - [Backups](#)
 - [Getting Started](#)
 - [Page index](#)
-

Snapshots

Purpose

Point-in-time volume snapshots — clone or restore into new volumes.

When to use it

- Operate **Snapshots** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/snapshots`
- Nav: **STORAGE** → **Snapshots**

Operate from the console (UX)

1. Open `/snapshots` to list PIT copies.
2. Create snaps from **Volumes** row → Snapshot (or schedule).
3. Clone or Restore from a snapshot row (confirm modal).
4. Bulk-delete selected snaps when retiring retention.
5. **Empty / fail:** No copies → open Volumes and snapshot a volume first.
6. **Success:** Snapshot row + clone/restore job succeeds.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Volumes](#)
 - [Schedules](#)
 - [Getting Started](#)
 - [Page index](#)
-

Volumes

Purpose

Intent-backed volume inventory — create, expand, snapshot, schedule, and delete across backends.

When to use it

- Operate **Volumes** when your job matches this page
- Prefer **Command Deck** (/) if you are unsure where to start
- Confirm gateway auth and that a storage driver is registered if inventories look empty

How to get there

- Route: `/volumes`
- Nav: **STORAGE** → **Volumes** (sidebar **Volumes**)

Operate from the console (UX)

1. Open `/volumes` and wait for the inventory table.
2. Click **Create volume** — pick name, size, policy/intent, tenant; submit starts a durable job.
3. Use **Refresh** / **Export CSV**; select rows for bulk delete when needed.
4. Open a row → SlideOver: Snapshot, Expand, Create schedule, or delete.
5. Watch **Jobs** (/jobs) until create/expand/snapshot succeed.
6. **Empty / fail**: No volumes → Create volume; empty after create → check Jobs and backend registration.
7. **Success**: Volume appears with state/size; mutations return `202` + job id.

Use `http://<host>:5110/` for Storage Center (cluster NodePort often `:30511` , HTTPS `:30543`). Health: `GET /health` . Mutations return durable jobs — watch **Jobs**. Never publish lab IPs in customer docs.

Related pages

- [Snapshots](#)
 - [Schedules](#)
 - [Jobs](#)
 - [Getting Started](#)
 - [Page index](#)
-

Atlas — Complete page index

Every primary navigable dashboard route.

Generated: 2026-08-30 · 32 routes

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

STORAGE

Page	Route	Purpose	Guide
Command Deck	<code>/</code>	Estate overview — capacity sounding, pool tiles, protection gaps, and quick jumps into volumes, snapshots, and backups.	Open
Volumes	<code>/volumes</code>	Intent-backed volume inventory — create, expand, snapshot, schedule, and delete across backends.	Open
RBD Images	<code>/rbd</code>	Raw Ceph RBD images for machina/libvirt and bare VMs (bypassing CSI).	Open
Snapshots	<code>/snapshots</code>	Point-in-time volume snapshots — clone or restore into new volumes.	Open
Schedules	<code>/schedules</code>	Automate periodic snapshots or backups for a volume.	Open

DATA PROTECTION

Page	Route	Purpose	Guide
Backups	<code>/backups</code>	Volume backups into object buckets — create, restore, and retire copies.	Open
Buckets	<code>/buckets</code>	Object gateway buckets for exports and backup destinations.	Open
Protection Status	<code>/protection</code>	Per-volume protection verdict — healthy / degraded / unprotected rollup.	Open

OBSERVABILITY

Page	Route	Purpose	Guide
Observatory	<code>/observatory</code>	Estate telemetry canvas — capacity lenses and jump to Deck or Alerts.	Open
Activity	<code>/activity</code>	Recent operator and system activity stream.	Open
Alerts	<code>/alerts</code>	Open alert ledger — silence or resolve before capacity work.	Open
Metrics	<code>/metrics-dashboard</code>	Ceph-native metric samples and OSD utilization averages.	Open
Jobs	<code>/jobs</code>	Durable async jobs for every mutation — progress, SSE live updates, failure detail.	Open
Audit	<code>/audit</code>	Compliance trail of state-changing and sensitive actions.	Open

GOVERNANCE

Page	Route	Purpose	Guide
Tenants	<code>/tenants</code>	Tenant index — quotas and policy overrides.	Open
Access	<code>/access</code>	Local users for Storage Center sign-in — create and delete accounts.	Open

Page	Route	Purpose	Guide
Policies	/policies	Built-in intent → placement catalog (atlas-policy) used when creating volumes.	Open
Settings	/settings	Console settings — theme and session preferences for Storage Center.	Open
API Docs	/api-docs	Curated REST + gRPC map for operators and integrators.	Open

DATABRIDGE

Page	Route	Purpose	Guide
Cloud Databases	/databridge/sources	Register external / cloud database sources for DataBridge migrations.	Open
Migration Plans	/databridge/plans	Create and list DataBridge migration plans from registered sources.	Open
Plan Detail	/databridge/plans/:id	Single migration plan — stages, CDC controls, cutover, and validation hooks.	Open
Edge DB Clusters	/databridge/edge-clusters	Edge database clusters provisioned as migration targets.	Open
Replication	/databridge/replication	CDC replication streams for active migration plans.	Open
Validation	/databridge/validation	Validation runs and per-table results for migrated data.	Open

INFRASTRUCTURE

Page	Route	Purpose	Guide
Backends	/backends	Registered storage backends — discovery and capacity summary.	Open
Kubernetes	/kubernetes	Discovered StorageClasses from the attached cluster.	Open
Cluster	/cluster	Primary cluster inventory — health, pools, OSDs.	Open
Ceph	/ceph	Day-2 Ceph signals — health rollup, df pools, OSD tree.	Open
Pool Detail	/pools/:id	Single pool sounding — volumes and OSD cells for one pool.	Open
Maintenance	/maintenance	Pause the job engine, cordon backends, and clean orphan backups.	Open
Disaster Recovery	/dr	Cross-cluster RBD mirroring — peers, mirrors, promote/demote/failover.	Open

Related

- [Customer docs home](#)
- [Page-by-page guides](#)