

ZYVORAI LABS · CUSTOMER DOCUMENTATION



Page-by-Page Product Manual

2026-07-26

Page-by-page guides

Each guide follows: Purpose → When to use it → How to get there → What you can do → Related pages.

Every route is also listed in the [complete page index](#).

Data Protection

Page	What it covers
Backups	Backup jobs and restore entry points for protected volumes.
Buckets	Object / RGW bucket inventory and lifecycle.

Databridge

Page	What it covers
Edge DB Clusters	Edge database clusters managed through DataBridge.
Plan Detail	Single migration plan detail — stages, validation, and cutover.
Migration Plans	Database and object migration plans.
Replication	Ongoing replication links for DataBridge workloads.
Cloud Databases	Cloud / external database sources for DataBridge migrations.
Validation	Pre/post migration validation results.

Governance

Page	What it covers
Access	Tokens, roles, and API access for Storage Center and clients.
Policies	Storage intent policies (production, database, development, shared, ai).
Tenants	Multi-tenant isolation and quota boundaries.

Infrastructure

Page	What it covers
Backends	Registered StorageDriver backends (Ceph first; NFS/ZFS/etc. as added).
Ceph	Ceph-specific day-2 operations (OSD, pool, RGW health).
Cluster	Atlas gateway cluster / HA membership view.
Disaster Recovery	Disaster recovery plans and failover for Atlas-managed data.
Kubernetes	Kubernetes StorageClass / CSI integration status for Atlas.
Maintenance	Maintenance windows and safe ops against storage backends.

Observability

Page	What it covers
Activity	Recent storage activity feed (provisions, deletes, migrations).
Alerts	Storage and backend alerts requiring operator attention.
Audit	Audit log of storage control-plane actions (exportable).
Jobs	Durable async jobs from every mutating Atlas API call.
Metrics	Metrics dashboards for pools, devices, and gateway latency.
Observatory	Cross-cutting health and capacity observatory for the storage plane.

Storage

Page	What it covers
Command Deck	Storage Center home — capacity, job health, backend status, and shortcuts into volumes and protection.
RBD Images	Ceph RBD image inventory when the Ceph driver is active.
Schedules	Snapshot / backup schedule policies.
Snapshots	Volume and image snapshots for point-in-time recovery.
Volumes	Intent-backed volume inventory across registered storage backends.

28 guides. Regenerate: `node scripts/customer-docs/generate-guide-index.mjs` .

Backups

Purpose

Backup jobs and restore entry points for protected volumes.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/backups`
- Nav: **DATA PROTECTION** → **Backups** (sidebar, dock, or spotlight)

What you can do

1. Open `/backups` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Buckets

Purpose

Object / RGW bucket inventory and lifecycle.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/buckets`
- Nav: **DATA PROTECTION** → **Buckets** (sidebar, dock, or spotlight)

What you can do

1. Open `/buckets` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Edge DB Clusters

Purpose

Edge database clusters managed through DataBridge.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/databridge/edge-clusters`
- Nav: **DATABRIDGE** → **Edge DB Clusters** (sidebar, dock, or spotlight)

What you can do

1. Open `/databridge/edge-clusters` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Plan Detail

Purpose

Single migration plan detail — stages, validation, and cutover.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/databridge/plans/:id`
- Nav: **DATABRIDGE** → **Plan Detail** (sidebar, dock, or spotlight)

What you can do

1. Open `/databridge/plans/:id` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Migration Plans

Purpose

Database and object migration plans.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/databridge/plans`
- Nav: **DATABRIDGE** → **Migration Plans** (sidebar, dock, or spotlight)

What you can do

1. Open `/databridge/plans` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Replication

Purpose

Ongoing replication links for DataBridge workloads.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/databridge/replication`
- Nav: **DATABRIDGE** → **Replication** (sidebar, dock, or spotlight)

What you can do

1. Open `/databridge/replication` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Cloud Databases

Purpose

Cloud / external database sources for DataBridge migrations.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/databridge/sources`
- Nav: **DATABRIDGE** → **Cloud Databases** (sidebar, dock, or spotlight)

What you can do

1. Open `/databridge/sources` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Validation

Purpose

Pre/post migration validation results.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/databridge/validation`
- Nav: **DATABRIDGE** → **Validation** (sidebar, dock, or spotlight)

What you can do

1. Open `/databridge/validation` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Access

Purpose

Tokens, roles, and API access for Storage Center and clients.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/access`
- Nav: **GOVERNANCE** → **Access** (sidebar, dock, or spotlight)

What you can do

1. Open `/access` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Policies

Purpose

Storage intent policies (production, database, development, shared, ai).

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/policies`
- Nav: **GOVERNANCE** → **Policies** (sidebar, dock, or spotlight)

What you can do

1. Open `/policies` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Tenants

Purpose

Multi-tenant isolation and quota boundaries.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/tenants`
- Nav: **GOVERNANCE** → **Tenants** (sidebar, dock, or spotlight)

What you can do

1. Open `/tenants` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Backends

Purpose

Registered StorageDriver backends (Ceph first; NFS/ZFS/etc. as added).

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/backends`
- Nav: **INFRASTRUCTURE** → **Backends** (sidebar, dock, or spotlight)

What you can do

1. Open `/backends` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Ceph

Purpose

Ceph-specific day-2 operations (OSD, pool, RGW health).

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/ceph`
- Nav: **INFRASTRUCTURE** → **Ceph** (sidebar, dock, or spotlight)

What you can do

1. Open `/ceph` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Cluster

Purpose

Atlas gateway cluster / HA membership view.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/cluster`
- Nav: **INFRASTRUCTURE** → **Cluster** (sidebar, dock, or spotlight)

What you can do

1. Open `/cluster` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Disaster Recovery

Purpose

Disaster recovery plans and failover for Atlas-managed data.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/dr`
- Nav: **INFRASTRUCTURE** → **Disaster Recovery** (sidebar, dock, or spotlight)

What you can do

1. Open `/dr` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Kubernetes

Purpose

Kubernetes StorageClass / CSI integration status for Atlas.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/kubernetes`
- Nav: **INFRASTRUCTURE** → **Kubernetes** (sidebar, dock, or spotlight)

What you can do

1. Open `/kubernetes` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Maintenance

Purpose

Maintenance windows and safe ops against storage backends.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/maintenance`
- Nav: **INFRASTRUCTURE** → **Maintenance** (sidebar, dock, or spotlight)

What you can do

1. Open `/maintenance` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Activity

Purpose

Recent storage activity feed (provisions, deletes, migrations).

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/activity`
- Nav: **OBSERVABILITY** → **Activity** (sidebar, dock, or spotlight)

What you can do

1. Open `/activity` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Alerts

Purpose

Storage and backend alerts requiring operator attention.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/alerts`
- Nav: **OBSERVABILITY** → **Alerts** (sidebar, dock, or spotlight)

What you can do

1. Open `/alerts` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Audit

Purpose

Audit log of storage control-plane actions (exportable).

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/audit`
- Nav: **OBSERVABILITY** → **Audit** (sidebar, dock, or spotlight)

What you can do

1. Open `/audit` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Jobs

Purpose

Durable async jobs from every mutating Atlas API call.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/jobs`
- Nav: **OBSERVABILITY** → **Jobs** (sidebar, dock, or spotlight)

What you can do

1. Open `/jobs` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Metrics

Purpose

Metrics dashboards for pools, devices, and gateway latency.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/metrics-dashboard`
- Nav: **OBSERVABILITY** → **Metrics** (sidebar, dock, or spotlight)

What you can do

1. Open `/metrics-dashboard` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Observatory

Purpose

Cross-cutting health and capacity observatory for the storage plane.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/observatory`
- Nav: **OBSERVABILITY** → **Observatory** (sidebar, dock, or spotlight)

What you can do

1. Open `/observatory` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Command Deck

Purpose

Storage Center home — capacity, job health, backend status, and shortcuts into volumes and protection.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: /
- Nav: **STORAGE** → **Command Deck** (sidebar, dock, or spotlight)

What you can do

1. Open / and wait for live data from the Atlas gateway (default :5110).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (202 + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check /health , auth (ATLAS_AUTH_REQUIRED / JWT), that a storage driver is registered, and run atlasctl discover if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

RBD Images

Purpose

Ceph RBD image inventory when the Ceph driver is active.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/rbd`
- Nav: **STORAGE** → **RBD Images** (sidebar, dock, or spotlight)

What you can do

1. Open `/rbd` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Schedules

Purpose

Snapshot / backup schedule policies.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/schedules`
- Nav: **STORAGE** → **Schedules** (sidebar, dock, or spotlight)

What you can do

1. Open `/schedules` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Snapshots

Purpose

Volume and image snapshots for point-in-time recovery.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/snapshots`
- Nav: **STORAGE** → **Snapshots** (sidebar, dock, or spotlight)

What you can do

1. Open `/snapshots` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health`, auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Volumes

Purpose

Intent-backed volume inventory across registered storage backends.

When to use it

- Open this page when the job matches the purpose above
- Prefer **Command Deck** (/) first if you are unsure where to start
- Confirm gateway auth and backend connectivity if inventories look empty

How to get there

- Route: `/volumes`
- Nav: **STORAGE** → **Volumes** (sidebar, dock, or spotlight)

What you can do

1. Open `/volumes` and wait for live data from the Atlas gateway (default **:5110**).
2. Use filters (backend, tenant, kind, status) when the page provides them.
3. Drill into a volume, job, or plan for detail — mutations return durable jobs (`202` + job id).
4. For mutating actions (provision, backup, migrate, DR): review tenant quotas and job status in **Jobs**.

If the page stays empty, check `/health` , auth (`ATLAS_AUTH_REQUIRED` / JWT), that a storage driver is registered, and run `atlasctl discover` if inventory is cold.

Related pages

- [Getting Started](#)
 - [Command Deck](#)
 - [Volumes](#)
 - [Page index](#)
-

Atlas — Complete page index

Every primary navigable dashboard route.

Generated: 2026-07-26 · 28 routes

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

STORAGE

Page	Route	Purpose	Guide
Command Deck	<code>/</code>	Storage Center home — capacity, job health, backend status, and shortcuts into volumes and protection.	Open
Volumes	<code>/volumes</code>	Intent-backed volume inventory across registered storage backends.	Open
RBD Images	<code>/rbd</code>	Ceph RBD image inventory when the Ceph driver is active.	Open
Snapshots	<code>/snapshots</code>	Volume and image snapshots for point-in-time recovery.	Open
Schedules	<code>/schedules</code>	Snapshot / backup schedule policies.	Open

DATA PROTECTION

Page	Route	Purpose	Guide
Backups	<code>/backups</code>	Backup jobs and restore entry points for protected volumes.	Open
Buckets	<code>/buckets</code>	Object / RGW bucket inventory and lifecycle.	Open

OBSERVABILITY

Page	Route	Purpose	Guide
Observatory	<code>/observatory</code>	Cross-cutting health and capacity observatory for the storage plane.	Open
Activity	<code>/activity</code>	Recent storage activity feed (provisions, deletes, migrations).	Open
Alerts	<code>/alerts</code>	Storage and backend alerts requiring operator attention.	Open
Metrics	<code>/metrics-dashboard</code>	Metrics dashboards for pools, devices, and gateway latency.	Open
Jobs	<code>/jobs</code>	Durable async jobs from every mutating Atlas API call.	Open
Audit	<code>/audit</code>	Audit log of storage control-plane actions (exportable).	Open

GOVERNANCE

Page	Route	Purpose	Guide
Tenants	<code>/tenants</code>	Multi-tenant isolation and quota boundaries.	Open
Access	<code>/access</code>	Tokens, roles, and API access for Storage Center and clients.	Open
Policies	<code>/policies</code>	Storage intent policies (production, database, development, shared, ai).	Open

DATABRIDGE

Page	Route	Purpose	Guide
Cloud Databases	/databridge/sources	Cloud / external database sources for DataBridge migrations.	Open
Migration Plans	/databridge/plans	Database and object migration plans.	Open
Plan Detail	/databridge/plans/:id	Single migration plan detail — stages, validation, and cutover.	Open
Edge DB Clusters	/databridge/edge-clusters	Edge database clusters managed through DataBridge.	Open
Replication	/databridge/replication	Ongoing replication links for DataBridge workloads.	Open
Validation	/databridge/validation	Pre/post migration validation results.	Open

INFRASTRUCTURE

Page	Route	Purpose	Guide
Backends	/backends	Registered StorageDriver backends (Ceph first; NFS/ZFS/etc. as added).	Open
Kubernetes	/kubernetes	Kubernetes StorageClass / CSI integration status for Atlas.	Open
Cluster	/cluster	Atlas gateway cluster / HA membership view.	Open
Ceph	/ceph	Ceph-specific day-2 operations (OSD, pool, RGW health).	Open
Maintenance	/maintenance	Maintenance windows and safe ops against storage backends.	Open
Disaster Recovery	/dr	Disaster recovery plans and failover for Atlas-managed data.	Open

Related

- [Customer docs home](#)
- [Page-by-page guides](#)