ZYVORAI LABS · CUSTOMER DOCUMENTATION

# Axiom

Page-by-Page Product Manual

2026-08-29

zyvor.dev · Confidential — for licensed customers

# Page-by-page guides

Each guide follows: Purpose → When to use it → How to get there → Operate from the console (UX) → Related pages.

Every route is also listed in the complete page index.

### Admin

| Page | What it covers |
|---|---|
| Ops hub | Day-2 ops tabs — GitOps/Helm/RBAC/Identity and related operator tools. |
| Settings | Integrations, clusters, theme, and console configuration. |
| Users | Local user accounts with admin or viewer roles. |

### Auth

| Page | What it covers |
|---|---|
| Login | Sign in to the Liquid Glass console — local Basic auth, SSO (OIDC/SAML), or lab demo helper. |

### Cluster

| Page | What it covers |
|---|---|
| Custom Resources | Browse CRD kinds and list custom resource instances. |
| Namespaces | Namespace inventory — create and delete tenancy boundaries. |
| Node detail | Single-node conditions, capacity, taints, and related workloads. |
| Nodes | Kubernetes node inventory — Ready state, capacity, and entry into node detail. |

### Compute

| Page | What it covers |
|---|---|
| Virtual Machines | KubeVirt VM inventory and day-2 actions in the Axiom console. |

### Config

| Page | What it covers |
|---|---|
| ConfigMaps | ConfigMap inventory — create, edit keys, delete. |
| Quotas & Limits | ResourceQuotas, LimitRanges, PDBs, PriorityClasses. |
| Secrets | Secret inventory — create typed secrets, add keys, delete. |

### Console

| Page | What it covers |
|---|---|
| Getting Started | Live setup checklist — integration status and first tasks after sign-in. |

| Page | What it covers |
| --- | --- |
| Overview | Cluster pulse — capacity metrics, activity, and shortcuts into day-2 centers. |

### Networking

| Page | What it covers |
| --- | --- |
| Ingresses | Ingress and Gateway API exposure inventory. |
| Networking · Cilium | Service graph, NetworkPolicies, and live PacketWolf flows when configured. |
| Services | Kubernetes Service inventory and endpoints overview. |

### Observe

| Page | What it covers |
| --- | --- |
| Alerts | Alert inventory and webhook-driven notifications. |
| Events | Kubernetes warning/normal events stream for triage. |
| Pod Logs | Stream and inspect pod/container logs from the console. |

### Protect

| Page | What it covers |
| --- | --- |
| Backups | Volume snapshots, Velero backups, and schedules. |

### Storage

| Page | What it covers |
| --- | --- |
| Atlas | Atlas storage control-plane panel — backends, pools, volumes, buckets, policies. |
| Storage | PVC / storage class intelligence for the connected cluster. |

### Workloads

| Page | What it covers |
| --- | --- |
| Autoscaling | Horizontal Pod Autoscalers — create and delete. |
| Jobs & CronJobs | Batch Jobs and CronJobs — trigger runs, inspect status, delete. |
| Platform Intents | Intent-driven placement / platform requests surfaced in the console. |
| Pod detail | Container specs, metrics, multi-tab PTY terminal, manifest Save, port Open. |
| Pods | Pod inventory across namespaces — phase, restarts, entry into pod detail. |
| Workload detail | Single controller — owned pods, events, labels, rollout, raw YAML. |
| Workloads | Deployments, StatefulSets, DaemonSets — scale, restart, seal, rollout, and Run workload wizard. |

---

30 guides. Regenerate: `node scripts/customer-docs/generate-guide-index.mjs`.

# Ops hub

## Purpose

Day-2 ops tabs — GitOps/Helm/RBAC/Identity and related operator tools.

## When to use it

- Operate **Ops hub** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/ops`
- Nav: **Sidebar → Ops (** `/ops` **or** `/ops/:tab` **)**

## Operate from the console (UX)

1. Open `/ops` and switch tabs as labeled in the UI.
2. RBAC: **New Role** / **New RoleBinding**; Sync where offered.
3. Identity tab: Haven/Keycloak health when installed.
4. **Empty / fail:** Tab empty → optional component not installed.
5. **Success:** Sync/create toasts succeed; RBAC objects listed.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Users
- Settings
- Getting Started
- Page index

# Settings

### Purpose

Integrations, clusters, theme, and console configuration.

### When to use it

- Operate **Settings** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/settings`
- Nav: **Sidebar → Settings**

### Operate from the console (UX)

1. Open `/settings`.
2. Integrations: Atlas URL/token → Save → Test connection; OIDC/SAML; PacketWolf.
3. Clusters: review activated cluster label ( `AXIOM_CLUSTER_NAME` ).
4. Theme toggle via shell control.
5. **Empty / fail:** Test connection failed → network/token; OIDC redirect URI must be `https://<host>:30590/api/v1/auth/oidc/callback`.
6. **Success:** Integration cards healthy; Atlas/Networking panels populate.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT` ). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Atlas
- Users
- Getting Started
- Getting Started
- Page index

# Users

## Purpose

Local user accounts with admin or viewer roles.

## When to use it

- Operate **Users** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/users`
- Nav: **Sidebar → Users**

## Operate from the console (UX)

1. Open `/users` (admin).
2. Create users with admin/viewer; viewers read-only on mutating APIs.
3. **Empty / fail:** Persistence needs `zyvor-axiom-users` Secret in production.
4. **Success:** New user can sign in with the assigned role.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Settings
- Login
- Getting Started
- Page index

# Login

## Purpose

Sign in to the Liquid Glass console — local Basic auth, SSO (OIDC/SAML), or lab demo helper.

## When to use it

- Operate **Login** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/login`
- Nav: **Shown when unauthenticated →** `/login`

## Operate from the console (UX)

1. Open `https://<host>:30590/` and accept the self-signed certificate once if needed.
2. When SSO is off, use **fill demo / demo** then **Sign in** (lab default `demo` / `demo`).
3. Or enter operator credentials from Secret `zyvor-axiom-auth` / `AXIOM_USERNAME` + `AXIOM_PASSWORD`.
4. When SSO is configured, use the OIDC/SAML buttons (public client + PKCE).
5. **Empty / fail:** Sign in failed toast → check credentials / SSO redirect URI `/api/v1/auth/oidc/callback`; health: `curl -k https://<host>:30590/api/v1/health`.
6. **Success:** Redirect to **Overview**; cluster switcher and sidebar appear.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Overview
- Getting Started
- Getting Started
- Page index

# Custom Resources

## Purpose

Browse CRD kinds and list custom resource instances.

## When to use it

- Operate **Custom Resources** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/custom-resources`
- Nav: **Sidebar → Custom Resources**

## Operate from the console (UX)

1. Open `/custom-resources`.
2. Select a kind; inspect instance table.
3. **Empty / fail:** No CRDs → expected on minimal clusters; install operators as needed.
4. **Success:** Instances for installed operators appear.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Ops hub
- Getting Started
- Page index

# Namespaces

### Purpose

Namespace inventory — create and delete tenancy boundaries.

### When to use it

- Operate **Namespaces** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/namespaces`
- Nav: **Sidebar → Namespaces**

### Operate from the console (UX)

1. Open `/namespaces`.
2. **Create namespace** → name → Create; Delete from row actions (confirm).
3. **Empty / fail:** 403 → viewer; delete blocked if resources remain.
4. **Success:** Namespace appears in filters across Workloads/Pods.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Workloads
- Quotas & Limits
- Getting Started
- Page index

# Node detail

### Purpose

Single-node conditions, capacity, taints, and related workloads.

### When to use it

- Operate **Node detail** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/nodes/:name`
- Nav: **Nodes → row**

### Operate from the console (UX)

1. Open a node from `/nodes`.
2. Review conditions and capacity; add/remove taints as needed.
3. Correlate NotReady with Events and Pods.
4. **Empty / fail:** 404 → stale name; permission errors → ClusterRole.
5. **Success:** Taint/condition changes reflect after refresh.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Nodes
- Events
- Getting Started
- Page index

# Nodes

### Purpose

Kubernetes node inventory — Ready state, capacity, and entry into node detail.

### When to use it

- Operate **Nodes** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/nodes`
- Nav: **Sidebar → Nodes**

### Operate from the console (UX)

1. Open `/nodes` and wait for the table.
2. Filter/search; open a row → `/nodes/:name` for taints, conditions, capacity.
3. On detail: **Add taint** when draining or isolating capacity.
4. **Empty / fail:** No nodes → cluster API / RBAC; demo mode should still show fixtures.
5. **Success:** Ready nodes listed; detail matches cluster state.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Node detail
- Events
- Pods
- Getting Started
- Page index

# Virtual Machines

### Purpose

KubeVirt VM inventory and day-2 actions in the Axiom console.

### When to use it

- Operate **Virtual Machines** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/vms`
- Nav: **Sidebar → Virtual Machines**

### Operate from the console (UX)

1. Open `/vms`.
2. Filter and open VMs; use lifecycle actions the page exposes (start/stop when available).
3. Confirm KubeVirt is installed if the list stays empty on a real cluster.
4. **Empty / fail:** No VMs → install KubeVirt or use demo fixtures.
5. **Success:** VM phases update after power actions.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Storage
- Overview
- Getting Started
- Page index

# ConfigMaps

## Purpose

ConfigMap inventory — create, edit keys, delete.

## When to use it

- Operate **ConfigMaps** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/configmaps`
- Nav: **Sidebar → ConfigMaps**

## Operate from the console (UX)

1. Open `/configmaps`.
2. **Create ConfigMap** — add keys → Create; delete retired maps.
3. **Empty / fail:** 403 on mutate → viewer role.
4. **Success:** ConfigMap listed and mountable by workloads.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Secrets
- Workloads
- Getting Started
- Page index

# Quotas & Limits

## Purpose

ResourceQuotas, LimitRanges, PDBs, PriorityClasses.

## When to use it

- Operate **Quotas & Limits** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/quotas`
- Nav: **Sidebar → Quotas & Limits**

## Operate from the console (UX)

1. Open `/quotas`.
2. Review quota / limit range / PDB / priority class tables.
3. Adjust via YAML apply when the UI does not offer inline edit.
4. **Empty / fail:** No quotas → create for multi-tenant namespaces.
5. **Success:** Hard limits visible; workload create respects them.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Namespaces
- Workloads
- Getting Started
- Page index

# Secrets

## Purpose

Secret inventory — create typed secrets, add keys, delete.

## When to use it

- Operate **Secrets** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/secrets`
- Nav: **Sidebar → Secrets**

## Operate from the console (UX)

1. Open `/secrets`.
2. **Create secret** — type + keys → Create; treat values as sensitive in UI.
3. **Empty / fail:** ClusterRole must allow secrets write in scope used by Users/Integrations.
4. **Success:** Secret available to workloads; delete cleans up.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- ConfigMaps
- Users
- Getting Started
- Page index

# Getting Started

### Purpose

Live setup checklist — integration status and first tasks after sign-in.

### When to use it

- Operate **Getting Started** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/getting-started`
- Nav: **Sidebar → Getting Started**

### Operate from the console (UX)

1. Open `/getting-started` after first login.
2. Walk the checklist; items reflect live Atlas/OIDC/PacketWolf/Haven status.
3. Jump from incomplete items into Settings → Integrations or the related center.
4. **Empty / fail:** Checklist stale → refresh; viewer role can read but cannot complete mutating setup.
5. **Success:** Critical integrations green; you can run a workload or open Overview confidently.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Overview
- Settings
- Workloads
- Getting Started
- Page index

# Overview

## Purpose

Cluster pulse — capacity metrics, activity, and shortcuts into day-2 centers.

## When to use it

- Operate **Overview** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/overview`
- Nav: **Sidebar → Overview (default after login)**

## Operate from the console (UX)

1. Land on `/overview` after sign-in (or click Overview).
2. Confirm cluster name/metrics and recent activity load.
3. Use the sidebar cluster switcher when multiple clusters are configured (demo mode ships three).
4. Jump to Nodes / Workloads / Alerts from shortcuts or ⌘K.
5. **Empty / fail:** Metrics blank → API unreachable or wrong activated cluster; re-login.
6. **Success:** Cluster headline + cards match `kubectl` reality (or demo fixtures).

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Nodes
- Workloads
- Alerts
- Getting Started
- Getting Started
- Page index

# Ingresses

## Purpose

Ingress and Gateway API exposure inventory.

## When to use it

- Operate **Ingresses** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/ingresses`
- Nav: **Sidebar → Ingresses**

## Operate from the console (UX)

1. Open `/ingresses`.
2. Review host/path rules and Gateway API section when present.
3. **Empty / fail:** No ingresses → install ingress controller / apply manifests.
4. **Success:** Hosts listed match customer DNS expectations.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Services
- Getting Started
- Page index

# Networking · Cilium

### Purpose

Service graph, NetworkPolicies, and live PacketWolf flows when configured.

### When to use it

- Operate **Networking · Cilium** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/networking`
- Nav: **Sidebar → Networking · Cilium**

### Operate from the console (UX)

1. Open `/networking`.
2. Inspect service graph / Cilium summary.
3. NetworkPolicies: **Create via YAML** (ApplyManifest) or Delete rows.
4. When `AXIOM_PACKETWOLF_URL` is set, read the live eBPF flow panel.
5. **Empty / fail:** No flows → PacketWolf unreachable; policies empty → create first.
6. **Success:** Graph + policies match cluster; seal on a workload shows isolation.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Services
- Workloads
- Settings
- Getting Started
- Page index

# Services

## Purpose

Kubernetes Service inventory and endpoints overview.

## When to use it

- Operate **Services** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/services`
- Nav: **Sidebar → Services**

## Operate from the console (UX)

1. Open `/services`; filter by namespace.
2. Open a row for ports/selectors; correlate with Ingresses and Pods.
3. **Empty / fail:** No services → deploy a workload first.
4. **Success:** ClusterIP/NodePort/LB entries listed.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Ingresses
- Networking · Cilium
- Getting Started
- Page index

# Alerts

## Purpose

Alert inventory and webhook-driven notifications.

## When to use it

- Operate **Alerts** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/alerts`
- Nav: **Sidebar → Alerts**

## Operate from the console (UX)

1. Open `/alerts`.
2. Review firing/open alerts; configure webhooks under Settings when available.
3. **Empty / fail:** No alerts → healthy or integrations not wired.
4. **Success:** Alert rows match monitoring rules / webhooks.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Events
- Settings
- Getting Started
- Page index

# Events

## Purpose

Kubernetes warning/normal events stream for triage.

## When to use it

- Operate **Events** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/events`
- Nav: **Sidebar → Events**

## Operate from the console (UX)

1. Open `/events`.
2. Filter by type/namespace; open related object links when present.
3. **Empty / fail:** Quiet cluster is OK; missing events → API watch issue.
4. **Success:** Recent warnings explain Pending/Failed pods.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Pods
- Alerts
- Getting Started
- Page index

# Pod Logs

### Purpose

Stream and inspect pod/container logs from the console.

### When to use it

- Operate **Pod Logs** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/logs`
- Nav: **Sidebar → Pod Logs**

### Operate from the console (UX)

1. Open `/logs`.
2. Select namespace/pod/container; stream or fetch recent lines.
3. Correlate with Events and Pod detail when diagnosing CrashLoop.
4. **Empty / fail:** No lines → wrong container / pod gone; 403 → RBAC logs.
5. **Success:** Live or recent log text for the selected container.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Pods
- Events
- Getting Started
- Page index

# Backups

## Purpose

Volume snapshots, Velero backups, and schedules.

## When to use it

- Operate **Backups** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/backups`
- Nav: **Sidebar → Backups**

## Operate from the console (UX)

1. Open `/backups`.
2. **Create snapshot** for a PVC; **Restore** into a new PVC name when offered.
3. Velero: create schedules / list backups when Velero is installed.
4. **Empty / fail:** Snapshot class missing → install CSI snapshotter; Velero empty → install Velero.
5. **Success:** Snapshot/backup row appears; restore binds a PVC.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Storage
- Atlas
- Getting Started
- Page index

# Atlas

## Purpose

Atlas storage control-plane panel — backends, pools, volumes, buckets, policies.

## When to use it

- Operate **Atlas** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/atlas`
- Nav: **Sidebar → Atlas**

## Operate from the console (UX)

1. Wire Atlas under **Settings → Integrations** (URL + token) or deploy with `--with-atlas`.
2. Open `/atlas` — backends/pools should load when connected.
3. **Create volume** for a smoke provision; review buckets/policies tables.
4. **Empty / fail:** Connection failed → Test connection in Settings; token/RBAC.
5. **Success:** Volume appears; Storage page reflects new PVC if bound into k8s.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Storage
- Settings
- Getting Started
- Page index

# Storage

## Purpose

PVC / storage class intelligence for the connected cluster.

## When to use it

- Operate **Storage** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/storage`
- Nav: **Sidebar → Storage**

## Operate from the console (UX)

1. Open `/storage`.
2. Review PVCs/StorageClasses; note bound vs pending.
3. Cross-link to Atlas for intent-backed provisioning.
4. **Empty / fail:** Pending PVCs → check provisioner / Atlas.
5. **Success:** Bound volumes listed for workloads.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Atlas
- Backups
- Getting Started
- Page index

# Autoscaling

### Purpose

Horizontal Pod Autoscalers — create and delete.

### When to use it

- Operate **Autoscaling** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/autoscaling`
- Nav: **Sidebar → Autoscaling**

### Operate from the console (UX)

1. Open `/autoscaling`.
2. **Create autoscaler** — pick workload + min/max/CPU target → Create.
3. Delete retired HPAs from the table.
4. **Empty / fail:** metrics-server missing → HPA cannot compute.
5. **Success:** HPA listed; replicas move under load.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Workloads
- Getting Started
- Page index

# Jobs & CronJobs

## Purpose

Batch Jobs and CronJobs — trigger runs, inspect status, delete.

## When to use it

- Operate **Jobs & CronJobs** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/jobs`
- Nav: **Sidebar → Jobs & CronJobs**

## Operate from the console (UX)

1. Open `/jobs`.
2. On CronJobs: **Run now** to trigger; delete retired jobs/cronjobs from row actions.
3. Confirm Job pods under Pods / Logs.
4. **Empty / fail:** No CronJobs → create via Apply YAML or workload wizard.
5. **Success:** Triggered Job appears with completions.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Pods
- Pod Logs
- Getting Started
- Page index

# Platform Intents

### Purpose

Intent-driven placement / platform requests surfaced in the console.

### When to use it

- Operate **Platform Intents** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/platform-intents`
- Nav: **Sidebar → Platform Intents**

### Operate from the console (UX)

1. Open `/platform-intents`.
2. Review intent cards/status; create via Workloads → Run → Intent when offered.
3. **Empty / fail:** No intents → submit one from the wizard.
4. **Success:** Intent progresses to a concrete workload.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Workloads
- Getting Started
- Page index

# Pod detail

### Purpose

Container specs, metrics, multi-tab PTY terminal, manifest Save, port Open.

### When to use it

- Operate **Pod detail** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/pods/:namespace/:name`
- Nav: **Pods → row**

### Operate from the console (UX)

1. Open a pod from `/pods`.
2. Read resources/env/probes; Metrics tab for CPU/memory sparklines.
3. Terminal: open sessions (multi-tab WebSocket); demo falls back to one-shot exec.
4. YAML tab → **Save** (server-side apply); Open buttons for container ports.
5. **Empty / fail:** Terminal blocked → auth/token on WS; Save 403 → viewer role.
6. **Success:** Shell prompt or metrics stream; Save toast OK.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Pods
- Pod Logs
- Workloads
- Getting Started
- Page index

# Pods

## Purpose

Pod inventory across namespaces — phase, restarts, entry into pod detail.

## When to use it

- Operate **Pods** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/pods`
- Nav: **Sidebar → Pods**

## Operate from the console (UX)

1. Open `/pods`; filter by namespace/status.
2. Open `/pods/:ns/:name` for specs, metrics, terminal, YAML.
3. Use scheduling-diagnosis banner when not Running.
4. **Empty / fail:** Empty → broaden namespace; CrashLoop → Logs + Events.
5. **Success:** Running pods listed; detail terminal connects (HTTPS / token).

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Pod detail
- Pod Logs
- Events
- Getting Started
- Page index

# Workload detail

### Purpose

Single controller — owned pods, events, labels, rollout, raw YAML.

### When to use it

- Operate **Workload detail** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

### How to get there

- Route: `/workloads/:namespace/:kind/:name`
- Nav: **Workloads → row**

### Operate from the console (UX)

1. Open a workload from the list.
2. Inspect owned Pods and Events; use lifecycle actions from the page.
3. Edit YAML carefully — Save uses server-side apply where offered.
4. **Empty / fail:** Missing pods → check selectors / Events.
5. **Success:** Desired replicas match Ready; rollout history coherent.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

### Related pages

- Workloads
- Pods
- Events
- Getting Started
- Page index

# Workloads

## Purpose

Deployments, StatefulSets, DaemonSets — scale, restart, seal, rollout, and Run workload wizard.

## When to use it

- Operate **Workloads** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

## How to get there

- Route: `/workloads`
- Nav: **Sidebar → Workloads**

## Operate from the console (UX)

1. Open `/workloads`.
2. **Run workload** — Form / Intent / YAML tabs → submit.
3. Row menu: Start / Stop / Restart / Scale / Seal / Unseal / Delete / Rollout (pause, resume, undo).
4. Open detail `/workloads/:ns/:kind/:name` for pods, events, YAML.
5. **Empty / fail:** Viewer gets 403 on mutate; empty list → wrong namespace filter or fresh cluster.
6. **Success:** New Deployment appears; scale/restart toasts succeed.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

## Related pages

- Workload detail
- Pods
- Platform Intents
- Getting Started
- Page index

# Axiom — Complete page index

Every primary navigable dashboard route.

*Generated: 2026-08-29 · 30 routes*

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

## AUTH

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Login | `/login` | Sign in to the Liquid Glass console — local Basic auth, SSO (OIDC/SAML), or lab demo helper. | Open |

## CONSOLE

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Getting Started | `/getting-started` | Live setup checklist — integration status and first tasks after sign-in. | Open |
| Overview | `/overview` | Cluster pulse — capacity metrics, activity, and shortcuts into day-2 centers. | Open |

## CLUSTER

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Nodes | `/nodes` | Kubernetes node inventory — Ready state, capacity, and entry into node detail. | Open |
| Node detail | `/nodes/:name` | Single-node conditions, capacity, taints, and related workloads. | Open |
| Namespaces | `/namespaces` | Namespace inventory — create and delete tenancy boundaries. | Open |
| Custom Resources | `/custom-resources` | Browse CRD kinds and list custom resource instances. | Open |

## WORKLOADS

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Workloads | `/workloads` | Deployments, StatefulSets, DaemonSets — scale, restart, seal, rollout, and Run workload wizard. | Open |
| Workload detail | `/workloads/:namespace/:kind/:name` | Single controller — owned pods, events, labels, rollout, raw YAML. | Open |
| Jobs & CronJobs | `/jobs` | Batch Jobs and CronJobs — trigger runs, inspect status, delete. | Open |
| Pods | `/pods` | Pod inventory across namespaces — phase, restarts, entry into pod detail. | Open |
| Pod detail | `/pods/:namespace/:name` | Container specs, metrics, multi-tab PTY terminal, manifest Save, port Open. | Open |

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Platform Intents | `/platform-intents` | Intent-driven placement / platform requests surfaced in the console. | Open |
| Autoscaling | `/autoscaling` | Horizontal Pod Autoscalers — create and delete. | Open |

### NETWORKING

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Networking · Cilium | `/networking` | Service graph, NetworkPolicies, and live PacketWolf flows when configured. | Open |
| Services | `/services` | Kubernetes Service inventory and endpoints overview. | Open |
| Ingresses | `/ingresses` | Ingress and Gateway API exposure inventory. | Open |

### COMPUTE

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Virtual Machines | `/vms` | KubeVirt VM inventory and day-2 actions in the Axiom console. | Open |

### STORAGE

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Storage | `/storage` | PVC / storage class intelligence for the connected cluster. | Open |
| Atlas | `/atlas` | Atlas storage control-plane panel — backends, pools, volumes, buckets, policies. | Open |

### OBSERVE

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Pod Logs | `/logs` | Stream and inspect pod/container logs from the console. | Open |
| Events | `/events` | Kubernetes warning/normal events stream for triage. | Open |
| Alerts | `/alerts` | Alert inventory and webhook-driven notifications. | Open |

### CONFIG

| Page | Route | Purpose | Guide |
|---|---|---|---|
| ConfigMaps | `/configmaps` | ConfigMap inventory — create, edit keys, delete. | Open |
| Secrets | `/secrets` | Secret inventory — create typed secrets, add keys, delete. | Open |
| Quotas & Limits | `/quotas` | ResourceQuotas, LimitRanges, PDBs, PriorityClasses. | Open |

### PROTECT

| Page | Route | Purpose | Guide |
|---|---|---|---|
| Backups | `/backups` | Volume snapshots, Velero backups, and schedules. | Open |

### ADMIN

| Page | Route | Purpose | Guide |
| --- | --- | --- | --- |
| Ops hub | `/ops` | Day-2 ops tabs — GitOps/Helm/RBAC/Identity and related operator tools. | Open |
| Users | `/users` | Local user accounts with admin or viewer roles. | Open |
| Settings | `/settings` | Integrations, clusters, theme, and console configuration. | Open |

## Related

- Customer docs home
- Page-by-page guides