ZYVORAI LABS · CUSTOMER DOCUMENTATION

Axiom

Getting Started

2026-09-02

Prerequisites

Requirement	Notes
k3s / Kubernetes	Or `AXIOM_MODE=demo` for a local deterministic lab
Browser	Accept self-signed HTTPS on lab NodePort **30590**
Credentials	Lab `demo` / `demo`, operator Secret, local Users, or SSO

1. Open the console

1. Browse to `https://<host>:30590/` (or your ingress). Accept the certificate warning once if needed.
2. Probe health: `curl -k https://<host>:30590/api/v1/health`.
3. If NodePort **30590** is taken, redeploy with `AXIOM_NODE_PORT=30591` (or another free port).

Lab deploy (remote)

```
./scripts/deploy-remote.sh <host> <user>
./scripts/deploy-remote.sh <host> <user> --quick          # skip image rebuild
./scripts/deploy-remote.sh <host> <user> --with-atlas     # optional Atlas on same host
```

Local demo (no cluster)

Follow product QUICKSTART for `AXIOM_MODE=demo` on port **5090**.

2. Sign in

Account	Credentials	When
Lab demo	`demo` / `demo`	SSO not configured
Operator	`AXIOM_USERNAME` / `AXIOM_PASSWORD`	Secret `zyvor-axiom-auth`
Local user	Settings → Users	`admin` or `viewer`
SSO	OIDC/SAML	Settings → Integrations

Use **Lab mode — fill demo** on the login screen's username step when SSO is off — it fills both fields and jumps straight to the password step.

3. Orient yourself (UX)

1. **Overview** — product home (capacity, inventory, utilization) and links into day-2 pages.
2. **Getting Started** — live integration checklist.
3. Sidebar + command palette (⌘K) — Workloads, Pods, Networking, Atlas, Ops, Settings.
4. Cluster switcher — real multi-cluster activate; demo mode ships three clusters.
5. Viewer role can read everything but mutating APIs return **403**.

4. First useful work

1. **Workloads → Run workload** (Form / Intent / YAML).
2. Open **Pods** / **Pod detail** — logs and terminal.
3. **Settings → Integrations** — wire Atlas or PacketWolf if needed.

Next steps

- Using the Dashboard
- Admin basics
- Page guides
- Workflows

Axiom is a Go API with an embedded React SPA. Production talks to k3s/Kubernetes; demo mode uses deterministic fixtures.

Shell chrome

Element	Job
Sidebar	NAV_ITEMS — Getting Started through Settings
Cluster switcher	`GET/POST /api/v1/clusters…/activate`
Command palette	⌘K / Ctrl+K — same route list as the sidebar
Top bar / user menu	Session, theme, sign out
Toasts	Mutation results (create/scale/delete)

Operate tips

1. Start on **Overview**, then **Getting Started** for integration gaps.
2. Prefer semantic workload actions (Start/Stop/Restart/Scale/Seal) over raw kubectl for day-2.
3. Pod detail terminal needs a valid session (WebSocket may use `?access_token=` for Basic auth).
4. Deterministic navigation calls the router — do not send “open Workloads” through an AI helper.
5. Never paste lab IPs into runbooks — use `<host>`.

Related

- Getting Started
- Page index
- Workflows

Each recipe assumes you can reach `https://<host>:30590/` and have signed in.

Verify a fresh deploy

1. Deploy: `./scripts/deploy-remote.sh <host> <user>` (Getting Started).
2. `curl -k https://<host>:30590/api/v1/health`.
3. Sign in (`demo` / `demo` when SSO is off).
4. Overview → metrics load.
5. Getting Started checklist.
6. Nodes → Ready nodes.
7. Settings → integrations.

If NodePort conflicts: `AXIOM_NODE_PORT=30592 ./scripts/deploy-remote.sh <host> <user> --quick`.

Connect Atlas

```
./scripts/deploy-remote.sh <host> <user> --with-atlas
```

Or Settings → Integrations → Atlas → Save → Test → Atlas → **Create volume**.

Connect PacketWolf

Set `AXIOM_PACKETWOLF_URL` (and key) → Networking live flow panel → seal a workload to confirm isolation.

Run and scale a workload

1. Workloads → **Run workload** (Form / Intent / YAML).
2. Open workload detail → owned Pods.
3. Scale / Restart from the row menu.
4. Pod detail → Logs / Terminal.

Backup a PVC

1. Backups → **Create snapshot**.
2. Restore to a new PVC name when rehearsing DR.

Related

- Using the Dashboard
- Admin basics