ZYVORAI LABS · CUSTOMER DOCUMENTATION

Axiom

Page-by-Page Product Manual

2026-08-30

zyvor.dev · Confidential — for licensed customers

Page-by-page guides

Each guide follows: Purpose → When to use it → How to get there → Operate from the console (UX) → Related pages.

Every route is also listed in the complete page index.

Admin

Page	What it covers
Ops hub	Day-2 ops tabs — GitOps/Helm/RBAC/Identity and related operator tools.
Settings	Integrations, clusters, theme, and console configuration.
Users	Local user accounts with admin or viewer roles.

Auth

Page	What it covers
Login	Sign in to the Axiom console — local Basic auth, SSO (OIDC/SAML), or lab demo helper.

Cluster

Page	What it covers
Custom Resources	Browse CRD kinds and list custom resource instances.
Namespaces	Namespace inventory — create and delete tenancy boundaries.
Node detail	Single-node conditions, capacity, taints, and related workloads.
Nodes	Kubernetes node inventory — Ready state, capacity, and entry into node detail.

Compute

Page	What it covers
Virtual Machines	KubeVirt VM inventory and day-2 actions in the Axiom console.

Config

Page	What it covers
ConfigMaps	ConfigMap inventory — create, edit keys, delete.
Quotas & Limits	ResourceQuotas, LimitRanges, PDBs, PriorityClasses.
Secrets	Secret inventory — create typed secrets, add keys, delete.

Console

Page	What it covers
Getting Started	Live setup checklist — integration status and first tasks after sign-in.

Page	What it covers
Overview	Cluster pulse — capacity metrics, activity, and shortcuts into day-2 centers.

Networking

Page	What it covers
Ingresses	Ingress and Gateway API exposure inventory.
Networking · Cilium	Service graph, NetworkPolicies, and live PacketWolf flows when configured.
Services	Kubernetes Service inventory and endpoints overview.

Observe

Page	What it covers
Alerts	Alert inventory and webhook-driven notifications.
Events	Kubernetes warning/normal events stream for triage.
Pod Logs	Stream and inspect pod/container logs from the console.

Protect

Page	What it covers
Backups	Volume snapshots, Velero backups, and schedules.

Storage

Page	What it covers
Atlas	Atlas storage control-plane panel — backends, pools, volumes, buckets, policies.
Storage	PVC / storage class intelligence for the connected cluster.

Workloads

Page	What it covers
Autoscaling	Horizontal Pod Autoscalers — create and delete.
Jobs & CronJobs	Batch Jobs and CronJobs — trigger runs, inspect status, delete.
Platform Intents	Intent-driven placement / platform requests surfaced in the console.
Pod detail	Container specs, metrics, multi-tab PTY terminal, manifest Save, port Open.
Pods	Pod inventory across namespaces — phase, restarts, entry into pod detail.
Workload detail	Single controller — owned pods, events, labels, rollout, raw YAML.
Workloads	Deployments, StatefulSets, DaemonSets — scale, restart, seal, rollout, and Run workload wizard.

---

30 guides. Regenerate: `node scripts/customer-docs/generate-guide-index.mjs`.

Ops hub

Purpose

Day-2 ops tabs — GitOps/Helm/RBAC/Identity and related operator tools.

When to use it

- Operate **Ops hub** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/ops`
- Nav: **Sidebar → Ops (** `/ops` **or** `/ops/:tab` **)**

Operate from the console (UX)

1. Open `/ops` and switch tabs as labeled in the UI.
2. RBAC: **New Role** / **New RoleBinding**; Sync where offered.
3. Identity tab: Haven/Keycloak health when installed.
4. **Empty / fail:** Tab empty → optional component not installed.
5. **Success:** Sync/create toasts succeed; RBAC objects listed.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Users
- Settings
- Getting Started
- Page index

Settings

Purpose

Integrations, clusters, theme, and console configuration.

When to use it

- Operate **Settings** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/settings`
- Nav: **Sidebar → Settings**

Operate from the console (UX)

1. Open `/settings`.
2. Integrations: Atlas URL/token → Save → Test connection; OIDC/SAML; PacketWolf.
3. Clusters: review activated cluster label (`AXIOM_CLUSTER_NAME`).
4. Theme toggle via shell control.
5. **Empty / fail:** Test connection failed → network/token; OIDC redirect URI must be `https://<host>:30590/api/v1/auth/oidc/callback`.
6. **Success:** Integration cards healthy; Atlas/Networking panels populate.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Atlas
- Users
- Getting Started
- Getting Started
- Page index

Users

Purpose

Local user accounts with admin or viewer roles.

When to use it

- Operate **Users** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/users`
- Nav: **Sidebar → Users**

Operate from the console (UX)

1. Open `/users` (admin).
2. Create users with admin/viewer; viewers read-only on mutating APIs.
3. **Empty / fail:** Persistence needs `zyvor-axiom-users` Secret in production.
4. **Success:** New user can sign in with the assigned role.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Settings
- Login
- Getting Started
- Page index

Login

Purpose

Sign in to the Axiom console — local Basic auth, SSO (OIDC/SAML), or lab demo helper.

When to use it

- Operate **Login** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/login`
- Nav: **Shown when unauthenticated →** `/login`

Operate from the console (UX)

1. Open `https://<host>:30590/` and accept the self-signed certificate once if needed.
2. Sign-in is two steps: enter a username and **Continue**, then enter the password and **Sign in**. Use **Not you?** on the password screen to go back and change the username.
3. When SSO is off, click **Lab mode — fill demo** to fill both fields and jump straight to the password screen (lab default `demo` / `demo`).
4. Or enter operator credentials from Secret `zyvor-axiom-auth` / `AXIOM_USERNAME` + `AXIOM_PASSWORD`.
5. When SSO is configured, use the OIDC/SAML buttons (public client + PKCE) on the first screen instead.
6. **Empty / fail:** Sign in failed toast → check credentials / SSO redirect URI `/api/v1/auth/oidc/callback`; health: `curl -k https://<host>:30590/api/v1/health`.
7. **Success:** Redirect to **Overview**; cluster switcher and sidebar appear.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Overview
- Getting Started
- Getting Started
- Page index

Custom Resources

Purpose

Browse CRD kinds and list custom resource instances.

When to use it

- Operate **Custom Resources** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/custom-resources`
- Nav: **Sidebar → Custom Resources**

Operate from the console (UX)

1. Open `/custom-resources`.
2. Select a kind; inspect instance table.
3. **Empty / fail:** No CRDs → expected on minimal clusters; install operators as needed.
4. **Success:** Instances for installed operators appear.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Ops hub
- Getting Started
- Page index

Namespaces

Purpose

Namespace inventory — create and delete tenancy boundaries.

When to use it

- Operate **Namespaces** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/namespaces`
- Nav: **Sidebar → Namespaces**

Operate from the console (UX)

1. Open `/namespaces`.
2. **Create namespace** → name → Create; Delete from row actions (confirm).
3. **Empty / fail:** 403 → viewer; delete blocked if resources remain.
4. **Success:** Namespace appears in filters across Workloads/Pods.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Workloads
- Quotas & Limits
- Getting Started
- Page index

Node detail

Purpose

Single-node conditions, capacity, taints, and related workloads.

When to use it

- Operate **Node detail** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/nodes/:name`
- Nav: **Nodes → row**

Operate from the console (UX)

1. Open a node from `/nodes`.
2. Review conditions and capacity; add/remove taints as needed.
3. Correlate NotReady with Events and Pods.
4. **Empty / fail:** 404 → stale name; permission errors → ClusterRole.
5. **Success:** Taint/condition changes reflect after refresh.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Nodes
- Events
- Getting Started
- Page index

Nodes

Purpose

Kubernetes node inventory — Ready state, capacity, and entry into node detail.

When to use it

- Operate **Nodes** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/nodes`
- Nav: **Sidebar → Nodes**

Operate from the console (UX)

1. Open `/nodes` and wait for the table.
2. Filter/search; open a row → `/nodes/:name` for taints, conditions, capacity.
3. On detail: **Add taint** when draining or isolating capacity.
4. **Empty / fail:** No nodes → cluster API / RBAC; demo mode should still show fixtures.
5. **Success:** Ready nodes listed; detail matches cluster state.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Node detail
- Events
- Pods
- Getting Started
- Page index

Virtual Machines

Purpose

KubeVirt VM inventory and day-2 actions in the Axiom console.

When to use it

- Operate **Virtual Machines** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/vms`
- Nav: **Sidebar → Virtual Machines**

Operate from the console (UX)

1. Open `/vms`.
2. Filter and open VMs; use lifecycle actions the page exposes (start/stop when available).
3. Confirm KubeVirt is installed if the list stays empty on a real cluster.
4. **Empty / fail:** No VMs → install KubeVirt or use demo fixtures.
5. **Success:** VM phases update after power actions.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Storage
- Overview
- Getting Started
- Page index

ConfigMaps

Purpose

ConfigMap inventory — create, edit keys, delete.

When to use it

- Operate **ConfigMaps** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/configmaps`
- Nav: **Sidebar → ConfigMaps**

Operate from the console (UX)

1. Open `/configmaps`.
2. **Create ConfigMap** — add keys → Create; delete retired maps.
3. **Empty / fail:** 403 on mutate → viewer role.
4. **Success:** ConfigMap listed and mountable by workloads.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Secrets
- Workloads
- Getting Started
- Page index

Quotas & Limits

Purpose

ResourceQuotas, LimitRanges, PDBs, PriorityClasses.

When to use it

- Operate **Quotas & Limits** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/quotas`
- Nav: **Sidebar → Quotas & Limits**

Operate from the console (UX)

1. Open `/quotas`.
2. Review quota / limit range / PDB / priority class tables.
3. Adjust via YAML apply when the UI does not offer inline edit.
4. **Empty / fail:** No quotas → create for multi-tenant namespaces.
5. **Success:** Hard limits visible; workload create respects them.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Namespaces
- Workloads
- Getting Started
- Page index

Secrets

Purpose

Secret inventory — create typed secrets, add keys, delete.

When to use it

- Operate **Secrets** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/secrets`
- Nav: **Sidebar → Secrets**

Operate from the console (UX)

1. Open `/secrets`.
2. **Create secret** — type + keys → Create; treat values as sensitive in UI.
3. **Empty / fail:** ClusterRole must allow secrets write in scope used by Users/Integrations.
4. **Success:** Secret available to workloads; delete cleans up.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- ConfigMaps
- Users
- Getting Started
- Page index

Getting Started

Purpose

Live setup checklist — integration status and first tasks after sign-in.

When to use it

- Operate **Getting Started** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/getting-started`
- Nav: **Sidebar → Getting Started**

Operate from the console (UX)

1. Open `/getting-started` after first login.
2. Walk the checklist; items reflect live Atlas/OIDC/PacketWolf/Haven status.
3. Jump from incomplete items into Settings → Integrations or the related center.
4. **Empty / fail:** Checklist stale → refresh; viewer role can read but cannot complete mutating setup.
5. **Success:** Critical integrations green; you can run a workload or open Overview confidently.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Overview
- Settings
- Workloads
- Getting Started
- Page index

Overview

Purpose

Cluster pulse — capacity metrics, activity, and shortcuts into day-2 centers.

When to use it

- Operate **Overview** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/overview`
- Nav: **Sidebar → Overview (default after login)**

Operate from the console (UX)

1. Land on `/overview` after sign-in (or click Overview).
2. Confirm cluster name/metrics and recent activity load.
3. Use the sidebar cluster switcher when multiple clusters are configured (demo mode ships three).
4. Jump to Nodes / Workloads / Alerts from shortcuts or ⌘K.
5. **Empty / fail:** Metrics blank → API unreachable or wrong activated cluster; re-login.
6. **Success:** Cluster headline + cards match `kubectl` reality (or demo fixtures).

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Nodes
- Workloads
- Alerts
- Getting Started
- Getting Started
- Page index

Ingresses

Purpose

Ingress and Gateway API exposure inventory.

When to use it

- Operate **Ingresses** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/ingresses`
- Nav: **Sidebar → Ingresses**

Operate from the console (UX)

1. Open `/ingresses`.
2. Review host/path rules and Gateway API section when present.
3. **Empty / fail:** No ingresses → install ingress controller / apply manifests.
4. **Success:** Hosts listed match customer DNS expectations.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Services
- Getting Started
- Page index

Networking · Cilium

Purpose

Service graph, NetworkPolicies, and live PacketWolf flows when configured.

When to use it

- Operate **Networking · Cilium** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/networking`
- Nav: **Sidebar → Networking · Cilium**

Operate from the console (UX)

1. Open `/networking`.
2. Inspect service graph / Cilium summary.
3. NetworkPolicies: **Create via YAML** (ApplyManifest) or Delete rows.
4. When `AXIOM_PACKETWOLF_URL` is set, read the live eBPF flow panel.
5. **Empty / fail:** No flows → PacketWolf unreachable; policies empty → create first.
6. **Success:** Graph + policies match cluster; seal on a workload shows isolation.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Services
- Workloads
- Settings
- Getting Started
- Page index

Services

Purpose

Kubernetes Service inventory and endpoints overview.

When to use it

- Operate **Services** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/services`
- Nav: **Sidebar → Services**

Operate from the console (UX)

1. Open `/services`; filter by namespace.
2. Open a row for ports/selectors; correlate with Ingresses and Pods.
3. **Empty / fail:** No services → deploy a workload first.
4. **Success:** ClusterIP/NodePort/LB entries listed.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Ingresses
- Networking · Cilium
- Getting Started
- Page index

Alerts

Purpose

Alert inventory and webhook-driven notifications.

When to use it

- Operate **Alerts** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/alerts`
- Nav: **Sidebar → Alerts**

Operate from the console (UX)

1. Open `/alerts`.
2. Review firing/open alerts; configure webhooks under Settings when available.
3. **Empty / fail:** No alerts → healthy or integrations not wired.
4. **Success:** Alert rows match monitoring rules / webhooks.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Events
- Settings
- Getting Started
- Page index

Events

Purpose

Kubernetes warning/normal events stream for triage.

When to use it

- Operate **Events** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/events`
- Nav: **Sidebar → Events**

Operate from the console (UX)

1. Open `/events`.
2. Filter by type/namespace; open related object links when present.
3. **Empty / fail:** Quiet cluster is OK; missing events → API watch issue.
4. **Success:** Recent warnings explain Pending/Failed pods.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Pods
- Alerts
- Getting Started
- Page index

Pod Logs

Purpose

Stream and inspect pod/container logs from the console.

When to use it

- Operate **Pod Logs** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/logs`
- Nav: **Sidebar → Pod Logs**

Operate from the console (UX)

1. Open `/logs`.
2. Select namespace/pod/container; stream or fetch recent lines.
3. Correlate with Events and Pod detail when diagnosing CrashLoop.
4. **Empty / fail:** No lines → wrong container / pod gone; 403 → RBAC logs.
5. **Success:** Live or recent log text for the selected container.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Pods
- Events
- Getting Started
- Page index

Backups

Purpose

Volume snapshots, Velero backups, and schedules.

When to use it

- Operate **Backups** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/backups`
- Nav: **Sidebar → Backups**

Operate from the console (UX)

1. Open `/backups`.
2. **Create snapshot** for a PVC; **Restore** into a new PVC name when offered.
3. Velero: create schedules / list backups when Velero is installed.
4. **Empty / fail:** Snapshot class missing → install CSI snapshotter; Velero empty → install Velero.
5. **Success:** Snapshot/backup row appears; restore binds a PVC.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Storage
- Atlas
- Getting Started
- Page index

Atlas

Purpose

Atlas storage control-plane panel — backends, pools, volumes, buckets, policies.

When to use it

- Operate **Atlas** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/atlas`
- Nav: **Sidebar → Atlas**

Operate from the console (UX)

1. Wire Atlas under **Settings → Integrations** (URL + token) or deploy with `--with-atlas`.
2. Open `/atlas` — backends/pools should load when connected.
3. **Create volume** for a smoke provision; review buckets/policies tables.
4. **Empty / fail:** Connection failed → Test connection in Settings; token/RBAC.
5. **Success:** Volume appears; Storage page reflects new PVC if bound into k8s.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Storage
- Settings
- Getting Started
- Page index

Storage

Purpose

PVC / storage class intelligence for the connected cluster.

When to use it

- Operate **Storage** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/storage`
- Nav: **Sidebar → Storage**

Operate from the console (UX)

1. Open `/storage`.
2. Review PVCs/StorageClasses; note bound vs pending.
3. Cross-link to Atlas for intent-backed provisioning.
4. **Empty / fail:** Pending PVCs → check provisioner / Atlas.
5. **Success:** Bound volumes listed for workloads.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Atlas
- Backups
- Getting Started
- Page index

Autoscaling

Purpose

Horizontal Pod Autoscalers — create and delete.

When to use it

- Operate **Autoscaling** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/autoscaling`
- Nav: **Sidebar → Autoscaling**

Operate from the console (UX)

1. Open `/autoscaling`.
2. **Create autoscaler** — pick workload + min/max/CPU target → Create.
3. Delete retired HPAs from the table.
4. **Empty / fail:** metrics-server missing → HPA cannot compute.
5. **Success:** HPA listed; replicas move under load.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Workloads
- Getting Started
- Page index

Jobs & CronJobs

Purpose

Batch Jobs and CronJobs — trigger runs, inspect status, delete.

When to use it

- Operate **Jobs & CronJobs** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/jobs`
- Nav: **Sidebar → Jobs & CronJobs**

Operate from the console (UX)

1. Open `/jobs`.
2. On CronJobs: **Run now** to trigger; delete retired jobs/cronjobs from row actions.
3. Confirm Job pods under Pods / Logs.
4. **Empty / fail:** No CronJobs → create via Apply YAML or workload wizard.
5. **Success:** Triggered Job appears with completions.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Pods
- Pod Logs
- Getting Started
- Page index

Platform Intents

Purpose

Intent-driven placement / platform requests surfaced in the console.

When to use it

- Operate **Platform Intents** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/platform-intents`
- Nav: **Sidebar → Platform Intents**

Operate from the console (UX)

1. Open `/platform-intents`.
2. Review intent cards/status; create via Workloads → Run → Intent when offered.
3. **Empty / fail:** No intents → submit one from the wizard.
4. **Success:** Intent progresses to a concrete workload.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Workloads
- Getting Started
- Page index

Pod detail

Purpose

Container specs, metrics, multi-tab PTY terminal, manifest Save, port Open.

When to use it

- Operate **Pod detail** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/pods/:namespace/:name`
- Nav: **Pods → row**

Operate from the console (UX)

1. Open a pod from `/pods`.
2. Read resources/env/probes; Metrics tab for CPU/memory sparklines.
3. Terminal: open sessions (multi-tab WebSocket); demo falls back to one-shot exec.
4. YAML tab → **Save** (server-side apply); Open buttons for container ports.
5. **Empty / fail:** Terminal blocked → auth/token on WS; Save 403 → viewer role.
6. **Success:** Shell prompt or metrics stream; Save toast OK.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Pods
- Pod Logs
- Workloads
- Getting Started
- Page index

Pods

Purpose

Pod inventory across namespaces — phase, restarts, entry into pod detail.

When to use it

- Operate **Pods** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/pods`
- Nav: **Sidebar → Pods**

Operate from the console (UX)

1. Open `/pods`; filter by namespace/status.
2. Open `/pods/:ns/:name` for specs, metrics, terminal, YAML.
3. Use scheduling-diagnosis banner when not Running.
4. **Empty / fail:** Empty → broaden namespace; CrashLoop → Logs + Events.
5. **Success:** Running pods listed; detail terminal connects (HTTPS / token).

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Pod detail
- Pod Logs
- Events
- Getting Started
- Page index

Workload detail

Purpose

Single controller — owned pods, events, labels, rollout, raw YAML.

When to use it

- Operate **Workload detail** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/workloads/:namespace/:kind/:name`
- Nav: **Workloads → row**

Operate from the console (UX)

1. Open a workload from the list.
2. Inspect owned Pods and Events; use lifecycle actions from the page.
3. Edit YAML carefully — Save uses server-side apply where offered.
4. **Empty / fail:** Missing pods → check selectors / Events.
5. **Success:** Desired replicas match Ready; rollout history coherent.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Workloads
- Pods
- Events
- Getting Started
- Page index

Workloads

Purpose

Deployments, StatefulSets, DaemonSets — scale, restart, seal, rollout, and Run workload wizard.

When to use it

- Operate **Workloads** when your job matches this page
- Prefer **Overview** after login if you are unsure where to start
- Confirm auth and activated cluster if inventories look empty

How to get there

- Route: `/workloads`
- Nav: **Sidebar → Workloads**

Operate from the console (UX)

1. Open `/workloads`.
2. **Run workload** — Form / Intent / YAML tabs → submit.
3. Row menu: Start / Stop / Restart / Scale / Seal / Unseal / Delete / Rollout (pause, resume, undo).
4. Open detail `/workloads/:ns/:kind/:name` for pods, events, YAML.
5. **Empty / fail:** Viewer gets 403 on mutate; empty list → wrong namespace filter or fresh cluster.
6. **Success:** New Deployment appears; scale/restart toasts succeed.

Console: `https://<host>:30590/` (NodePort HTTPS; override with `AXIOM_NODE_PORT`). Local demo: `http://<host>:5090` when `AXIOM_MODE=demo`. Never publish lab IPs — use `<host>`.

Related pages

- Workload detail
- Pods
- Platform Intents
- Getting Started
- Page index

Axiom — Complete page index

Every primary navigable dashboard route.

Generated: 2026-08-30 · 30 routes

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

AUTH

Page	Route	Purpose	Guide
Login	`/login`	Sign in to the Axiom console — local Basic auth, SSO (OIDC/SAML), or lab demo helper.	Open

CONSOLE

Page	Route	Purpose	Guide
Getting Started	`/getting-started`	Live setup checklist — integration status and first tasks after sign-in.	Open
Overview	`/overview`	Cluster pulse — capacity metrics, activity, and shortcuts into day-2 centers.	Open

CLUSTER

Page	Route	Purpose	Guide
Nodes	`/nodes`	Kubernetes node inventory — Ready state, capacity, and entry into node detail.	Open
Node detail	`/nodes/:name`	Single-node conditions, capacity, taints, and related workloads.	Open
Namespaces	`/namespaces`	Namespace inventory — create and delete tenancy boundaries.	Open
Custom Resources	`/custom-resources`	Browse CRD kinds and list custom resource instances.	Open

WORKLOADS

Page	Route	Purpose	Guide
Workloads	`/workloads`	Deployments, StatefulSets, DaemonSets — scale, restart, seal, rollout, and Run workload wizard.	Open
Workload detail	`/workloads/:namespace/:kind/:name`	Single controller — owned pods, events, labels, rollout, raw YAML.	Open
Jobs & CronJobs	`/jobs`	Batch Jobs and CronJobs — trigger runs, inspect status, delete.	Open
Pods	`/pods`	Pod inventory across namespaces — phase, restarts, entry into pod detail.	Open
Pod detail	`/pods/:namespace/:name`	Container specs, metrics, multi-tab PTY terminal, manifest Save, port Open.	Open

Page	Route	Purpose	Guide
Platform Intents	`/platform-intents`	Intent-driven placement / platform requests surfaced in the console.	Open
Autoscaling	`/autoscaling`	Horizontal Pod Autoscalers — create and delete.	Open

NETWORKING

Page	Route	Purpose	Guide
Networking · Cilium	`/networking`	Service graph, NetworkPolicies, and live PacketWolf flows when configured.	Open
Services	`/services`	Kubernetes Service inventory and endpoints overview.	Open
Ingresses	`/ingresses`	Ingress and Gateway API exposure inventory.	Open

COMPUTE

Page	Route	Purpose	Guide
Virtual Machines	`/vms`	KubeVirt VM inventory and day-2 actions in the Axiom console.	Open

STORAGE

Page	Route	Purpose	Guide
Storage	`/storage`	PVC / storage class intelligence for the connected cluster.	Open
Atlas	`/atlas`	Atlas storage control-plane panel — backends, pools, volumes, buckets, policies.	Open

OBSERVE

Page	Route	Purpose	Guide
Pod Logs	`/logs`	Stream and inspect pod/container logs from the console.	Open
Events	`/events`	Kubernetes warning/normal events stream for triage.	Open
Alerts	`/alerts`	Alert inventory and webhook-driven notifications.	Open

CONFIG

Page	Route	Purpose	Guide
ConfigMaps	`/configmaps`	ConfigMap inventory — create, edit keys, delete.	Open
Secrets	`/secrets`	Secret inventory — create typed secrets, add keys, delete.	Open
Quotas & Limits	`/quotas`	ResourceQuotas, LimitRanges, PDBs, PriorityClasses.	Open

PROTECT

Page	Route	Purpose	Guide
Backups	`/backups`	Volume snapshots, Velero backups, and schedules.	Open

ADMIN

Page	Route	Purpose	Guide
Ops hub	`/ops`	Day-2 ops tabs — GitOps/Helm/RBAC/Identity and related operator tools.	Open
Users	`/users`	Local user accounts with admin or viewer roles.	Open
Settings	`/settings`	Integrations, clusters, theme, and console configuration.	Open

Related

- Customer docs home
- Page-by-page guides