

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Chimera

Admin Basics

2026-09-04

Topic	Detail
Persona	<code>persona</code> / <code>CHIMERA_PERSONA</code> — <code>vsphere</code> (default), <code>nutanix</code> , <code>hyperv</code> , <code>aws</code> , or <code>azure</code>
Listen	<code>listen</code> in JSON config — default <code>0.0.0.0:8989</code>
Public host	<code>public_host</code> for NFC URLs (use real hostname for remote clients)
TLS	<code>tls: true</code> or <code>CHIMERA_TLS=true</code> — self-signed HTTPS
Simulator auth	<code>username</code> / <code>password</code> — default <code>administrator@vsphere.local</code> / <code>vmware</code> (also used by Nutanix/Hyper-V basic auth; AWS access key / secret; Azure subscription ID / bearer token)
Admin UI login	Default <code>admin</code> / <code>admin</code> ; <code>CHIMERA_ADMIN_USERNAME</code> / <code>CHIMERA_ADMIN_PASSWORD</code> ; changeable in Settings drawer (vSphere only)
Admin API token	<code>admin_token</code> — default <code>chimera-admin</code> (Bearer for curl/scenario scripts)
Fixtures	<code>fixture_vmdk</code> , <code>fixture_vmdk_dir</code> , <code>fixture_vmdk_dirs</code> , <code>fixture_size_mb</code> (vSphere NFC path)
Estate shape	<code>datacenters</code> , <code>clusters</code> , <code>hosts_per_cluster</code> , <code>datastores</code> , <code>vms_per_pool</code>
Packages	<code>make package</code> → <code>.deb</code> / <code>.rpm</code> ; systemd unit <code>chimera.service</code>
Remote deploy	<code>./scripts/deploy-remote.sh <host> [user]</code>
Logs	<code>journalctl -u chimera</code> or <code>-t chimera</code>

Endpoints

Path	Purpose	Persona
<code>/__chimera/</code>	Command Center UX	<code>vsphere</code>
<code>/sdk</code>	vSphere SOAP/VIM for govmomi / Transiva	<code>vsphere</code>
<code>/</code>	Redirects to Command Center	<code>vsphere</code>
<code>/api/nutanix/v3</code>	Prism-compatible REST (auth, VMs, power, disk export)	<code>nutanix</code>
<code>/wsman</code>	Hyper-V WS-Man SOAP (Identify, Enumerate/Pull, power)	<code>hyperv</code>
<code>/</code> and <code>/snapshots/...</code>	AWS EC2 Query + EBS snapshot blocks (SigV4)	<code>aws</code>
<code>/subscriptions/...</code>	Azure ARM Compute + managed disk SAS (Bearer)	<code>azure</code>

Use `http(s)://<host>:8989/...` in docs and client configs — substitute your lab hostname or DNS name for `<host>`.

Operate from the console (UX)

1. **Listen address:** Settings drawer (gear) → read-only bind shown at top; restart required to change `CHIMERA_LISTEN` / config `listen` .
2. **Rotate UI login:** Settings → new username + password → **Save login** → log out from user chip → sign in again.
3. **Verify estate:** Overview topology subtitle + Inventory VM count vs config fields above.
4. **Fixture dirs:** VMDK Library subtitle must show configured path; empty subtitle → set `fixture_vmdk_dir` and restart.
5. **API automation:** Use `Authorization: Bearer <admin_token>` for `/__chimera/scenario/*` , `/__chimera/faults` , `/__chimera/reset` — same privilege as an logged-in browser tab.
6. **Remote clients:** Footer persona strip shows public SDK URL Transiva should mirror; align `public_host` when NFC URLs must not say `localhost` .

Empty / fail: Settings save while logged out → login gate. VMDK upload 401 → sign in or pass Bearer token. Simulator login fails with correct UI admin → simulator creds are separate (`administrator@vsphere.local` / `vmware`).

Success: Listen matches curl/browser port; rotated admin login works; remote Transiva reaches `/sdk` on `<host>` .

Security notes

- Change default admin credentials before exposing beyond a lab VLAN.
- Simulator credentials are strict (wrong password fails) — not an “accept anything” mock.
- Chimera is for **test and compatibility**, not production VM hosting.

See also product-repo [docs/UX.md](#) , [docs/TRANSIVA.md](#) , [docs/PROVIDER_ARCHITECTURE.md](#) .

Related pages

- [Settings](#)
- [Login](#)
- [Getting Started](#)