

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Ephemera

Admin Basics

2026-08-29

Topic	Guidance
Service	Run <code>ephemera serve</code> under the provided systemd unit; the TTL reaper and pool backfill only run while <code>serve</code> is up
Logs	<code>journalctl -u ephemera -f</code> ; each VM also has its own console log under <code><state_dir>/instances/<uuid>/console.log</code>
State	<code><state_dir>/vms.json</code> is the source of truth, coordinated across concurrent <code>ephemera</code> processes via an OS-level <code>flock</code> on <code>vms.lock</code>
Security	Bearer-token auth/RBAC is opt-in — configure <code>[[auth.tokens]]</code> before exposing the REST API beyond localhost; <code>extra_args</code> on a create request is an administrator escape hatch, never expose it to untrusted callers
Support	GitHub issues · Contact Zyvor for Enterprise

See also [Getting started](#) and [Configuration](#).

Operate from the console (UX)

1. Open this route from the nav or command palette and wait for live API data.
2. Use filters/search when present; drill into a row for detail.
3. For mutating actions: confirm role gates and impact before applying.
4. **Empty / fail:** Check service health, auth, and that required CRDs/backends for this domain are installed.
5. **Success:** Live data loads; created/updated objects appear without error toasts.