

ZYVORAI LABS · CUSTOMER DOCUMENTATION



Page-by-Page Product Manual

2026-08-29

Page-by-page guides

Each guide follows: Purpose → When to use it → How to get there → Operate from the console (UX) → Related pages.

Every route is also listed in the [complete page index](#).

Auth

Page	What it covers
Login	Sign in to the Haven identity console — lab demo, local console user, or Keycloak admin.

Console

Page	What it covers
Atlas	Traffic path to identity — Console → Ingress → Keycloak → Postgres.
Clients	OIDC clients across all realms — mint, rotate secrets, manage redirect URIs.
Command Deck	Home operations surface — Keycloak connection, IdentityPlane health cards, reconcile timeline.
Deploy wizard	Spin up an identity plane — Postgres + Keycloak via Haven compose path.
Planes	IdentityPlane instances — health, profile, and endpoints.
Realm detail	Users and clients inside one realm — invite, set password, mint/rotate secrets.
Realm Studio	Create and manage Keycloak realms as tenant boundaries.
Settings	Connect Haven to Keycloak and manage console appearance / passwords.

Public

Page	What it covers
Landing	Public product landing — sign in or jump to Command Deck when already authenticated.

10 guides. Regenerate: `node scripts/customer-docs/generate-guide-index.mjs` .

Login

Purpose

Sign in to the Haven identity console — lab demo, local console user, or Keycloak admin.

When to use it

- Operate **Login** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/login`
- Nav: **Unauthenticated** → `/login`

Operate from the console (UX)

1. Open `http://<host>:30742/login` .
2. Lab: `demo / demo` when `HAVEN_LAB_LOGIN` is enabled.
3. Or Keycloak admin / `HAVEN_CONSOLE_USER + PASSWORD` .
4. **Sign in** — failures show an inline error.
5. **Empty / fail:** Wrong password → check `haven-keycloak-admin` secret; lab demo cannot change its own password.
6. **Success:** Redirect to Command Deck; sidebar shows Keycloak connected status.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Command Deck](#)
 - [Settings](#)
 - [Getting Started](#)
 - [Page index](#)
-

Atlas

Purpose

Traffic path to identity — Console → Ingress → Keycloak → Postgres.

When to use it

- Operate **Atlas** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/atlas`
- Nav: **Sidebar** → **Atlas**

Operate from the console (UX)

1. Open `/atlas` .
2. Walk the path diagram; confirm each hop looks healthy.
3. Use this before debugging OIDC redirect or login failures.
4. **Empty / fail:** Broken hop → Settings connection or ingress NodePorts.
5. **Success:** Path matches your deploy (console 30742 → Keycloak 30180 typical).

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Command Deck](#)
 - [Settings](#)
 - [Getting Started](#)
 - [Page index](#)
-

Clients

Purpose

OIDC clients across all realms — mint, rotate secrets, manage redirect URIs.

When to use it

- Operate **Clients** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/clients`
- Nav: **Sidebar** → **Clients**

Operate from the console (UX)

1. Open `/clients` .
2. Filter by realm; create or edit clients (redirect URIs, public/confidential).
3. Rotate secrets carefully; copy the new secret immediately.
4. **Empty / fail:** Empty list → create realm first; 403 → console role.
5. **Success:** Client appears with correct redirect URI for your app callback.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Realm Studio](#)
 - [Command Deck](#)
 - [Getting Started](#)
 - [Page index](#)
-

Command Deck

Purpose

Home operations surface — Keycloak connection, IdentityPlane health cards, reconcile timeline.

When to use it

- Operate **Command Deck** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/deck`
- Nav: **Sidebar** → **Command Deck**

Operate from the console (UX)

1. Land on `/deck` after sign-in.
2. Read **Connected Keycloak** strip (URL, version, realm count).
3. Scan orbit cards: Keycloak, Phase, Postgres, backup, certificate, login RPS.
4. Follow **Reconcile Timeline** conditions (DatabaseReady, KeycloakReady, ...).
5. Quick links: Realm Studio, Clients, Deploy wizard, Settings.
6. If offline: **Connect Keycloak** / Settings → Test & connect.
7. **Empty / fail**: Not connected → Settings; external plane may show Ready with Postgres `external` — expected.
8. **Success**: Connected banner + Ready phase (or understood external mode).

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Planes](#)
 - [Realm Studio](#)
 - [Atlas](#)
 - [Settings](#)
 - [Deploy wizard](#)
 - [Getting Started](#)
 - [Page index](#)
-

Deploy wizard

Purpose

Spin up an identity plane — Postgres + Keycloak via Haven compose path.

When to use it

- Operate **Deploy wizard** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/deploy`
- Nav: **Sidebar** → **Deploy wizard**

Operate from the console (UX)

1. Open `/deploy`.
2. Walk profile / capacity steps in the wizard.
3. **Review & Deploy** → when ready; watch toast and Deck reconcile timeline.
4. Return to Planes / Deck to confirm Phase Ready.
5. **Empty / fail:** Deploy failed toast → operators/RBAC/storage; use external Keycloak via Settings instead.
6. **Success:** Plane appears Ready; Keycloak reachable from Settings.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Planes](#)
 - [Command Deck](#)
 - [Getting Started](#)
 - [Page index](#)
-

Planes

Purpose

IdentityPlane instances — health, profile, and endpoints.

When to use it

- Operate **Planes** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/planes`
- Nav: **Sidebar** → **Planes**

Operate from the console (UX)

1. Open `/planes` .
2. **+ Deploy plane** or **Deploy wizard** when empty.
3. Open a plane card → endpoints / health; jump **Open Command Deck**.
4. **Empty / fail**: No planes → Deploy wizard or connect external Keycloak in Settings.
5. **Success**: Fleet card shows Ready with Keycloak/Postgres endpoints.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Command Deck](#)
 - [Deploy wizard](#)
 - [Atlas](#)
 - [Getting Started](#)
 - [Page index](#)
-

Realm detail

Purpose

Users and clients inside one realm — invite, set password, mint/rotate secrets.

When to use it

- Operate **Realm detail** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/realms/:realm`
- Nav: **Realm Studio** → **realm row**

Operate from the console (UX)

1. Open a realm from `/realms`.
2. Users: **+ Invite user**; set password via dialog when offered.
3. Clients: create/manage; **Regenerate client secret** with confirm; copy secret once.
4. **Empty / fail**: Invite fails → Keycloak permissions; secret regenerate is irreversible.
5. **Success**: User can authenticate to the realm; client secret pasted into your app.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Realm Studio](#)
 - [Clients](#)
 - [Getting Started](#)
 - [Page index](#)
-

Realm Studio

Purpose

Create and manage Keycloak realms as tenant boundaries.

When to use it

- Operate **Realm Studio** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/realms`
- Nav: **Sidebar** → **Realm Studio**

Operate from the console (UX)

1. Open `/realms`.
2. **+ Create realm** → name → Create.
3. Open a row → `/realms/:realm` for users/clients tabs.
4. Delete realm only with confirm (destructive).
5. **Empty / fail:** No realms → create one; Keycloak offline → Settings.
6. **Success:** Realm listed and openable in detail.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Realm detail](#)
 - [Clients](#)
 - [Command Deck](#)
 - [Getting Started](#)
 - [Page index](#)
-

Settings

Purpose

Connect Haven to Keycloak and manage console appearance / passwords.

When to use it

- Operate **Settings** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/settings`
- Nav: **Sidebar** → **Settings**

Operate from the console (UX)

1. Open `/settings` .
2. Enter Keycloak URL → **Test & connect**; expect green Connected banner.
3. Change console password or Keycloak admin password via dialogs (persist secrets before restart).
4. Open Keycloak SPI console link when connected.
5. **Empty / fail**: Connection failed → URL/network/admin creds; lab demo cannot change its password.
6. **Success**: `Connected to ... · v... · N realms` ; Deck status goes green.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Command Deck](#)
 - [Login](#)
 - [Getting Started](#)
 - [Page index](#)
-

Landing

Purpose

Public product landing — sign in or jump to Command Deck when already authenticated.

When to use it

- Operate **Landing** when your job matches this screen
- Prefer **Command Deck** after login if you are unsure where to start
- Confirm Keycloak connected in the sidebar status chip

How to get there

- Route: `/`
- Nav: Route `/` (marketing shell)

Operate from the console (UX)

1. Open `http://<host>:30742/`.
2. **Sign in** → `/login`, or **Open Command Deck** if you already have a session.
3. Read the Deploy Postgres + Keycloak story only as orientation — day-2 work lives under `/deck`.
4. **Empty / fail:** Page blank → console NodePort / ingress; not a substitute for Keycloak admin.
5. **Success:** You can reach Login or Deck without certificate/network surprises.

Console: `http://<host>:30742/` · Keycloak admin often `http://<host>:30180/admin` · Health: `GET /api/v1/health` . Never publish lab IPs — use `<host>` .

Related pages

- [Login](#)
 - [Command Deck](#)
 - [Getting Started](#)
 - [Page index](#)
-

Haven — Complete page index

Every primary navigable dashboard route.

Generated: 2026-08-29 · 10 routes

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

PUBLIC

Page	Route	Purpose	Guide
Landing	<code>/</code>	Public product landing — sign in or jump to Command Deck when already authenticated.	Open

AUTH

Page	Route	Purpose	Guide
Login	<code>/login</code>	Sign in to the Haven identity console — lab demo, local console user, or Keycloak admin.	Open

CONSOLE

Page	Route	Purpose	Guide
Command Deck	<code>/deck</code>	Home operations surface — Keycloak connection, IdentityPlane health cards, reconcile timeline.	Open
Deploy wizard	<code>/deploy</code>	Spin up an identity plane — Postgres + Keycloak via Haven compose path.	Open
Planes	<code>/planes</code>	IdentityPlane instances — health, profile, and endpoints.	Open
Atlas	<code>/atlas</code>	Traffic path to identity — Console → Ingress → Keycloak → Postgres.	Open
Realm Studio	<code>/realms</code>	Create and manage Keycloak realms as tenant boundaries.	Open
Realm detail	<code>/realms/:realm</code>	Users and clients inside one realm — invite, set password, mint/rotate secrets.	Open
Clients	<code>/clients</code>	OIDC clients across all realms — mint, rotate secrets, manage redirect URIs.	Open
Settings	<code>/settings</code>	Connect Haven to Keycloak and manage console appearance / passwords.	Open

Related

- [Customer docs home](#)
- [Page-by-page guides](#)