

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Haven

Getting Started

2026-09-04

Prerequisites

Requirement	Notes
Kubernetes / k3s	kubectI access
Keycloak Admin URL or Haven compose operators	Existing Keycloak or Deploy wizard
Browser	Console NodePort (default 30742)

1. Lab deploy (remote)

```
git clone https://github.com/zyvorai/haven.git
cd haven
./scripts/deploy-remote.sh <host> <user>
./scripts/deploy-remote.sh <host> <user> --quick # skip image rebuild
```

Open `http://<host>:30742/login` .

2. Sign in

Account	Credentials	When
Lab demo	demo / demo	HAVEN_LAB_LOGIN enabled
Admin	Keycloak admin user/password	Synced into haven-keycloak-admin
Local console	HAVEN_CONSOLE_USER / PASSWORD	Role admin

Full login UX: [Login](#).

3. Orient yourself (UX)

1. **Command Deck** (`/deck`) — Keycloak connected? Phase Ready?
2. **Planes** — fleet card for your IdentityPlane.
3. **Atlas** — Console → Ingress → Keycloak → Postgres path.
4. **Realm Studio** — list/create realms; open detail for users/clients.
5. **Settings** — **Test & connect** until the green banner appears.

Command palette: `⌘K` / `Ctrl+K` .

4. First real job

- [Verify a fresh lab](#)
- [Create a realm and invite a user](#)
- [Mint an OIDC client](#)

Next steps

- [Using the Dashboard](#)
 - [Admin basics](#)
 - [Passwords](#)
-

Haven's console is the day-2 identity operator surface over Keycloak (and optional CloudNativePG).

Shell chrome

Element	Job
Sidebar	Command Deck · Deploy · Planes · Realm Studio · Clients · Atlas · Settings
Status chip	Keycloak connected / version / realm count · plane phase
Command palette	⌘K / Ctrl+K
Top bar / mobile nav	Same destinations on small viewports

Backups / Approvals may appear as placeholders (#) until shipped — ignore for production recipes.

Operate tips

1. Always confirm **Connected** on Deck or Settings before realm work.
2. Create realms in **Realm Studio**; mint OIDC clients under **Clients** or realm detail.
3. Persist password changes in secrets before pod restart — see [Passwords](#).
4. Never paste lab IPs into runbooks — use `<host>` .

Related

- [Getting Started](#)
 - [Page index](#)
 - [Command Deck](#)
-

Each recipe assumes `http://<host>:30742/` is reachable.

Verify a fresh lab

1. Deploy: `./scripts/deploy-remote.sh <host> <user>` ([Getting Started](#)).
2. Sign in (`demo` / `demo` or admin).
3. [Command Deck](#) — Connected + Ready (or external Postgres noted).
4. [Settings](#) — green Connected banner.
5. [Atlas](#) — path hops look healthy.

Create a realm and invite a user

1. [Realm Studio](#) → + **Create realm**.
2. Open [Realm detail](#) → + **Invite user**.
3. Set password when prompted; verify login against that realm's account console if needed.

Mint an OIDC client

1. [Clients](#) (or realm detail Clients tab).
2. Create confidential/public client with redirect URI for your app.
3. Copy client secret once; paste into the relying party.
4. Optional: regenerate secret later with confirm.

Deploy a new identity plane

1. [Deploy wizard](#) → Review & Deploy.
2. Watch [Planes](#) and Deck reconcile timeline until Ready.

Related

- [Using the Dashboard](#)
- [Passwords](#)