hypercluster ? end-to-end Kubernetes cluster lifecycle wrapper for Kubespray.

Usage: hypercluster [OPTIONS] <command> [ARGS]

Commands:

```
 init             Clone Kubespray and generate inventory + group_vars
                Use init --wizard to create cluster.conf interactively first
 wizard           Interactive cluster.conf generator (no existing config required)
 preflight        Verify local tools and SSH connectivity to all nodes
 deploy           Full cluster deployment (preflight + init + cluster.yml)
 scale            Add worker nodes listed in cluster.conf (scale.yml)
 upgrade          Upgrade Kubernetes to the version in cluster.conf
 remove-node      Drain and remove a single node
 fetch-kubeconfig  Copy admin.conf from the first control-plane node
 merge-kubeconfig  Merge the cluster kubeconfig into ~/.kube/config
 install-kubevirt  Install KubeVirt operator + CDI (also runs after deploy if KUBEVIRT_ENABLED=true)
 test             Run platform smoke tests (k3s path; optional --full, --json)
 destroy          Tear down the cluster (reset.yml or k3s uninstall)
 status           Node status (optional --json for machine-readable output)
 unlock           Remove stale per-cluster lock after a crash
```

Options:

```
 -c <file>   Path to cluster config (default: ./cluster.conf)
 -f          Force overwrite of existing inventory
 -n          Dry run ? print what would be executed, skip actual changes
 -v          Verbose Ansible output
 -V          Show version
 -h          Show this help
?? defaults ????????????????????????????????????????????????????????????
?? parse options ???????????????????????????????????????????????????????
?? load libraries ??????????????????????????????????????????????????????
shellcheck source=lib/log.sh
shellcheck source=lib/wizard.sh
shellcheck source=lib/progress.sh
shellcheck source=lib/postdeploy.sh
shellcheck source=lib/preflight.sh
shellcheck source=lib/inventory.sh
shellcheck source=lib/kubespray.sh
shellcheck source=lib/kubeconfig.sh
shellcheck source=lib/k3s.sh
shellcheck source=lib/platform-stack.sh
shellcheck source=lib/platform-tools.sh
shellcheck source=lib/platform-test.sh
?? wizard (no cluster.conf required) ????????????????????????????????????
?? load cluster config ??????????????????????????????????????????????????
shellcheck source=/dev/null
Validate required config variables
?? lock helpers ?????????????????????????????????????????????????????????
```

unlock skips lock acquisition
Resolve KUBESPRAY_DIR: absolute paths pass through, relative paths are anchored to SCRIPT_DIR
?? commands ??
?? dispatch ??