CLI GUIDE

HYPERCLUSTER CLI GUIDE

Task-oriented reference for the bash CLI. Generated CLI help is also at docs/_build/cli-reference.txt (run make docs).

Quick paths

Goal · Commands
Remote k3s platform · preflight ? deploy ? test
Kubespray HA cluster · wizard or edit conf ? preflight ? deploy
Automation / CI · test --json, status --json
Day-2 add nodes · Update WORKER_IPS ? scale
Upgrade K8s · Bump KUBE_VERSION ? upgrade

Global flags

Flag · Meaning
-c <file> · Config file (default ./cluster.conf)
-f · Force inventory regen; skip destroy confirm; force remove-node
-n · Dry run
-v · Verbose Ansible output
-V · Print version
-h · Help

Commands

Command · k3s · Kubespray · Description
wizard · ? · ? · Interactive cluster.conf generator
init · ? · ? · Clone Kubespray + inventory
preflight · ? · ? · Local tools + SSH checks
deploy · ? · ? · Full install
test · ? · ? · Platform smoke tests
test --full · ? · ? · Extended snapshot checks
test --json · ? · ? · Machine-readable results
status · ? · ? · Node status
status --json · ? · ? · Machine-readable node JSON
scale · partial · ? · Add workers from conf
upgrade · ? · ? · Upgrade to KUBE_VERSION
remove-node · ? · ? · Drain + remove node
fetch-kubeconfig · ? · ? · Copy admin kubeconfig
merge-kubeconfig · ? · ? · Merge into ~/.kube/config
install-kubevirt · ? · ? · KubeVirt + CDI
destroy · ? · ? · Tear down cluster
unlock · ? · ? · Clear stale lock

k3s platform workflow

cp config/cluster.conf.example cluster.conf
$EDITOR cluster.conf # K8S_DISTRO=k3s, METALLB_IP_POOL, SSH_*, CONTROL_PLANE_IPS

```
./hypercluster -c cluster.conf preflight
./hypercluster -c cluster.conf deploy
./hypercluster -c cluster.conf test
./hypercluster -c cluster.conf status --json
```

Deploy behavior: skips k3s reinstall when server is healthy. Set FORCE_K3S_REINSTALL=1 to replace.
Stack order: Cilium ? cert-manager ? MetalLB ? KubeVirt/CDI ? metrics-server.

JSON output

`test --json`:

Stdout (stderr has human PASS/FAIL lines):

{"pass": 10, "fail": 0, "checks": [{"name": "Cilium healthy", "passed": true}]}

`status --json`:

{"ready": 1, "total": 1, "nodes": [{"name": "node1", "ready": true, "roles": "true"}]}

Make shortcuts

make deploy CONFIG=cluster.conf
make test-remote CONFIG=cluster.conf
make status CONFIG=cluster.conf
make docs
See docs/generated/MAKE-TARGETS.md for full list.

Related

- Desktop UX guide
- Configuration reference
- Documentation hub

Doc version: 2026-06-04T17:43:57Z · hypercluster v0.1.0