ZYVORAI LABS · CUSTOMER DOCUMENTATION

HyperCluster

Page-by-Page Product Manual

2026-07-26

Page-by-page guides

Each guide follows: Purpose → When to use it → How to get there → What you can do → Related pages.

Every route is also listed in the complete page index.

Cli

Page	What it covers
Discovery & Preflight	Discovery sources and preflight checks before deploy.
Health & Status	health / status / test / forge-handoff JSON ops.
Lab Mode	Lab mode storage/tune/setup helpers.
Node Lifecycle	Scale, upgrade, destroy, unlock via hypercluster CLI.
CLI Provisioning	CLI deploy / wizard / profiles for bare-metal Kubernetes.
SSH & Kubeconfig	SSH, jump hosts, kubeconfig fetch/merge, API tunnels.
Zyvor Platform Handoff	Hand off a ready cluster to the Zyvor product stack.

Cockpit

Page	What it covers
Backups	Backup and etcd/snapshot related ops.
GPU	GPU node and operator status.
Instruments	Instrument / telemetry panels for the cluster.
Networking	CNI / MetalLB / ingress networking status.
Nodes	Node inventory, SSH status, and scale actions.
Observability	Observability stack status (metrics, logs).
Overview	Cluster overview — health, version, and capacity summary.
Platform	Zyvor platform components installed on the cluster.
Security	Security posture and hardening checklist.
Cluster Settings	Per-cluster settings and conf linkage.
Storage	Storage classes and CSI status.
Templates	Cluster / workload templates.
Upgrades	Upgrade paths for k3s/Kubespray clusters.
Virtual Machines	KubeVirt VMs when virtualization add-ons are installed.
Workloads	Workloads running on the provisioned cluster.

Create

Page	What it covers
Quick Deploy	Opinionated quick path for a standard cluster profile.
Cluster Studio	Full Cluster Studio wizard (nodes → storage → network → validate → deploy).

Edit

Page	What it covers
Conf editor	Raw cluster.conf editor with validation.

Nav

Page	What it covers
Cluster detail	Cluster cockpit — open a selected cluster into overview and day-2 tabs.
Ask Zeus	Ask Zeus / Copilot overlay for cluster-grounded assistance.
Dashboard	Fleet home for Hypercluster Desktop — registered clusters and deploy shortcuts.
Advanced ops	Advanced Day-2 operations against the selected cluster.
Settings	Desktop app settings, providers, and trial/license status.
Create Cluster	Create Cluster hub — pick Kubernetes, virtualization, AI, or edge intent.

Ops

Page	What it covers
Deploy console	Live deploy console — pipeline logs and stage status.

---

32 guides. Regenerate: `node scripts/customer-docs/generate-guide-index.mjs`.

Discovery & Preflight

Purpose

Discovery sources and preflight checks before deploy.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cli/discover`
- Nav: **CLI → Discovery & Preflight** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cli/discover` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Health & Status

Purpose

health / status / test / forge-handoff JSON ops.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cli/health`
- Nav: **CLI → Health & Status** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cli/health` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Lab Mode

Purpose

Lab mode storage/tune/setup helpers.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cli/lab`
- Nav: **CLI → Lab Mode** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cli/lab` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Node Lifecycle

Purpose

Scale, upgrade, destroy, unlock via hypercluster CLI.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cli/lifecycle`
- Nav: **CLI → Node Lifecycle** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cli/lifecycle` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

CLI Provisioning

Purpose

CLI deploy / wizard / profiles for bare-metal Kubernetes.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cli/provision`
- Nav: **CLI → CLI Provisioning** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cli/provision` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

SSH & Kubeconfig

Purpose

SSH, jump hosts, kubeconfig fetch/merge, API tunnels.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cli/ssh`
- Nav: **CLI → SSH & Kubeconfig** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cli/ssh` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Zyvor Platform Handoff

Purpose

Hand off a ready cluster to the Zyvor product stack.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cli/zyvor-handoff`
- Nav: **CLI → Zyvor Platform Handoff** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cli/zyvor-handoff` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Backups

Purpose

Backup and etcd/snapshot related ops.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/backups`
- Nav: **Cockpit → Backups** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/backups` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

GPU

Purpose

GPU node and operator status.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/gpu`
- Nav: **Cockpit → GPU** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/gpu` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Instruments

Purpose

Instrument / telemetry panels for the cluster.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/instruments`
- Nav: **Cockpit → Instruments** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/instruments` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Networking

Purpose

CNI / MetalLB / ingress networking status.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/network`
- Nav: **Cockpit → Networking** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/network` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Nodes

Purpose

Node inventory, SSH status, and scale actions.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/nodes`
- Nav: **Cockpit → Nodes** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/nodes` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Observability

Purpose

Observability stack status (metrics, logs).

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/observability`
- Nav: **Cockpit → Observability** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/observability` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Overview

Purpose

Cluster overview — health, version, and capacity summary.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/overview`
- Nav: **Cockpit → Overview** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/overview` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Platform

Purpose

Zyvor platform components installed on the cluster.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/platform`
- Nav: **Cockpit → Platform** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/platform` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Security

Purpose

Security posture and hardening checklist.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/security`
- Nav: **Cockpit → Security** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/security` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Cluster Settings

Purpose

Per-cluster settings and conf linkage.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/settings`
- Nav: **Cockpit → Cluster Settings** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/settings` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Storage

Purpose

Storage classes and CSI status.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/storage`
- Nav: **Cockpit → Storage** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/storage` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Templates

Purpose

Cluster / workload templates.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/templates`
- Nav: **Cockpit → Templates** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/templates` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Upgrades

Purpose

Upgrade paths for k3s/Kubespray clusters.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/upgrades`
- Nav: **Cockpit → Upgrades** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/upgrades` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Virtual Machines

Purpose

KubeVirt VMs when virtualization add-ons are installed.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/vms`
- Nav: **Cockpit → Virtual Machines** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/vms` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Workloads

Purpose

Workloads running on the provisioned cluster.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster/workloads`
- Nav: **Cockpit → Workloads** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster/workloads` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Quick Deploy

Purpose

Opinionated quick path for a standard cluster profile.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `quick-deploy`
- Nav: **Create → Quick Deploy** (sidebar, command palette, or desktop nav)

What you can do

1. Open `quick-deploy` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Cluster Studio

Purpose

Full Cluster Studio wizard (nodes → storage → network → validate → deploy).

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `studio`
- Nav: **Create → Cluster Studio** (sidebar, command palette, or desktop nav)

What you can do

1. Open `studio` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Conf editor

Purpose

Raw cluster.conf editor with validation.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `editor`
- Nav: **Edit → Conf editor** (sidebar, command palette, or desktop nav)

What you can do

1. Open `editor` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Cluster detail

Purpose

Cluster cockpit — open a selected cluster into overview and day-2 tabs.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `cluster`
- Nav: **Nav → Cluster detail** (sidebar, command palette, or desktop nav)

What you can do

1. Open `cluster` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Ask Zeus

Purpose

Ask Zeus / Copilot overlay for cluster-grounded assistance.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `copilot`
- Nav: **Nav → Ask Zeus** (sidebar, command palette, or desktop nav)

What you can do

1. Open `copilot` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Dashboard

Purpose

Fleet home for Hypercluster Desktop — registered clusters and deploy shortcuts.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `dashboard`
- Nav: **Nav → Dashboard** (sidebar, command palette, or desktop nav)

What you can do

1. Open `dashboard` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Advanced ops

Purpose

Advanced Day-2 operations against the selected cluster.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `operations`
- Nav: **Nav → Advanced ops** (sidebar, command palette, or desktop nav)

What you can do

1. Open `operations` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Settings

Purpose

Desktop app settings, providers, and trial/license status.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `settings`
- Nav: **Nav → Settings** (sidebar, command palette, or desktop nav)

What you can do

1. Open `settings` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Create Cluster

Purpose

Create Cluster hub — pick Kubernetes, virtualization, AI, or edge intent.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `studio-hub`
- Nav: **Nav → Create Cluster** (sidebar, command palette, or desktop nav)

What you can do

1. Open `studio-hub` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

Deploy console

Purpose

Live deploy console — pipeline logs and stage status.

When to use it

- Open this surface when the job matches the purpose above
- Start from the product home / dashboard if you are unsure where to begin
- Confirm auth and that required backends/operators are reachable if data looks empty

How to get there

- Route / id: `deploy`
- Nav: **Ops → Deploy console** (sidebar, command palette, or desktop nav)

What you can do

1. Open `deploy` and wait for live data from HyperCluster.
2. Use filters and search when the page provides them.
3. Drill into a row or card for detail, then jump to related surfaces.
4. For mutating actions: review impact, role gates, and confirmation dialogs first.

If the page stays empty, check service health, auth configuration, and that dependencies for this domain are installed.

Related pages

- Getting Started
- Page index

HyperCluster — Complete page index

Every primary navigable dashboard route.

Generated: 2026-07-26 · 32 routes

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

Nav

Page	Route	Purpose	Guide
Dashboard	`dashboard`	Fleet home for Hypercluster Desktop — registered clusters and deploy shortcuts.	Open
Cluster detail	`cluster`	Cluster cockpit — open a selected cluster into overview and day-2 tabs.	Open
Create Cluster	`studio-hub`	Create Cluster hub — pick Kubernetes, virtualization, AI, or edge intent.	Open
Advanced ops	`operations`	Advanced Day-2 operations against the selected cluster.	Open
Settings	`settings`	Desktop app settings, providers, and trial/license status.	Open
Ask Zeus	`copilot`	Ask Zeus / Copilot overlay for cluster-grounded assistance.	Open

Create

Page	Route	Purpose	Guide
Cluster Studio	`studio`	Full Cluster Studio wizard (nodes → storage → network → validate → deploy).	Open
Quick Deploy	`quick-deploy`	Opinionated quick path for a standard cluster profile.	Open

Edit

Page	Route	Purpose	Guide
Conf editor	`editor`	Raw cluster.conf editor with validation.	Open

Ops

Page	Route	Purpose	Guide
Deploy console	`deploy`	Live deploy console — pipeline logs and stage status.	Open

Cockpit

Page	Route	Purpose	Guide
Overview	`cluster/overview`	Cluster overview — health, version, and capacity summary.	Open
Nodes	`cluster/nodes`	Node inventory, SSH status, and scale actions.	Open
Workloads	`cluster/workloads`	Workloads running on the provisioned cluster.	Open

Page	Route	Purpose	Guide
Networking	`cluster/network`	CNI / MetalLB / ingress networking status.	Open
Storage	`cluster/storage`	Storage classes and CSI status.	Open
Virtual Machines	`cluster/vms`	KubeVirt VMs when virtualization add-ons are installed.	Open
Templates	`cluster/templates`	Cluster / workload templates.	Open
GPU	`cluster/gpu`	GPU node and operator status.	Open
Platform	`cluster/platform`	Zyvor platform components installed on the cluster.	Open
Instruments	`cluster/instruments`	Instrument / telemetry panels for the cluster.	Open
Observability	`cluster/observability`	Observability stack status (metrics, logs).	Open
Security	`cluster/security`	Security posture and hardening checklist.	Open
Backups	`cluster/backups`	Backup and etcd/snapshot related ops.	Open
Upgrades	`cluster/upgrades`	Upgrade paths for k3s/Kubespray clusters.	Open
Cluster Settings	`cluster/settings`	Per-cluster settings and conf linkage.	Open

CLI

Page	Route	Purpose	Guide
CLI Provisioning	`cli/provision`	CLI deploy / wizard / profiles for bare-metal Kubernetes.	Open
Node Lifecycle	`cli/lifecycle`	Scale, upgrade, destroy, unlock via hypercluster CLI.	Open
SSH & Kubeconfig	`cli/ssh`	SSH, jump hosts, kubeconfig fetch/merge, API tunnels.	Open
Discovery & Preflight	`cli/discover`	Discovery sources and preflight checks before deploy.	Open
Health & Status	`cli/health`	health / status / test / forge-handoff JSON ops.	Open
Lab Mode	`cli/lab`	Lab mode storage/tune/setup helpers.	Open
Zyvor Platform Handoff	`cli/zyvor-handoff`	Hand off a ready cluster to the Zyvor product stack.	Open

Related

- Customer docs home
- Page-by-page guides