

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Hermes

Admin Basics

2026-08-29

Ports / access

Port	Service
31847	UI NodePort (common)
8080	Controller / server

Auth

OIDC + API key. `server.auth.mode` defaults to `none` — no login required at all — **set it to `api_key` or `oidc` before any internet-facing or production install.**

```
helm upgrade --install hermes charts/hermes -n hermes-system \
--set server.auth.mode=api_key --set server.auth.apiKey="a-real-key"
```

Session secret

Sessions are signed with `HERMES_SESSION_SECRET`. This is auto-generated (random, 64 chars) by the chart on first install and preserved across upgrades — never set it to a fixed value checked into source control, since it's the token-signing key, not a login credential. Retrieve it if needed:

```
kubectl -n hermes-system get secret hermes-session-secret -o jsonpath='{.data.session-secret}' | base64 -d
```

If you run `hermes-server` **outside this chart** (standalone binary, `docker run`, `docker-compose`), you must set `HERMES_SESSION_SECRET` yourself — without it, the binary falls back to a hardcoded development default and logs a warning; that fallback value is public (it's in the source), so relying on it is not safe for anything other than local dev.

Install sketch

Follow the product README and deploy/Helm docs in the repository. Verify health endpoints or CLI status before opening the UI.

Related

- [Getting Started](#)

Operate from the console (UX)

1. Open this route from the nav or command palette and wait for live API data.
2. Use filters/search when present; drill into a row for detail.
3. For mutating actions: confirm role gates and impact before applying.
4. **Empty / fail:** Check service health, auth, and that required CRDs/backends for this domain are installed.
5. **Success:** Live data loads; created/updated objects appear without error toasts.