

ZYVORAI LABS · CUSTOMER DOCUMENTATION

relay-edge

Getting Started

2026-08-29

Purpose

Full stack order: [Relay stack day-0 onboarding](#).

1. Open `https://<edge-host>:18086/ui/` (accept self-signed TLS).
2. Complete the **Get started** panel: Health → Auth (if required) → Wire publish → Probe → Lab.
3. In **Configure**, set `gateway_base_url` to your **pubsub host** (or clear it and set `relay_base_url` for direct).
Paste JWT. Enable TLS insecure for lab certs. **Save**, then **Probe**.
4. Run Lab **Store** → **Send** → **Receive**. Do **not** put laptop `127.0.0.1` in peer URLs when Relay or pubsub run on another machine.

When to use it

- Open **Getting started — relay-edge** when the job matches this screen
- Prefer the product home / Get started panel if you are unsure where to begin
- Confirm health and auth tokens if probes fail

How to get there

- UI path: `/ui/` → **Getting started — relay-edge** (or matching nav tab)
- Spotlight / in-app links when available

Operate from the console (UX)

1. Open the relay-edge UI (`/ui/`) on `https://<host>:...` (see Admin basics for the default port).
2. Navigate to **Getting started — relay-edge**.
3. Complete the on-screen fields / actions for this surface (Full stack order: [Relay stack day-0 onboarding](#)).
4. Open `https://:18086/u...`.
5. Use **Probe** / **Save** / **Send** (or the primary button on the page) and watch status chips.
6. **Empty / fail:** Check Admin basics env vars, JWT/ `API_TOKEN` , TLS insecure for lab certs, and backend reachability.
7. **Success:** Status shows healthy / accepted; related Lab or Logs surfaces reflect the change.

Never publish lab IPs — use `<host>` .

Related pages

- [Getting Started](#)
 - [Using the Dashboard](#)
 - [Admin basics](#)
 - [Page index](#)
-

Purpose

Area	Purpose
Configure	Runtime gateway/Relay URLs, JWT, browser API token
Self-test lab	Health, Store, Send, Receive, simulator shortcuts
Logs	Admin ring buffer
Fire-water / Remote edge / Fleet	Simulator control rooms
Docs	In-app stack docs + first-time setup link

When to use it

- Open **Using the dashboard** when the job matches this screen
- Prefer the product home / Get started panel if you are unsure where to begin
- Confirm health and auth tokens if probes fail

How to get there

- UI path: `/ui/` → **Using the dashboard** (or matching nav tab)
- Spotlight / in-app links when available

Operate from the console (UX)

1. Open the relay-edge UI (`/ui/`) on `https://<host>:...` (see Admin basics for the default port).
2. Navigate to **Using the dashboard**.
3. Complete the on-screen fields / actions for this surface (| Area | Purpose | |-----|-----| | **Configure** | Runtime gateway/Relay URLs, JWT, browser API token | | **Self-te...).
4. Use **Probe** / **Save** / **Send** (or the primary button on the page) and watch status chips.
5. **Empty / fail:** Check Admin basics env vars, JWT/ `API_TOKEN` , TLS insecure for lab certs, and backend reachability.
6. **Success:** Status shows healthy / accepted; related Lab or Logs surfaces reflect the change.

Never publish lab IPs — use `<host>` .

Related pages

- [Getting Started](#)
 - [Using the Dashboard](#)
 - [Admin basics](#)
 - [Page index](#)
-

Purpose

1. **Store → Send → Receive** — Lab creates domain rows, publishes stamped `crop.advisory` , shows path.
2. **Simulator** — Seed → Publish into Relay → scenario → SSE stream.
3. **Full stack e2e** — From a workstation with remote URLs:

```
set -a && source config/lab-stack.env && set -x  
/scripts/e2e-stack.sh
```

When to use it

- Open **Common workflows** when the job matches this screen
- Prefer the product home / Get started panel if you are unsure where to begin
- Confirm health and auth tokens if probes fail

How to get there

- UI path: `/ui/` → **Common workflows** (or matching nav tab)
- Spotlight / in-app links when available

Operate from the console (UX)

1. Open the relay-edge UI (`/ui/`) on `https://<host>:...` (see Admin basics for the default port).
2. Navigate to **Common workflows**.
3. Complete the on-screen fields / actions for this surface (1. **Store** → **Send** → **Receive** — Lab creates domain rows, publishes stamped `crop.advisory` , shows path.
4. **Simulator...**).
5. Use **Probe** / **Save** / **Send** (or the primary button on the page) and watch status chips.
6. **Empty / fail:** Check Admin basics env vars, JWT/ `API_TOKEN` , TLS insecure for lab certs, and backend reachability.
7. **Success:** Status shows healthy / accepted; related Lab or Logs surfaces reflect the change.

Never publish lab IPs — use `<host>` .

Related pages

- [Getting Started](#)
- [Using the Dashboard](#)
- [Admin basics](#)
- [Page index](#)