

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Veyron

Getting Started

2026-09-10

What you need

Requirement	Notes
Kubernetes + KubeVirt	CDI recommended for disk imports
Veyron API + console	Local :8080 or cluster HTTPS :5151 (NodePort often 30151)
Auth	Username/password against the console's login screen, or <code>VEYRON_API_KEY</code> / <code>VEYRON_API_KEYS</code> for API/CLI clients

1. Open the console

- Local: `http://127.0.0.1:8080/console`
- Cluster: `https://<host>:30151/console` (chart defaults vary — use your deploy output)

2. Sign in

The console's login screen takes a **username and password**, posted to `POST /api/v1/auth/login`, which returns a bearer token the console stores and sends back as `Authorization: Bearer <token>` on every API call.

Mode	What you do
Username/password	The only method the console's login screen exposes today. <code>admin</code> + the password from <code>VEYRON_API_KEY / auth.adminPassword</code> works out of the box — see Admin basics for the default.
API key (<code>X-API-Key</code>)	For CLI, scripts, and direct API calls — not used by the console's login screen. <code>VEYRON_API_KEY</code> (single admin key) or <code>VEYRON_API_KEYS="name:key:role,..."</code> (multi-key RBAC).
OIDC / SSO	Backend support exists (<code>VEYRON_OIDC_*</code> , <code>GET /api/v1/auth/oidc/config</code> , <code>POST /api/v1/auth/oidc/token</code>) for programmatic PKCE flows — see Setting Up SSO . The console's login screen does not yet have an SSO button; this is API-level today.

3. Orient yourself

1. **Mission Control** (Overview) — fleet summary and quick create.
2. **Left rail** — five groups: Overview, Compute, Storage & network, Security, System.
3. **Search** (top bar) — filter/jump within the current page's data.
4. See [Using the Console](#) for the full shell layout.

4. First workflows

A. List and open a VM

Virtual machines (Compute) → select a row → the **Inspector** (right panel) opens with detail, console access, and the per-VM action bar.

B. Open a console session

ConsoleHub (Overview), or open a VM's Inspector and use its console action directly.

C. Create from a template

Template Foundry (Compute) to browse OS templates, or the **+ New** button (top bar) to create a VM directly.

Next steps

- [Using the Console](#)
 - [Admin basics](#)
 - [Page guides](#)
-

Create and console into a VM

1. [Template Foundry](#) — browse OS templates, or use **+ New** directly
2. [Virtual machines](#) — confirm the VM reaches **Running**
3. [ConsoleHub](#), or the VM's own Inspector — open a console session

Snapshot and protect

1. [Snapshots](#) — native KubeVirt VM snapshots
2. [Atlas](#) — Ceph-backed snapshots/backups, when Atlas is configured
3. [DR & Velero](#) — cluster-level backup and failback, when Velero is configured

Investigate a firing alert

1. [Mission Control](#) — fleet-level "nothing needs a look" summary
2. [Alerts](#) — real Kubernetes/KubeVirt events surfaced as alerts
3. [Security](#) — SOC-pipeline detections, when configured

Related

- [Getting Started](#)
- [Page index](#)