

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Veyron

Admin Basics

2026-08-29

Ports

Port	Service
8080	Local HTTP API + dashboard (<code>veyron api-serve</code> / <code>serve</code>)
5151	Container / Helm HTTPS API + dashboard
5150 / 30150	HTTP→HTTPS redirect (chart)
30151	Common HTTPS NodePort for dashboard / API

Auth

- `VEYRON_API_KEY` (admin) or `VEYRON_API_KEYS="name:key:role,..."` .
- OIDC PKCE via `VEYRON_OIDC_*` (Keycloak/Auth0/Okta) — set `VEYRON_OIDC_GROUP_ADMIN` / `VEYRON_OIDC_GROUP_WRITE` to your IdP's group names (defaults: `veyron-admins`, `cluster-admins` / `veyron-write`, `veyron-editors`). Confidential IdP clients (Keycloak's default) also need `VEYRON_OIDC_CLIENT_SECRET` . Full walkthrough: [Setting Up SSO](#) .
- WebSocket consoles use one-shot tickets: `POST /api/v1/ws/ticket` .
- Shell HTML (`/` , `/dashboard` , `/assets/*`) and health/OIDC bootstrap paths are auth-exempt.

Default credentials

On first install, if you don't set `auth.apiKey` / `auth.adminPassword` , the chart's `veyron-api-key` Secret defaults both to `Admin@321` — **change these before any internet-facing or production install**.

`auth.jwtSecret` is different: it's the token *signing* key, not a login credential — a predictable default there would let anyone forge a valid session token, not just guess a password. It's auto-generated (random, 64 chars) on first install and preserved across upgrades; never set it to a fixed value checked into source control.

Retrieve the generated values:

```
kubectl -n veyron get secret veyron-api-key -o jsonpath='{.data.api-key}' | base64 -d; echo  
kubectl -n veyron get secret veyron-api-key -o jsonpath='{.data.admin-password}' | base64 -d; echo
```

Set your own at install time:

```
helm upgrade --install veyron charts/veyron -n veyron \\\n  --set auth.apiKey="a-real-key" --set auth.adminPassword="a-real-password" \\\n  --set auth.jwtSecret: leave unset to keep the auto-generated value, or override explicitly if needed
```

Install sketch

```
# Local
veyron api-serve # or: veyron serve

# Helm (example)
helm upgrade --install veyron charts/veyron -n veyron --create-namespace
```

From a binary bundle (no git clone, no build tools)

If you're a customer, you'll receive `veyron-<version>-linux-amd64.tar.gz` directly from us (email sales@zyvor.dev if you need it re-sent). It ships the Helm chart plus a script that builds a runtime image from the bundle's own binaries — no source tree, no cargo:

```
tar xzf veyron-*linux-amd64.tar.gz && cd veyron-*linux-amd64
./install-cluster.sh # Kubevirt/CDI/Cilium prereqs
./install-to-kubernetes.sh --registry <your-registry>/veyron --push
./apply-cluster-network.sh
```

`install-to-kubernetes.sh --help` shows namespace/release/dry-run options, and a local single-node cluster (kind/k3s/minikube) sharing the build daemon's image store can skip `--push` entirely.

Just evaluating? Grab the 30-day trial bundle

Download from github.com/zyvorai/veyron-releases — same tarball, plus a signed `trial.token` next to the binary, no purchase needed to try it. After 30 days the binary stops starting until you [contact sales@zyvor.dev](mailto:sales@zyvor.dev) for a full, unrestricted license.

OpenAPI: `/api/openapi.json` . Route dump: `veyron api-routes` .

Related

- [Getting Started](#)