ZYVORAI LABS · CUSTOMER DOCUMENTATION

Zeus OS

Page-by-Page Product Manual

Visual day-2 control plane for KubeVirt and Kubernetes

2026-10-21

Page-by-page guides

Each guide follows the same shape:

1. **Purpose** — what this screen is for
2. **When to use it** — typical jobs
3. **How to get there** — route and nav path
4. **Operate from the console (UX)** — concrete clicks after you land
5. **Related pages** — where to go next

Every dashboard route, including screens without a deep guide, is listed in the complete page index.

Core — VMs and daily operations

Page	What it covers
Favorites	Pinned VM list for quick access: star VMs you care about, search the fleet, and open VNC or serial console deep links.
Home (Mission Control)	Apple.com-style chapter home: greeting hero, Get the highlights (fleet KPIs on a dark band), infrastructure pulse, a light Attention teaser, running machines, and apps/insights — without the heavy triage deck.
Instance types	Browse KubeVirt instance types and preferences — standardized CPU/memory shapes for consistent VM sizing.
Compare VMs	Side-by-side diff of two VMs' configuration so you can spot drift, clone mistakes, or environment mismatches.
VM setup (create a machine)	Guided creation of a new KubeVirt VM from instance types, preferences, templates, or AI-assisted manifests.
VM workbench	Full-page operations surface for one virtual machine: power, console, hardware, networking, backup panels, guest agent, and remote access.
VM fleets (VMIRS)	Manage VirtualMachineInstanceReplicaSet-style fleets — scale homogeneous VM groups as a unit.
VM Instances (VMI)	List of running VirtualMachineInstance objects — the live pods/instances behind VirtualMachine definitions.
Virtual Machines	Inventory of every KubeVirt virtual machine you can see: live status, filters, and entry into the per-VM workbench.

Consoles and remote access

Page	What it covers
ConsoleHub	Unified launcher and session manager for browser consoles — multiple VMs, policies, and session visibility.
Consoles & remote access	Reach the guest: graphical VNC, serial text console, and native RDP/SSH via NodePort expose.

Cluster, storage and images

Page	What it covers
Blueprints	Blueprint Marketplace for one-click application stacks (for example Windows AD, RDS, SQL, IIS, jump boxes) registered in the cluster.
Enterprise networking	Direct management of Cilium-native Egress Gateway policies, BGP peering, L2 announcement policies,
Customization Profiles	Reusable guest customization specs — cloud-init, Windows sysprep/unattend XML, and SSH authorized keys — applied from create/clone flows or onto an existing VM.
DataVolumes	CDI DataVolume inventory — disk import/clone/upload jobs that back VM disks.
Device Plugins	Read-only view of Kubernetes device-plugin resources and GPU capacity reported by the cluster.
Disk Manager	Manage VM disks: attach, hot-plug, resize entry points, and disk inventory beyond the raw PVC list.
GPU Devices	GPU / PCI passthrough inventory: host VGA/3D devices, allocation to VMs, plus a vGPU orchestration panel for mdev profiles and assign actions.
HPA	Monitor and manage Horizontal Pod Autoscalers — replica counts, CPU utilization, and scaling status across namespaces.
Image Factory	Golden Image Factory pipelines that take a customer-supplied OS ISO through VirtIO, updates, optional GuestKit bake, sysprep/generalize, snapshot, and catalog publish.
Image Library	One catalog for golden images, import guidance, and cluster images so operators can pick OS media when creating VMs.
Image Registry	Browse container disk images for KubeVirt VMs — cluster images from running pods, or a reference catalog — then open Create VM with the image prefilled.
MetalLB & external IPs	Operator guidance for LoadBalancer Services (SSH, RDP, and other external access) via MetalLB address pools — not a pool editor UI.
Networks	Multus NetworkAttachmentDefinition management so VMs can attach additional L2 NICs — bridge, macvlan, ipvlan, host-device, or SR-IOV.
Nodes	Kubernetes worker/control-plane node inventory: capacity, conditions, and drain/placement context for VMs.
Pods	Kubernetes pod inventory — including `virt-launcher` pods that back running VMIs.
Priority Classes	Read-only list of Kubernetes PriorityClass objects — numeric value, global default, preemption policy, and usage.
PVC Resize	Expand existing PersistentVolumeClaims or create empty PVCs. CDI image imports still belong on DataVolumes.
Runtime Classes	Read-only inventory of cluster RuntimeClass objects — handler, scheduling hints, overhead, and usage counts.
Services	Cluster-wide Kubernetes Service inventory for VM SSH/RDP exposes and other workloads — ports, addresses, and YAML in one place.
Storage	Storage and PVC intelligence for the cluster: volumes, capacity signals, and entry points into disk/resize workflows.
Taints	Read-only analysis of node taints and which VMs tolerate them — plus scheduling impact warnings for unschedulable guests.

Page	What it covers
Templates	Curated VM templates for one-click or guided deploy of known-good shapes.
VPA	List, create, and delete Vertical Pod Autoscalers, and inspect container resource recommendations.
Windows via Kryton	

Observe — health, metrics and incidents

Page	What it covers
Alerts	Zeus-native alerting console — active fired alerts, threshold rules, history, and webhook destinations — separate from PrometheusRule CRDs in Alerting V2.
APM	Application performance dashboard for services, traces, and latency percentiles — when an APM backend is connected to Zeus OS.
Attention	Ranked next steps, live fleet signals (Issue Stream), and day-2 remediation activity — the triage surface that used to live as a heavy block on Home.
Capacity	Cluster capacity and overcommit dashboard — utilization pulse, per-node breakdown, capacity alerts, planning scenarios, and HA/DRS context.
Containers	Pod-centric container inventory with status stats, detail sheet, and (for non-viewers) deploy / apply-YAML shortcuts alongside a deployments panel.
Custom Metrics	Dashboard for operator-defined metrics and their alert rules — create PromQL (or custom) configurations, then watch values and firing alerts.
Events	Live Kubernetes event browser — type, reason, object, message, namespace, count, and age — for correlating cluster noise with VM or workload symptoms.
Forecasting	AI-assisted resource predictions — per-VM and cluster forecasts, capacity recommendations, and seasonal pattern detection — to plan before you run out of headroom.
Resource Heatmap	Cluster-wide utilization heatmap built from per-VM cells rolled up by node — CPU, memory, disk, and network pressure for capacity planning.
Host Info	Read-only view of the Zeus OS host — OS, hardware, disks, NICs, and local services — for operators checking the control-plane node itself.
Incident chat	Lightweight multi-user chat channel for incident collaboration. Marked labs in navigation; messages sync through Zeus OS, while slash commands run locally.
Incidents	Incident center with context and guided remediation — not just a raw alert dump.
Logs Explorer	On-demand log search across pods in a namespace — query text, severity filter, and optional live tail — for day-2 debugging from the dashboard.
Monitoring Targets	Inventory of Prometheus Operator objects in the cluster — ServiceMonitors, Prometheus instances, and PrometheusRule groups — plus high-level monitoring stats.
Network Info	Host network interface inventory for the Zeus OS host — physical, bridge, veth, VM TAP, Cilium, bond, VLAN, and tunnel devices — with traffic counters.
SLO Manager	Service level objective tracker — create availability-style objectives, watch met / burning / breached status, and refresh error-budget posture for the fleet.
System Health	Platform health dashboard — control-plane and Zeus-related component pulse for operators and admins.
VM Monitor	Activity Monitor for the VM fleet — live and historical CPU, memory, network, and disk — with per-VM charts and links into the VM workbench.

Run — lifecycle, migration and backup

Page	What it covers
AutoScaler	Define policies that resize VMs automatically, and review right-sizing recommendations with their estimated monthly cost impact before applying them.
Backup Wizard	Guided backup workflow for VMs / volumes — complementary to Velero and snapshot managers.
Cluster Autoscale	Read-only status of the cluster autoscaler and its node pools: whether it is enabled, how each pool is sized against its min and max, and what scale-up or scale-down actions it is recommending.
Live Migrations	Plan, dry-run, and execute live VM migrations between nodes with pre-flight checks and history.
Node Drain	A guided five-step wizard for taking a node out of service safely: pick the node, see exactly which VMs will move and which will lose availability, choose a strategy, cordon and drain, then watch it finish.
Operations	One console for the recurring day-2 chores: alert rules, outbound webhooks, quotas, GPU inventory, backup and power and snapshot schedules, RBAC review, quick deploy, cluster context, and labels.
Snapshots	Create and manage VM snapshots (on-demand and scheduled) for point-in-time recovery.
Velero	Velero-backed backup and restore operations for cluster and VM-related resources.
Windows Licensing	Read-only inventory of Windows activation state across your KubeVirt VMs, collected through the guest agent (`slmgr`). Zeus OS never hosts a KMS or redistributes licenses — it reports what your own activation infrastructure says.
Workflows	Read-only view of the automation workflows registered with Zeus OS: what is scheduled, when each last ran, how reliable it has been, and the template gallery you can copy from.

Security, compliance and governance

Page	What it covers
Admission control	Read-only inventory of what intercepts writes to your cluster: validating and mutating admission webhooks, Kyverno policy rules, webhook statistics, and recent admission-related events.
Affinity Rules	Surfaces where your affinity and anti-affinity placement intent is not being honoured — which rule is violated, which VMs are affected, and on which node.
Certificates	Tracks the TLS certificates in your cluster and how long each one has left, so an expiry never surprises you. Renewal can be triggered from the table.
Change Approval	A review queue for VM changes: destructive requests wait for a human approver, non-destructive ones are auto-approved, and every decision is recorded with a comment and a timestamp.
Compliance	Scores your VMs against Zeus OS policy checks and gives you a cluster grade, per-category pass rates, and a per-VM breakdown you can export as evidence.
External Secrets	Monitor the `ExternalSecret` and `SecretStore` resources that pull credentials from Vault, cloud secret managers, and other providers into Kubernetes — with sync, validate, and delete actions.
Image Scanning	Vulnerability posture for your container and VM images: critical, high, medium, and low counts per image, when each was last scanned, and the scan policies that decide pass or fail.
OPA Gatekeeper	Read-only inventory of your OPA Gatekeeper constraints and constraint templates, with the current violation count and the offending resources behind each one.
PDB	Shows every PodDisruptionBudget in the cluster and whether it currently permits any voluntary disruption — the fastest way to know if a drain will proceed or stall.
Security	Security posture overview — findings, hardening status, and entry into compliance / scanning / policies.
Tenancy	Organise namespaces into tenants, see each tenant's namespace, CPU, and memory footprint, manage who belongs to a tenant, and track quota consumption per namespace.
Users	Shows who you are signed in as and what that identity may do, manages built-in local accounts, and issues revocable API tokens for automation.

Cost and FinOps

Page	What it covers
Budget Alerts	Monthly spend budgets for the cluster, a tenant or a namespace. Budgets are stored and evaluated on the server from recorded cost history, and alerts go out through your notification channels once per threshold per month. Spend is an estimate from your configured unit prices, not an invoice.
Chargeback	Nav alias for namespace cost allocation / showback. There is no separate Chargeback UI — the link opens Cost Allocation.
Cost Allocation	Namespace-level chargeback view: estimated monthly cost rolled up by namespace, with CPU, memory, and storage share plus per-VM detail.
Cost Estimator	What-if cost calculator for planned VM fleets: adjust count, shape, and unit prices to estimate monthly and annual spend (labs-tier page).
Cost Intelligence	Per-VM and per-namespace spend visibility, trends, and FinOps entry points.
Costs	Cluster cost dashboard: monthly spend trends, namespace and resource-type breakdowns, top expensive VMs, and optimization opportunities.
Rightsizing	Recommendations for idle, oversized, or orphaned resources — turn Cost Intelligence into concrete shape changes.
SLA Dashboard	Live VM up/down posture plus configurable SLO targets (uptime % and latency). Historical uptime and error budget are not synthesized without availability history.
Spot Savings	Nav alias for the Optimization Center. There is no separate Spot Savings page — the link opens resource optimization recommendations and savings tracking.

Insights, network, delivery and tools

Page	What it covers
AI Center	AI-assisted SRE, migration, and security advisors grounded in cluster evidence (Forge / built-in LLM when configured).
Anomaly Detector	Surfaces VM health, CPU, and memory outliers with risk levels and suggested next actions. The view auto-refreshes about every 10 seconds from live inventory and health scores.
API Docs	Browsable REST reference for Zeus OS: live OpenAPI when available, plus categorized method/path descriptions for VMs, nodes, pods, and more.
API Playground	In-browser HTTP client for Zeus OS REST endpoints: pick a method and path, send authenticated requests, and inspect status, headers, and body.
ArgoCD	Read-only dashboard of Argo CD Applications and Projects — sync and health status for GitOps workloads in the cluster.
Auto-Remediation	Day-2 playbooks and policy controls that respond to common VM failures — crash loops, node pressure migrations, and advisory rightsizing or PVC expansion — with optional closed-loop autonomy.
Catalog	Infrastructure app catalog (Helm-oriented installs) for common day-2 stack pieces: browse categories, search apps, and trigger install.
Chaos Engineering	Controlled fault experiments against VMs — primarily kill virt-launcher pods to validate recovery; other stress types are listed when a fault-injection backend is available.
CI/CD	Pipeline inventory and run history with on-demand trigger controls for cluster-integrated CI/CD definitions.
Cilium CNI	Cilium status, endpoints, policies, Hubble packet flows, VM internet-egress controls, and a VM policy builder — when Cilium is installed in the cluster.
Cluster Upgrade	Version awareness and an upgrade checklist for Kubernetes and KubeVirt — plus VLCM rollout controls — so operators plan upgrades without skipping critical backups and drains.
Database Ops	Day-2 view of database instances and their backups — status, storage, endpoints, and connection details for operator copy-out.
Debug	Host-level diagnostics for the Zeus OS node: live system stats, network interfaces, disk partitions, services, and a downloadable support bundle.
Dependencies	Live graph of resource relationships — nodes, VMs, PVCs, Services, and labeled edges — so you can see what depends on what before a change.
Deployment Strategies	Define and run progressive delivery strategies (Rolling Update, Canary, Blue/Green, Recreate) against Kubernetes workloads, with execute and rollback controls.
Disaster Recovery	Disaster Recovery Center — visual DR plans, RPO/RTO targets, failover test scheduling, and step runbooks for day-2 resilience.
DNS	Derived DNS / FQDN helpers for pods and VMs: search inventory, copy cluster-style names, and map IPs to names operators can use.
GitOps	Compare desired versus actual VM power state, show Flux/Argo cluster stats, and sync power-status drift back toward the intended running/stopped state.
Helm Releases	List, install, upgrade history, rollback, and uninstall Helm releases, and manage chart repositories on the cluster.

Page	What it covers
IaC	Infrastructure-as-code resource inventory with drift detection and a sync action for IaC-managed objects Zeus OS can see.
Kernel Info	Host hardware and OS inventory: hostname, kernel, CPU, BIOS, PCI devices, and memory modules for the Zeus OS node.
Kustomize	Browse Kustomize bases and overlays, then preview the rendered diff before you apply changes outside the dashboard.
Multi-Cluster	Multi-Cluster Command Center — list federation contexts, view the current cluster overview, and compare up to two clusters side by side.
Network Flow	Zeus Network Center — service map, flows, DNS health, policies, and PacketWolf-backed containment actions, with Cilium/Hubble and cluster metrics as fallbacks when PacketWolf is offline.
NLP Command	Natural-language bar for VM power and lifecycle intents — parse plain English into a confirmed action before execution (labs tier).
Operators	OLM inventory for ClusterServiceVersions, Subscriptions, OperatorGroups, CatalogSources, and InstallPlans with aggregate health stats.
Optimization	Resource optimization recommendations and estimated savings — review rightsizing suggestions and apply supported hotplug/shape changes when enabled.
PacketWolf VM Guard	Network intelligence and VM Shield containment — see allowed/denied flows and apply quarantine / internet-lock profiles (typically Cilium/Hubble backed).
Performance Testing	List and run performance tests defined in the cluster, with live metrics (users/pods tracked, estimated RPS, error rate, latency).
Placement Advisor	Legacy nav entry for smart VM placement. The dashboard redirects this route to Placement, where node scoring and topology-manager recommendations live.
Placement	Heuristic node scores from live topology, plus topology-manager API recommendations, so you can pick a suitable host for VM CPU/memory and affinity needs.
Progressive Delivery	Operate canary deployments and progressive rollouts — traffic weight, health signals, promote, and rollback — from one delivery dashboard.
Resource Tags	Tag coverage and compliance for cluster resources: distribution of keys, untagged inventory, required-tag checks, and bulk apply.
Mesh Detail	Legacy nav entry for service-mesh detail. The dashboard redirects this route to Service Mesh, the Multus NAD and VM attachment inventory.
Status Page	Operator-facing fleet status board: overall operational / degraded / outage banner, per-VM health, and recent Warning events.
Terminal	In-browser cluster shell: pick a pod/container, open an authenticated WebSocket session, and run commands with multi-tab support.
Topology Mgr	Node topology detail for NUMA zones, CPU pins, device allocations, and topology policies — deeper than the live map on Topology.
Topology	Live map of infrastructure relationships — nodes, VMs, networks, and dependencies visualized.
Webhook Tester	Validate alert webhook delivery: test configured alert webhooks or POST a custom payload to any URL and inspect latency and response.

Page	What it covers
Widgets	Customizable dashboard widget grid (VM count, capacity, health, events, favorites, alerts) with layout persistence in the browser.

Product centers and wizards

Page	What it covers
Application Center	Group VMs into business applications with workspace scoping, health pulse, and an inspector for protection and membership.
Approvals	Single inbox for decisions waiting on you — day-2 remediations pending approval and change requests.
Auth audit log	Login and security event table sourced from `auth-audit.jsonl` on the Zeus OS data volume (`ZEUS_OS_DATA_DIR`).
Backup & DR	Recovery Theatre hub — backup stats plus shortcuts to Velero, restore, snapshots, DR, and backup wizards.
Console Sessions	Legacy route that redirects to ConsoleHub's active sessions tab. Bookmarks and Settings links still resolve.
Developer Center	Operator and integrator hub for REST docs, API playground, CLI examples, webhooks, and plugin SDK entry points.
Edge Center	Guidance hub for branch clusters, air-gapped operation, and sync or compliance posture tied to multi-cluster views.
Forge	Native AI module hub — prompt handoff from AI Center, links to AI providers and GPU passthrough. Dedicated agent builder is not shipped on this page yet.
Identity Center	Landing hub for authentication and access governance — links to SSO, LDAP, MFA, Users & RBAC, auth audit, and API tokens.
Machine Finder	Browse the datacenter → cluster → host → VM hierarchy, then jump into Machine Runway for fleet operations.
Kubernetes Center	Hub for the container layer under your Zeus virtual datacenter — cluster pulse plus shortcuts to pods, services, nodes, and related day-2 tools.
Marketplace	Browse and deploy VM templates and blueprints — search, OS and category filters, favorites, AI draft assist, and a deploy wizard.
Migration Command Center	VMware exit planning — migration waves, Transiva discovery handoff, preflight blockers, and wave readiness. Zeus OS does not perform VMware import itself.
Cluster onboarding	Guided preflight for a new Zeus OS cluster — platform readiness, Cilium status check, and cluster info — then links into core navigation.
Patch Center	Windows and Linux patch readiness across running VMs — risk signals, maintenance-window links, and compliance handoff.
Plugins	Preview of partner and custom Zeus OS plugin categories. Install and uninstall are not available yet.
Reports	Executive and operational report catalog — shortcuts into health, protection, DR, security, network, cost, audit, and compliance exports.
Restore Wizard	Guided Velero restore — select a completed backup, configure target namespace and PV restore, then monitor restore phase to completion.
Support	Operator support hub — download a redacted diagnostics bundle and jump to health, debug, API docs, audit, and terminal tools.
Task Center	Long-running operations inbox — migrations, backups, and platform jobs with status, progress, and cancel when supported.

Page	What it covers
Time Machine	Cluster DVR and per-VM flight recorder — scrub recorded state over time. Frames come from the server-side sampler ring buffer.
VM Groups	Label-based VM groups with bulk start, stop, and restart across matching members.
War Room	Live incident assembly — active incident, affected VMs and nodes, recommended actions, pending remediations, and a warning-event feed in one place.
Resource Canvas	Spatial map of compute, storage, networking, and AI entry points — click a node to open its window.

Settings

Page	What it covers
Settings — Advanced	Shortcuts into platform, debug, and developer tooling, plus keyboard shortcuts and build information.
Settings — AI providers	Register and manage the language-model providers that power Zeus OS AI features, plus routing rules, API keys, stored memory, and the prompt library.
Settings — API access	Everything needed to automate against Zeus OS: scoped API tokens, the OpenAPI specification, rate-limit behaviour, and the FinOps change audit.
Settings — Appearance	Control how the Zeus OS shell looks and behaves: Light or Dark theme, wallpaper, glass and motion effects, sidebar mode, and the dock.
Settings — Backup & DR	Configuration entry points for Velero backups and disaster recovery, linking settings to the operational backup centers.
Settings — General	Server information and dashboard-wide preferences: what build you are running and how lists and cards behave for your account.
Settings — Network	Entry point for network-related configuration and the PacketWolf network-intelligence integration.
Settings — Security	Security-related configuration surfaced in the UI: active product edition, identity and SSO panels, browser console access policy, and a link into the security overview.
Settings	Configure the Zeus OS experience and platform integrations: general, appearance, network, security, backup/DR, AI providers, API access, and advanced options.

---

157 guides. Regenerate this index with `node scripts/customer-docs/generate-guide-index.mjs`.

Capability-oriented reference (not page-oriented): Feature Guide.

Favorites

Purpose

Pinned VM list for quick access: star VMs you care about, search the fleet, and open VNC or serial console deep links.

When to use it

- Keep critical VMs at the top of your day
- Jump to console without hunting the full inventory
- Confirm status, CPU, and memory for pinned guests
- Refresh after create/delete waves

How to get there

- Route: `/favorites`
- Nav: **Core → Favorites**
- Related: `/vms`, `/widgets`, `/consolehub`

Operate from the console (UX)

1. Open `/favorites` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Pinned VM list for quick access: star VMs you care about, search the fleet, and open VNC or serial console deep links.
3. Use filters and search on the page; open a row for detail / inspector.
4. Run the primary action (create, apply, run, export) from the PageHead or empty-state CTA.
5. Confirm success via toast + refreshed inventory; check Incidents if the action fails.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Pinned VM list for quick access: star VMs you care about, search the fleet, and open VNC or serial c.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- VM workbench
- Widgets
- Console Hub — `/consolehub`

Home (Mission Control)

Purpose

Apple.com-style chapter home: greeting hero, **Get the highlights** (fleet KPIs on a dark band), infrastructure pulse, a light Attention teaser, running machines, and apps/insights — without the heavy triage deck.

When to use it

- Start of shift — “is the platform healthy?”
- Jump to Machine Runway, Attention, Health, or Incidents from localnav
- Spot open issues via the Attention teaser, then open `/attention` for actions and Issue Stream

How to get there

- Route: `/`
- Nav: **Home** · workspace **Dashboard**

Operate from the console (UX)

1. Open `/` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the hero (greeting + fleet summary) and localnav: **Machines · Attention · Health · Incidents · Create**.
3. Scan **Get the highlights**, then **Infrastructure pulse**, then the light **What needs you next** teaser — use **Open Attention** for ranked actions and Issue Stream (not embedded on Home).
4. Browse **Running machines** and **Apps and insights** chapters.
5. Open **Getting started checklist** (Help → Getting Started) if you are new — progress is saved to your account.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed.
7. **Success:** You can reach Attention, VMs, or Health without hunting the full sidebar.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Attention — `/attention`
- Virtual Machines — `/vms`
- System Health — `/system-health`
- Incidents — `/incidents`
- Capacity — `/capacity`

Instance types

Purpose

Browse KubeVirt instance types and preferences — standardized CPU/memory shapes for consistent VM sizing.

When to use it

- Pick a corporate-standard size before create
- Audit which shapes exist in the cluster
- Align FinOps rightsizing recommendations with catalog names

How to get there

- Route: `/instance-types`
- Nav: **Core → Instance types**

Operate from the console (UX)

1. Open `/instance-types` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Browse KubeVirt instance types and preferences — standardized CPU/memory shapes for consistent VM sizing.
3. Use filters and search on the page; open a row for detail / inspector.
4. Run the primary action (create, apply, run, export) from the PageHead or empty-state CTA.
5. Confirm success via toast + refreshed inventory; check Incidents if the action fails.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Browse KubeVirt instance types and preferences — standardized CPU/memory shapes for consistent VM si.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM setup
- Rightsizing
- Templates

Compare VMs

Purpose

Side-by-side diff of two VMs' configuration so you can spot drift, clone mistakes, or environment mismatches.

When to use it

- After cloning a VM
- When prod and staging "should match" but behave differently
- Auditing template drift

How to get there

- Route: `/vm-compare`
- Nav: **Core → Compare VMs**

Operate from the console (UX)

1. Open `/vm-compare` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Side-by-side diff of two VMs' configuration so you can spot drift, clone mistakes, or environment mismatches.
3. Use filters and search on the page; open a row for detail / inspector.
4. Run the primary action (create, apply, run, export) from the PageHead or empty-state CTA.
5. Confirm success via toast + refreshed inventory; check Incidents if the action fails.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Side-by-side diff of two VMs' configuration so you can spot drift, clone mistakes, or environment mi.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- VM workbench

VM setup (create a machine)

Purpose

Guided creation of a new KubeVirt VM from instance types, preferences, templates, or AI-assisted manifests.

When to use it

- Provision a new workload VM without writing YAML
- Standardize on catalog shapes (instance types)
- Clone-like create from a template or blueprint
- Create **Windows** via Kryton catalog when Settings → Network shows Kryton Connected (otherwise Autounattend / ISO / Zeus golden PVC)

How to get there

- Routes: `/vm-setup`, `/vms/new` (and Create Machine sheet flows)
- Nav: **Core → VM setup** · shortcut from VMs inventory

Operate from the console (UX)

1. Open `/vm-setup` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Pick Linux or Windows. For Windows with Kryton Connected: choose a Kryton catalog image (e.g. `windows-11-enterprise`) — Zeus posts to `/api/v1/kryton/machines`.
3. Review disks, network, and namespace; deploy.
4. Confirm success via toast + refreshed inventory; Kryton VMs open at `/vms/{ns}/{name}` from `providerRef`.
5. **Empty / fail:** Check auth, namespace, KubeVirt/CDI; for Kryton also `GET /api/v1/kryton/status`.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Windows via Kryton
- Instance types
- Templates
- Virtual Machines
- DataVolumes
- Image Factory

VM workbench

Purpose

Full-page operations surface for one virtual machine: power, console, hardware, networking, backup panels, guest agent, and remote access.

When to use it

- Start, stop, restart, or pause a specific VM
- Open VNC / serial / remote access
- Hot-plug CPU, memory, or disks
- Inspect guest OS / agent data
- Run backup, HA, or affinity controls for that VM

How to get there

- Route: `/vms/:namespace/:name`
- From **VMs** inventory — click a row
- Command palette — search the VM name (when indexed)

Operate from the console (UX)

1. Open `/vms/:namespace/:name` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Full-page operations surface for one virtual machine: power, console, hardware, networking, backup panels, guest agent, ….
3. Filter by namespace / name; open a row into the VM workbench (`/vms/<ns>/<name>`).
4. Power actions (Start / Stop / Restart / Pause) live on the workbench — not the browse list.
5. Open consoles (VNC needs HTTPS), disks, or migration tools from the workbench tabs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Full-page operations surface for one virtual machine: power, console, hardware, networking, backup p.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- Consoles overview
- Disk Manager
- PacketWolf — contain this VM's traffic

VM fleets (VMIRS)

Purpose

Manage VirtualMachineInstanceReplicaSet-style fleets — scale homogeneous VM groups as a unit.

When to use it

- Stateless or similarly shaped VM pools
- Scale replica count without editing each VM
- Oversee fleet health in one place

How to get there

- Route: `/vmirs`
- Nav: **Core → VM fleets**

Operate from the console (UX)

1. Open `/vmirs` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Manage VirtualMachineInstanceReplicaSet-style fleets — scale homogeneous VM groups as a unit.
3. Use filters and search on the page; open a row for detail / inspector.
4. Run the primary action (create, apply, run, export) from the PageHead or empty-state CTA.
5. Confirm success via toast + refreshed inventory; check Incidents if the action fails.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Manage VirtualMachineInstanceReplicaSet-style fleets — scale homogeneous VM groups as a unit.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- AutoScaler — `/autoscaler`

VM Instances (VMI)

Purpose

List of **running** VirtualMachineInstance objects — the live pods/instances behind VirtualMachine definitions.

When to use it

- Debug “VM exists but nothing is running”
- See which node a live instance is on
- Correlate phase with migration or crash loops

How to get there

- Route: `/vmis`
- Nav: **Core → VM Instances**

Operate from the console (UX)

1. Open `/vmis` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: List of **running** VirtualMachineInstance objects — the live pods/instances behind VirtualMachine definitions.
3. Use filters and search on the page; open a row for detail / inspector.
4. Run the primary action (create, apply, run, export) from the PageHead or empty-state CTA.
5. Confirm success via toast + refreshed inventory; check Incidents if the action fails.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: List of **running** VirtualMachineInstance objects — the live pods/instances behind VirtualMachine d.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- Live Migrations
- Pods — `/pods` for the virt-launcher pod

Virtual Machines

Purpose

Inventory of every KubeVirt virtual machine you can see: live status, filters, and entry into the per-VM workbench.

When to use it

- Find a VM by name, namespace, or status
- Confirm fleet health after a change
- Open a workbench for power, console, hardware, or guest ops
- Start bulk or group operations (where enabled)

How to get there

- Route: `/vms`
- Nav: **Core → VMs** · workspace **VMs**

Operate from the console (UX)

1. Open `/vms` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Inventory of every KubeVirt virtual machine you can see: live status, filters, and entry into the per-VM workbench.
3. Filter by namespace / name; open a row into the VM workbench (`/vms/<ns>/<name>`).
4. Power actions (Start / Stop / Restart / Pause) live on the workbench — not the browse list.
5. Open consoles (VNC needs HTTPS), disks, or migration tools from the workbench tabs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Inventory of every KubeVirt virtual machine you can see: live status, filters, and entry into the pe.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM workbench
- VM setup
- VM Instances — running VMI objects
- VM fleets — instance-type fleets / VMIRS
- REST: `GET /api/v1/vms`

ConsoleHub

Purpose

Unified launcher and session manager for browser consoles — multiple VMs, policies, and session visibility.

When to use it

- Operate several consoles side by side
- Audit who has active console sessions
- Apply console access policy at a fleet level

How to get there

- Route: `/consolehub`
- Related: `/console-sessions`, `/workspace`

Operate from the console (UX)

1. Open `/consolehub` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Unified launcher and session manager for browser consoles — multiple VMs, policies, and session visibility.
3. Pick a session target (VM / pod / node) and attach VNC, serial, SSH, or RDP as offered.
4. Confirm HTTPS for in-browser VNC; RDP/SSH use guest credentials, not Zeus login.
5. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Unified launcher and session manager for browser consoles — multiple VMs, policies, and session visi.
6. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Consoles overview
- Virtual Machines

Consoles & remote access

Purpose

Reach the guest: graphical VNC, serial text console, and native RDP/SSH via NodePort expose.

When to use it

- Install or configure an OS interactively
- Debug boot failures (serial)
- Give operators desktop/SSH access without kubectl port-forward

How to get there

Method	Entry
From a VM	Workbench → Console / Remote access
Multi-session	`/consolehub`
Pop-out VNC	`/vm-console/vnc/...` (from UI)
Workspace	`/workspace`

Operate from the console (UX)

1. Open `/overview` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Reach the guest: graphical VNC, serial text console, and native RDP/SSH via NodePort expose.
3. Use filters and search on the page; open a row for detail / inspector.
4. Run the primary action (create, apply, run, export) from the PageHead or empty-state CTA.
5. Confirm success via toast + refreshed inventory; check Incidents if the action fails.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Reach the guest: graphical VNC, serial text console, and native RDP/SSH via NodePort expose.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM workbench
- ConsoleHub
- Terminal — `/terminal` for cluster/pod shells

Blueprints

Purpose

Blueprint Marketplace for one-click application stacks (for example Windows AD, RDS, SQL, IIS, jump boxes) registered in the cluster.

When to use it

- Deploy a multi-resource stack into a target namespace
- Register a new blueprint shell for later parameterization
- Jump to Image Factory for golden-image builds
- Deploy multi-VM blueprints as a VMIRS fleet when offered

How to get there

- Route: `/blueprints`
- Nav: **Cluster → Blueprints**
- Related: `/image-factory` , `/vmirs`

Operate from the console (UX)

1. Open `/blueprints` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Blueprint Marketplace for one-click application stacks (for example Windows AD, RDS, SQL, IIS, jump boxes) registered in….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Blueprint Marketplace for one-click application stacks (for example Windows AD, RDS, SQL, IIS, jump .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Image Factory
- Templates
- VMs
- VM fleets — `/vmirs`

Enterprise networking

Purpose

Direct management of Cilium-native Egress Gateway policies, BGP peering, L2 announcement policies, and Gateway API `Gateway` / `HTTPRoute` objects — no separate controller or CRD editing required.

When to use it

- Pin a set of pods' outbound traffic to a stable IP via a chosen gateway node
- Peer the cluster with an upstream router over BGP, or announce Service IPs over L2 as an alternative to MetalLB
- Expose a VM's Service through the Kubernetes Gateway API instead of classic Ingress, for richer per-route traffic splitting and header matching

How to get there

- Route: `/cilium-enterprise-networking`
- Nav: **Cluster → Enterprise networking**
- Related: `/metallb-external-ips`, `/network-attachments`, `/network-flow?tab=firewall`

Operate from the console (UX)

1. Open `/cilium-enterprise-networking` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Direct management of Cilium-native Egress Gateway policies, BGP peering, L2 announcement policies, and Gateway API `Gate….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Direct management of Cilium-native Egress Gateway policies, BGP peering, L2 announcement policies, a.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- MetalLB & external IPs
- Network hub (Firewall tab)

Customization Profiles

Purpose

Reusable guest customization specs — cloud-init, Windows sysprep/unattend XML, and SSH authorized keys — applied from create/clone flows or onto an existing VM.

When to use it

- Standardize Linux cloud-init across many VMs
- Store a Windows unattend / sysprep baseline
- Push SSH keys onto an existing guest without rewriting YAML by hand
- Share a named profile with operators who create VMs

How to get there

- Route: `/customization-profiles`
- Nav: **Cluster → Customization Profiles**
- Related: `/vm-setup`, `/vms`, `/templates`

Operate from the console (UX)

1. Open `/customization-profiles` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Reusable guest customization specs — cloud-init, Windows sysprep/unattend XML, and SSH authorized keys — applied from cr….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Reusable guest customization specs — cloud-init, Windows sysprep/unattend XML, and SSH authorized ke.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM setup
- VMs
- Templates

DataVolumes

Purpose

CDI DataVolume inventory — disk import/clone/upload jobs that back VM disks.

When to use it

- Watch ISO/image import progress
- Debug “VM stuck pending” while DV is Importing
- Confirm PVC bound after DV succeeds

How to get there

- Route: `/datavolumes`
- Nav: **Cluster → DataVolumes**

Operate from the console (UX)

1. Open `/datavolumes` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: CDI DataVolume inventory — disk import/clone/upload jobs that back VM disks.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: CDI DataVolume inventory — disk import/clone/upload jobs that back VM disks.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM setup
- Storage
- Image Library — `/image-library`

Device Plugins

Purpose

Read-only view of Kubernetes device-plugin resources and GPU capacity reported by the cluster.

When to use it

- Confirm device plugins are registered and healthy
- See GPU allocation counts (total / allocated / available)
- Search plugins or GPU rows by name, node, or type
- Correlate with the GPU Devices page before binding hardware to VMs

How to get there

- Route: `/device-plugins`
- Nav: **Cluster → Device Plugins**
- Related: `/gpu`, `/nodes`

Operate from the console (UX)

1. Open `/device-plugins` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only view of Kubernetes device-plugin resources and GPU capacity reported by the cluster.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only view of Kubernetes device-plugin resources and GPU capacity reported by the cluster.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- GPU Devices
- Nodes
- Pods

Disk Manager

Purpose

Manage VM disks: attach, hot-plug, resize entry points, and disk inventory beyond the raw PVC list.

When to use it

- Add a data disk to a running VM
- Grow capacity (with PVC Resize / guest grow-fs as needed)
- Audit disks attached to a workload

How to get there

- Route: `/disk-manager`
- Also: VM workbench hardware / disk panels

Operate from the console (UX)

1. Open `/disk-manager` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Manage VM disks: attach, hot-plug, resize entry points, and disk inventory beyond the raw PVC list.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Manage VM disks: attach, hot-plug, resize entry points, and disk inventory beyond the raw PVC list.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Storage
- VM workbench
- PVC Resize — `/pvc-resize`

GPU Devices

Purpose

GPU / PCI passthrough inventory: host VGA/3D devices, allocation to VMs, plus a vGPU orchestration panel for mdev profiles and assign actions.

When to use it

- See which host GPUs are free vs allocated
- Confirm IOMMU group, driver, and PCI address before passthrough
- Review VM GPU assignment rows
- Assign a GPU resource or host device to a VM from the vGPU panel

How to get there

- Route: `/gpu`
- Nav: **Cluster → GPU Devices**
- Related: `/device-plugins`, `/vms`, `/nodes`

Operate from the console (UX)

1. Open `/gpu` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: GPU / PCI passthrough inventory: host VGA/3D devices, allocation to VMs, plus a vGPU orchestration panel for mdev profil….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: GPU / PCI passthrough inventory: host VGA/3D devices, allocation to VMs, plus a vGPU orchestration p.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Device Plugins
- Nodes
- VMs

HPA

Purpose

Monitor and manage Horizontal Pod Autoscalers — replica counts, CPU utilization, and scaling status across namespaces.

When to use it

- See which workloads are at min/max or actively scaling
- Create an HPA for a Deployment or similar target
- Delete an unused autoscaler
- Search HPAs by name, namespace, or target

How to get there

- Route: `/hpa`
- Nav: **Cluster → HPA**
- Related: `/vpa`, `/pods`, `/rightsizing`

Operate from the console (UX)

1. Open `/hpa` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Monitor and manage Horizontal Pod Autoscalers — replica counts, CPU utilization, and scaling status across namespaces.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Monitor and manage Horizontal Pod Autoscalers — replica counts, CPU utilization, and scaling status .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VPA
- Pods
- Rightsizing

Image Factory

Purpose

Golden Image Factory pipelines that take a customer-supplied OS ISO through VirtIO, updates, optional GuestKit bake, sysprep/generalize, snapshot, and catalog publish.

When **Kryton** is Connected (Settings → Network), the same page also offers **Build with Kryton**: live Kryton catalog → dockur golden → CDI bootstrap, without embedding Kryton's UI.

When to use it

- Build a Windows or Ubuntu golden template from an ISO URL (Zeus pipeline)
- Prefer **Build with Kryton** for Windows dockur catalog images when Kryton is healthy
- Track pipeline / golden progress; **Advance** Zeus pipelines when the next stage is ready
- Bake the GuestKit agent into Zeus-pipeline images before publish

How to get there

- Route: `/image-factory`
- Nav: **Cluster → Image Factory**
- Related: `/blueprints` , `/templates` , `/image-library` , Windows via Kryton

Operate from the console (UX)

1. Open `/image-factory` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. If Kryton is Connected: pick a Kryton catalog image → **Build with Kryton**; poll golden status on the page (or via `/api/v1/kryton/golden`).
3. For Zeus ISO pipelines: create/advance pipelines as before (VirtIO → publish).
4. Mutations go through confirm sheets — wait for status refresh.
5. **Empty / fail:** No data → check auth, namespace filter, KubeVirt/CDI; for Kryton builds also check Settings → Network → Kryton and `GET /api/v1/kryton/status` .
6. **Success:** Live inventory or job progress matches the deck; related centers open without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Windows via Kryton
- Blueprints
- Templates
- Image Library
- Image Registry

Image Library

Purpose

One catalog for golden images, import guidance, and cluster images so operators can pick OS media when creating VMs.

When to use it

- Browse golden templates and container disks before deploy
- See cluster-discovered images
- Open Create VM with an image reference prefilled
- Find links into DataVolumes, Image Factory, or Migration Factory for imports

How to get there

- Route: `/image-library`
- Nav: **Cluster → Image Library**
- Related: `/vms`, `/datavolumes`, `/image-factory`, `/templates`

Operate from the console (UX)

1. Open `/image-library` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: One catalog for golden images, import guidance, and cluster images so operators can pick OS media when creating VMs.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: One catalog for golden images, import guidance, and cluster images so operators can pick OS media wh.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- DataVolumes
- Image Factory
- Templates
- VMs

Image Registry

Purpose

Browse container disk images for KubeVirt VMs — cluster images from running pods, or a reference catalog — then open Create VM with the image prefilled.

When to use it

- Pick a containerdisk / cloud image for a new VM
- Copy a full image URL (`registry/repo:tag`)
- Enter a custom image reference and quick-spawn with defaults
- Fall back to the built-in reference catalog when the cluster list is empty

How to get there

- Route: `/image-registry`
- Nav: **Cluster → Image Registry**
- Related: `/vms` , `/image-library` , `/images-volumes`

Operate from the console (UX)

1. Open `/image-registry` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Browse container disk images for KubeVirt VMs — cluster images from running pods, or a reference catalog — then open Cre….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Browse container disk images for KubeVirt VMs — cluster images from running pods, or a reference cat.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Image Library
- Image library
- VMs
- VM setup

MetalLB & external IPs

Purpose

Operator guidance for LoadBalancer Services (SSH, RDP, and other external access) via MetalLB address pools — not a pool editor UI.

When to use it

- Check whether the MetalLB IPAddressPool API is present
- See how many IPAddressPool objects exist
- Follow L2 or BGP configuration examples
- Understand deploy-time env vars for optional MetalLB install

How to get there

- Route: `/metallb-external-ips`
- Nav: **Cluster → MetalLB & external IPs**
- Related: `/services`, `/vms`

Operate from the console (UX)

1. Open `/metallb-external-ips` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Operator guidance for LoadBalancer Services (SSH, RDP, and other external access) via MetalLB address pools — not a pool….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Operator guidance for LoadBalancer Services (SSH, RDP, and other external access) via MetalLB addres.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Services
- VMs
- VM workbench

Networks

Purpose

Multus NetworkAttachmentDefinition management so VMs can attach additional L2 NICs — bridge, macvlan, ipvlan, host-device, or SR-IOV.

When to use it

- Add a second NIC / VLAN for a VM
- Create a Multus NAD and attach it to a guest in one wizard
- Inventory bridge vs macvlan vs SR-IOV attachments
- Remove an unused network definition

How to get there

- Route: `/network-attachments`
- Nav: **Cluster → Networks**
- Related: `/vms`, `/device-plugins`

Operate from the console (UX)

1. Open `/network-attachments` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Multus NetworkAttachmentDefinition management so VMs can attach additional L2 NICs — bridge, macvlan, ipvlan, host-devic….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Multus NetworkAttachmentDefinition management so VMs can attach additional L2 NICs — bridge, macvlan.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VMs
- Device Plugins
- MetalLB & external IPs

Nodes

Purpose

Kubernetes worker/control-plane node inventory: capacity, conditions, and drain/placement context for VMs.

When to use it

- Before live migration or maintenance
- Find which node hosts a hot VM
- Investigate NotReady / pressure conditions

How to get there

- Route: `/nodes`
- Nav: **Cluster → Nodes**

Operate from the console (UX)

1. Open `/nodes` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Kubernetes worker/control-plane node inventory: capacity, conditions, and drain/placement context for VMs.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Kubernetes worker/control-plane node inventory: capacity, conditions, and drain/placement context fo.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Live Migrations
- Capacity — `/capacity`
- Placement — `/placement`

Pods

Purpose

Kubernetes pod inventory — including `virt-launcher` pods that back running VMIs.

When to use it

- Debug scheduling failures behind a stuck VM
- Inspect restarts, node assignment, and ages
- Bridge VM ops and raw Kubernetes troubleshooting

How to get there

- Route: `/pods`
- Nav: **Cluster → Pods**
- Related workspace: **Kubernetes**

Operate from the console (UX)

1. Open `/pods` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Kubernetes pod inventory — including `virt-launcher` pods that back running VMIs.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Kubernetes pod inventory — including `virt-launcher` pods that back running VMIs.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM Instances
- Nodes
- Events — `/events`

Priority Classes

Purpose

Read-only list of Kubernetes PriorityClass objects — numeric value, global default, preemption policy, and usage.

When to use it

- Find the global default priority class
- Compare priority values before assigning workloads
- See which classes allow preempting lower-priority pods
- Diagnose 403/401 if RBAC blocks listing PriorityClass

How to get there

- Route: `/priority-classes`
- Nav: **Cluster → Priority Classes**
- Related: `/runtime-classes`, `/taints`, `/pods`

Operate from the console (UX)

1. Open `/priority-classes` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only list of Kubernetes PriorityClass objects — numeric value, global default, preemption policy, and usage.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only list of Kubernetes PriorityClass objects — numeric value, global default, preemption polic.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Runtime Classes
- Taints
- Pods

PVC Resize

Purpose

Expand existing PersistentVolumeClaims or create empty PVCs. CDI image imports still belong on DataVolumes.

When to use it

- Grow a VM disk claim that is running out of space
- Create a blank PVC in a namespace before attaching it
- Pick storage class and access mode for a new claim
- Deep-link with `?namespace=` and `?pvc=` from other storage views

How to get there

- Route: `/pvc-resize`
- Nav: **Cluster → PVC Resize**
- Related: `/storage`, `/disk-manager`, `/datavolumes`

Operate from the console (UX)

1. Open `/pvc-resize` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Expand existing PersistentVolumeClaims or create empty PVCs. CDI image imports still belong on DataVolumes.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Expand existing PersistentVolumeClaims or create empty PVCs. CDI image imports still belong on DataV.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Storage
- Disk Manager
- DataVolumes

Runtime Classes

Purpose

Read-only inventory of cluster RuntimeClass objects — handler, scheduling hints, overhead, and usage counts.

When to use it

- Confirm which runtime handlers exist (for example kata, gvisor, runc)
- See CPU/memory overhead configured on a class
- Check how many workloads reference each class
- Sort or search before assigning `runtimeClassName` on pods/VMs elsewhere

How to get there

- Route: `/runtime-classes`
- Nav: **Cluster → Runtime Classes**
- Related: `/priority-classes`, `/pods`, `/nodes`

Operate from the console (UX)

1. Open `/runtime-classes` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only inventory of cluster RuntimeClass objects — handler, scheduling hints, overhead, and usage counts.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only inventory of cluster RuntimeClass objects — handler, scheduling hints, overhead, and usage.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Priority Classes
- Pods
- Nodes

Services

Purpose

Cluster-wide Kubernetes Service inventory for VM SSH/RDP exposes and other workloads — ports, addresses, and YAML in one place.

When to use it

- Find the NodePort or LoadBalancer address for a VM
- Filter Zeus-managed SSH/RDP/pod Services
- Copy a primary address without leaving the dashboard
- Confirm ClusterIP and port mappings before opening a firewall

How to get there

- Route: `/services`
- Nav: **Cluster → Services**
- Related: `/metallb-external-ips`, `/vms`

Operate from the console (UX)

1. Open `/services` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Cluster-wide Kubernetes Service inventory for VM SSH/RDP exposes and other workloads — ports, addresses, and YAML in one….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Cluster-wide Kubernetes Service inventory for VM SSH/RDP exposes and other workloads — ports, addres.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- MetalLB & external IPs
- VMs
- Pods

Storage

Purpose

Storage and PVC intelligence for the cluster: volumes, capacity signals, and entry points into disk/resize workflows.

When to use it

- See where VM disks live
- Spot full or failing storage classes
- Jump to resize, DataVolumes, or Disk Manager

How to get there

- Route: `/storage`
- Nav: **Cluster → Storage** · workspace **Storage**

Operate from the console (UX)

1. Open `/storage` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the editorial hero and **Get the highlights** (bound PVC ratio, PVC count, pending, classes), then use the PVC fleet / backends / profiles tabs.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Storage and PVC intelligence for the cluster: volumes, capacity signals, and entry points into disk/.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Disk Manager
- DataVolumes
- PVC Resize — `/pvc-resize`
- VM workbench

Taints

Purpose

Read-only analysis of node taints and which VMs tolerate them — plus scheduling impact warnings for unschedulable guests.

When to use it

- Before maintenance: see NoSchedule / PreferNoSchedule / NoExecute coverage
- Find VMs that tolerate a given tainted node
- Spot unschedulable VM counts from the analysis endpoint
- Search nodes or taint keys when placement fails

How to get there

- Route: `/taints`
- Nav: **Cluster → Taints**
- Related: `/nodes`, `/vms`, `/priority-classes`

Operate from the console (UX)

1. Open `/taints` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only analysis of node taints and which VMs tolerate them — plus scheduling impact warnings for unschedulable guests.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only analysis of node taints and which VMs tolerate them — plus scheduling impact warnings for .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Nodes
- VMs
- Priority Classes

Templates

Purpose

Curated VM templates for one-click or guided deploy of known-good shapes.

When to use it

- Standard golden images / org templates
- Faster create than blank instance-type only
- Hand off approved configs to app teams
- Windows Kryton catalog templates (`windows-11-enterprise` , `windows-server-2025` , …) when Kryton is Connected

How to get there

- Route: `/templates`
- Nav: **Cluster → Templates**
- Related: Windows via Kryton

Operate from the console (UX)

1. Open `/templates` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Filter Windows / Linux; Kryton-tagged Windows templates prefill the wizard with `windowsInstall=kryton` .
3. Use namespace / label filters; open an object for inspector details.
4. Deploy / prefill; wait for toast + inventory refresh.
5. **Empty / fail:** Check auth and catalog; for Kryton Windows also Settings → Network → Kryton (`GET /api/v1/kryton/status`).

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Windows via Kryton
- VM setup
- Image Factory
- Customization Profiles — `/customization-profiles`
- Blueprints — `/blueprints`

VPA

Purpose

List, create, and delete Vertical Pod Autoscalers, and inspect container resource recommendations.

When to use it

- Review VPA update mode (Auto, Recreate, Initial, Off) for a workload
- Read target / lower / upper bound recommendations per container
- Create a VPA against a Deployment (or other kind)
- Remove a VPA so the controller stops managing requests

How to get there

- Route: `/vpa`
- Nav: **Cluster → VPA**
- Related: `/hpa`, `/pods`, `/rightsizing`

Operate from the console (UX)

1. Open `/vpa` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: List, create, and delete Vertical Pod Autoscalers, and inspect container resource recommendations.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: List, create, and delete Vertical Pod Autoscalers, and inspect container resource recommendations.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- HPA
- Pods
- Rightsizing

Windows via Kryton

Zeus OS can create Windows machines by calling **Kryton's REST API** (no Kryton UI embed). Day-2 (VNC, NodePort RDP, GuestKit) stays in Zeus.

When to use it

- Prefer **Kryton catalog** in the Create VM wizard when Settings → Network shows Kryton **Connected**.
- Use **Build with Kryton** on Image Factory for golden-image builds Kryton owns (dockur install → Sysprep → CDI bootstrap).
- Keep Zeus Autounattend / ISO / Zeus Image Factory PVC paths when Kryton is not deployed.

Catalog (12 dockur IDs)

Zeus built-in Windows templates match Kryton's catalog (template id = Kryton `imageId`):

Desktop	Server
`windows-11-enterprise`, `windows-11-pro`, `windows-11-ltsc`	`windows-server-2025`, `windows-server-2022`
`windows-10-enterprise`, `windows-10-pro`, `windows-10-ltsc`	`windows-server-2019`, `windows-server-2016`
`windows-tiny11`, `windows-tiny11-core`	

Legacy Zeus-only IDs (`windows-11`, `windows-10`, `windows-server-2012-r2`, `windows-server-sql-2022`) are no longer primary marketplace templates.

Operator wiring

Helm / env	Purpose
`config.krytonUrl` / `ZEUS_OS_KRYTON_URL`	Kryton base URL (lab kubevirt API often `:9088`)
`config.krytonApiKey` or Secret / `ZEUS_OS_KRYTON_API_KEY`	API bearer token
`config.krytonApiKeySecretName`	Prefer Secret (`api-key` key) over plaintext
`config.krytonProject` / `ZEUS_OS_KRYTON_PROJECT`	Default project (`default`)
`config.krytonEnabled: false` / `ZEUS_OS_KRYTON=off`	Kill-switch

The API key stays on the server. The browser only calls `/api/v1/kryton/*` on Zeus. Do **not** drop the API key based on URL shape (in-cluster vs host IP).

Lab harden (Kryton)

On the Kryton host, after deploy:

```
# Kryton repo
./scripts/deploy-remote.sh <host> <user> --quick --key
make harden-lab H=<host> U=<user>
# kubevirt API :9088, dockur lab :7088, token ~/.kryton/lab.token
```

Wire into Zeus (example):

```
TOKEN=$(ssh <user>@<host> 'cat ~/.kryton/lab.token')
kubectl -n zeus-os create secret generic zeus-os-kryton-apikey \
  --from-literal=api-key="$TOKEN" --dry-run=client -o yaml | kubectl apply -f -
helm upgrade zeus-os ./chart -n zeus-os --reuse-values \
  --set-string config.krytonUrl=http://<host>:9088 \
  --set-string config.krytonApiKeySecretName=zeus-os-kryton-apikey \
  --set-string config.krytonProject=default \
  --set config.krytonEnabled=true
```

Verify: Settings → Network → Kryton **Connected**, or `GET /api/v1/kryton/status` → `configured: true`, `healthy: true`.

Zeus API surface

Route	Purpose
`GET /api/v1/kryton/status`	Configured / healthy / capabilities / doctor
`GET /api/v1/kryton/images`	Live catalog
`POST /api/v1/kryton/machines`	Create Windows machine
`GET/DELETE …/kryton/machines/{id}`	List / delete
`POST …/kryton/machines/{id}/{start|stop|reboot}`	Lifecycle
`GET/POST /api/v1/kryton/golden`	List / start golden
`GET /api/v1/kryton/golden/{id}`	Poll build
`POST /api/v1/kryton/golden/{id}/bootstrap`	Bootstrap DataSource into cluster

Create body (kubevirt provider)

`POST /kryton/machines` (Zeus or Kryton) requires a disk size. Omitting it returns `disk.sizeGiB must be between 16 and 65536`. The Create VM wizard sends `disk.sizeGiB` from the catalog `defaultDiskGiB` (see `useCreateVmSubmit`).

```
{
  "name": "win-lab-01",
  "image": "windows-tiny11-core",
  "project": "default",
  "compute": { "cpu": 2, "memoryMiB": 4096 },
  "disk": { "sizeGiB": 64 }
}
```

When Kryton's provider is **kubevirt**, only images with a CDI `DataSource` in `kryton-images` create successfully (`GET /kryton/status` → doctor `kubevirt-images`).

Golden images — do not trust a one-minute "ready"

A real dockur install + Sysprep takes **well over an hour**. If `GET /kryton/golden/{id}` flips to `ready` in ~1 minute, treat the qcow2 as **suspect**: VNC of a clone often shows Windows Setup ("restarted unexpectedly") instead of a desktop, and RDP never comes up.

Before bootstrap / create:

1. Confirm the dockur console finished install + Sysprep (not stuck at “58% windows_setup”).
2. Confirm `outputPath` qcow2 is from a **FINALIZE=1** capture (Kryton `build-golden-image.sh` must preserve parent `FINALIZE` / `IMAGE_ID` — see Kryton `docs/GOLDEN-IMAGES.md`).
3. Prefer `availability: stored` + a fresh sha after a long build over catalog aliases that share one path (lab saw `windows-11-pro` and `windows-tiny11-core` pointing at the same core11 qcow2).

CDI bootstrap gotchas

Symptom	Cause / fix
Bootstrap / `virtctl image-upload` can’t reach uploadproxy	Service is ClusterIP-only — port-forward or set an external uploadproxy URL
Import fails on small PVC	Virtual disk can be ~80 Gi — use a **≥96 Gi** PVC
`IncompatibleVolumeModes` on clone	Golden DV was **Filesystem**; target expected **Block** (or reverse). Match volume modes on clone, or rebuild golden as Block
Doctor lists missing DataSources	Run `POST /kryton/golden/{id}/bootstrap` or Kryton `bootstrap-kubevirt-images.sh` after a real golden

Day-2 (VNC + native RDP)

After create, open the VM in Zeus (VNC, native RDP NodePort, GuestKit) using Kryton’s `providerRef` namespace/name (`zeusVm` deep-link). Guest agent tooling remains GuestKit / QEMU-GA — not Kryton.

Native RDP (`POST /api/v1/vms/{ns}/{name}/rdp-access/expose`) needs all of:

1. **Guest listening on 3389** (finalized golden / RDP enabled — not mid-Setup).
2. **Masquerade port 3389** on the VM interface (`vm_spec_has_rdp_port`; Zeus Windows create merges this automatically — hand-rolled VMs must add it and restart).
3. **Service selector** `vm.kubevirt.io/name=<vm>` (KubeVirt always labels virt-launcher pods this way). Empty endpoints + `No route to host` on the NodePort usually means a stale `kubevirt.io/vm=` selector.

Probe from the host: Service endpoints → pod IP:3389 (masquerade DNAT to `10.0.2.2`) → NodePort. Guest-agent absence is common on Tiny11; use VNC to confirm desktop vs Setup.

E2E catalog script

```
ZEUS_OS_E2E_INSECURE=1 ./scripts/e2e-kryton-catalog.sh https://<host>:30050
# Writes docs/kryton-e2e-ledger-<timestamp>.md (or LEDGER=…)
```

Sequential golden → bootstrap → create → delete for every catalog image. Wall time is long (hours); Microsoft media/licensing remains operator responsibility.

Related

- WINDOWS_ENTERPRISE.md
- Image Factory
- Windows Licensing

Alerts

Purpose

Zeus-native alerting console — active fired alerts, threshold rules, history, and webhook destinations — separate from PrometheusRule CRDs in Alerting V2.

When to use it

- Triage currently firing Zeus alerts by severity
- Create or edit CPU, memory, restart, or node-pressure rules
- Acknowledge or resolve noise while investigating
- Wire Slack or other HTTPS webhooks for notifications
- Review history filtered by severity

How to get there

- Route: `/alerting`
- Nav: **Observe → Alerts**
- Related: `/incidents` , `/monitoring`

Tabs

One route, tabs in the URL (`?tab=`):

Tab	Deep link	What it is
Active alerts	`/alerting`	Alerts fired by the Zeus alerting engine
Rules	`/alerting?tab=rules`	Zeus-native alert rules
History	`/alerting?tab=history` (`&severity=warning`)	Past alerts
Webhooks	`/alerting?tab=webhooks`	Alert webhook destinations
Channels	`/alerting?tab=channels`	Notification channels (Slack, email, webhook, PagerDuty), test sends, delivery history
Prometheus	`/alerting?tab=prometheus`	PrometheusRule-CRD rules, Alertmanager firing alerts, and the rule-group editor (`?view=rules

Operate from the console (UX)

1. Open `/alerting` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Zeus-native alerting console — active fired alerts, threshold rules, history, and webhook destinations — separate from P….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Zeus-native alerting console — active fired alerts, threshold rules, history, and webhook destinatio.

7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Incidents
- Monitoring Targets
- System Health

APM

Purpose

Application performance dashboard for services, traces, and latency percentiles — when an APM backend is connected to Zeus OS.

When to use it

- See which services are healthy vs degraded
- Search traces by service, operation, or trace id
- Watch p50 / p95 / p99 latency over time
- Confirm whether an incident is infra-only or also service-latency related

How to get there

- Route: `/apm`
- Nav: **Observe → APM**
- Related: `/slo-manager`, `/logs-explorer`, `/custom-metrics`

Operate from the console (UX)

1. Open `/apm` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Application performance dashboard for services, traces, and latency percentiles — when an APM backend is connected to Ze….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Application performance dashboard for services, traces, and latency percentiles — when an APM backen.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- SLO Manager
- Logs Explorer
- Custom Metrics
- Incidents

Attention

Purpose

Ranked next steps, live fleet signals (Issue Stream), and day-2 remediation activity — the triage surface that used to live as a heavy block on Home.

When to use it

- Start of shift when Home shows warnings or error VMs
- Follow AI-ranked recommended actions (guest agent, unhealthy workloads, alerts)
- Watch the live Issue Stream and day-2 playbook activity without cluttering Home

How to get there

- Route: `/attention`
- Nav: **Observe → Attention** · Home localnav **Attention** · Home CTA **Open Attention**
- Related: `/incidents`, `/system-health`, `/events`, `/ai-center`

Operate from the console (UX)

1. Open `/attention` from Home (**Open Attention**), Observe nav, or command palette (⌘K / Ctrl+K).
2. Use the chapter localnav (brand left, **Home · Health · Incidents · Event log** spaced on the right) to jump between triage lenses.
3. Scan **Get the highlights**, then **Recommended actions** — P1/P2 cards with CTAs into VM Guest Tools, Incidents, or System Health.
4. Use **Issue Stream** (ink chapter + Replay window) for live Warning/Normal fleet events; open **Event log** for the full stream.
5. Review **Day-2 activity** for closed-loop remediation status.
6. Jump to **Incidents** when correlation or collaboration is needed, or **System Health** for host/vitality lenses.
7. **Empty / fail:** No actions → fleet is quiet; Ask Zyra or System Health for a deeper scan. No events → widen Replay or check Events.
8. **Success:** You can act on a ranked item or open a related center without returning to Home for the heavy deck.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Home — `/`
- Incidents — `/incidents`
- System Health — `/system-health`
- Events — `/events`

Capacity

Purpose

Cluster capacity and overcommit dashboard — utilization pulse, per-node breakdown, capacity alerts, planning scenarios, and HA/DRS context.

When to use it

- Morning check of CPU/memory headroom and overcommit ratios
- Find which nodes are hot or cordoned before placing VMs
- Open linked capacity scenarios for what-if planning
- Act on capacity alerts before they become incidents

How to get there

- Route: `/capacity`
- Nav: **Observe → Capacity**
- Related: `/forecasting`, `/heatmap`, `/nodes`

Operate from the console (UX)

1. Open `/capacity` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Cluster capacity and overcommit dashboard — utilization pulse, per-node breakdown, capacity alerts, planning scenarios, ….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Cluster capacity and overcommit dashboard — utilization pulse, per-node breakdown, capacity alerts, .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Forecasting
- Resource Heatmap
- Nodes
- Cost Intelligence

Containers

Purpose

Pod-centric container inventory with status stats, detail sheet, and (for non-viewers) deploy / apply-YAML shortcuts alongside a deployments panel.

When to use it

- See Running / Failed / Pending pod counts at a glance
- Find pods by name, namespace, node, or linked VM name
- Open a pod sheet for containers, restarts, IP, and node
- Deploy a workload or apply YAML when your role allows
- Cross-check container health next to VM issues on the same nodes

How to get there

- Route: `/containers`
- Nav: **Observe → Containers**
- Related: `/pods`, `/vms`

Operate from the console (UX)

1. Open `/containers` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Pod-centric container inventory with status stats, detail sheet, and (for non-viewers) deploy / apply-YAML shortcuts alo….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Pod-centric container inventory with status stats, detail sheet, and (for non-viewers) deploy / appl.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Pods
- Virtual Machines
- VM Instances
- Logs Explorer

Custom Metrics

Purpose

Dashboard for operator-defined metrics and their alert rules — create PromQL (or custom) configurations, then watch values and firing alerts.

When to use it

- Track a metric that is not on the stock VM Monitor cards
- Add a PromQL-backed series for a tenant-specific KPI
- See which custom alert rules are firing
- Prototype a metric before promoting it into Alerting V2 / PrometheusRules

How to get there

- Route: `/custom-metrics`
- Nav: **Observe → Custom Metrics**
- Related: `/alerting?tab=prometheus`, `/monitoring`, `/apm`

Operate from the console (UX)

1. Open `/custom-metrics` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Dashboard for operator-defined metrics and their alert rules — create PromQL (or custom) configurations, then watch valu….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Dashboard for operator-defined metrics and their alert rules — create PromQL (or custom) configurati.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Monitoring Targets
- APM
- SLO Manager

Events

Purpose

Live Kubernetes event browser — type, reason, object, message, namespace, count, and age — for correlating cluster noise with VM or workload symptoms.

When to use it

- Investigate FailedScheduling, FailedMount, or Warning storms
- Filter events to one namespace during a rollout
- Switch to search when the table is too noisy
- Confirm whether a VM issue is backed by recent cluster events

How to get there

- Route: `/events`
- Nav: **Observe → Events**
- Related: `/incidents` , `/system-health`

Tabs

One route, tabs in the URL (`?tab=`), so links and the back button work:

Tab	Deep link	What it is
Events	`/events`	Live event table, search, and **Analysis** (patterns and anomalies) as modes of the same tab (`?view=search` , `?view=analysis`)
Timeline	`/events?tab=timeline`	Cross-engine timeline with bookmarks and export; empty until `ZEUS_OS_EVENT_STORE` is enabled or a remediation has run
Audit log	`/events?tab=audit`	Searchable operator/audit trail with CSV export
Gantt	`/events?tab=gantt`	VM lifecycle Gantt built from Kubernetes events
Scheduled ops	`/events?tab=scheduled`	Per-VM lifecycle actions on a cron expression

Operate from the console (UX)

1. Open `/events` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Live Kubernetes event browser — type, reason, object, message, namespace, count, and age — for correlating cluster noise….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Live Kubernetes event browser — type, reason, object, message, namespace, count, and age — for corre.

7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Incidents
- System Health

Forecasting

Purpose

AI-assisted resource predictions — per-VM and cluster forecasts, capacity recommendations, and seasonal pattern detection — to plan before you run out of headroom.

When to use it

- Estimate when a VM or the cluster will hit a resource ceiling
- Review capacity recommendations before buying nodes
- Spot weekly or daily seasonal load patterns
- Feed planning discussions with trend labels (increasing / decreasing / stable)

How to get there

- Route: `/forecasting`
- Nav: **Observe → Forecasting**
- Related: `/capacity`, `/heatmap`, `/cost-intelligence`

Operate from the console (UX)

1. Open `/forecasting` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: AI-assisted resource predictions — per-VM and cluster forecasts, capacity recommendations, and seasonal pattern detectio….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: AI-assisted resource predictions — per-VM and cluster forecasts, capacity recommendations, and seaso.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Capacity
- Resource Heatmap
- Cost Intelligence
- VM Monitor

Resource Heatmap

Purpose

Cluster-wide utilization heatmap built from per-VM cells rolled up by node — CPU, memory, disk, and network pressure for capacity planning.

When to use it

- Spot hot nodes (high CPU or memory) before migrations fail
- Find underutilized nodes for placement or consolidation
- Watch live pressure during a load test or incident
- Cross-check Capacity numbers with a spatial view

How to get there

- Route: `/heatmap`
- Nav: **Observe → Resource Heatmap**
- Related: `/capacity`, `/vm-monitor`, `/nodes`

Operate from the console (UX)

1. Open `/heatmap` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Cluster-wide utilization heatmap built from per-VM cells rolled up by node — CPU, memory, disk, and network pressure for….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Cluster-wide utilization heatmap built from per-VM cells rolled up by node — CPU, memory, disk, and .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Capacity
- VM Monitor
- Forecasting
- Nodes

Host Info

Purpose

Read-only view of the Zeus OS host — OS, hardware, disks, NICs, and local services — for operators checking the control-plane node itself.

When to use it

- Confirm host CPU, memory, disk, and load after a platform upgrade
- Inventory PCI devices and memory modules before GPU or device passthrough work
- Check NIC state and traffic counters when the UI or API feels slow
- See which systemd-style services are running on the Zeus host

How to get there

- Route: `/host`
- Nav: **Observe → Host Info**
- Related: `/network-info`, `/system-health`

Operate from the console (UX)

1. Open `/host` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only view of the Zeus OS host — OS, hardware, disks, NICs, and local services — for operators checking the control-….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only view of the Zeus OS host — OS, hardware, disks, NICs, and local services — for operators c.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Network Info
- System Health
- Nodes

Incident chat

Purpose

Lightweight multi-user chat channel for incident collaboration. Marked **labs** in navigation; messages sync through Zeus OS, while slash commands run locally.

When to use it

- Coordinate responders during an active incident thread
- Leave a short status trail without leaving the dashboard
- Use offline-cached messages when the labs API is unreachable
- Practice war-room style notes before escalating to Incidents or War Room

How to get there

- Route: `/incident-chat`
- Nav: **Observe → Incident chat** (labs tier)
- Related: `/incidents` , `/war-room`

Operate from the console (UX)

1. Open `/incident-chat` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Lightweight multi-user chat channel for incident collaboration. Marked **labs** in navigation; messages sync through Zeu….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Lightweight multi-user chat channel for incident collaboration. Marked **labs** in navigation; messa.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Incidents
- System Health
- Alerts
- War Room — `/war-room`

Incidents

Purpose

Incident center with context and guided remediation — not just a raw alert dump.

When to use it

- Triage an outage or degraded VM fleet
- Assign / track remediation steps
- Jump to War Room or chat when collaboration is needed

How to get there

- Route: `/incidents`
- Nav: **Observe → Incidents**
- Related: `/incident-chat`, `/war-room`, `/incident-response` (wizard)

Operate from the console (UX)

1. Open `/incidents` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the editorial hero and **Get the highlights** (critical / warnings / cluster readiness), then filter and open an incident.
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Incident center with context and guided remediation — not just a raw alert dump.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- System Health
- Auto-Remediation — `/auto-remediation`
- Events — `/events`

Logs Explorer

Purpose

On-demand log search across pods in a namespace — query text, severity filter, and optional live tail — for day-2 debugging from the dashboard.

When to use it

- Search for `error`, `OOMKilled`, or a pod name during an incident
- Narrow to one namespace before opening a terminal
- Live-tail a query while reproducing a failure
- Confirm whether a VM-adjacent pod is logging failures

How to get there

- Route: `/logs-explorer`
- Nav: **Observe → Logs Explorer**
- Related: `/containers`, `/pods`, `/events?view=analysis`

Operate from the console (UX)

1. Open `/logs-explorer` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: On-demand log search across pods in a namespace — query text, severity filter, and optional live tail — for day-2 debugg….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: On-demand log search across pods in a namespace — query text, severity filter, and optional live tai.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Containers
- Pods
- APM
- Events

Monitoring Targets

Purpose

Inventory of Prometheus Operator objects in the cluster — ServiceMonitors, Prometheus instances, and PrometheusRule groups — plus high-level monitoring stats.

When to use it

- Verify scrape coverage after installing kube-prometheus or similar
- Open a ServiceMonitor or PrometheusRule detail before changing GitOps
- Confirm Prometheus CRs exist and note external URLs
- Correlate missing metrics with missing ServiceMonitors

How to get there

- Route: `/monitoring`
- Nav: **Observe → Monitoring Targets**
- Related: `/alerting?tab=prometheus`, `/custom-metrics`, `/vm-monitor`

Operate from the console (UX)

1. Open `/monitoring` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Inventory of Prometheus Operator objects in the cluster — ServiceMonitors, Prometheus instances, and PrometheusRule grou….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Inventory of Prometheus Operator objects in the cluster — ServiceMonitors, Prometheus instances, and.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM Monitor
- Custom Metrics
- System Health

Network Info

Purpose

Host network interface inventory for the Zeus OS host — physical, bridge, veth, VM TAP, Cilium, bond, VLAN, and tunnel devices — with traffic counters.

When to use it

- Confirm which NICs are up after a host network change
- Find VM TAP (`vnet*`) or Cilium interfaces during connectivity triage
- Copy MAC or IP addresses for tickets or firewall rules
- Spot high RX/TX interfaces before blaming a guest VM

How to get there

- Route: `/network-info`
- Nav: **Observe → Network Info**
- Related: `/host` , `/packetwolf`

Operate from the console (UX)

1. Open `/network-info` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Host network interface inventory for the Zeus OS host — physical, bridge, veth, VM TAP, Cilium, bond, VLAN, and tunnel d….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Host network interface inventory for the Zeus OS host — physical, bridge, veth, VM TAP, Cilium, bond.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Host Info
- PacketWolf
- VM Workbench
- Topology

SLO Manager

Purpose

Service level objective tracker — create availability-style objectives, watch met / burning / breached status, and refresh error-budget posture for the fleet.

When to use it

- Define a target percent for a service or cluster KPI
- See how many SLOs are met, burning budget, or breached
- Refresh during an incident to check burn status
- Pair with APM or custom metrics when those backends feed indicators

How to get there

- Route: `/slo-manager`
- Nav: **Observe → SLO Manager**
- Related: `/apm`, `/custom-metrics`, `/alerting`

Operate from the console (UX)

1. Open `/slo-manager` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Service level objective tracker — create availability-style objectives, watch met / burning / breached status, and refre….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Service level objective tracker — create availability-style objectives, watch met / burning / breach.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- APM
- Custom Metrics
- Alerts
- Incidents

System Health

Purpose

Platform health dashboard — control-plane and Zeus-related component pulse for operators and admins.

When to use it

- Morning check / after upgrades
- Correlate “UI slow” with backend or dependency health
- Decide whether an incident is cluster-wide or VM-local

How to get there

- Route: `/system-health`
- Nav: **Observe → System Health** · workspace **Monitoring**

Operate from the console (UX)

1. Open `/system-health` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Platform health dashboard — control-plane and Zeus-related component pulse for operators and admins.
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Platform health dashboard — control-plane and Zeus-related component pulse for operators and admins.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Home
- Incidents
- Alerts — `/alerting`

VM Monitor

Purpose

Activity Monitor for the VM fleet — live and historical CPU, memory, network, and disk — with per-VM charts and links into the VM workbench.

When to use it

- Find which VMs are hottest on CPU, memory, network, or disk right now
- Watch fleet averages and top consumers during an incident
- Drill into one VM's charts before opening the full workbench
- Compare live samples vs Prometheus history ranges

How to get there

- Route: `/vm-monitor`
- Nav: **Observe → VM Monitor**
- Related: `/vms`, `/heatmap`, `/monitoring`

Operate from the console (UX)

1. Open `/vm-monitor` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Activity Monitor for the VM fleet — live and historical CPU, memory, network, and disk — with per-VM charts and links in….
3. Filter firing vs resolved; open an incident or alert for guided remediation.
4. Jump to related VMs/pods/nodes from the detail panel.
5. Silence only with an expiry when paging must pause — keep the alert visible in-ledger.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Activity Monitor for the VM fleet — live and historical CPU, memory, network, and disk — with per-VM.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- VM Workbench
- Resource Heatmap
- Monitoring Targets

AutoScaler

Purpose

Define policies that resize VMs automatically, and review right-sizing recommendations with their estimated monthly cost impact before applying them.

When to use it

- Create a CPU/memory scaling policy for a namespace, label set, or all VMs
- Apply a right-sizing recommendation to an over- or under-provisioned VM
- Check whether recent automatic scaling events succeeded
- Estimate monthly savings available from resizing

How to get there

- Route: `/autoscaler`
- Nav: **Run -> AutoScaler**
- Related: `/cluster-autoscaling`, `/optimization`, `/vms`

Operate from the console (UX)

1. Open `/autoscaler` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Define policies that resize VMs automatically, and review right-sizing recommendations with their estimated monthly cost….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Define policies that resize VMs automatically, and review right-sizing recommendations with their es.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Cluster Autoscale
- VMs
- VM Workbench
- Operations

Backup Wizard

Purpose

Guided backup workflow for VMs / volumes — complementary to Velero and snapshot managers.

When to use it

- Operator-driven one-shot backup
- When you want a checklist rather than raw Velero YAML
- Before major changes when Velero schedules are not enough

How to get there

- Route: `/backup-wizard`
- Nav: **Run → Backup Wizard**
- Related: `/backup-dr`, `/disaster-recovery`

Operate from the console (UX)

1. Open `/backup-wizard` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Guided backup workflow for VMs / volumes — complementary to Velero and snapshot managers.
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Guided backup workflow for VMs / volumes — complementary to Velero and snapshot managers.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Velero
- Snapshots
- Disaster Recovery — `/disaster-recovery`

Cluster Autoscale

Purpose

Read-only status of the cluster autoscaler and its node pools: whether it is enabled, how each pool is sized against its min and max, and what scale-up or scale-down actions it is recommending.

When to use it

- Confirm the cluster autoscaler is enabled and which provider is driving it
- See whether a node pool is pinned at its maximum and blocking scheduling
- Review recommended pool size changes and the savings attached to them
- Check how many scale-ups and scale-downs happened in the last 24 hours

How to get there

- Route: `/cluster-autoscaling`
- Nav: **Run -> Cluster Autoscale**
- Related: `/autoscaler`, `/nodes`, `/optimization`

Operate from the console (UX)

1. Open `/cluster-autoscaling` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only status of the cluster autoscaler and its node pools: whether it is enabled, how each pool is sized against its….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only status of the cluster autoscaler and its node pools: whether it is enabled, how each pool .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- AutoScaler
- Nodes
- Node Drain
- Operations

Live Migrations

Purpose

Plan, dry-run, and execute live VM migrations between nodes with pre-flight checks and history.

When to use it

- Node maintenance / drain
- Rebalance load across workers
- Evacuate VMs from a failing node

How to get there

- Route: `/migrations`
- Nav: **Run → Live Migrations**
- Related: `/migration-factory` for batch campaigns (links Transiva/h2kvm where applicable)

Operate from the console (UX)

1. Open `/migrations` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Plan, dry-run, and execute live VM migrations between nodes with pre-flight checks and history.
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Plan, dry-run, and execute live VM migrations between nodes with pre-flight checks and history.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Nodes
- Node Drain — `/node-drain`
- VM Instances

Node Drain

Purpose

A guided five-step wizard for taking a node out of service safely: pick the node, see exactly which VMs will move and which will lose availability, choose a strategy, cordon and drain, then watch it finish.

When to use it

- Patch, reboot, or decommission a worker node
- Evacuate VMs from a node showing hardware or disk problems
- Check the blast radius of maintenance before committing to a window
- Cancel a maintenance window and put a node back in service

How to get there

- Route: `/node-drain` (accepts `?node=<name>`, which is how the **Drain wizard** links on the Nodes page arrive here)
- Nav: **Run -> Node Drain**
- Related: `/nodes`, `/migrations`, `/vms`

Operate from the console (UX)

1. Open `/node-drain` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: A guided five-step wizard for taking a node out of service safely: pick the node, see exactly which VMs will move and wh….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: A guided five-step wizard for taking a node out of service safely: pick the node, see exactly which .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Nodes
- Live Migrations
- VMs
- Pod Disruption Budgets

Operations

Purpose

One console for the recurring day-2 chores: alert rules, outbound webhooks, quotas, GPU inventory, backup and power and snapshot schedules, RBAC review, quick deploy, cluster context, and labels.

When to use it

- Add an alert rule or check what is currently firing
- Wire a webhook so another system hears about Zeus OS events
- See which namespaces are close to their resource quota
- Create or remove a power schedule so dev VMs stop overnight
- Confirm what the current identity is allowed to do before a change window

How to get there

- Route: `/operations` (the active tab is kept in the `?tab=` query parameter, so a tab is linkable)
- Nav: **Run -> Operations**
- Related: `/events?tab=scheduled`, `/snapshots`, `/alerting?tab=prometheus`, `/users`

Operate from the console (UX)

1. Open `/operations` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the editorial intro, then pick a tab (`?tab=`) for alert rules, webhooks, quotas, GPU, schedules, or RBAC.
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: One console for the recurring day-2 chores: alert rules, outbound webhooks, quotas, GPU inventory, b.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Events (Scheduled ops tab)
- Snapshots
- Backup Wizard
- Users
- Alerting (Prometheus tab)

Snapshots

Purpose

Create and manage VM snapshots (on-demand and scheduled) for point-in-time recovery.

When to use it

- Before risky upgrades or config changes
- Enforce periodic snapshot policy
- Prepare for Restore Wizard recovery

How to get there

- Routes: `/snapshots`, `/snapshot-manager`
- Nav: **Run → Snapshots / Snapshot Manager**

Operate from the console (UX)

1. Open `/snapshots` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Create and manage VM snapshots (on-demand and scheduled) for point-in-time recovery.
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Create and manage VM snapshots (on-demand and scheduled) for point-in-time recovery.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Backup Wizard
- Velero
- VM workbench

Velero

Purpose

Velero-backed backup and restore operations for cluster and VM-related resources.

When to use it

- Scheduled cluster/namespace backups
- Restore after accidental deletion
- DR drills with Backup / DR centers

How to get there

- Route: `/velero`
- Nav: **More → Resilience → Velero** (integrate tier)
- Related: `/backup-dr`, Restore Wizard `/restore-wizard`

Operate from the console (UX)

1. Open `/velero` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Velero-backed backup and restore operations for cluster and VM-related resources.
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Velero-backed backup and restore operations for cluster and VM-related resources.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Backup Wizard
- Snapshots
- Disaster Recovery

Windows Licensing

Purpose

Read-only inventory of Windows activation state across your KubeVirt VMs, collected through the guest agent (`slmgr`). Zeus OS never hosts a KMS or redistributes licenses — it reports what your own activation infrastructure says.

When to use it

- Confirm every Windows guest is activated before an audit
- Find VMs sitting in a grace period or about to expire
- Verify newly provisioned Windows VMs picked up the right KMS host
- Spot guests where the agent is offline, so licensing state is unknown

How to get there

- Route: `/windows-licensing`
- Nav: **Run -> Windows Licensing**
- Related: `/vms`, `/compliance`

Operate from the console (UX)

1. Open `/windows-licensing` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only inventory of Windows activation state across your KubeVirt VMs, collected through the guest agent (`slmgr`). Z….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only inventory of Windows activation state across your KubeVirt VMs, collected through the gues.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VMs
- VM Workbench
- Compliance
- Security

Workflows

Purpose

Read-only view of the automation workflows registered with Zeus OS: what is scheduled, when each last ran, how reliable it has been, and the template gallery you can copy from.

When to use it

- Check whether a nightly automation ran and succeeded
- Find a workflow whose success rate has dropped
- See what is scheduled to run next
- Browse the template gallery before authoring a new workflow

How to get there

- Route: `/workflows`
- Nav: **Run -> Workflows**
- Related: `/events?tab=scheduled`, `/operations`, `/cicd`

Operate from the console (UX)

1. Open `/workflows` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only view of the automation workflows registered with Zeus OS: what is scheduled, when each last ran, how reliable ….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only view of the automation workflows registered with Zeus OS: what is scheduled, when each las.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Events (Scheduled ops tab)
- Operations
- Change Approval

Admission control

Purpose

Read-only inventory of what intercepts writes to your cluster: validating and mutating admission webhooks, Kyverno policy rules, webhook statistics, and recent admission-related events.

When to use it

- Find out which webhook is rejecting a create or update
- Check a webhook's failure policy before taking its backing service down
- Confirm Kyverno policies are installed and ready
- Review recent admission events during an incident

How to get there

- Route: `/admission-control` (the active tab is kept in the `?tab=` query parameter)
- Nav: **Security -> Admission Control**
- Related: `/opa`, `/security`, `/compliance`

Operate from the console (UX)

1. Open `/admission-control` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only inventory of what intercepts writes to your cluster: validating and mutating admission webhooks, Kyverno polic….
3. Scan health cards and shortcuts into VMs, incidents, capacity, and consoles.
4. Open **Getting started checklist** (Help → Getting Started) if you are new — progress is saved to your account.
5. Use workspace switcher: Dashboard · VMs · Kubernetes · AI · Storage · Monitoring.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only inventory of what intercepts writes to your cluster: validating and mutating admission web.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- OPA Gatekeeper
- Security
- Image Scanning
- Compliance

Affinity Rules

Purpose

Surfaces where your affinity and anti-affinity placement intent is not being honoured — which rule is violated, which VMs are affected, and on which node.

When to use it

- Verify an HA pair really is spread across separate nodes
- Investigate why a workload landed on an unexpected node
- Check placement compliance before or after a node drain
- Track the cluster's overall affinity compliance percentage

How to get there

- Route: `/affinity-rules`
- Nav: **Security -> Affinity Rules**
- Related: `/nodes`, `/node-drain`, `/taints`

Operate from the console (UX)

1. Open `/affinity-rules` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Surfaces where your affinity and anti-affinity placement intent is not being honoured — which rule is violated, which VM….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Surfaces where your affinity and anti-affinity placement intent is not being honoured — which rule i.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Nodes
- Node Drain
- Pod Disruption Budgets
- Live Migrations
- Taints & Tolerations — `/taints`

Certificates

Purpose

Tracks the TLS certificates in your cluster and how long each one has left, so an expiry never surprises you. Renewal can be triggered from the table.

When to use it

- Weekly check for certificates expiring inside 30 days
- Find an already-expired certificate behind a TLS failure
- Force an early renewal ahead of a maintenance window
- Confirm a newly issued certificate reached Ready

How to get there

- Route: `/certificates`
- Nav: **Security -> Certificates**
- Related: `/security`, `/compliance`, `/settings`

Operate from the console (UX)

1. Open `/certificates` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Tracks the TLS certificates in your cluster and how long each one has left, so an expiry never surprises you. Renewal ca….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Tracks the TLS certificates in your cluster and how long each one has left, so an expiry never surpr.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Security
- Compliance
- External Secrets
- Settings

Change Approval

Purpose

A review queue for VM changes: destructive requests wait for a human approver, non-destructive ones are auto-approved, and every decision is recorded with a comment and a timestamp.

When to use it

- Require sign-off before a VM is deleted or migrated
- Work through the pending queue as the on-call approver
- Record why a change was allowed or refused
- Show an auditor the decision history for a change window

How to get there

- Route: `/change-approval`
- Nav: **Security -> Change Approval**
- Related: `/events?tab=audit`, `/security`, `/vms`

Operate from the console (UX)

1. Open `/change-approval` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: A review queue for VM changes: destructive requests wait for a human approver, non-destructive ones are auto-approved, a….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: A review queue for VM changes: destructive requests wait for a human approver, non-destructive ones .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Security
- Events (Audit log tab)
- Users
- VMs
- Live Migrations

Compliance

Purpose

Scores your VMs against Zeus OS policy checks and gives you a cluster grade, per-category pass rates, and a per-VM breakdown you can export as evidence.

When to use it

- Produce a point-in-time compliance snapshot before an audit
- Find which VMs are dragging the cluster score down and why
- Track a category (for example hardening or backup coverage) over time
- Hand an auditor a machine-readable report

How to get there

- Route: `/compliance`
- Nav: **Security -> Compliance**
- Related: `/compliance?tab=frameworks`, `/auth-audit`, `/backup-dr`, `/reports`

Operate from the console (UX)

1. Open `/compliance` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Scores your VMs against Zeus OS policy checks and gives you a cluster grade, per-category pass rates, and a per-VM break….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Scores your VMs against Zeus OS policy checks and gives you a cluster grade, per-category pass rates.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Security
- Events (Audit log tab)
- Image Scanning
- Snapshots
- Compliance Frameworks — `/compliance?tab=frameworks`

External Secrets

Purpose

Monitor the `ExternalSecret` and `SecretStore` resources that pull credentials from Vault, cloud secret managers, and other providers into Kubernetes — with sync, validate, and delete actions.

When to use it

- Find an ExternalSecret stuck in a failed sync
- Force a refresh after rotating a secret in the upstream provider
- Validate an ExternalSecret's configuration before debugging further
- Confirm a SecretStore reached the Ready condition

How to get there

- Route: `/external-secrets`
- Nav: **Security -> External Secrets**
- Related: `/certificates`, `/security`, `/settings`

Operate from the console (UX)

1. Open `/external-secrets` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Monitor the `ExternalSecret` and `SecretStore` resources that pull credentials from Vault, cloud secret managers, and ot....
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Monitor the `ExternalSecret` and `SecretStore` resources that pull credentials from Vault, cloud sec.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Certificates
- Security
- Users
- Settings

Image Scanning

Purpose

Vulnerability posture for your container and VM images: critical, high, medium, and low counts per image, when each was last scanned, and the scan policies that decide pass or fail.

When to use it

- Check whether any image in use carries a critical CVE
- Find images that have not been rescanned recently
- See which scan policy blocks and which only warns
- Gather image risk evidence for a security review

How to get there

- Route: `/image-scanning`
- Nav: **Security -> Image Scanning**
- Related: `/security`, `/compliance`, `/admission-control`

Operate from the console (UX)

1. Open `/image-scanning` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Vulnerability posture for your container and VM images: critical, high, medium, and low counts per image, when each was ….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Vulnerability posture for your container and VM images: critical, high, medium, and low counts per i.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Security
- Admission Control
- Compliance
- OPA Gatekeeper

OPA Gatekeeper

Purpose

Read-only inventory of your OPA Gatekeeper constraints and constraint templates, with the current violation count and the offending resources behind each one.

When to use it

- See which Gatekeeper constraints are actively denying and which are in dry-run
- Find the exact pods breaching a policy before you enforce it
- Confirm a new ConstraintTemplate rolled out and has constraints bound to it
- Report total policy violations during a security review

How to get there

- Route: `/opa`
- Nav: **Security -> OPA Gatekeeper**
- Related: `/admission-control`, `/security`, `/compliance`

Operate from the console (UX)

1. Open `/opa` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only inventory of your OPA Gatekeeper constraints and constraint templates, with the current violation count and th….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only inventory of your OPA Gatekeeper constraints and constraint templates, with the current vi.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Admission Control
- Security
- Compliance
- Network hub (Policy builder tab)

PDB

Purpose

Shows every PodDisruptionBudget in the cluster and whether it currently permits any voluntary disruption — the fastest way to know if a drain will proceed or stall.

When to use it

- Pre-flight a node drain or rolling upgrade
- Diagnose an eviction that is hanging with no progress
- Confirm a critical workload actually has a PDB protecting it
- Find budgets sitting below their desired healthy count

How to get there

- Route: `/pdb`
- Nav: **Security -> PDB**
- Related: `/node-drain`, `/nodes`, `/affinity-rules`

Operate from the console (UX)

1. Open `/pdb` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Shows every PodDisruptionBudget in the cluster and whether it currently permits any voluntary disruption — the fastest w….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Shows every PodDisruptionBudget in the cluster and whether it currently permits any voluntary disrup.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Node Drain
- Nodes
- Affinity Rules
- Live Migrations

Security

Purpose

Security posture overview — findings, hardening status, and entry into compliance / scanning / policies.

When to use it

- Periodic security review
- After onboarding a new namespace or tenant
- Before audits (pair with Compliance)

How to get there

- Route: `/security` (also `/security-overview` / Security Operations depending on edition)
- Nav: **Security → Security**
- Related: `/compliance`, `/image-scanning`, `/admission-control`, `/opa`

Operate from the console (UX)

1. Open `/security` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Security posture overview — findings, hardening status, and entry into compliance / scanning / policies.
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Security posture overview — findings, hardening status, and entry into compliance / scanning / polic.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- PacketWolf
- Events → Audit log tab — `/events?tab=audit`
- Compliance — `/compliance`
- Users — `/users`

Tenancy

Purpose

Organise namespaces into tenants, see each tenant's namespace, CPU, and memory footprint, manage who belongs to a tenant, and track quota consumption per namespace.

When to use it

- Onboard a new team as a tenant with its own tier and contact
- Add or remove a member's access to a tenant's namespaces
- Check which tenant is closest to exhausting its quota
- Report per-tenant CPU and memory usage back to a business unit

How to get there

- Route: `/tenancy`
- Nav: **Security -> Tenancy**
- Related: `/users`, `/operations`, `/costs`

Operate from the console (UX)

1. Open `/tenancy` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Organise namespaces into tenants, see each tenant's namespace, CPU, and memory footprint, manage who belongs to a tenant….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Organise namespaces into tenants, see each tenant's namespace, CPU, and memory footprint, manage who.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Users
- Security
- Operations
- Events (Audit log tab)

Users

Purpose

Shows who you are signed in as and what that identity may do, manages built-in local accounts, and issues revocable API tokens for automation.

When to use it

- Onboard or offboard a local operator account
- Check whether the current session can delete VMs or manage network policies
- Mint an API token for CI, then revoke it when the pipeline is retired
- Copy the session bearer token for a quick API call

How to get there

- Route: `/users`
- Nav: **Security -> Users**
- Related: `/security`, `/events?tab=audit`, `/tenancy`, `/settings`

Operate from the console (UX)

1. Open `/users` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Shows who you are signed in as and what that identity may do, manages built-in local accounts, and issues revocable API ….
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Shows who you are signed in as and what that identity may do, manages built-in local accounts, and i.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Security
- Events (Audit log tab)
- Tenancy
- Change Approval
- Settings

Budget Alerts

Purpose

Monthly spend budgets for the cluster, a tenant or a namespace. Budgets are stored and evaluated on the server from recorded cost history, and alerts go out through your notification channels once per threshold per month. Spend is an estimate from your configured unit prices, not an invoice.

When to use it

- Set monthly ceilings for tenant or app namespaces
- Get notified as spend crosses 50 / 80 / 100 percent (or your own thresholds)
- See which budgets are on track, at a warning, over budget, or not measurable yet

How to get there

- Route: `/budget-alerts`
- Nav: **Cost → Budget Alerts**
- Related: `/cost-allocation` , `/costs` , `/cost-intelligence` , `/notifications`

Operate from the console (UX)

1. Open `/budget-alerts` .
2. **Add budget**: name, scope (namespace, tenant, or whole cluster for platform admins), monthly limit, thresholds and the notification channels to alert. Tenant users can only budget their own tenant and namespaces.
3. Each row shows month-to-date estimated spend, usage against the limit, a status chip, and which thresholds have already alerted this month. **Unknown** means no cost data has been recorded for that scope this month; it is never shown as zero and never alerts.
4. Budgets saved in this browser by an older version can be imported with **Import N budgets saved in this browser**.
5. **Empty / fail:** No budgets yet shows the empty state; a server error shows a retry panel. A banner appears when cost history recording or the alert engine is switched off.
6. Spend needs recorded history: the sampler records hourly, so a new install shows Unknown until the first sample. If history starts mid-month, month-to-date is a lower bound and the row says so.

Price assumptions are shown at the top of the page; platform admins can edit them there.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs.

Related pages

- Cost Allocation
- Costs
- Cost Intelligence
- Alerting (Channels tab)

Details: FINOPS_PRICING.md.

Chargeback

Purpose

Nav alias for namespace cost allocation / showback. There is no separate Chargeback UI — the link opens Cost Allocation.

When to use it

- Reach chargeback-style reporting from the Cost menu
- Share a familiar “chargeback” bookmark that lands on live allocation data
- Jump from older docs or bookmarks that still use `/chargeback`

How to get there

- Route: `/chargeback` (redirects to `/cost-allocation`)
- Nav: **Cost → Chargeback**
- Related: `/cost-allocation`, `/costs`, `/budget-alerts`

Operate from the console (UX)

1. Open `/chargeback` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Nav alias for namespace cost allocation / showback. There is no separate Chargeback UI — the link opens Cost Allocation.
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Nav alias for namespace cost allocation / showback. There is no separate Chargeback UI — the link op.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Cost Allocation
- Costs
- Budget Alerts
- Cost Intelligence

Cost Allocation

Purpose

Namespace-level chargeback view: estimated monthly cost rolled up by namespace, with CPU, memory, and storage share plus per-VM detail.

When to use it

- Prepare showback or chargeback for app owners
- Compare namespace share of total spend
- Drill into which VMs drive a namespace's bill
- Confirm unit rates used for the estimate

How to get there

- Route: `/cost-allocation`
- Nav: **Cost → Cost Allocation**
- Related: `/chargeback` (redirects here), `/costs`, `/budget-alerts`

Operate from the console (UX)

1. Open `/cost-allocation` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Namespace-level chargeback view: estimated monthly cost rolled up by namespace, with CPU, memory, and storage share plus….
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Namespace-level chargeback view: estimated monthly cost rolled up by namespace, with CPU, memory, an.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Costs
- Cost Intelligence
- Chargeback — alias to this page
- Budget Alerts

Cost Estimator

Purpose

What-if cost calculator for planned VM fleets: adjust count, shape, and unit prices to estimate monthly and annual spend (labs-tier page).

When to use it

- Size a new project before provisioning
- Compare CPU / memory / storage cost drivers
- Sanity-check a quote against cluster unit rates
- Copy an estimate for planning docs

How to get there

- Route: `/cost-estimator`
- Nav: **Cost → Cost Estimator** (labs)
- Related: `/costs`, `/cost-allocation`, `/instance-types`

Operate from the console (UX)

1. Open `/cost-estimator` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: What-if cost calculator for planned VM fleets: adjust count, shape, and unit prices to estimate monthly and annual spend….
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: What-if cost calculator for planned VM fleets: adjust count, shape, and unit prices to estimate mont.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Costs
- Cost Allocation
- Instance types
- Cost Intelligence

Cost Intelligence

Purpose

Per-VM and per-namespace spend visibility, trends, and FinOps entry points.

When to use it

- Monthly cost review
- Chargeback conversations with app owners
- Find expensive outliers before rightsizing

How to get there

- Route: `/cost-intelligence`
- Nav: **Cost → Cost Intelligence**
- Related: `/costs`, `/cost-allocation`, `/chargeback`, `/budget-alerts`

Operate from the console (UX)

1. Open `/cost-intelligence` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Per-VM and per-namespace spend visibility, trends, and FinOps entry points.
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Per-VM and per-namespace spend visibility, trends, and FinOps entry points.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Rightsizing
- Cost Allocation — `/cost-allocation`
- Capacity — `/capacity`

Costs

Purpose

Cluster cost dashboard: monthly spend trends, namespace and resource-type breakdowns, top expensive VMs, and optimization opportunities.

When to use it

- Monthly spend review for the whole cluster
- Find which namespaces or VMs drive cost
- Scan optimization opportunities before deeper FinOps work
- Compare projected spend over the last 30 days

How to get there

- Route: `/costs`
- Nav: **Cost → Costs**
- Related: `/cost-intelligence`, `/cost-allocation`, `/budget-alerts`

Operate from the console (UX)

1. Open `/costs` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Cluster cost dashboard: monthly spend trends, namespace and resource-type breakdowns, top expensive VMs, and optimizatio….
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Cluster cost dashboard: monthly spend trends, namespace and resource-type breakdowns, top expensive .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Cost Intelligence
- Cost Allocation
- Rightsizing
- Budget Alerts

Rightsizing

Purpose

Recommendations for idle, oversized, or orphaned resources — turn Cost Intelligence into concrete shape changes.

When to use it

- After reviewing expensive VMs
- Periodic waste sweeps
- Before purchasing more cluster capacity

How to get there

- Route: `/rightsizing`
- Nav: **More → Insights → Rightsizing** (also linked from Cost views)

Operate from the console (UX)

1. Open `/rightsizing` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Recommendations for idle, oversized, or orphaned resources — turn Cost Intelligence into concrete shape changes.
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Recommendations for idle, oversized, or orphaned resources — turn Cost Intelligence into concrete sh.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Cost Intelligence
- Instance types
- Optimization — `/optimization`

SLA Dashboard

Purpose

Live VM up/down posture plus configurable SLO targets (uptime % and latency). Historical uptime and error budget are not synthesized without availability history.

When to use it

- Check how many VMs are currently up vs down
- Define or edit SLO targets for production services
- Align operators and FinOps on declared SLO numbers
- Spot stopped or failed VMs during an incident

How to get there

- Route: `/sla`
- Nav: **Cost → SLA Dashboard**
- Related: `/vms`, `/system-health`, `/incidents`

Operate from the console (UX)

1. Open `/sla` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Live VM up/down posture plus configurable SLO targets (uptime % and latency). Historical uptime and error budget are not….
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Live VM up/down posture plus configurable SLO targets (uptime % and latency). Historical uptime and .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- System Health
- Costs
- Incidents — `/incidents`

Spot Savings

Purpose

Nav alias for the Optimization Center. There is no separate Spot Savings page — the link opens resource optimization recommendations and savings tracking.

When to use it

- Follow Cost → Spot Savings when hunting for spend reductions
- Open savings recommendations from an older bookmark at `/spot-savings`
- Continue into apply / rightsizing-style actions on Optimization

How to get there

- Route: `/spot-savings` (redirects to `/optimization`)
- Nav: **Cost → Spot Savings**
- Related: `/optimization`, `/costs`, `/rightsizing`, `/cost-intelligence`

Operate from the console (UX)

1. Open `/spot-savings` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Nav alias for the Optimization Center. There is no separate Spot Savings page — the link opens resource optimization rec….
3. Select the time range and scope (cluster / namespace / tenant).
4. Drill from rollup → workload; export or create a budget/alert if the page offers it.
5. Cross-check rightsizing recommendations before resizing production VMs.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Nav alias for the Optimization Center. There is no separate Spot Savings page — the link opens resou.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Optimization — `/optimization`
- Costs
- Rightsizing
- Cost Intelligence

AI Center

Purpose

AI-assisted SRE, migration, and security advisors grounded in cluster evidence (Forge / built-in LLM when configured).

When to use it

- Ask for remediation suggestions with citations
- Draft manifests or runbooks with guardrails
- Pair with Incidents / Auto-Remediation for day-2 loops

How to get there

- Route: `/ai-center`
- Related: `/forge`, `/nlp-command`, Settings → AI providers

Operate from the console (UX)

1. Open `/ai-center` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the editorial hero and **Get the highlights**, then pick an advisor (SRE, migration, security, cost, capacity, network).
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: AI-assisted SRE, migration, and security advisors grounded in cluster evidence (Forge / built-in LLM.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Incidents
- Auto-Remediation — `/auto-remediation`
- Settings

Anomaly Detector

Purpose

Surfaces VM health, CPU, and memory outliers with risk levels and suggested next actions. The view auto-refreshes about every 10 seconds from live inventory and health scores.

When to use it

- Triage noisy or degrading VMs before an incident page
- Spot sustained high CPU or memory before capacity work
- Confirm the cluster looks clear after a remediation
- Feed Auto-Remediation or Incidents with concrete targets

How to get there

- Route: `/anomaly-detector`
- Nav: **More → Insights → Anomaly Detector**
- Related: `/auto-remediation`, `/ai-center`, `/incidents`

Operate from the console (UX)

1. Open `/anomaly-detector` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Surfaces VM health, CPU, and memory outliers with risk levels and suggested next actions. The view auto-refreshes about ….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Surfaces VM health, CPU, and memory outliers with risk levels and suggested next actions. The view a.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Auto-Remediation
- AI Center
- Incidents
- VMs

API Docs

Purpose

Browsable REST reference for Zeus OS: live OpenAPI when available, plus categorized method/path descriptions for VMs, nodes, pods, and more.

When to use it

- Discover endpoints before scripting or automation
- Confirm request/response shapes for an integration
- Search the catalog by path or description
- Jump from docs into hands-on calls in the playground

How to get there

- Route: `/api-docs`
- Nav: **Top bar → API Docs** (also Support / quick links)
- Related: `/api-playground`, `/settings`, `/terminal`

Operate from the console (UX)

1. Open `/api-docs` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Browsable REST reference for Zeus OS: live OpenAPI when available, plus categorized method/path descriptions for VMs, no….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Browsable REST reference for Zeus OS: live OpenAPI when available, plus categorized method/path desc.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- API Playground
- Settings
- Terminal

API Playground

Purpose

In-browser HTTP client for Zeus OS REST endpoints: pick a method and path, send authenticated requests, and inspect status, headers, and body.

When to use it

- Try an API before wiring an integration
- Reproduce a failing call with the same bearer token as the UI
- Replay a recent request from history
- Explore preset inventory and health paths quickly

How to get there

- Route: `/api-playground`
- Nav: **More → Tools & settings → API Playground**
- Related: `/api-docs`, `/debug`

Operate from the console (UX)

1. Open `/api-playground` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: In-browser HTTP client for Zeus OS REST endpoints: pick a method and path, send authenticated requests, and inspect stat….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: In-browser HTTP client for Zeus OS REST endpoints: pick a method and path, send authenticated reques.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- API Docs
- Debug
- Settings

ArgoCD

Purpose

Read-only dashboard of Argo CD Applications and Projects — sync and health status for GitOps workloads in the cluster.

When to use it

- Verify Application sync after a Git merge
- Find OutOfSync or degraded apps quickly
- Confirm Argo CD is installed before relying on GitOps stats elsewhere
- Cross-check with the GitOps VM sync view

How to get there

- Route: `/argocd`
- Nav: **More → Insights → ArgoCD** (integrate tier)
- Related: `/gitops`

Operate from the console (UX)

1. Open `/argocd` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Read-only dashboard of Argo CD Applications and Projects — sync and health status for GitOps workloads in the cluster.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Read-only dashboard of Argo CD Applications and Projects — sync and health status for GitOps workloa.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- GitOps
- VMs

Auto-Remediation

Purpose

Day-2 playbooks and policy controls that respond to common VM failures — crash loops, node pressure migrations, and advisory rightsizing or PVC expansion — with optional closed-loop autonomy.

When to use it

- Arm restart or migrate responses for recurring VM faults
- Review the engine operations queue before or after autonomy runs
- Keep high-CPU / PVC expansion as advisory-only guidance
- Disable automation during change freezes

How to get there

- Route: `/auto-remediation`
- Nav: **More → Insights → Auto-Remediation**
- Related: `/anomaly-detector`, `/ai-center`, `/incidents`

Operate from the console (UX)

1. Open `/auto-remediation` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Day-2 playbooks and policy controls that respond to common VM failures — crash loops, node pressure migrations, and advi….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Day-2 playbooks and policy controls that respond to common VM failures — crash loops, node pressure .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Anomaly Detector
- AI Center
- Incidents
- Migrations
- VMs

Catalog

Purpose

Infrastructure app catalog (Helm-oriented installs) for common day-2 stack pieces: browse categories, search apps, and trigger install.

When to use it

- Install curated apps such as backup, monitoring, or registry stacks
- Browse by category or search publisher/name
- Check deploy counts and availability before installing
- Re-open the catalog after a failed install to retry

How to get there

- Route: `/catalog`
- Nav: **More → Tools & settings → Catalog**
- Related: `/helm`, `/velero`, `/settings`

Operate from the console (UX)

1. Open `/catalog` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Infrastructure app catalog (Helm-oriented installs) for common day-2 stack pieces: browse categories, search apps, and t….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Infrastructure app catalog (Helm-oriented installs) for common day-2 stack pieces: browse categories.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Velero
- Settings
- Topology
- Helm Releases — `/helm`

Chaos Engineering

Purpose

Controlled fault experiments against VMs — primarily kill virt-launcher pods to validate recovery; other stress types are listed when a fault-injection backend is available.

When to use it

- Prove VM restart/recovery after pod death
- Game-day drills before production cutovers
- Validate Auto-Remediation or alerts fire correctly
- Document experiment results for change records

How to get there

- Route: `/chaos-engineering`
- Nav: **More → Resilience → Chaos Engineering**
- Related: `/auto-remediation`, `/perf-testing`, `/vms`

Operate from the console (UX)

1. Open `/chaos-engineering` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Controlled fault experiments against VMs — primarily kill virt-launcher pods to validate recovery; other stress types ar….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Controlled fault experiments against VMs — primarily kill virt-launcher pods to validate recovery; o.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Auto-Remediation
- Performance Testing
- VMs
- Incidents

CI/CD

Purpose

Pipeline inventory and run history with on-demand trigger controls for cluster-integrated CI/CD definitions.

When to use it

- See which pipelines exist and their last-run status
- Trigger a pipeline manually after a config or image change
- Review recent runs, duration, commit SHA, and trigger type
- Correlate delivery work with Helm or progressive rollouts

How to get there

- Route: `/cicd`
- Nav: **More → Delivery → CI/CD** (integrate tier)
- Related: `/progressive-delivery`, `/deployment-strategies`, `/gitops`

Operate from the console (UX)

1. Open `/cicd` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Pipeline inventory and run history with on-demand trigger controls for cluster-integrated CI/CD definitions.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Pipeline inventory and run history with on-demand trigger controls for cluster-integrated CI/CD defi.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Progressive Delivery
- Deployment Strategies
- GitOps Sync — `/gitops`

Cilium CNI

Purpose

Cilium status, endpoints, policies, Hubble packet flows, VM internet-egress controls, and a VM policy builder — when Cilium is installed in the cluster.

When to use it

- Confirm Cilium and Hubble availability
- List endpoints and CiliumNetworkPolicies
- Apply or remove cluster-wide virt-launcher internet egress policy
- Build per-VM Cilium policies; correlate with PacketWolf containment

How to get there

- Route: `/cilium`
- Nav: **More → Mesh & traffic → Cilium CNI**
- Related: `/network-flow`, `/packetwolf`

Operate from the console (UX)

1. Open `/cilium` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Cilium status, endpoints, policies, Hubble packet flows, VM internet-egress controls, and a VM policy builder — when Cil….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Cilium status, endpoints, policies, Hubble packet flows, VM internet-egress controls, and a VM polic.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Network Flow
- PacketWolf VM Guard
- Security

Cluster Upgrade

Purpose

Version awareness and an upgrade checklist for Kubernetes and KubeVirt — plus VLCM rollout controls — so operators plan upgrades without skipping critical backups and drains.

When to use it

- Before upgrading Kubernetes or KubeVirt
- Track checklist progress across a maintenance window
- Review VLCM / operator rollout status alongside the plan
- Reset checklist progress after a completed upgrade

How to get there

- Route: `/cluster-upgrade`
- Nav: **More → Resilience → Cluster Upgrade**
- Related: `/nodes`, `/velero`, `/disaster-recovery`

Operate from the console (UX)

1. Open `/cluster-upgrade` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Version awareness and an upgrade checklist for Kubernetes and KubeVirt — plus VLCM rollout controls — so operators plan ….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Version awareness and an upgrade checklist for Kubernetes and KubeVirt — plus VLCM rollout controls .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Nodes
- Velero
- Disaster Recovery
- Migrations

Database Ops

Purpose

Day-2 view of database instances and their backups — status, storage, endpoints, and connection details for operator copy-out.

When to use it

- Inventory databases by type, version, and namespace
- Check running vs unhealthy instances at a glance
- Copy endpoint, port, or username for troubleshooting
- Review recent database backups and sizes

How to get there

- Route: `/database-ops`
- Nav: **More → Delivery → Database Ops**
- Related: `/backup-dr`, `/velero`, `/applications`

Operate from the console (UX)

1. Open `/database-ops` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Day-2 view of database instances and their backups — status, storage, endpoints, and connection details for operator cop….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Day-2 view of database instances and their backups — status, storage, endpoints, and connection deta.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Backup & DR
- Velero
- Application Center

Debug

Purpose

Host-level diagnostics for the Zeus OS node: live system stats, network interfaces, disk partitions, services, and a downloadable support bundle.

When to use it

- Investigate CPU, memory, or disk pressure on the control host
- Confirm interface and partition layout during an outage
- Capture a support bundle for vendor or platform escalation
- Watch host metrics with auto-refresh while reproducing an issue

How to get there

- Route: `/debug`
- Nav: **More → Tools & settings → Debug**
- Related: `/kernel`, `/system-health`, `/host`

Operate from the console (UX)

1. Open `/debug` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Host-level diagnostics for the Zeus OS node: live system stats, network interfaces, disk partitions, services, and a dow….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Host-level diagnostics for the Zeus OS node: live system stats, network interfaces, disk partitions,.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Kernel Info
- System Health
- API Playground
- Host Info — `/host`

Dependencies

Purpose

Live graph of resource relationships — nodes, VMs, PVCs, Services, and labeled edges — so you can see what depends on what before a change.

When to use it

- Estimate blast radius before drain, delete, or migrate
- Explain storage and service coupling to a new operator
- Correlate an incident with upstream/downstream objects
- Complement the Topology map with a dependency-focused layout

How to get there

- Route: `/dependencies`
- Nav: **More → Mesh & traffic → Dependencies**
- Related: `/topology`, `/network-flow`, `/vms`

Operate from the console (UX)

1. Open `/dependencies` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Live graph of resource relationships — nodes, VMs, PVCs, Services, and labeled edges — so you can see what depends on wh….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Live graph of resource relationships — nodes, VMs, PVCs, Services, and labeled edges — so you can se.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Topology
- Network Flow
- VMs
- Incidents

Deployment Strategies

Purpose

Define and run progressive delivery strategies (Rolling Update, Canary, Blue/Green, Recreate) against Kubernetes workloads, with execute and rollback controls.

When to use it

- Create a reusable strategy with surge, canary weight, or analysis settings
- Execute a strategy against a target workload in a namespace
- Pause-aware deployments: track running, paused, succeeded, or failed status
- Roll back or delete a strategy that is no longer needed

How to get there

- Route: `/deployment-strategies`
- Nav: **More → Delivery → Deployment Strategies**
- Related: `/progressive-delivery`, `/cicd`, `/helm`

Operate from the console (UX)

1. Open `/deployment-strategies` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Define and run progressive delivery strategies (Rolling Update, Canary, Blue/Green, Recreate) against Kubernetes workloa….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Define and run progressive delivery strategies (Rolling Update, Canary, Blue/Green, Recreate) agains.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Progressive Delivery
- CI/CD
- Helm Releases

Disaster Recovery

Purpose

Disaster Recovery Center — visual DR plans, RPO/RTO targets, failover test scheduling, and step runbooks for day-2 resilience.

When to use it

- Maintain DR plans and objective targets
- Schedule or record failover tests
- Walk plan steps during a drill or real event
- Coordinate with Velero backups before declaring readiness

How to get there

- Route: `/disaster-recovery`
- Nav: **More → Resilience → Disaster Recovery** (integrate tier)
- Related: `/velero`, `/multi-cluster`, `/snapshots`

Operate from the console (UX)

1. Open `/disaster-recovery` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Disaster Recovery Center — visual DR plans, RPO/RTO targets, failover test scheduling, and step runbooks for day-2 resil….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Disaster Recovery Center — visual DR plans, RPO/RTO targets, failover test scheduling, and step runb.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Velero
- Multi-Cluster
- Snapshots
- Incidents

DNS

Purpose

Derived DNS / FQDN helpers for pods and VMs: search inventory, copy cluster-style names, and map IPs to names operators can use.

When to use it

- Look up a pod or VM DNS name during connectivity troubleshooting
- Copy an FQDN or IP for curl, dig, or firewall rules
- Confirm guest/pod IP coverage after a deploy
- Filter a large inventory by name or namespace

How to get there

- Route: `/dns`
- Nav: **More → Tools & settings → DNS**
- Related: `/vms`, `/pods`, `/network-flow`

Operate from the console (UX)

1. Open `/dns` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Derived DNS / FQDN helpers for pods and VMs: search inventory, copy cluster-style names, and map IPs to names operators ….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Derived DNS / FQDN helpers for pods and VMs: search inventory, copy cluster-style names, and map IPs.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- PacketWolf VM Guard
- Pods — `/pods`
- Network Flow — `/network-flow`

GitOps

Purpose

Compare desired versus actual VM power state, show Flux/Argo cluster stats, and sync power-status drift back toward the intended running/stopped state.

When to use it

- After GitOps or pipeline updates that should change VM power
- Audit drift between declared and live VM status
- Confirm Flux GitRepositories / Kustomizations are present
- Bulk-correct power-status drifts when safe

How to get there

- Route: `/gitops`
- Nav: **More → Insights → GitOps** (integrate tier)
- Related: `/argocd` , `/vms`

Operate from the console (UX)

1. Open `/gitops` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Compare desired versus actual VM power state, show Flux/Argo cluster stats, and sync power-status drift back toward the ….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Compare desired versus actual VM power state, show Flux/Argo cluster stats, and sync power-status dr.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- ArgoCD
- VMs
- VMIs

Helm Releases

Purpose

List, install, upgrade history, rollback, and uninstall Helm releases, and manage chart repositories on the cluster.

When to use it

- Inventory releases by namespace and status
- Install a chart from a configured repository
- Inspect revision history and roll back a bad upgrade
- Add or remove Helm repositories used by the control plane

How to get there

- Route: `/helm`
- Nav: **More → Delivery → Helm Releases**
- Related: `/operators`, `/kustomize`, `/cicd`

Operate from the console (UX)

1. Open `/helm` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: List, install, upgrade history, rollback, and uninstall Helm releases, and manage chart repositories on the cluster.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: List, install, upgrade history, rollback, and uninstall Helm releases, and manage chart repositories.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Operators
- Kustomize
- Deployment Strategies

IaC

Purpose

Infrastructure-as-code resource inventory with drift detection and a sync action for IaC-managed objects Zeus OS can see.

When to use it

- List IaC-managed resources by provider, type, and sync status
- Investigate drift (expected vs actual field values)
- Trigger a sync after fixing source of truth in Git or Terraform
- Confirm how many resources are synced versus drifted

How to get there

- Route: `/iac`
- Nav: **More → Delivery → IaC** (integrate tier)
- Related: `/kustomize`, `/gitops`, `/developer-center`

Operate from the console (UX)

1. Open `/iac` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Infrastructure-as-code resource inventory with drift detection and a sync action for IaC-managed objects Zeus OS can see.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Infrastructure-as-code resource inventory with drift detection and a sync action for IaC-managed obj.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Kustomize
- Developer Center
- GitOps Sync — `/gitops`

Kernel Info

Purpose

Host hardware and OS inventory: hostname, kernel, CPU, BIOS, PCI devices, and memory modules for the Zeus OS node.

When to use it

- Confirm kernel and OS version before a host upgrade
- Inventory PCI devices for passthrough or driver issues
- Check DIMM locator, size, type, and speed
- Capture architecture and CPU model for capacity planning

How to get there

- Route: `/kernel`
- Nav: **More → Tools & settings → Kernel Info**
- Related: `/debug`, `/host`, `/system-health`

Operate from the console (UX)

1. Open `/kernel` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Host hardware and OS inventory: hostname, kernel, CPU, BIOS, PCI devices, and memory modules for the Zeus OS node.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Host hardware and OS inventory: hostname, kernel, CPU, BIOS, PCI devices, and memory modules for the.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Debug
- System Health
- Host Info — `/host`

Kustomize

Purpose

Browse Kustomize bases and overlays, then preview the rendered diff before you apply changes outside the dashboard.

When to use it

- Inventory overlays and which base each one builds on
- Count patches and see last-applied status per overlay
- Preview a diff for an overlay before a GitOps sync
- Orient new operators on how environments are layered

How to get there

- Route: `/kustomize`
- Nav: **More → Delivery → Kustomize** (integrate tier)
- Related: `/iac`, `/gitops`, `/helm`

Operate from the console (UX)

1. Open `/kustomize` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Browse Kustomize bases and overlays, then preview the rendered diff before you apply changes outside the dashboard.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Browse Kustomize bases and overlays, then preview the rendered diff before you apply changes outside.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- IaC
- Helm Releases
- GitOps Sync — `/gitops`

Multi-Cluster

Purpose

Multi-Cluster Command Center — list federation contexts, view the current cluster overview, and compare up to two clusters side by side.

When to use it

- Confirm which context Zeus OS is talking to
- Compare VM/node counts and health across contexts
- Inventory remote cluster endpoints registered with the API
- Plan DR or migration work across sites

How to get there

- Route: `/multi-cluster`
- Nav: **More → Resilience → Multi-Cluster**
- Related: `/disaster-recovery`, `/network-flow` (federation tabs)

Operate from the console (UX)

1. Open `/multi-cluster` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Multi-Cluster Command Center — list federation contexts, view the current cluster overview, and compare up to two cluste….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Multi-Cluster Command Center — list federation contexts, view the current cluster overview, and comp.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Disaster Recovery
- Network Flow
- Velero
- Nodes

Network Flow

Purpose

Zeus Network Center — service map, flows, DNS health, policies, and PacketWolf-backed containment actions, with Cilium/Hubble and cluster metrics as fallbacks when PacketWolf is offline.

When to use it

- Investigate denied or unexpected flows
- Check DNS health for VM/workloads
- Quarantine or mark trusted traffic during an incident
- Review policies, threats, and capture tabs for day-2 network ops

How to get there

- Route: `/network-flow`
- Nav: **More → Mesh & traffic → Network Flow**
- Related: `/packetwolf`, `/cilium`, `/dependencies`

Operate from the console (UX)

1. Open `/network-flow` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Zeus Network Center — service map, flows, DNS health, policies, and PacketWolf-backed containment actions, with Cilium/H….
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Zeus Network Center — service map, flows, DNS health, policies, and PacketWolf-backed containment ac.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- PacketWolf VM Guard
- Cilium CNI
- Dependencies
- Security
- Incidents

NLP Command

Purpose

Natural-language bar for VM power and lifecycle intents — parse plain English into a confirmed action before execution (labs tier).

When to use it

- Quick start/stop/restart without hunting inventory filters
- Bulk intents such as “stop all VMs in namespace prod”
- Reuse recent commands from history
- Pair with AI Center when you need longer advisory workflows

How to get there

- Route: `/nlp-command`
- Nav: **More → Insights → NLP Command** (labs tier)
- Related: `/ai-center`, `/vms`

Operate from the console (UX)

1. Open `/nlp-command` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Natural-language bar for VM power and lifecycle intents — parse plain English into a confirmed action before execution (….
3. Use the center’s primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Natural-language bar for VM power and lifecycle intents — parse plain English into a confirmed actio.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- AI Center
- VMs
- VMIs

Operators

Purpose

OLM inventory for ClusterServiceVersions, Subscriptions, OperatorGroups, CatalogSources, and InstallPlans with aggregate health stats.

When to use it

- Confirm which operators are installed and their CSV phase
- Trace subscription upgrade state or catalog health
- Inspect OperatorGroups and InstallPlans that need approval
- Drill into CRDs and conditions for a stuck operator

How to get there

- Route: `/operators`
- Nav: **More → Delivery → Operators**
- Related: `/helm`, `/kubernetes`, `/approvals`

Operate from the console (UX)

1. Open `/operators` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: OLM inventory for ClusterServiceVersions, Subscriptions, OperatorGroups, CatalogSources, and InstallPlans with aggregate….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: OLM inventory for ClusterServiceVersions, Subscriptions, OperatorGroups, CatalogSources, and Install.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Helm Releases
- Kubernetes Center
- Approvals

Optimization

Purpose

Resource optimization recommendations and estimated savings — review rightsizing suggestions and apply supported hotplug/shape changes when enabled.

When to use it

- Periodic waste and oversize sweeps
- After Cost Intelligence flags expensive VMs
- Track which recommendations were already applied
- Replace older `/rightsizing` and `/spot-savings` bookmarks (those routes redirect here)

How to get there

- Route: `/optimization`
- Nav: **More → Insights → Optimization**
- Related: `/rightsizing` (redirect), `/spot-savings` (redirect), `/cost-intelligence`

Operate from the console (UX)

1. Open `/optimization` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Resource optimization recommendations and estimated savings — review rightsizing suggestions and apply supported hotplug….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Resource optimization recommendations and estimated savings — review rightsizing suggestions and app.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Rightsizing
- VMs
- Anomaly Detector
- Cost Intelligence — `/cost-intelligence`

PacketWolf VM Guard

Purpose

Network intelligence and VM Shield containment — see allowed/denied flows and apply quarantine / internet-lock profiles (typically Cilium/Hubble backed).

When to use it

- Investigate unexpected egress/ingress for a VM
- Contain a compromised or noisy workload quickly
- Preview a policy as dry-run before enforce

How to get there

- Route: `/packetwolf`
- Nav: **More → Mesh & traffic → PacketWolf VM Guard**
- Related: `/network-flow`, `/network-flow?tab=firewall`, `/cilium`

Operate from the console (UX)

1. Open `/packetwolf` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Network intelligence and VM Shield containment — see allowed/denied flows and apply quarantine / internet-lock profiles ….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Network intelligence and VM Shield containment — see allowed/denied flows and apply quarantine / int.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Network Flow — `/network-flow`
- Security
- Incidents
- Deep dive: PACKETWOLF_VM_SHIELD.md

Performance Testing

Purpose

List and run performance tests defined in the cluster, with live metrics (users/pods tracked, estimated RPS, error rate, latency).

When to use it

- Load-test a service URL before a release
- Compare latency and error rate under concurrent users
- Validate capacity after rightsizing or placement changes
- Operationalize tests stored as labeled ConfigMaps

How to get there

- Route: `/perf-testing`
- Nav: **More → Resilience → Performance Testing**
- Related: `/chaos-engineering`, `/optimization`

Operate from the console (UX)

1. Open `/perf-testing` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: List and run performance tests defined in the cluster, with live metrics (users/pods tracked, estimated RPS, error rate,….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: List and run performance tests defined in the cluster, with live metrics (users/pods tracked, estima.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Chaos Engineering
- Optimization
- System Health

Placement Advisor

Purpose

Legacy nav entry for smart VM placement. The dashboard redirects this route to **Placement**, where node scoring and topology-manager recommendations live.

When to use it

- Choosing a host for a new or resized VM
- Balancing load across zones or affinity constraints
- Reviewing topology-manager placement suggestions
- Coordinating with NUMA / topology policies before pin work

How to get there

- Route: `/placement-advisor` (redirects to `/placement`)
- Nav: **More → Insights → Placement Advisor**
- Related: `/placement`, `/topology-manager`, `/nodes`

Operate from the console (UX)

1. Open `/placement-advisor` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Legacy nav entry for smart VM placement. The dashboard redirects this route to **Placement**, where node scoring and top….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Legacy nav entry for smart VM placement. The dashboard redirects this route to **Placement**, where .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Placement
- Topology Mgr
- Nodes
- Migrations

Placement

Purpose

Heuristic node scores from live topology, plus topology-manager API recommendations, so you can pick a suitable host for VM CPU/memory and affinity needs.

When to use it

- Place a new VM on the least-loaded capable node
- Prefer a zone or label affinity before scheduling
- Compare topology-manager recs with client-side scores
- Review host groups used by your placement policy

How to get there

- Route: `/placement`
- Nav: **More → Insights → Placement**
- Related: `/placement-advisor` (alias), `/topology-manager`, `/nodes`

Operate from the console (UX)

1. Open `/placement` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Heuristic node scores from live topology, plus topology-manager API recommendations, so you can pick a suitable host for….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Heuristic node scores from live topology, plus topology-manager API recommendations, so you can pick.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Placement Advisor
- Topology Mgr
- Nodes
- VMs

Progressive Delivery

Purpose

Operate canary deployments and progressive rollouts — traffic weight, health signals, promote, and rollback — from one delivery dashboard.

When to use it

- Watch canary weight and success or latency signals during a release
- Promote a healthy rollout to full traffic
- Roll back a failing progressive deployment
- Confirm whether any canaries or rollouts are still in progress

How to get there

- Route: `/progressive-delivery`
- Nav: **More → Delivery → Progressive Delivery**
- Related: `/deployment-strategies`, `/helm`, `/cicd`

Operate from the console (UX)

1. Open `/progressive-delivery` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Operate canary deployments and progressive rollouts — traffic weight, health signals, promote, and rollback — from one d….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Operate canary deployments and progressive rollouts — traffic weight, health signals, promote, and r.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Deployment Strategies
- Helm Releases
- CI/CD

Resource Tags

Purpose

Tag coverage and compliance for cluster resources: distribution of keys, untagged inventory, required-tag checks, and bulk apply.

When to use it

- Measure how many resources carry FinOps or ownership tags
- Find untagged workloads missing required keys
- Enforce tagging policy checks before chargeback
- Bulk-apply a key/value to a namespace

How to get there

- Route: `/resource-tagging`
- Nav: **More → Tools & settings → Resource Tags**
- Related: `/cost-allocation`, `/tenancy`, `/vms`

Operate from the console (UX)

1. Open `/resource-tagging` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Tag coverage and compliance for cluster resources: distribution of keys, untagged inventory, required-tag checks, and bu….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Tag coverage and compliance for cluster resources: distribution of keys, untagged inventory, require.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Cost Allocation
- Virtual Machines
- Settings
- Tenancy — `/tenancy`

Mesh Detail

Purpose

Legacy nav entry for service-mesh detail. The dashboard redirects this route to **Service Mesh**, the Multus NAD and VM attachment inventory.

When to use it

- Same jobs as Service Mesh (NAD inventory, VM attachments)
- Following older bookmarks or docs that cite `/service-mesh-detail`
- Cross-linking from Network Flow investigations

How to get there

- Route: `/service-mesh-detail` (redirects to `/service-mesh`)
- Nav: **More → Mesh & traffic → Mesh Detail**
- Related: `/service-mesh`, `/network-flow`, `/cilium`

Operate from the console (UX)

1. Open `/service-mesh-detail` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Legacy nav entry for service-mesh detail. The dashboard redirects this route to **Service Mesh**, the Multus NAD and VM ….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Legacy nav entry for service-mesh detail. The dashboard redirects this route to **Service Mesh**, th.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Network Flow
- Cilium CNI
- Network attachments

Status Page

Purpose

Operator-facing fleet status board: overall operational / degraded / outage banner, per-VM health, and recent Warning events.

When to use it

- Share a single “are we up?” view during an incident
- Scan VM health scores and running ratio
- Review recent Warning events as lightweight incident history
- Refresh while waiting for recoveries

How to get there

- Route: `/status-page`
- Nav: **More → Tools & settings → Status Page**
- Related: `/system-health` , `/incidents` , `/vms`

Operate from the console (UX)

1. Open `/status-page` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Operator-facing fleet status board: overall operational / degraded / outage banner, per-VM health, and recent Warning ev….
3. Use the center’s primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Operator-facing fleet status board: overall operational / degraded / outage banner, per-VM health, a.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- System Health
- Incidents — `/incidents`
- Virtual Machines
- SLA Dashboard

Terminal

Purpose

In-browser cluster shell: pick a pod/container, open an authenticated WebSocket session, and run commands with multi-tab support.

When to use it

- Exec into a workload without leaving the dashboard
- Keep recent namespace/pod targets handy for repeat access
- Open several shells (multi-session tabs) during an incident
- Deep-link from a pod context with `?namespace=&pod=&container=`

How to get there

- Route: `/terminal`
- Nav: **Top bar → Terminal** (also Support / quick links)
- Related: `/pods`, `/vms`, `/api-docs`

Operate from the console (UX)

1. Open `/terminal` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: In-browser cluster shell: pick a pod/container, open an authenticated WebSocket session, and run commands with multi-tab….
3. Pick a session target (VM / pod / node) and attach VNC, serial, SSH, or RDP as offered.
4. Confirm HTTPS for in-browser VNC; RDP/SSH use guest credentials, not Zeus login.
5. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: In-browser cluster shell: pick a pod/container, open an authenticated WebSocket session, and run com.
6. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- API Docs
- Debug
- Pods — `/pods`

Topology Mgr

Purpose

Node topology detail for NUMA zones, CPU pins, device allocations, and topology policies — deeper than the live map on Topology.

When to use it

- Plan CPU pinning or device-aware VM placement
- Inspect NUMA memory and device locality per node
- Audit topology policies and which nodes they cover
- Correlate with Placement scores before scheduling

How to get there

- Route: `/topology-manager`
- Nav: **More → Mesh & traffic → Topology Mgr**
- Related: `/topology`, `/placement`, `/nodes`

Operate from the console (UX)

1. Open `/topology-manager` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Node topology detail for NUMA zones, CPU pins, device allocations, and topology policies — deeper than the live map on T….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Node topology detail for NUMA zones, CPU pins, device allocations, and topology policies — deeper th.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Topology
- Placement
- Nodes
- Dependencies

Topology

Purpose

Live map of infrastructure relationships — nodes, VMs, networks, and dependencies visualized.

When to use it

- Understand blast radius before a change
- Explain environment layout to a new operator
- Correlate incidents with dependency edges

How to get there

- Route: `/topology`
- Nav: **More → Mesh & traffic → Topology**
- Related: `/dependencies`, `/network-flow`

Operate from the console (UX)

1. Open `/topology` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Live map of infrastructure relationships — nodes, VMs, networks, and dependencies visualized.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Live map of infrastructure relationships — nodes, VMs, networks, and dependencies visualized.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Dependencies — `/dependencies`
- Network Flow — `/network-flow`
- PacketWolf

Webhook Tester

Purpose

Validate alert webhook delivery: test configured alert webhooks or POST a custom payload to any URL and inspect latency and response.

When to use it

- Prove an alert channel receives events before go-live
- Debug failed webhook deliveries with status and body
- Fire a one-off manual POST to a Slack/HTTP endpoint
- Refresh the list of configured alert webhooks

How to get there

- Route: `/webhook-tester`
- Nav: **More → Tools & settings → Webhook Tester**
- Related: `/alerting?tab=channels`, `/alerting`, `/api-playground`

Operate from the console (UX)

1. Open `/webhook-tester` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Validate alert webhook delivery: test configured alert webhooks or POST a custom payload to any URL and inspect latency ….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Validate alert webhook delivery: test configured alert webhooks or POST a custom payload to any URL .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Alerting (Channels tab)
- API Playground
- Status Page
- Alerting — `/alerting`

Widgets

Purpose

Customizable dashboard widget grid (VM count, capacity, health, events, favorites, alerts) with layout persistence in the browser.

When to use it

- Build a personal at-a-glance operations board
- Add or remove widgets without changing the Home layout for everyone
- Reorder cards to match your shift workflow
- Reset to the default widget set

How to get there

- Route: `/widgets`
- Nav: **More → Tools & settings → Widgets**
- Related: `/favorites`, `/`, `/system-health`

Operate from the console (UX)

1. Open `/widgets` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Customizable dashboard widget grid (VM count, capacity, health, events, favorites, alerts) with layout persistence in th….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Customizable dashboard widget grid (VM count, capacity, health, events, favorites, alerts) with layo.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Favorites
- Home
- System Health

Application Center

Purpose

Group VMs into business applications with workspace scoping, health pulse, and an inspector for protection and membership.

When to use it

- Model a service as an application over multiple VMs
- Filter applications by workspace or search
- Inspect health and linked VMs for one application
- Create an application with selected VM membership

How to get there

- Route: `/applications`
- Nav: **Command palette / deep link**
- Related: `/vms`, `/backup-dr`, `/tasks`

Operate from the console (UX)

1. Open `/applications` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Group VMs into business applications with workspace scoping, health pulse, and an inspector for protection and membershi….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Group VMs into business applications with workspace scoping, health pulse, and an inspector for prot.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- Backup & DR
- Task Center

Approvals

Purpose

Single inbox for decisions waiting on you — day-2 remediations pending approval and change requests.

When to use it

- Clear pending remediations without opening Auto-Remediation first
- Approve or reject VM change requests
- Confirm inbox zero before a change freeze ends
- Pair with War Room during live incidents

How to get there

- Route: `/approvals`
- Nav: **Workspace → Approvals**
- Related: `/auto-remediation`, `/war-room`, `/change-approval`

Operate from the console (UX)

1. Open `/approvals` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Single inbox for decisions waiting on you — day-2 remediations pending approval and change requests.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Single inbox for decisions waiting on you — day-2 remediations pending approval and change requests.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Auto-Remediation
- War Room
- Change Approval — `/change-approval`

Auth audit log

Purpose

Login and security event table sourced from `auth-audit.jsonl` on the Zeus OS data volume (`ZEUS_OS_DATA_DIR`).

When to use it

- Investigate failed or unexpected sign-ins
- Support access reviews called out from Identity Center
- Confirm auth events after enabling SSO or MFA
- Export context for a security incident

How to get there

- Route: `/auth-audit`
- Nav: **Security → Audit Logs**
- Related: `/identity-center` , `/events?tab=audit` , `/settings/security`

Operate from the console (UX)

1. Open `/auth-audit` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Login and security event table sourced from `auth-audit.jsonl` on the Zeus OS data volume (`ZEUS_OS_DATA_DIR`).
3. Filter findings / policies by severity or namespace.
4. Open a row for evidence and remediation; use change-approval gates when enabled.
5. Export or acknowledge as your role allows — do not mute crit without a live condition handled.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Login and security event table sourced from `auth-audit.jsonl` on the Zeus OS data volume (`ZEUS_OS_.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Identity Center
- Security
- Settings

Backup & DR

Purpose

Recovery Theatre hub — backup stats plus shortcuts to Velero, restore, snapshots, DR, and backup wizards.

When to use it

- See total, completed, and failed backups at a glance
- Launch Velero, Restore Wizard, or Backup Wizard
- Open Disaster Recovery plans and DR settings (RPO/RTO)
- Start protection when no backups are detected yet

How to get there

- Route: `/backup-dr`
- Nav: **Monitoring → Backup & DR** (display name Recovery Theatre)
- Related: `/velero`, `/restore-wizard`, `/backup-wizard`, `/disaster-recovery`

Operate from the console (UX)

1. Open `/backup-dr` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Recovery Theatre hub — backup stats plus shortcuts to Velero, restore, snapshots, DR, and backup wizards.
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Recovery Theatre hub — backup stats plus shortcuts to Velero, restore, snapshots, DR, and backup wiz.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Velero
- Restore Wizard
- Backup Wizard
- Snapshots

Console Sessions

Purpose

Legacy route that redirects to ConsoleHub's active sessions tab. Bookmarks and Settings links still resolve.

When to use it

- Open an old `/console-sessions` bookmark
- Reach session inventory after following a Settings deep link
- Prefer ConsoleHub directly for day-to-day console work
- Audit who holds live console tunnels

How to get there

- Route: `/console-sessions` → redirects to `/consolehub?tab=sessions`
- Nav: **Command palette / deep link** (not a separate sidebar page)
- Related: `/consolehub`, VM workbench consoles

Operate from the console (UX)

1. Open `/console-sessions` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Legacy route that redirects to ConsoleHub's active sessions tab. Bookmarks and Settings links still resolve.
3. Pick a session target (VM / pod / node) and attach VNC, serial, SSH, or RDP as offered.
4. Confirm HTTPS for in-browser VNC; RDP/SSH use guest credentials, not Zeus login.
5. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Legacy route that redirects to ConsoleHub's active sessions tab. Bookmarks and Settings links still .
6. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- ConsoleHub
- Consoles overview
- VM workbench

Developer Center

Purpose

Operator and integrator hub for REST docs, API playground, CLI examples, webhooks, and plugin SDK entry points.

When to use it

- Explore the live OpenAPI catalog
- Try endpoints in the API Playground
- Copy `zeus` CLI examples for VM and AI workflows
- Reach webhook tester or Plugins from one place

How to get there

- Route: `/developer-center`
- Nav: **Admin → Developer Center**
- Related: `/api-docs`, `/api-playground`, `/terminal`, `/webhook-tester`, `/plugins`

Operate from the console (UX)

1. Open `/developer-center` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Operator and integrator hub for REST docs, API playground, CLI examples, webhooks, and plugin SDK entry points.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Operator and integrator hub for REST docs, API playground, CLI examples, webhooks, and plugin SDK en.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Plugins
- Settings
- API Playground

Edge Center

Purpose

Guidance hub for branch clusters, air-gapped operation, and sync or compliance posture tied to multi-cluster views.

When to use it

- Orient on retail, factory, or remote office cluster patterns
- Review air-gap capabilities (offline images, local AI, license, audit export)
- Jump to Multi-cluster for sync status
- Open Advanced settings for edge-related options

How to get there

- Route: `/edge-center`
- Nav: **Modules → Edge Center**
- Related: `/multi-cluster`, `/settings/advanced`

Operate from the console (UX)

1. Open `/edge-center` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Guidance hub for branch clusters, air-gapped operation, and sync or compliance posture tied to multi-cluster views.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Guidance hub for branch clusters, air-gapped operation, and sync or compliance posture tied to multi.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Multi-Cluster — `/multi-cluster`
- Settings
- Identity Center

Forge

Purpose

Native AI module hub — prompt handoff from AI Center, links to AI providers and GPU passthrough. Dedicated agent builder is not shipped on this page yet.

When to use it

- Land a prompt forwarded from AI Center (`?prompt=` / `?vm=`)
- Open AI provider configuration (OpenAI, Anthropic, Ollama, air-gap)
- Jump to GPU passthrough inventory
- Confirm where routing and models are configured today

How to get there

- Route: `/forge`
- Nav: **AI → Forge (AI)** (workspace switcher AI tile also points here)
- Related: `/ai-center` , `/settings/ai-providers` , `/gpu`

Operate from the console (UX)

1. Open `/forge` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the editorial intro (eyebrow **Intelligence**, title **Forge**), then use the prompt card (if forwarded from AI Center) and the links to AI providers / GPU.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Native AI module hub — prompt handoff from AI Center, links to AI providers and GPU passthrough. Ded.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- AI Center
- Settings
- GPU

Identity Center

Purpose

Landing hub for authentication and access governance — links to SSO, LDAP, MFA, Users & RBAC, auth audit, and API tokens.

When to use it

- Configure SSO / OIDC / SAML or LDAP
- Enforce MFA from Security settings
- Open Users & RBAC or API service accounts
- Review stale admin access via Auth Audit

How to get there

- Route: `/identity-center`
- Nav: **Admin → Identity Center**
- Related: `/users`, `/auth-audit`, `/settings/security`, `/settings/api-access`

Operate from the console (UX)

1. Open `/identity-center` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Landing hub for authentication and access governance — links to SSO, LDAP, MFA, Users & RBAC, auth audit, and API tokens.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Landing hub for authentication and access governance — links to SSO, LDAP, MFA, Users & RBAC, auth a.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Auth audit log
- Settings
- Users & RBAC — `/users`

Machine Finder

Purpose

Browse the datacenter → cluster → host → VM hierarchy, then jump into Machine Runway for fleet operations.

When to use it

- Orient on where a VM sits in infrastructure topology
- Search hosts, VMs, or clusters by name
- Jump from a VM node into the VM inventory deep link
- Spot critical cluster storage pressure while browsing

How to get there

- Route: `/infra-browser`
- Nav: **Workspace → Machine Finder** (module label Infrastructure Browser)
- Related: `/vms`, `/vm-groups`, `/topology`

Operate from the console (UX)

1. Open `/infra-browser` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Browse the datacenter → cluster → host → VM hierarchy, then jump into Machine Runway for fleet operations.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Browse the datacenter → cluster → host → VM hierarchy, then jump into Machine Runway for fleet opera.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- VM Groups
- Topology

Kubernetes Center

Purpose

Hub for the container layer under your Zeus virtual datacenter — cluster pulse plus shortcuts to pods, services, nodes, and related day-2 tools.

When to use it

- Check pod and node readiness at a glance
- Jump to Pods, Services, or Nodes inventory
- Open GitOps, catalog, MetalLB, or Task Center from one place
- Operate Kubernetes Pro features gated by edition

How to get there

- Route: `/kubernetes`
- Nav: **Compute → Kubernetes** (workspace switcher also lists Kubernetes)
- Related: `/pods`, `/services`, `/nodes`, `/tasks`

Operate from the console (UX)

1. Open `/kubernetes` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Hub for the container layer under your Zeus virtual datacenter — cluster pulse plus shortcuts to pods, services, nodes, ….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Hub for the container layer under your Zeus virtual datacenter — cluster pulse plus shortcuts to pod.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Pods
- Task Center
- Operators

Marketplace

Purpose

Browse and deploy VM templates and blueprints — search, OS and category filters, favorites, AI draft assist, and a deploy wizard.

When to use it

- Find a golden image or workload template to deploy
- Filter by OS family or marketplace category
- Deploy a template into a namespace via the wizard
- Generate a draft template from a natural-language prompt (when AI is configured)

How to get there

- Route: `/marketplace`
- Nav: **Modules → Marketplace**
- Related: `/templates`, `/blueprints`, `/image-factory`, `/vms`

Operate from the console (UX)

1. Open `/marketplace` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Browse and deploy VM templates and blueprints — search, OS and category filters, favorites, AI draft assist, and a deplo….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Browse and deploy VM templates and blueprints — search, OS and category filters, favorites, AI draft.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- Templates
- Plugins
- AI Center

Migration Command Center

Purpose

VMware exit planning — migration waves, Transiva discovery handoff, preflight blockers, and wave readiness. Zeus OS does not perform VMware import itself.

When to use it

- Plan waves (dev → production) before cutover
- Link a wave to a Transiva source reference
- Run preflight readiness on candidate VMs
- Open Transiva discovery in the sibling product

How to get there

- Route: `/migration-factory`
- Nav: **Modules → Migration** (display name Migration Studio)
- Related: `/migrations`, Transiva / h2kvm (external)

Operate from the console (UX)

1. Open `/migration-factory` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: VMware exit planning — migration waves, Transiva discovery handoff, preflight blockers, and wave readiness. Zeus OS does….
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: VMware exit planning — migration waves, Transiva discovery handoff, preflight blockers, and wave rea.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Live Migrations
- Virtual Machines
- AI Center

Cluster onboarding

Purpose

Guided preflight for a new Zeus OS cluster — platform readiness, Cilium status check, and cluster info — then links into core navigation.

When to use it

- First login after install
- Verify API reachability and baseline CRDs
- Confirm networking (Cilium) and KubeVirt-oriented cluster info
- Hand off into VMs or Settings when checks pass

How to get there

- Route: `/onboarding`
- Nav: **Command palette / deep link**
- Related: `/vms`, `/cilium`, `/settings`

Operate from the console (UX)

1. Open `/onboarding` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Guided preflight for a new Zeus OS cluster — platform readiness, Cilium status check, and cluster info — then links into….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Guided preflight for a new Zeus OS cluster — platform readiness, Cilium status check, and cluster in.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- Settings
- System Health

Patch Center

Purpose

Windows and Linux patch readiness across running VMs — risk signals, maintenance-window links, and compliance handoff.

When to use it

- Measure fleet patch readiness percentage
- Find VMs that need review or are high risk
- Follow the pre-patch snapshot → apply → reboot → health-check flow
- Schedule off-peak work via Scheduled Ops

How to get there

- Route: `/patch-center`
- Nav: **Compute → Patch Center**
- Related: `/vm-groups`, `/events?tab=scheduled`, `/compliance`, `/snapshots`

Operate from the console (UX)

1. Open `/patch-center` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Windows and Linux patch readiness across running VMs — risk signals, maintenance-window links, and compliance handoff.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Windows and Linux patch readiness across running VMs — risk signals, maintenance-window links, and c.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- VM Groups
- Snapshots
- Security

Plugins

Purpose

Preview of partner and custom Zeus OS plugin categories. Install and uninstall are not available yet.

When to use it

- See planned adapter types (storage, backup, network, monitoring, ticketing, AI)
- Understand that Install buttons are intentionally disabled
- Follow Developer Center for future SDK and webhook docs
- Prefer Marketplace templates for deployable content today

How to get there

- Route: `/plugins`
- Nav: **Modules → Plugins**
- Related: `/developer-center`, `/marketplace`

Operate from the console (UX)

1. Open `/plugins` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Preview of partner and custom Zeus OS plugin categories. Install and uninstall are not available yet.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Preview of partner and custom Zeus OS plugin categories. Install and uninstall are not available yet.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Developer Center
- Marketplace
- Velero

Reports

Purpose

Executive and operational report catalog — shortcuts into health, protection, DR, security, network, cost, audit, and compliance exports.

When to use it

- Brief leadership with an executive health path
- Jump to Velero or DR readiness reporting surfaces
- Export compliance evidence or a CSV catalog of report links
- Open security posture or zero-trust network views

How to get there

- Route: `/reports`
- Nav: **Command palette / deep link**
- Related: `/system-health`, `/velero`, `/compliance`, `/cost-intelligence`

Operate from the console (UX)

1. Open `/reports` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Executive and operational report catalog — shortcuts into health, protection, DR, security, network, cost, audit, and co….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Executive and operational report catalog — shortcuts into health, protection, DR, security, network,.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- System Health
- Velero
- Backup & DR
- Cost Intelligence

Restore Wizard

Purpose

Guided Velero restore — select a completed backup, configure target namespace and PV restore, then monitor restore phase to completion.

When to use it

- Restore after accidental deletion or failed upgrade
- Cross-namespace restore when `?crossNamespace=1` is set
- Prefill a known backup with `?backup=`
- Run a DR drill from Backup & DR

How to get there

- Route: `/restore-wizard`
- Nav: **Command palette / deep link** (also from Backup & DR)
- Related: `/backup-dr`, `/velero`, `/backup-wizard`

Operate from the console (UX)

1. Open `/restore-wizard` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Guided Velero restore — select a completed backup, configure target namespace and PV restore, then monitor restore phase….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Guided Velero restore — select a completed backup, configure target namespace and PV restore, then m.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Backup & DR
- Velero
- Backup Wizard

Support

Purpose

Operator support hub — download a redacted diagnostics bundle and jump to health, debug, API docs, audit, and terminal tools.

When to use it

- Collect a support bundle for Zyvor or internal escalation
- Open System Health or Debug Tools during an outage
- Share API docs with integrators
- Keep a single entry point for operator diagnostics

How to get there

- Route: `/support`
- Nav: **Command palette / deep link**
- Related: `/system-health`, `/debug`, `/api-docs`, `/events?tab=audit`, `/terminal`

Operate from the console (UX)

1. Open `/support` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Operator support hub — download a redacted diagnostics bundle and jump to health, debug, API docs, audit, and terminal t….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Operator support hub — download a redacted diagnostics bundle and jump to health, debug, API docs, a.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- System Health
- Debug Tools
- Developer Center

Task Center

Purpose

Long-running operations inbox — migrations, backups, and platform jobs with status, progress, and cancel when supported.

When to use it

- Watch async work after a migration or backup starts
- Filter to active, running, or failed tasks via `?status=`
- Cancel a stuck task when the API allows
- Jump to the related VM from a task row

How to get there

- Route: `/tasks`
- Nav: **Command palette / deep link** (also linked from Kubernetes Center)
- Related: `/migrations`, `/backup-dr`, `/vms`

Operate from the console (UX)

1. Open `/tasks` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Long-running operations inbox — migrations, backups, and platform jobs with status, progress, and cancel when supported.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Long-running operations inbox — migrations, backups, and platform jobs with status, progress, and ca.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Live Migrations
- Backup & DR
- Virtual Machines

Time Machine

Purpose

Cluster DVR and per-VM flight recorder — scrub recorded state over time. Frames come from the server-side sampler ring buffer.

When to use it

- Replay cluster health (nodes, VMs, pressure) around an incident
- Rewind a single VM's lifecycle phases and node placement
- Confirm the recorder is collecting after a fresh deploy
- Correlate War Room timelines with historical frames

How to get there

- Route: `/time-machine` (alias `/dvr` redirects here)
- Nav: **Workspace → Time Machine**
- Related: `/war-room`, `/incidents`, `/system-health`

Operate from the console (UX)

1. Open `/time-machine` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Cluster DVR and per-VM flight recorder — scrub recorded state over time. Frames come from the server-side sampler ring b….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Cluster DVR and per-VM flight recorder — scrub recorded state over time. Frames come from the server.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- War Room
- Incidents
- System Health

VM Groups

Purpose

Label-based VM groups with bulk start, stop, and restart across matching members.

When to use it

- Define a fleet slice with a label selector (`app=web, env=prod`)
- Start, stop, or restart all VMs in a group
- Scope groups to a namespace when needed
- Clean up obsolete group definitions

How to get there

- Route: `/vm-groups`
- Nav: **Compute → VM Groups** (also contextual under Machines)
- Related: `/vms` , `/infra-browser` , `/patch-center`

Operate from the console (UX)

1. Open `/vm-groups` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Label-based VM groups with bulk start, stop, and restart across matching members.
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Label-based VM groups with bulk start, stop, and restart across matching members.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- Machine Finder
- Patch Center

War Room

Purpose

Live incident assembly — active incident, affected VMs and nodes, recommended actions, pending remediations, and a warning-event feed in one place.

When to use it

- Respond to a P1 without hopping across dozens of routes
- Approve or reject day-2 remediations inline
- Evacuate or act on affected nodes with confirm-then-run controls
- Confirm the cluster is healthy when no incident is active

How to get there

- Route: `/war-room`
- Nav: **Workspace → War Room**
- Related: `/incidents`, `/approvals`, `/auto-remediation`, `/time-machine`

Operate from the console (UX)

1. Open `/war-room` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Live incident assembly — active incident, affected VMs and nodes, recommended actions, pending remediations, and a warni….
3. Use the center's primary CTA (create, scan, open workbench, ask Zeus when reasoning is required).
4. Deterministic navigation and filters call the router directly — do not round-trip those through Ask Zeus.
5. Pin frequent pages to Favorites (`/favorites`).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Live incident assembly — active incident, affected VMs and nodes, recommended actions, pending remed.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Incidents
- Approvals
- Auto-Remediation
- Time Machine

Resource Canvas

Purpose

Spatial map of compute, storage, networking, and AI entry points — click a node to open its window.

When to use it

- Orient visually across VMs and infra hubs
- Jump from a canvas VM node into console deep link
- Open Storage, Network Flow, or AI providers from fixed infra nodes
- Give operators a single spatial overview of recent VMs

How to get there

- Route: `/workspace`
- Nav: **Modules → Resource Canvas**
- Related: `/vms`, `/storage`, `/network-flow`, `/settings/ai-providers`

Operate from the console (UX)

1. Open `/workspace` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Spatial map of compute, storage, networking, and AI entry points — click a node to open its window.
3. Pick a session target (VM / pod / node) and attach VNC, serial, SSH, or RDP as offered.
4. Confirm HTTPS for in-browser VNC; RDP/SSH use guest credentials, not Zeus login.
5. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Spatial map of compute, storage, networking, and AI entry points — click a node to open its window.
6. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Virtual Machines
- Topology
- Consoles overview

Settings — Advanced

Purpose

Shortcuts into platform, debug, and developer tooling, plus keyboard shortcuts and build information.

When to use it

- Collect diagnostics for a support case
- Reach debug and developer tools without memorizing routes
- Look up keyboard shortcuts
- Check the About panel for build details

How to get there

- Route: `/settings/advanced`
- Nav: **Settings → Advanced**
- Related: `/debug`, `/kernel`, `/api-docs`, `/shortcuts`

Operate from the console (UX)

1. Open `/settings/advanced` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Shortcuts into platform, debug, and developer tooling, plus keyboard shortcuts and build information.
3. Change only the section you need (General / Appearance / Advanced / API access / …).
4. Save; API keys and SSO changes may require re-login.
5. Cluster-wide TLS/auth/data-dir remain server env — see Admin basics.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Shortcuts into platform, debug, and developer tooling, plus keyboard shortcuts and build information.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview
- Debug
- Kernel Info
- Support

Settings — AI providers

Purpose

Register and manage the language-model providers that power Zeus OS AI features, plus routing rules, API keys, stored memory, and the prompt library.

When to use it

- Point Zeus OS at Forge, a local Ollama endpoint, or another OpenAI-compatible provider
- Set which provider is the default and how requests are routed
- Review or clear stored AI memory before an audit
- Curate reusable prompts for your team

How to get there

- Route: `/settings/ai-providers`
- Nav: **Settings → AI providers**
- Related: `/ai-center`, `/forge`, `/nlp-command`

Operate from the console (UX)

1. Open `/settings/ai-providers` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Register and manage the language-model providers that power Zeus OS AI features, plus routing rules, API keys, stored me….
3. Change only the section you need (General / Appearance / Advanced / API access / …).
4. Save; API keys and SSO changes may require re-login.
5. Cluster-wide TLS/auth/data-dir remain server env — see Admin basics.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Register and manage the language-model providers that power Zeus OS AI features, plus routing rules,.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview
- AI Center
- Forge
- Auto-Remediation

Settings — API access

Purpose

Everything needed to automate against Zeus OS: scoped API tokens, the OpenAPI specification, rate-limit behaviour, and the FinOps change audit.

When to use it

- Issue a token for CI, Terraform, or a monitoring integration
- Look up the live OpenAPI spec before writing a client
- Understand why an automation is being rate limited
- Review audited FinOps changes

How to get there

- Route: `/settings/api-access`
- Nav: **Settings → API access**
- Related: `/users`, `/api-docs`, `/api-playground`

Operate from the console (UX)

1. Open `/settings/api-access` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Everything needed to automate against Zeus OS: scoped API tokens, the OpenAPI specification, rate-limit behaviour, and t….
3. Change only the section you need (General / Appearance / Advanced / API access / …).
4. Save; API keys and SSO changes may require re-login.
5. Cluster-wide TLS/auth/data-dir remain server env — see Admin basics.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Everything needed to automate against Zeus OS: scoped API tokens, the OpenAPI specification, rate-li.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview
- API Docs
- API Playground
- Users
- Developer Center

Settings — Appearance

Purpose

Control how the Zeus OS shell looks and behaves: Light or Dark theme, wallpaper, glass and motion effects, sidebar mode, and the dock.

When to use it

- Switch between **Light** (Tahoe paper + Action Blue) and **Dark** (Netra carbon)
- Use the sun/moon control in the menubar or WebShell header for the same flip
- Reduce motion or glass effects on lower-powered machines
- Collapse the sidebar to an icon rail for more screen space
- Pin the centers you use most to the dock and Finder favourites

How to get there

- Route: `/settings/appearance`
- Nav: **Settings → Appearance**
- Quick toggle: circular sun/moon button in the Mac menubar or Web page header

Themes (Light / Dark only)

Appearance	Store id	Look
Light	`tahoe-light`	Quiet Apple paper (`#f5f5f7`), ink `#1d1d1f` , Action Blue CTAs
Dark	`zyvor-carbon`	Near-black page (`#000`), elevated `#1d1d1f` , Action Blue intent

Older exotic shells (Aurora, Predator, Dark steel, Zinc metal, Emerald Noir, Nova, Classic Blue) are removed. Stored values migrate to Dark on next load.

Zyvor branding: bare orange **Z** in chrome; filled orange tile on the login page and favicon (`#ff5a15` → `#cc420a`). Brand orange is for the Z mark — interactive chrome uses Action Blue.

Operate from the console (UX)

1. Open `/settings/appearance` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Choose **Light** or **Dark** — the shell updates immediately (also via the sun/moon toggle).
3. Change only the section you need next (wallpaper, glass intensity, sidebar, dock).
4. Save; API keys and SSO changes may require re-login.
5. Cluster-wide TLS/auth/data-dir remain server env — see Admin basics.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview

- Using the Dashboard
- Liquid Glass design system
- Favorites

Settings — Backup & DR

Purpose

Configuration entry points for Velero backups and disaster recovery, linking settings to the operational backup centers.

When to use it

- Verify Velero is installed and wired before promising backup coverage
- Reach the backups or DR center quickly during a drill
- Check DR configuration ahead of an audit

How to get there

- Route: `/settings/backup-dr`
- Nav: **Settings → Backup / DR**
- Related: `/velero`, `/backup-dr`, `/disaster-recovery`, `/backup-wizard`

Operate from the console (UX)

1. Open `/settings/backup-dr` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Configuration entry points for Velero backups and disaster recovery, linking settings to the operational backup centers.
3. Prefer dry-run / plan when the UI offers it before mutating production.
4. Start the wizard or job; watch progress and history panels.
5. Confirm completion on the target inventory (VMs, snapshots, backup store).
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Configuration entry points for Velero backups and disaster recovery, linking settings to the operati.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview
- Velero
- Backup Wizard
- Backup / DR center
- Snapshots

Settings — General

Purpose

Server information and dashboard-wide preferences: what build you are running and how lists and cards behave for your account.

When to use it

- Confirm the Zeus OS version and server details before raising a support case
- Toggle dashboard preferences such as health scores on inventory cards
- Verify you are pointed at the expected cluster/server

How to get there

- Route: `/settings/general`
- Nav: **Settings → General**
- Related: `/settings/appearance`, `/settings/advanced`

Operate from the console (UX)

1. Open `/settings/general` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the editorial intro (eyebrow **Settings**), then confirm hostname / OS / kernel, and adjust dashboard refresh if needed.
3. Change only the section you need (General / Appearance / Advanced / API access / …).
4. Save; API keys and SSO changes may require re-login.
5. Cluster-wide TLS/auth/data-dir remain server env — see Admin basics.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Server information and dashboard-wide preferences: what build you are running and how lists and card.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview
- Settings — Appearance
- Settings — Advanced
- Support

Settings — Network

Purpose

Entry point for network-related configuration and the PacketWolf network-intelligence integration.

When to use it

- Check whether PacketWolf is paired and reachable
- Jump to the network center after changing cluster networking
- Verify network integration before relying on flow data or containment

How to get there

- Route: `/settings/network`
- Nav: **Settings → Network**
- Related: `/packetwolf`, `/network-flow`, `/network-info`

Operate from the console (UX)

1. Open `/settings/network` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Entry point for network-related configuration and the PacketWolf network-intelligence integration.
3. Use namespace / label filters; open an object for inspector details.
4. Mutations (drain, resize PVC, attach NAD) go through confirm sheets — wait for status refresh.
5. If empty: broaden namespace filter, confirm RBAC, and that the cluster API is reachable.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Entry point for network-related configuration and the PacketWolf network-intelligence integration.
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview
- PacketWolf VM Guard
- Network Flow
- Admin basics

Settings — Security

Purpose

Security-related configuration surfaced in the UI: active product edition, identity and SSO panels, browser console access policy, and a link into the security overview.

When to use it

- Confirm which edition and feature set is active
- Review or configure Active Directory / LDAP and SAML SSO integration
- Decide whether browser console access is permitted for operators
- Jump to the security posture overview during a review

How to get there

- Route: `/settings/security`
- Nav: **Settings → Security**
- Related: `/security`, `/users`, `/identity-center`, `/auth-audit`

Operate from the console (UX)

1. Open `/settings/security` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Security-related configuration surfaced in the UI: active product edition, identity and SSO panels, browser console acce….
3. Change only the section you need (General / Appearance / Advanced / API access / …).
4. Save; API keys and SSO changes may require re-login.
5. Cluster-wide TLS/auth/data-dir remain server env — see Admin basics.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Security-related configuration surfaced in the UI: active product edition, identity and SSO panels, .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Settings overview
- Security
- Users
- Identity Center
- Admin basics

Settings

Purpose

Configure the Zeus OS experience and platform integrations: general, appearance, network, security, backup/DR, AI providers, API access, and advanced options.

When to use it

- First login personalization (theme, sidebar)
- Admins enabling auth-related or backup integrations exposed in UI
- Creating API tokens for automation
- Pointing AI features at Forge / LLM providers

How to get there

- Route: `/settings` (categories under `/settings/...`)
- Top bar quick link · rail pin

Common categories

Category	Typical path	Who
General	`/settings/general`	Everyone
Appearance	`/settings/appearance`	Everyone
Network	`/settings/network`	Admin
Security	`/settings/security`	Admin
Backup / DR	`/settings/backup-dr`	Admin
AI providers	`/settings/ai-providers`	Admin
API access	`/settings/api-access`	Admin / automation users
Advanced	`/settings/advanced`	Admin

Exact category routes follow the Settings shell in your build.

Operate from the console (UX)

1. Open `/settings` from the sidebar, workspace switcher, or command palette (⌘K / Ctrl+K).
2. Read the PageHead / deck line — confirm it matches: Configure the Zeus OS experience and platform integrations: general, appearance, network, security, backup/DR, AI provid….
3. Change only the section you need (General / Appearance / Advanced / API access / …).
4. Save; API keys and SSO changes may require re-login.
5. Cluster-wide TLS/auth/data-dir remain server env — see Admin basics.
6. **Empty / fail:** No data → check auth, namespace filter, and that required operators (KubeVirt/CDI/monitoring) are installed; purpose was: Configure the Zeus OS experience and platform integrations: general, appearance, network, security, .
7. **Success:** Live inventory or job progress matches the deck line; you can navigate to a related center without re-auth.

Use `https://<host>:30050/` (NodePort) or your ingress URL — never publish lab IPs. HTTPS is required for in-browser VNC. Browse lists are safe; power actions live on workbenches.

Related pages

- Using the Dashboard
- API Docs — `/api-docs`
- Identity Center — `/identity-center`

Zeus OS — Complete page index

Every navigable dashboard page from `ui/src/navigation/navConfig.ts`. Deep how-to guides exist for primary journeys under `pages/`; this index covers the **full catalog** (including labs/integrate-tier screens).

Generated: 2026-10-21 · 135 pages

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

Observe

Page	Route	Purpose	Guide
System Health	`/system-health`	Platform component health dashboard.	Open
Host Info	`/host`	Host / control host information.	Open
Monitoring Targets	`/monitoring`	Prometheus/monitoring scrape targets.	Open
VM Monitor	`/vm-monitor`	Per-VM health scoring and repair entry.	Open
Capacity	`/capacity`	Cluster capacity planning views.	Open
Resource Heatmap	`/heatmap`	Resource utilization heatmap.	Open
Events	`/events`	Kubernetes and platform events stream.	Open
APM	`/apm`	Application performance monitoring dashboard.	Open
Custom Metrics	`/custom-metrics`	Custom metrics browser.	Open
Alerting	`/alerting`	Alert rules and firing alerts.	Open
Logs Explorer	`/logs-explorer`	Log search and exploration.	Open
SLO Manager	`/slo-manager`	SLO definitions and burn-rate views.	Open
Incident chat	`/incident-chat`	Collaborative incident chat (labs).	Open
Ask Zyra	`/ask-zyra`	Operator page **Ask Zyra** at `/ask-zyra` — open from the sidebar or command palette.	—
AI Center	`/ai-center`	Operator page **AI Center** at `/ai-center` — open from the sidebar or command palette.	Open
Forge (AI)	`/forge`	Operator page **Forge (AI)** at `/forge` — open from the sidebar or command palette.	Open
GPU Devices	`/gpu`	GPU device inventory for accelerated VMs.	Open
Anomaly Detector	`/anomaly-detector`	Metric and behavior anomaly detection.	Open
Auto-Remediation	`/auto-remediation`	Day-2 auto-remediation playbooks.	Open
NLP Command	`/nlp-command`	Natural-language command bar (labs).	Open
Costs	`/costs`	Cost overview dashboard.	Open
Cost Intelligence	`/cost-intelligence`	Per-VM / namespace spend and trends.	Open
Cost Allocation	`/cost-allocation`	Cost allocation by team or label.	Open
Cost Estimator	`/cost-estimator`	What-if cost estimator (labs).	Open
Budget Alerts	`/budget-alerts`	Budget thresholds and alerts.	Open

Page	Route	Purpose	Guide
Forecasting	`/forecasting`	Capacity and demand forecasting.	Open
SLA Dashboard	`/sla`	SLA dashboard and breach tracking.	Open
Optimization	`/optimization`	Optimization center recommendations.	Open

Security

Page	Route	Purpose	Guide
Security	`/security`	Security posture overview.	Open
Security operations	`/security?tab=operations`	Operator page **Security operations** at `/security?tab=operations` — open from the sidebar or command palette.	—
Compliance	`/compliance`	Compliance checks and evidence.	Open
Compliance frameworks	`/compliance?tab=frameworks`	Operator page **Compliance frameworks** at `/compliance?tab=frameworks` — open from the sidebar or command palette.	—
Certificates	`/certificates`	Certificate inventory and expiry.	Open
Change Approval	`/change-approval`	Gated change approval queue.	Open
OPA Gatekeeper	`/opa`	OPA/Gatekeeper constraint overview.	Open
Admission Control	`/admission-control`	Admission policy controls.	Open
Image Scanning	`/image-scanning`	Vulnerability image scan results.	Open
External Secrets	`/external-secrets`	External Secrets Operator resources.	Open
Policies	`/cloudos-policies`	Operator page **Policies** at `/cloudos-policies` — open from the sidebar or command palette.	—
CI/CD	`/cicd`	CI/CD pipeline views (integrate).	Open
GitOps	`/gitops`	GitOps sync status (integrate).	Open
ArgoCD	`/argocd`	Argo CD application overview (integrate).	Open
Kustomize	`/kustomize`	Kustomize overlays dashboard (integrate).	Open
IaC	`/iac`	Infrastructure-as-code integrations.	Open
Helm Releases	`/helm`	Helm release inventory.	Open
Progressive Delivery	`/progressive-delivery`	Canary/blue-green progressive delivery.	Open
Deployment Strategies	`/deployment-strategies`	Deployment strategy catalog.	Open
Catalog	`/catalog`	Service / VM catalog browser.	Open
Marketplace	`/marketplace`	Operator page **Marketplace** at `/marketplace` — open from the sidebar or command palette.	Open
Automation	`/shortcuts`	Operator page **Automation** at `/shortcuts` — open from the sidebar or command palette.	—
Workflows	`/workflows`	Automation workflow manager.	Open
Chaos Engineering	`/chaos-engineering`	Chaos experiments and safety rails.	Open

Page	Route	Purpose	Guide
Performance Testing	`/perf-testing`	Performance testing campaigns.	Open
Database Ops	`/database-ops`	Database operations helpers.	Open
Developer Center	`/developer-center`	Operator page **Developer Center** at `/developer-center` — open from the sidebar or command palette.	Open
API Docs	`/api-docs`	OpenAPI / API documentation for /api/v1.	Open
API Playground	`/api-playground`	Interactive REST API playground.	Open
Webhook Tester	`/webhook-tester`	Test outbound webhooks.	Open
Terminal	`/terminal`	In-browser cluster/pod terminal over WebSocket.	Open
Plugins	`/plugins`	Operator page **Plugins** at `/plugins` — open from the sidebar or command palette.	Open
Resource Canvas	`/workspace`	Operator page **Resource Canvas** at `/workspace` — open from the sidebar or command palette.	Open
Widgets	`/widgets`	Customizable dashboard widgets.	Open
Debug	`/debug`	Debug tools for support cases.	Open
Kernel Info	`/kernel`	Kernel / node kernel information.	Open
Settings	`/settings`	Configure appearance, security, backup/DR, AI providers, and API access.	Open
Identity Center	`/identity-center`	Operator page **Identity Center** at `/identity-center` — open from the sidebar or command palette.	Open
Users	`/identity-center?tab=users`	Operator page **Users** at `/identity-center?tab=users` — open from the sidebar or command palette.	—
Auth Audit	`/identity-center?tab=review`	Operator page **Auth Audit** at `/identity-center?tab=review` — open from the sidebar or command palette.	—
Tenancy	`/tenancy`	Multi-tenant namespace scoping.	Open
Multi-Cluster	`/multi-cluster`	Multi-cluster fleet registration.	Open
Edge Center	`/edge-center`	Operator page **Edge Center** at `/edge-center` — open from the sidebar or command palette.	Open
Provider Portal	`/provider-portal`	Operator page **Provider Portal** at `/provider-portal` — open from the sidebar or command palette.	—
Status Page	`/status-page`	Public/internal status page builder.	Open
Support	`/support`	Operator page **Support** at `/support` — open from the sidebar or command palette.	Open

Workbench, wizards & centers (routed, not always in nav)

Page	Route	Purpose	Guide
VM workbench	`/vms/:namespace/:name`	Power, console, hardware, guest ops for one VM	Open
Create machine	`/vms/new`	Create VM wizard alias	Open
Consoles overview	`(from workbench)`	VNC, serial, RDP/SSH	Open
ConsoleHub	`/consolehub`	Multi-console launcher and session manager	Open
Console Sessions	`/console-sessions`	Session list (opens ConsoleHub sessions tab)	Open
Restore Wizard	`/restore-wizard`	Guided restore from snapshot/backup	Open
Onboarding	`/onboarding`	First-run wizard	Open
Atlas	`/atlas`	Hierarchical infrastructure browser	—
Applications	`/applications`	Application-centric workload view	Open
Kubernetes	`/kubernetes`	Cluster pulse center (edition-gated)	Open
VM Groups	`/vm-groups`	Logical VM cohorts and bulk operations	Open
AI Center	`/ai-center`	AI SRE / advisors	Open
Identity Center	`/identity-center`	SSO, MFA, access reviews	Open
Developer Center	`/developer-center`	API, CLI, Terraform, webhooks	Open
Backup / DR	`/backup-dr`	Backup and DR center	Open
Migration Factory	`/migration-factory`	Batch migration campaigns (links out to Transiva/h2kvm)	Open
Edge Center	`/edge-center`	Edge fleet overview	Open
Patch Center	`/patch-center`	Guest patch status and campaigns	Open
Marketplace	`/marketplace`	Deployable content marketplace	Open
Plugins	`/plugins`	Plugin catalog (preview)	Open
Forge	`/forge`	AI infrastructure workspace	Open
Workspace	`/workspace`	Infinite canvas multi-console workspace	Open
Machine Firewall	`/network-flow?tab=firewall`	Host and VM firewall posture	—
War Room	`/war-room`	Collaborative incident response surface	Open
Time Machine	`/time-machine`	Cluster DVR / point-in-time flight recorder	Open
Approvals	`/approvals`	Pending action approval queue	Open
Reports	`/reports`	Reports and exports center	Open
Task Center	`/tasks`	Long-running task tracking	Open
Support	`/support`	Support bundle and help	Open
Auth Audit	`/auth-audit`	Authentication audit trail	Open

Page	Route	Purpose	Guide
Security Operations	`/security?tab=operations`	Security operations hub	—

Related

- Customer docs home
- Page-by-page guides
- Feature Guide