ZYVORAI LABS · CUSTOMER DOCUMENTATION

Zeus OS

Getting Started

Visual day-2 control plane for KubeVirt and Kubernetes

2026-10-21

zyvor.dev · Confidential — for licensed customers

This guide gets a customer from “I have a URL” to first useful work in the web dashboard.

What you need

Requirement	Notes
Kubernetes cluster with **KubeVirt** installed	Zeus is day-2 ops — it does not bootstrap the cluster
Reachable Zeus OS URL	Often `https://<host>:30050` (NodePort) or `https://<host>:5050`
Login credentials	Provided by your platform admin (local / LDAP / SAML / OIDC)
Browser	Modern Chromium, Firefox, or Safari. **HTTPS required for in-browser VNC**

Optional: `kubectl` access is not required for normal UI work.

1. Open the dashboard

1. Open the URL your admin shared (example: `https://cluster.example:30050`).
2. If the browser warns about a self-signed certificate, confirm with your admin, then proceed (or install the org CA).
3. You should land on login, or directly on **Home** (`/`) if auth is disabled in a lab.

Common mistake: Port **5092** is GuestKit / Machina territory on some Zyvor stacks — not Zeus OS. Prefer the URL that ends in the Zeus NodePort (often **30050**) or the documented ingress host.

2. Sign in

Auth depends on how the deployment is configured:

Mode	What you do
Local users	Username + password from your admin
LDAP / Active Directory	Corporate directory credentials
SAML / OIDC	"Sign in with …" → identity provider
Lab only	`ZEUS_OS_NO_AUTH` — no login (never use in production)

API automation uses bearer tokens / API keys from **Settings → API access** or Identity Center — not the guest OS password.

Windows **RDP** prompts for the **guest** credentials, not your Zeus login.

3. Orient yourself (60 seconds)

1. **Home** (`/`) — chapter pulse, **Get the highlights**, and teaser into **Attention**, VMs, Health.
2. **Attention** (`/attention`) — ranked actions, Issue Stream, and day-2 activity when Home shows warnings.
3. **Sidebar / Finder** — centers such as VMs, Storage, Monitoring, Settings.
4. **Command palette** — open with the keyboard shortcut shown in the shell (typically ⌘K / Ctrl+K) and type a page name.
5. **Browse vs workbench** — inventory lists are safe to explore; power actions live on the VM workbench so production VMs are harder to disrupt by accident.
6. **Getting started checklist** — first-time visitors see a banner on Home; click **Getting started checklist** (or **Help → Getting Started**) for a short, role-aware task list (admins get cluster/team setup, everyone else gets "find/create a VM", "open a console", "check cost"). Progress is saved to your account, so it follows you across devices and browsers — not just this one tab.

See Using the Dashboard for navigation details.

4. Your first five workflows

A. Browse and power a VM

1. Go to **VMs** → `/vms`.
2. Filter by namespace or name.
3. Open a VM → `/vms/<namespace>/<name>` (workbench).
4. Use **Start / Stop / Restart / Pause** as needed.
5. Confirm status updates in the inventory.

Guide: Virtual Machines

B. Open a live console

1. From a **Running** VM workbench, open **Console → VNC** (graphical) or **Serial** (text).
2. VNC needs HTTPS. If the session is black, click **Focus** in the console toolbar.
3. For RDP/SSH: use **Remote access** to expose a NodePort, then connect with your OS client (downloadable `.rdp` or `ssh` command). VNC remains the in-browser default.

Guide: Consoles & remote access

C. Create a VM

1. Open **VM setup** → `/vm-setup` (or `/vms/new`).
2. Choose instance type / preference / template (or AI-assisted manifest if enabled).
3. For **Windows**: if Settings → Network shows Kryton **Connected**, prefer the Kryton catalog path (template IDs like `windows-11-enterprise`). Otherwise use Autounattend / ISO.
4. Review disks, network, and namespace.
5. Deploy — the VM appears under `/vms` (Kryton creates deep-link via `providerRef`).

Guides: Create a machine · Windows via Kryton

D. Snapshot and restore

1. **Snapshot Manager** → `/snapshot-manager` — take an on-demand or scheduled snapshot.
2. To recover: **Restore Wizard** → `/restore-wizard` and follow the guided restore.

Guide: Snapshots

E. Cost check and rightsizing

1. **Cost Intelligence** → `/cost-intelligence` — spend by VM / namespace.
2. **Rightsizing** → `/rightsizing` — idle / oversized recommendations.

Guide: Cost Intelligence

5. Optional: TUI and CLI

Same cluster, different surfaces:

```
# Terminal UI (k9s-style)
zeus-os
zeus-os production    # namespace filter

# Headless CLI (examples depend on install path)
zeus-os-cli --help
```

API: `/api/v1` on the same host as the dashboard. OpenAPI lives under **Developer Center** / **API Docs** (`/api-docs`).

Next steps

Role	Read next
VM operator	Page guides — Core
Platform admin	Admin basics
Security / network	PacketWolf
Full capability map	Feature Guide

If something fails at login or console, see Troubleshooting.

How the Zeus OS web shell works — so page guides make sense.

Surfaces inside the browser

Element	Purpose
Home / Mission Control	Chapter home + highlights band + Attention teaser
Sidebar / Finder tree	Primary navigation by product center
Workspace switcher	Quick jump: Dashboard, VMs, Kubernetes, AI, Storage, Monitoring
Command palette	Search any page or action by name
Top bar	Context (cluster/namespace), quick links (Settings, Terminal, API Docs)
Inspector / sheets	Detail panels without leaving the list
Workbench routes	Full-page ops for a single VM or object

Browse vs workbench (important)

Zeus separates **inventory** from **actions**:

- **Browse** (`/vms` , `/pods` , `/nodes` , …) — read, filter, compare, open details.
- **Workbench** (`/vms/:namespace/:name` , hardware studio, consoles) — start/stop, hot-plug, remote access, guest agent.

That design reduces accidental power actions on production fleets.

Finding any page

1. Sidebar section (Core, Cluster, Observe, Run, Security, Cost, More).
2. Command palette — type “packetwolf”, “velero”, “cost”, etc.
3. This manual’s PAGE_INDEX.md — every route with a one-line purpose.
4. Favorites (`/favorites`) — pin pages you use daily.

Every page guide includes **Operate from the console (UX)** — concrete clicks after you land on the route.

Namespaces and tenancy

Lists usually respect the active namespace filter (and tenant scope if multi-tenancy is enabled). If a VM “disappeared”:

1. Clear or broaden the namespace filter.
2. Confirm you are in the correct tenant (Identity / Tenancy).
3. Refresh — live watches may lag briefly after create/delete.

Consoles

Method	Where	Notes
VNC	VM workbench / ConsoleHub	HTTPS required
Serial	VM workbench	Works over HTTP or HTTPS
RDP / SSH	Remote access panel	Native OS client via NodePort
Multi-session	`/consolehub`, `/workspace`	Tabs and session policy

Keyboard and accessibility

- Command palette: ⌘K / Ctrl+K (exact binding shown in the shell).
- Escape closes sheets and overlays.
- Focus traps exist on modals — tab stays inside the dialog.

Settings you may need early

Setting area	Path	Why
Appearance / sidebar	`/settings/appearance`	Light or Dark theme, density, rail-only sidebar
Security	`/settings/security`	Session / policy (admin)
API access	`/settings/api-access`	Tokens for automation
AI providers	`/settings/ai-providers`	Optional LLM for wizards

Full admin env vars and production checklist: Admin basics and Handbook — Admin.

Related

- Getting Started
- Page-by-page guides

End-to-end jobs that span multiple pages. Use with the page guides.

Start-of-shift triage

1. Home — scan pulse and the Attention teaser
2. Attention — ranked actions, Issue Stream, day-2 activity
3. Incidents or System Health — drill down when correlation or host health is needed
4. VMs — act on VM-scoped recommended actions (guest agent, power, console)

Create → console → snapshot

1. VM setup — `/vm-setup`
2. Wait until status is Running on VMs
3. Open workbench → Console
4. Before changes: Snapshots

Maintain a node

1. Nodes — identify the node
2. Live Migrations — evacuate VMs (dry-run first)
3. Node Drain — `/node-drain`
4. Confirm VM Instances on remaining workers

Contain a noisy or compromised VM

1. Incidents — open or create context
2. PacketWolf — dry-run then apply containment
3. Console — inspect guest if needed
4. Remove containment when resolved

Cost waste sweep

1. Cost Intelligence
2. Rightsizing
3. Apply safer shapes via workbench / instance types
4. Re-check spend after metrics catch up

Backup before upgrade

1. Snapshot Manager and/or Velero
2. Backup Wizard if you want a guided checklist
3. Perform change
4. Restore Wizard `/restore-wizard` only if needed

Related

- Getting Started
- Feature Guide