EECS 495--Introduction to Database Systems
Homework Assignment 2
Due: Wednesday, November 25, 2015

1   Prove, or disprove the following inference rules for a relation   R
      with X, Y, Z, W subsets of R.

   a. $X \rightarrow Y$ and $Y \rightarrow Z$ imply $X \rightarrow YZ$
   b. $X \rightarrow Y$ and $Z \rightarrow W$ imply $XZ \rightarrow YW$
   c. $XY \rightarrow Z$ and $Z \rightarrow X$ imply $Z \rightarrow Y$

      Note: To prove an inference rule you need to use Armstrong's rules.
To disprove a rule it is sufficient to exhibit a relation (extension) which does violate it.

(15 pts)

2.   Given the relational schema R(A,B,C,D,E,F,G,H) with F = (ABH $\rightarrow$ C ; A$\rightarrow$ DE ;
BGH $\rightarrow$ F; F $\rightarrow$ ADH ; BH $\rightarrow$ GE).

Use the decomposition algorithm to obtain a lossless BCNF schema. Examine the functional
dependencies in F for violation of BCF in the order in which they appear above (i.e., consider
first ABH $\rightarrow$ C)

(20pts)

3.   Consider a database schema R=(A,B) that has only two attributes. Is an instance *r* of the
schema R always in BCNF ? If your answer is no explain briefly your reasoning., Otherwise, give
a proof that the claim is true.

`   (15 pts)

4.   Consider a relation R with the following set of dependencies F: = { A $\rightarrow$BC, B $\rightarrow$AC,
      C$\rightarrow$AB}. Obtain at least two canonical covers of F. Use the algorithm given in class.

5. Given the database schema R=(A,B, C) and a relation *r* on the schema , write an SQL query to test whether the functional dependency B →C holds in *r*. Also write an SQL assertion that enforces the functional dependency. Assume that no null values are present.

6. Consider the relation schema R =(A,B,C,D,E) with the following set of functional dependencies:

    F= { A→BC, CD →E, B →D, E→A).

a. Find the candidate keys of of R

b. Show that the following decomposition of R is a lossless-join decomposition:

    R_1=(A, B,C) and R_2=(A,D,E).