Diego's Doom Emacs Cheat Sheet

Non-Evil bindings. C- Ctrl · M- Alt/Meta. Run commands with M-x. Documents tasks according to my personal configuration, may not match defaults.

Create a Hugo blog post

Action	Shortcut	Command / next step
New post	C-c n n h	org-capture → h — enter a title.
Finish capture	C-c C-c	org-capture-finalize — jump to the new post.
Cancel capture	C-c C-k	org-capture-kill
Export current post	C-x C-s	save-buffer (org-hugo-auto-export is enabled).
	C-c C-e H	org-hugo-export-wim-to-md
Export all posts	C-c C-e A	Review changes before committing!
Change status	C-c C-t	org-todo — choose DONE when ready, then export again.

Fill in the description before finishing capture; replace <write here> with the body afterward. Export with point inside the post. TODO / DRAFT mean draft; DONE means non-draft. Export writes Markdown; it does not deploy.
Source: under Ideas in ~/Personal/websites/zzamboni.org/content-org/zzamboni.org. The template supplies an ID and a YYYY-MM-DD-title-slug bundle, exporting to content/post/<bundle>/index.md.
Check the property drawer: EXPORT_HUGO_CUSTOM_FRONT_MATTER defaults to :featured_image / images/tram-zurich.jpg :toc false — adjust for the post.

Filter and focus on Org headings

Use a sparse tree to find draft posts in the current Org file, then narrow to one post for distraction-free editing.

Action	Shortcut	Command / next step
Show draft headings	C-c / t	org-show-todo-tree — enter DRAFT ancestors remain visible.
Narrow to one subtree	C-x n s	org-narrow-to-subtree — show only the current heading and children.
Restore entire buffer	C-x n w	widen — remove narrowing.
Edit in separate buffer	C-c C-x b	org-tree-to-indirect-buffer — edit subtree in an indirect buffer.
Reset outline visibility	S-TAB	org-shifttab — cycle global visibility after sparse-tree filtering.
Expand archived heading	C-c C-<TAB>	org-cycle-force-archived — cycle an ARCHIVE subtree; point on its heading.

Workflow: use C-c / t to find DRAFT headings; move to the desired heading and use C-x n s to focus on its subtree. Use C-x n w afterward. Alternatively, C-c C-x b opens an indirect buffer that shares the original text, so edits also update the source buffer.

Insert images into posts or Org documents

Place point beneath the appropriate heading, inside the post for Hugo.

Action	Shortcut	Command / next step
Paste image	C-y	zz/org-smart-yank — enter a filename.
Force text yank	C-u C-y	org-yank via the smart-yank helper.
Copy image file	C-c C-a c	org-attach → copy; select the file.
Download image	C-c C-a u	org-attach-url — enter the direct image URL.
Insert link	C-c C-l	org-insert-link — select the stored attachment.
Toggle previews	C-c C-i	org-toggle-inline-images
	C-c TAB	
	C-c C-x C-v	

Clipboard: copy the image itself. In graphical Emacs, smart yank uses yank-media for PNG/JPEG/WebP/GIF; otherwise it uses org-yank. Use M-x yank-media to invoke media paste explicitly.
File or URL: after attaching, insert the stored link with C-c C-l. Leave the description empty to display the image. Dragging an image file into the buffer also attaches it automatically.
Storage: attachments/ beside the Org file, partitioned by ID; child headings inherit the post's ID. Keep attachments with the source. Links look like [[attachment:photo.png]]. Export the post again after changes.
Image Previews: The 300-pixel buffer preview limit does not set the exported image size.

Others

Action	Shortcut	Command / next step
Reveal / hide	C-c t v	visible-mode — toggle hidden text in this buffer.
Export PDF	C-c C-e y	org-typst-export-to-pdf
Export and open	C-c C-e Y	Export PDF, then open it.

PDF export uses Typst via ox-typst (M-x org-typst-export-to-pdf). Typst downloads the package on first use; subsequent exports use its cache. Add new use cases as top-level headings with shortcuts and command names.