Diego's Doom Emacs Cheat Sheet

Non-Evil bindings. C– Ctrl · M– Alt/Meta. Run commands with M–x. Documents tasks according to my personal configuration, may not match defaults.

Create a Hugo blog post

Action	Shortcut	Command / next step
New post	C–c n n h	org-capture → h — enter a title.
Finish capture	C–c C–c	org-capture-finalize — jump to the new post.
Cancel capture	C–c C–k	org-capture-kill
Export current post	C–x C–s	save-buffer (org-hugo-auto-export is enabled).
	C–c C–e H H	org-hugo-export-wim-to-md
Export all posts	C–c C–e H A	Review changes before committing!
Change status	C–c C–t	org-todo — choose DONE when ready, then export again.

Fill in the description before finishing capture; replace <write here> with the body afterward. Export with point inside the post. TODO / DRAFT mean draft; DONE means non-draft. Export writes Markdown; it does not deploy.
Source: under Ideas in ~/Personal/websites/zzamboni.org/content-org/zzamboni.org. The template supplies an ID and a YYYY-MM-DD-title-slug bundle, exporting to content/post/<bundle>/index.md.
Check the property drawer: EXPORT_HUGO_CUSTOM_FRONT_MATTER defaults to :featured_image /images/tram-zurich.jpg :toc false — adjust for the post.

Insert images into posts or Org documents

Place point beneath the appropriate heading, inside the post for Hugo.

Action	Shortcut	Command / next step
Paste image	C–y	zz/org-smart-yank — enter a filename.
Force text yank	C–u C–y	org-yank via the smart-yank helper.
Copy image file	C–c C–a c	org-attach → copy; select the file.
Download image	C–c C–a u	org-attach-url — enter the direct image URL.
Insert link	C–c C–l	org-insert-link — select the stored attachment.
Toggle previews	C–c C–i	org-toggle-inline-images
	C–c TAB	
	C–c C–x C–v	

Clipboard: copy the image itself. In graphical Emacs, smart yank uses yank-media for PNG/JPEG/WebP/GIF; otherwise it uses org-yank. Use M–x yank-media to invoke media paste explicitly.
File or URL: after attaching, insert the stored link with C–c C–l. Leave the description empty to display the image. Dragging an image file into the buffer also attaches it automatically.
Storage: attachments/ beside the Org file, partitioned by ID; child headings inherit the post's ID. Keep attachments with the source. Links look like [[attachment:photo.png]]. Export the post again after changes.
Image Previews: The 300-pixel buffer preview limit does not set the exported image size.

Filter and focus on Org headings

Use a sparse tree to find draft posts in the current Org file, then narrow to one post for distraction-free editing.

Action	Shortcut	Command / next step
Show draft headings	C–c / t	org-show-todo-tree — enter DRAFT ancestors remain visible.
Narrow to one subtree	C–x n s	org-narrow-to-subtree — show only the current heading and children.
Restore entire buffer	C–x n w	widen — remove narrowing.
Edit in separate buffer	C–c C–x b	org-tree-to-indirect-buffer — edit subtree in an indirect buffer.
Reset outline visibility	S–TAB	org-shifttab — cycle global visibility after sparse-tree filtering.
Expand archived heading	C–c C–<TAB>	org-cycle-force-archived — cycle an ARCHIVE subtree; point on its heading.

Workflow: use C–c / t to find DRAFT headings; move to the desired heading and use C–x n s to focus on its subtree. Use C–x n w afterward. Alternatively, C–c C–x b opens an indirect buffer that shares the original text, so edits also update the source buffer.

Others

Action	Shortcut	Command / next step
Reveal / hide	C–c t v	visible-mode — toggle hidden text in this buffer.
Export PDF	C–c e y	org-typst-export-to-pdf
Export and open	C–c e Y	Export PDF, then open it.

PDF export uses Typst via ox-typst (M–x org-typst-export-to-pdf). Typst downloads the package on first use; subsequent exports use its cache. Add new use cases as top-level headings with shortcuts and command names.

This layout uses cram-snap 0.2.2, Source Sans 3, and Cascadia Code.