Q-Learning □□ SDN □□□ □□□ □□

A Q-Learning based Routing Optimization Model in a Software Defined Network

Yupeng Wang, Xin Zhou, Xinyue Fan

Shenyang Aerospace University

IEEE 19th Int'l Conference on Embedded and Ubiquitous Computing (EUC), 2021

□□ □□

□□	A Q-Learning based Routing Optimization Model in a Software Defined Network
□□	Yupeng Wang, Xin Zhou, Xinyue Fan
□□	Shenyang Aerospace University / Liaoning General Aviation Academy
□□□□	IEEE 19th Int'l Conference on Embedded and Ubiquitous Computing (EUC)
□□□□	2021

□□ □□

[□□ □□]

SDN(Software Defined Network) □□□□ □□□ QoS □ □□□□
□□□ □□□ □□□□ □□ , Q-Learning □□□ □□□ □□□□□ □□□□ .

□□□ □ □□□ □□□□ □□□ QoS □□□ □□□ □□□□
□□□ □□ □□ (Reward Function) □ □□□□ □□ □□□ □□□□□ .

[□□ □□]

1. SDN Controller □ Q-Learning □ Agent □ □□
2. □□□□ □□ (State) □ □□ □□ □ (Action) □□
3. □□□ + □□□ □□□ □□□ □□ □□ □□
4. epsilon-greedy □□□□ □□ / □□ □□
5. Q-Table □□ -> □□ □□□ □□□ □□

[□□ □□]

- □□ □□□□ □□□□ □□ :
  □□ □□ □□ **43.38%** □□
  □□ □□ □□ **69.57%** □□

- 30% □□ □□□ □□□□ □□□ □□ □□
- 가 □□□ □□ □ □□□□□

□□ □□ □□

[□□ □□□□□ □□]

1. □□ □□ + □□□ □□□ □□□□□ □□
   -> □□□□ □□ □ □□□□ □□□
2. □□ □□□ QoS □□ □□ □□ □□
3. □□ □□□□ (Shortest Path) □□□□□
   □□□□ □□□ □□□ □□□□ □□
4. 가 □□ □□□□ □□□□□
   □□ □□ □□ □□

[□ □□□ □□□□□ □□ □□]

SDN □□□□
- □□□ □ □□□ (non-identical) □□□□
- □□□ (heterogeneous) QoS □□□ □□□□

□□ □□ (Delay) □ □□□□□□
- □□□ QoS □ □□□□

□□□ □□□ □□□ □□□□ □□
-> Q-Learning □□ □□

□□ □□ : □□□ □□ □□ (Reward Function) □□

□□□ □□ □□ : SDN + Q-Learning

STEP 1

SDN Controller (Agent)

□□□□ □□ □□ □□
(□□□□ , □□□ , □□□)

STEP 2

Q-Learning □□□□

□□□ □□ □□ □□□
□□ □□ (ε-greedy)

STEP 3

Q-Table □□

□□ □□□ □□□
□□ □ □□

[□□ □□□□]

SDN Controller □ Agent □□ □□□□ □□□ □□□□□□ Q-Learning □□ □□
□□□ (Bandwidth) □ □□ □□ (Delay) □ □□□ □□□ □□ □□□ □□ (Q-Table) □□

Q-Table □□ □ , □□□ □□□ Q-Table □ □□ □□□ -> □□ □□ □□□ + QoS □□

□□□□ □□ (1) : Agent & State

Agent (□□□□) = SDN Controller

[□□]
- □□□□ □□ □□ (Global View) □□ □□
- Q-Learning □□ □□□ □□□□ □□
- Flow Table □ □□□□ □□

[□□]
- 가 □□□□□□□□ □□□□
- □□□ □□ □□□□□□□ Q-Table □□
- □□ □□ □ □□ □□□□ □□□ □□

State (□□)

[□□] s(h,k) = i, i = [1, 10]

[□□]
- □□ □□□ k 가 □□□ □□□ □□ i
- □ (hop) h □□□ □□□□ □□

[□□ □□]
- □□□□ □□□□ □□ Y[i,j]
  (Y[i,j]=1: □□ / Y[i,j]!=1: □□□)
- 가 □□□□ Ba (0~1 □□□)
- □□□ □□ □□□ T

□□□□ □□ (2) : Action & Reward

Action (□□)

[□□] a(h,k) = i, Y[i,h]=1 □□□□□

- □□ □ (hop) □□ □□□ □□□ □□ □□
- 가 □□□ □□□□ □□ □ □□□□□
- □□ : epsilon-greedy (□□ + □□)

Reward (□□) - □□□ □□ □□

[□□ □□ □□] (□□□ □ □□ □□)

R = B1*(1 - delay) + B2*(Bmin/Ba)

[□ , Ba < Bmin □□ R = B3*(Ba - Bmin)]

delay □□□□ , Bmin/Ba □□□□ -> 가 □□

B1, B2 : QoS 가 □ □□(□□ □□)

[□□ □□ □□ □□]

□□ □□ □□□ □□ :

- □□ □ □ □□ □□ □□□ □□
- -> □□ □□□ / □□ □□

□□ □□ □□□ 3 가□□ □□ :

(1) delay □□□ :

delay = T / (SE * Ba)

(T: □□□□ , SE: □□□□□□ , Ba: □□□□□)

(2) □□□ □□□ □□□ :

Bmin/Ba (가 □□ □ □□□□)

(3) 가 □□□□ □□ -> □□ □□

Policy Evaluation - Q □ □□□□

$$Q(s, a) \leftarrow Q(s, a) + a\,[\,R + g * \max Q(s', a') - Q(s, a)\,]$$

a (□□□ , 0<a<1)	□□□ □□□ □□ Q □□ □□□□ □□
g (□□□□ , 0<g<1)	□□ □□□ □□□ g 가 □□□ □□ □□ □□
R(h,k) (□□ □□)	□□ □□□ □□ □□ □ h, □□□ k □ □□
max Q(s', a')	□□ □□□□□ □□ Q □ -> □□ □□ □□□

-> □ □□ □ Q 가ㅅ 가 □□□ □□□ □□□□□ □□ □□

Policy Control - epsilon-greedy □□ □□

[□□ □□ □□]

pi(a | s) = P(a = a* | s(h,k) = s)

epsilon-greedy □□ :
- □□ epsilon -> □□□ □□ (□□)
- □□ 1-epsilon -> □□ □□ (□□)

□□ □□ □□ □ : epsilon = 0.3
(□□□ □□□□□ □□ □□□)

□□ □□ :
Q-Table □ □ □□ □□□ □□ □□□
□□ □□ -> □□ □□ □□

Algorithm: Q-Learning Routing

1 Q(s, a) □□□ □□□
2 □ h, □□ s(h,k) □□ :
3 a(h,k) <- epsilon-greedy □ □□ □□
4 □□ □□ -> □□ R(h,k) □□
5 □□ □□ s(h+1,k) □□
6 Q □ □□□□ (□□□□ □□ □□)
7 h+1 □ □□□□ □□
8 Q-Table □□ □ □□

Q-Learning □□□ □□ □□ □□

(1) □□ □□

SDN Controller 가
□□□□ □□ ,
□□□ , □□□ □□

(2) □□ □□

Q-Table +
epsilon-greedy □
□□ □□□ □□

(3) □□ □□

Flow Table □□
□□□□ □□
□□□ □□

(4) □□ □□

□□ + □□□ □□
□□ □□ R □□
(□□□ = □□)

(5) Q-Table □□

a, g □ □□□
Q □ □□□□
□□□□ □□

[□□ □□]

□□ Q-Table = □□ □□□ □□
□□□ □□□ Q-Table □ □□ □□□
-> □□ □□ □□□ + QoS □□

□□ □□ □ □□ □□

[□□ □□]

- □□□ 10 □ □□□□ □□□□
- □□ □□□ Ba: 0~1 □□
- □□ : Shortest Path □□□□
- □□ epsilon = 0.3 (5,000 □ □□)

□□ □□
□□□
43.38%
(epsilon=0.3)

□□□ □□
□□□
33.11%
(epsilon=0.3)

□□ □□
□□□
69.57%
(epsilon=0.3)

□□□□	□□ □□	Gain	□□ □□	Gain	□□ □□	Gain
Q-Learning (e=0.3)	**2.01**	**43.38%**	**2.00**	**33.11%**	**4.29**	**69.57%**
Q-Learning (e=0.2)	2.31	34.93%	2.28	23.75%	6.26	55.60%
Q-Learning (e=0.5)	2.08	41.41%	2.07	30.77%	4.40	68.79%
Shortest Path	**3.55**	**-**	**2.99**	**-**	**14.10**	**-**

[□□□] 30% □□ □□□ □□ (delta) □□ □□ □□ -> 까 □□□ □□ □ □□□□□

□□

[□□ □□]

SDN □□□□ □□□ □□□ , □□□ QoS □□□ □□
□□□ □□ □□□ □□□□ Q-Learning □ □□

[□□ □□]

□□ □□□□ □□ □□ □□ 43%, □□ □□ 69% □□
-> □□□ QoS □□ □□

[□□□]

30% □□ □□□ □□□□ □□ □□
-> 가 가 □□ □□ □ □□□□

[□□]

RL □ SDN □□□□ □□ □□□ □□
-> □□□ □□ □□□□ □□□ □□ □□