9 in Ratchet Self-Locking Pliers

Ratchet-assisted clamping · 33 mm jaw opening · 55 high-carbon steel



KEY COMPONENTS

Fig. 1 - Parts overview

1 **Serrated jaws**
Cross-cut teeth bite round, square and irregular parts.

2 **Long-nose tip**
Narrow profile for work in tight spaces and at depth.

3 **Pivot plate**
Main joint; carries the full clamping load.

4 **Ratchet sector**
Toothed arc holds the jaw position without hand pressure.

5 **Release lever**
Press to disengage the ratchet and open the jaws.

6 **Two-tone grip**
TPR over steel. Grip and comfort only - not insulation.

SPECIFICATIONS

Overall length	230 mm / 9.06 in
Max. jaw opening	33 mm / 1.30 in
Body	55 high-carbon steel, hardened faces
Handle	TPR over steel, orange / grey
Locking	Ratchet with quick release
Pack	1-piece set / 2-piece set

IN THE BOX

1-piece set	1 x pliers · 1 x user manual
2-piece set	2 x pliers · 1 x user manual

What the ratchet does
The toothed sector holds the jaws wherever you stop squeezing, so the tool keeps clamping after you let go. The release lever frees it in one press - no need to fight the handles open.

READ BEFORE USE - NOT AN INSULATED TOOL
The grips give comfort and grip only. Never use the pliers on or near a live circuit: switch off, lock out and prove the circuit dead first. Wear ANSI Z87.1 eye protection. Stay within the 33 mm jaw opening and do not cut hardened or spring steel. Never extend the handles with pipe, and never hammer the tool. Inspect before each use - retire it if the jaws are cracked, the teeth are worn flat or the pivot has play.

How to Use

The ratchet does the holding. Set the opening, squeeze once, and both hands are free to work.

STEP BY STEP

1. **Open and set the gap**
   Pull the handles apart until the jaw gap is just wider than the workpiece, so the teeth can bite as the jaws close.
2. **Seat the tool**
   Place the jaws square to the part. Seat hex fasteners on the flats, and round parts deep in the jaw where both rows of teeth engage.
3. **Squeeze once to lock**
   One smooth squeeze engages the ratchet tooth by tooth. Release your hand - the tool stays clamped on the part.
4. **Work, then release**
   Load along the jaw axis, not sideways. Press the release lever to open; never pry the jaws apart or twist the handles.

If the tool stays clamped
Unload the part first - stop pulling or turning - then press the release lever all the way. Do not lever the jaws open with a screwdriver.

WORKING TECHNIQUES

Task	How
Grip / hold	Clamp across flats or rod; keep the load along the jaw axis.
Turn	Hex up to 33 mm, light torque. Use a proper wrench for seized bolts.
Bend	Grip close to the pivot for leverage; bend progressively.
Cut soft wire	Cut at the jaw root, one firm squeeze. Not for hardened or spring steel.

CARE

Wipe the jaws dry after use and brush metal dust out of the ratchet teeth. Put one or two drops of light oil on the pivot and ratchet monthly. Keep oil and solvent off the grips. Store closed and dry.

TROUBLESHOOTING

Symptom	Likely cause	What to do
Does not stay locked	Gap set wider than the part; ratchet not engaged	Release, set a smaller gap, clamp again with one firm squeeze
Will not release	Lever not pressed fully, or the jaw is still loaded	Stop loading the part, then press the lever all the way
Ratchet slips	Oily or worn teeth, or the part is harder than the jaw	Clean and dry the teeth; oil only at the pivot; use the right tool for hardened steel
Stiff handles	Dirt or dried lubricant in the joint	One drop of light oil, then cycle the handles

Set the gap first
Squeezing the jaws over a part that is too big loads the jaw arms and the pivot, not the ratchet.

Know when to retire it
Cracked jaw base, teeth worn flat, or a pivot with visible play means replace - repairs are not safe.

Use the right tool
Hardened or spring steel belongs in bolt cutters. The jaws are hard, but the handles are not a press.

WARRANTY AND SUPPORT

Covered against defects in materials and workmanship; the term is as stated on the product listing at purchase. Wear, rust and misuse are not covered. Message us through your Amazon order page (Seller Messages) with your order number and a photo of the issue - we reply to the same thread.