

Terrain-Aware, Latency-Robust Control for Off-Road Autonomy and Teleoperation on Deformable Terrain

Kyle Sha, Zhenhao Zhou, Radu Serban, Dan Negrut

Department of Mechanical Engineering, University of Wisconsin–Madison

1513 University Ave., Madison, WI 53706, USA

Email: {kasha2, zzhou292, serban, negrut}@wisc.edu

Abstract—We present a modular, latency-aware framework for safe shared and autonomous control of ground vehicles on deformable Soil Contact Model (SCM) terrain. The runtime is organised around six explicit swap points — command source, safety filter, collision warning, tire model, terrain estimator, and latency profile — each declared as a Python `Protocol` and resolved through a per-role registry, so new variants register without touching consumers. A differentiable neural tire surrogate is embedded in an *acados* nonlinear MPC (NMPC), a sliding-window estimator re-conditions the surrogate online from inertial and wheel-speed signals, and an asymmetric throttle disturbance observer closes the residual soft-soil speed gap. A two-layer obstacle-avoidance stack pairs in-horizon NMPC softplus barriers with a swappable downstream safety filter (DOB-CBF, MPPI, or gradient NMPC); a parallel terrain- and latency-aware forward collision warning re-uses the same tire surrogate to derive a soil-conditioned braking budget and advise the operator without overriding commands. `Chrono::Vehicle` inside `Chrono::HIL` provides the plant; a learned 5G profile drives the configurable command and camera delays. A multi-seed evaluation shows the terrain-aware neural stack cuts median RMS crosstrack error by 35–43 % over SCM-calibrated Pacejka and TMeasy baselines in the live-estimator regime (recovering near-oracle tracking with no prior terrain knowledge), the disturbance observer recovers part of the soft-soil speed gap at a small tracking cost, both safety filters cut collisions by more than 90 % under the learned 5G profile, and the warning predicts stopping distance to within 0.17 m mean absolute error against actual `Chrono` brake stops.

Index Terms—Off-road teleoperation, soil contact model, neural surrogate, model predictive control, safety filter, MPPI, 5G latency, `Chrono`.

I. INTRODUCTION

Off-road teleoperation must contend with two compounding sources of uncertainty: time-varying soil mechanics that rigid-terrain tire models cannot capture without per-deployment recalibration [3], [1], and time-varying network latency that destabilises naive shared-control arbitration [2], [8]. Existing approaches address these in isolation: terrain-adaptive trajectory planning typically assumes nominal communication, while delay-compensated safety filters typically assume rigid-terrain dynamics. This paper integrates the two into a single closed-loop framework and reports a multi-seed empirical evaluation of every architectural choice.

The framework spans four coupled layers around a single deformable-terrain plant: (i) a terrain-aware NMPC built on a

differentiable neural tire surrogate; (ii) an online terrain estimator that re-conditions that surrogate from onboard sensors; (iii) a two-layer obstacle-avoidance stack (in-horizon barriers + swappable downstream safety filter) for both autonomous and teleoperated commands; and (iv) a terrain- and latency-aware forward collision warning that re-uses the same tire surrogate to provide an advisory channel when an override-style filter is undesirable. All four layers share the same `Chrono::Vehicle` plant inside `Chrono::HIL`, the same ZeroMQ messaging substrate, and the same benchmarking harness, so the architectural choices are comparable on the same matrix.

Concretely, this work contributes:

- 1) A modular framework (Section II) in which six runtime roles are declared as Python `Protocols` and resolved through per-role registries; a runtime conformance test rejects any variant that drifts from its declared API, making the swap-ability claim structural rather than rhetorical.
- 2) A differentiable neural SCM tire surrogate (Section III) that augments the static MLP of Dallas et al. [3] with rate-aware and axle-rate-aware variants, exported as a CasADi expression through which the *acados* NMPC auto-differentiates at every horizon stage.
- 3) A sliding-window online terrain estimator (Section IV) that recovers Bekker n from inertial and wheel-speed signals alone and re-conditions the surrogate over the controller-to-sim socket. The deployed estimator fuses a learned lateral-force channel with a proprioceptive window-MLP inside a state-augmented UKF [3]; on a 100-soil sweep along the clay–dirt–sand Bekker–Mohr manifold (`Chrono` SCM, live closed-loop NMPC), it tracks n across the full deployable range with a 4.5 % median $|\Delta n|/n_{\text{true}}$ (94 % of soils within ± 20 %) — the best of four backends, and well ahead of the force-only UKFs, which saturate on firm soils once closed-loop slip is small.
- 4) An asymmetric throttle disturbance observer (Section V) that closes the residual soft-soil speed gap left by the open-loop longitudinal integrator.
- 5) A two-layer obstacle-avoidance stack (Section VI) pairing in-horizon NMPC softplus barriers with a swappable

downstream safety filter: an intent-preserving DOB-CBF-QP inspired by [8], an MPPI predictive safety filter with seeded recovery trajectories, and a gradient-based NMPC variant on the same rollout.

- 6) A learned 5G latency model (Section VII) that drives a queue-load delay on both the operator-command and camera paths and exercises closed-loop robustness.
- 7) A terrain- and latency-aware forward collision warning (Section VIII) that re-uses the rig tire surrogate for a soil-conditioned braking budget, advises without override, and matches actual Chrono brake stops to 0.17 m mean absolute error.
- 8) An open-source benchmarking suite (Section IX) that reproduces every non-HIL figure and CSV from a single command.

Several of these components individually extend prior work incrementally. The contribution of this paper is their *integration* and head-to-head evaluation on one deformable-terrain plant, one messaging substrate, and one benchmarking harness — which is what exposes the cross-layer interactions that isolated studies cannot, such as the safety filter re-using the controller’s tire surrogate for its traction-budget rollouts and the collision warning re-using the same soil-conditioned braking budget. Terrain adaptation and delay-compensated safety have previously been studied separately; here they are measured together on the same matrix.

II. SYSTEM ARCHITECTURE

The runtime is organised around six explicit swap points (Fig. 1, Table I). Each swap point is a single Python protocol with a corresponding registry; adding a new variant is a one-line registration with no edits to the consumers. Chrono::Vehicle simulates an HMMWV on a Soil Contact Model (SCM) [4] patch within Chrono::HIL [11]. The simulation and controller nodes run as separate operating-system processes and exchange messages over ZeroMQ pub/sub sockets: a vehicle-state message at the physics state rate (100 Hz), a control command at the controller rate (10 Hz), and a life-cycle status message. The control command carries the most recent live terrain estimate as optional fields so the sim-side safety filter re-conditions itself without a separate high-priority channel; the deployed estimator is *n*-only, and the remaining Bekker–Mohr fields are mapped from $\hat{n}$ along the terrain manifold before attachment. Piggy-backing is required because the controller-to-simulation socket is latest-only (conflating), which would drop a separate terrain-update message arriving between estimator ticks.

Both processes pace to wall clock, and the benchmark harness parallelises across runs, so a single workstation completes the static-terrain tire benchmark of Section III-B in well under an hour.

The split between process-boundary contracts (ZMQ messages) and in-process Protocol contracts is deliberate. Any controller that subscribes to the vehicle-state message and publishes the control command can replace the acados NMPC without modifying the simulator; this is how the tire-model

TABLE I: The six swap points of the framework. Each role is defined by one Protocol and resolved through one registry. A conformance test instantiates one of each shipped variant and checks it against the declared Protocol, so the swap-ability is structural rather than rhetorical.

Role	Protocol method	Shipped variants
Command source	next_command	NMPC, G29, WASD
Safety filter	filter	DOB-CBF, MPPI, NMPC, none
Collision warning	evaluate	TTC
Tire model	predict	rate-MLP, axle-rate-MLP, Pacejka, TMeasy
Terrain estimator	observe/estimate	force+proprioceptive UKF, window-MLP, Bekker/NN-UKF
Latency profile	delay	constant, replay, learned 5G

variants of §III are evaluated. Human teleoperation is reduced to the same normalised steering, throttle, and brake command channels before actuation, so the safety layer screens either autonomous or human commands behind one contract. Safety filters and the forward collision warning live behind their own Protocols, are resolved by name through their registries, and never share state — the warning attaches to the same vehicle-state stream but never writes to the command path, so it composes with any selected filter (including the no-filter case) without re-plumbing. This is what makes the suite a framework rather than a single monolithic controller demonstration.

III. DIFFERENTIABLE SCM TIRE SURROGATE

A multilayer perceptron (MLP) maps the tire operating point (κ, α, F_z, u) , steering rate, and soil parameters $\theta_{\text{soil}} = (K_\phi, K_c, n, c, \phi, k)$ (Bekker–Wong-style rig inputs [6]) to longitudinal and lateral tire forces (F_x, F_y) . Where Dallas et al. [3] use a static MLP only, we train three variants: the static baseline, a *rate-augmented* MLP that takes the steering rate $\dot{\delta}$ as an explicit input, and an *axle-rate* MLP with per-axle rate inputs $(\dot{\delta}_f, \dot{\delta}_r)$. All three export as CasADi expressions through which the acados solver auto-differentiates at every horizon stage. Two surrogate generations are kept distinct: a *tire-rig surrogate* trained from controlled single-tire SCM sweeps (a reproducible baseline against [3]) and a *whole-vehicle surrogate* trained from closed-loop Chrono::Vehicle HMMWV runs (the model used for the main NMPC and safety-filter results). The first generation tests whether the single-tire learning problem is solved; the second tests whether the controller sees accurate forces in the regimes it actually visits.

A. Training data: from rig sweeps to closed-loop rollouts

The training-data pipeline followed two generations. The first generation, mirroring the rig protocol of [3], drove a single SCM tire over a Cartesian grid of $(\kappa, \alpha, F_z, \theta_{\text{soil}})$ and recorded the SCM ground-truth force at every queried operating point. Rig training is appealing because every label is exact, no closed-loop feedback confounds the supervision, and the data collection parallelises trivially. It produced surrogates with rig-grid coefficient of determination $R^2 \gtrsim 0.95$ on a held-out rig split, and it is therefore retained as the controlled baseline. The




Fig. 1: Shared-control framework. Yellow nodes are in-process swap points resolved by the corresponding registry; blue/green nodes are process-boundary or operator endpoints. Solid arrows are runtime data flow over ZeroMQ; dashed arrows are the latency-affected operator paths; dotted arrows are tire-surrogate queries (build-time CasADi export plus per-tick safety-filter rollouts).

second generation targets the controller’s deployed operating distribution: rather than sampling an open-loop tire grid, it collects training tuples from the closed-loop stack itself so the labels include the high-yaw-rate, lateral-acceleration, and body-frame force conventions that arise during aggressive references on deformable soil.

For the closed-loop generation, a parallel pool of randomised (terrain, path, speed, bumpiness, seed) scenarios runs the NMPC against Chrono::Vehicle and logs the live operating point alongside the SCM ground-truth force. The deployed whole-vehicle surrogate `vehicle_rate_64_32_lhs` is trained on **800 such scenarios**, LHS-sampled jointly over the soil parameters in `TRAINING_RANGES_V6` (Bekker-Mohr box around clay/dirt/sand) and the maneuver axes — 264 sand, 270 dirt, 266 clay; 214 sinusoidal, 201 right-left, 200 lane-change, 185 double-lane-change; commanded speeds randomised in $[3, 7]$ m/s; bumpiness and rock-count randomised; each scenario simulated for ~ 10 s at the controller rate. The aggregated training table contains approximately 1.85M rows of $(\kappa, \alpha, F_z, u, \delta) \rightarrow (F_x, F_y)$ tuples (front + rear axle per tick) — fewer samples than the rig’s ~ 100 k single-tire grid but drawn from the operating-point distribution the deployed MPC actually visits. The resulting distribution is matched to the regime the planner actually visits, and the body-frame convention is enforced at the collection step rather than at the import step. The three checkpoints used throughout this paper’s pilot sweeps are all closed-loop trained; two rig-trained checkpoints from the first generation are retained as

a baseline so the rig-versus-closed-loop comparison remains reproducible (Sec. III-B selects them as the `rig_static` and `rig_rate` model identifiers).

The NMPC queries the surrogate at each stage. The longitudinal traction budget F_x^{trac} is evaluated at reference slip κ_{ref} , $\alpha = 0$, with axle loads F_z , speed u , and θ_{soil} taken from terrain presets or the online estimator. Cornering forces F_y use the live operating point (κ, α, F_z, u) at each stage.

The two *learned terrain estimators* are trained on deliberately different data, and the distinction matters for reading their results. The deployed sliding-window MLP (`terrain_window_mlp`, Sec. IV) regresses the Bekker exponent n from a 4 s window of proprioceptive statistics; it is trained on 180 LHS soil cells $\times$ 20 scenarios, split between closed-loop NMPC tracking (sinusoidal / lane-change / right-left at $\{4, 6, 8\}$ m/s) and scripted open-loop cruise-bias runs, at bumpiness $\in \{0, 4\}$ only — the envelope that bounds its in-distribution claims (Table II). The NN-UKF tire surrogate (`vehicle_fy`, Sec. IV-B) is instead trained on 300 *scripted* sinusoidal-steer runs with no controller in the loop, half at constant open-loop throttle and half under a PI cruise loop, over a widened soil box so the canonical presets are interior points. The throttle convention thus differs across models — the deployed surrogates see NMPC cruise throttle, the rig surrogate sees none (fixed rig), and the UKF surrogate sees a mix of constant-open-loop and PI-cruise throttle — so each model’s accuracy is reported only within its own excitation envelope.

TABLE II: Training-data provenance for the learned models. “Loop” distinguishes scripted open-loop excitation from closed-loop NMPC tracking; bumpiness is the terrain-roughness level present during training (and hence the envelope within which each model is evaluated).

Model (role)	Loop / excitation	Throttle	Bumpiness	Soil / n coverage
rig_rate (rig tire baseline)	open-loop single-tire rig, scripted κ/α	— (fixed rig)	—	LHS around clay/dirt/sand
vehicle_rate (deployed NMPC tire)	closed-loop NMPC, 4 paths	NMPC cruise, [3, 7] m/s	{0, 2, 4}	full Bekker–Mohr LHS box
terrain_window_mlp (deployed estimator)	closed-loop NMPC + scripted open-loop	NMPC + cruise-bias	{0, 4}	$n \in [0.40, 1.30]$, 180 LHS cells
vehicle_fy (NN-UKF tire, Sec. IV-B)	scripted sinusoidal steer, no controller	half const. OL / half PI-cruise	0	widened $n \in [0.35, 1.35]$

B. Static-terrain benchmark

The standard MPC is swept over the three deployable tire models (Pacejka, TMeasy, and the deployed vehicle NN rate-MLP) across all three terrains (clay, dirt, sand), three reference paths (sinusoidal, lane-change, right-left), three reference speeds $v_{\text{ref}} \in \{5, 7, 9\}$ m/s, three bumpiness levels, and five random seeds, for a total of 1215 closed-loop trials. Sensor noise is enabled in every trial. To keep the comparison fair, the analytical baselines are *not* run at rigid-road defaults: their peak lateral friction is calibrated to a single global $\mu = 0.42$ by least-squares fit to the pooled SCM tire-rig forces across the soil box (the SCM peak $|F_y|/F_z$ ranges from ≈ 0.18 clay-like to ≈ 0.47 sand-like, far below a rigid road), with the magic-formula and TMeasy shape factors kept at their standard values; one global set is used for every terrain because the controller has no per-terrain knowledge. This removes the rigid-road over-grip that otherwise inflates the baseline error, so the reported gap reflects what a fixed analytical parameterisation structurally cannot capture, not a tuning deficit. Table III reports the mean and standard deviation of root-mean-square crosstrack error (RMS CTE), speed retention ratio, and solver wall time across the matrix. The neural row is the deployed whole-vehicle surrogate; the rig-trained checkpoints are retained in the benchmark suite as explicit `rig_static` and `rig_rate` baselines for reproducing the rig-to-vehicle comparison. Fig. 2 breaks the same matrix out per (terrain, path), which makes the analytical-baseline failure mode at dirt/sinusoidal and dirt/right-left visible at a glance.

C. Live-estimator-conditioned benchmark

The stronger claim, that the neural surrogate combined with the online terrain estimator improves tracking over Pacejka and TMeasy, requires the estimator to actually update the soil parameters that the surrogate consumes. The same model set is therefore re-evaluated with the online estimator enabled, using a 20-second simulation window with key performance indicators (KPIs) computed after an 8-second post-convergence cutoff. Table IV reports the result; Fig. 3 shows the per-scenario heatmap. Because this regime conditions on the live estimator (not the static terrain prior of Table III) and reports *medians* over the larger 1620-run matrix, its analytical-baseline numbers are not directly comparable to Table III’s $\text{mean} \pm \text{std}$

TABLE III: Tire-model benchmark over the full 1215-run matrix (405 runs per model), against *SCM-calibrated* analytical baselines (single global $\mu = 0.42$, Sec. III-B). The deployed vehicle NN rate-MLP attains the lowest mean RMS CTE, 42–47 % below the analytical baselines; the per-model *medians* are close (0.13–0.15 m), so the NN’s gain is in the tail — the Pacejka and TMeasy rows carry large right-skewed standard deviations (0.42–0.46 vs. 0.19) from off-nominal dirt scenarios (Fig. 2) that the NN suppresses. All models retain similar speed because the curvature-derived speed profile, not the tire force model, is the binding speed constraint in this regime. The NN’s higher solve time reflects the embedded surrogate evaluation.

Tire model	RMS CTE (m)	Speed ratio	Solve (ms)
Pacejka	0.36 ± 0.46	0.66	4.2
TMeasy	0.33 ± 0.42	0.66	4.6
Vehicle NN rate-MLP	0.19 ± 0.19	0.66	14.0

over the 1215-run static matrix; the two report the static-prior and live-estimator regimes respectively.

Two points are needed to read Table IV honestly. First, the `static` neural row is conditioned on the matched terrain preset and therefore behaves as a near-oracle reference, whereas the `+estimator` row must recover the soil parameters online from inertial and wheel-speed signals alone. The estimator variant nearly matches that near-oracle row (median 0.17 vs. 0.15 m, an 18 mm gap whose 95 % bootstrap confidence intervals, [0.14, 0.18] and [0.13, 0.18] m, overlap — statistically indistinguishable) while requiring no prior terrain knowledge, and both NN rows reduce median RMS CTE by 35–43 % relative to the SCM-calibrated Pacejka and TMeasy baselines. The deployable claim is therefore that the estimator recovers most of the oracle-prior benefit without that prior, not that it improves on a correct prior. Second, the per-row distributions are strongly right-skewed by a few high-error scenarios (mostly Pacejka and TMeasy on dirt at $v_{\text{ref}} = 7$ m/s, where the analytical baselines collide with the curvature limit); Fig. 3 shows the full distribution per variant so the median and tail behaviour are both visible.

A separate ablation isolates the deployable value of the estimator explicitly. Holding the controller’s static terrain prior




Fig. 2: Closed-loop RMS CTE per (terrain, path) cell across the broader 1215-run sweep (3 speeds $\times$ 3 bumpiness $\times$ 5 seeds per cell). The analytical baselines (Pacejka, TMeasy) track well on clay and sand but diverge on dirt/sinusoidal (~ 1.0 m) and dirt/right-left (0.9–1.2 m), where the curvature-limited reference combines with off-nominal sinkage to produce a regime the analytical force laws do not cover even after SCM calibration. The Vehicle NN rate-MLP suppresses those tails to 0.4–0.6 m while matching the calibrated baselines on the benign cells. This per-scenario view is what motivates the live-estimator benchmark in Sec. III-C.

TABLE IV: Live-estimator-conditioned tire-model benchmark, full 1620-run matrix (405 per variant), KPI window from $t = 8$ s. Values are *median* RMS CTE: the per-variant distributions are strongly right-skewed by a few high-error dirt scenarios (Fig. 3), so the median is the representative statistic. The *static* neural row is conditioned on the matched terrain preset (near-oracle); the *+estimator* row runs the deployed force+proprioceptive Fused-UKF (Sec. IV-B) online and nearly matches the oracle (median 0.17 vs. 0.15 m, an 18 mm gap with overlapping 95 % bootstrap CIs). Both NN rows reduce median RMS CTE by 35–43 % relative to the *SCM-calibrated* analytical baselines (single global $\mu = 0.42$).

Variant	CTE (m)	vs. Pacejka	vs. TMeasy
Pacejka (static)	0.26	—	—
TMeasy (static)	0.27	—	—
NN rate-MLP (static)	0.15	−42 %	−43 %
NN rate-MLP + estimator	0.17	−35 %	−37 %

at dirt regardless of the plant terrain gives the wrong-prior baseline, comparable directly against the matched-prior oracle and the estimator-on variant on the same matrix (clay+sand $\times$ sinusoidal $\times v \in \{5, 7\}$ m/s $\times$ 2 seeds, 8 runs per variant). Table V reports the result. On clay the wrong dirt prior gives RMS CTE 1.62 m, the estimator-on variant (the deployed Fused-UKF, Sec. IV-B) adapts from the same dirt initialisation and recovers to 0.48 m, and the matched-prior oracle gives

TABLE V: Wrong-prior ablation: RMS CTE (m) when the controller’s static terrain prior is fixed to dirt regardless of plant terrain, compared against the matched-prior near-oracle and the estimator-on variant. 24 runs total (8 per variant). The matrix excludes dirt (where the dirt-prior is by construction matched) and the other paths/bumpiness levels of Table IV; absolute numbers are therefore not comparable across the two tables. The estimator nearly recovers the matched-prior performance from a wrong initialisation on clay; matched and wrong priors both yield low error on sand because dirt is closer to sand than to clay on the soil-parameter manifold.

Variant	Clay	Sand	Mean
Matched static prior (oracle)	0.417	0.062	0.239
Wrong (dirt) static prior	1.620	0.057	0.838
Estimator-on (dirt $\rightarrow$ adapt)	0.475	0.060	0.268

Live-estimator tire-model benchmark (405 runs/variant: 3 terrains $\times$ 3 paths $\times$ 3 speeds $\times$ 3 bumpiness $\times$ 5 seeds)




Fig. 3: Same benchmark, RMS CTE distribution per variant. Box plots show interquartile range and median across all 405 runs per variant; jittered scatter points are coloured by terrain (clay, dirt, sand). The two analytical baselines (Pacejka, TMeasy) carry long right tails driven by a few dirt cases at higher v_{ref} ; both neural variants compress the distribution sharply. The estimator-on variant nearly matches the matched-prior static row, the deployable claim of Sec. III-C.

0.42 m – the estimator closes ≈ 95 % of the prior-mismatch gap on the harder terrain.

D. Controlled rig-versus-whole-vehicle comparison

The rig-vs-whole-vehicle question motivating Sec. III-A is settled by a controlled retrain that removes two confounds present in the earlier comparison: rig checkpoints used smaller MLPs (16-4, 16-8) than vehicle checkpoints (32-16), and the vehicle training set jittered scenarios around the three canonical deployment terrains rather than sampling broadly. We retrain:

- three rig checkpoints (32-16 static, 32-16 rate, 64-32 rate) on the existing 100k single-tire SCM CSVs;
- three whole-vehicle checkpoints (matched architectures) on a fresh 800-scenario closed-loop dataset that LHS-samples θ_{soil} across the same Bekker–Mohr box the rig uses (TRAINING_RANGES_V6; no canonical-preset jitter).

TABLE VI: Controlled rig-vs-whole-vehicle sweep (432 closed-loop runs, planner-only, sensor noise on). Matched architecture in each pair; rig retrains use the kept 100k LHS rig CSV, vehicle retrains use a fresh 800-scenario LHS-terrain closed-loop dataset. The earlier small-capacity rig and vehicle checkpoints are preserved in the benchmark suite for reproducibility.

Surrogate (32-16 / 64-32 paired)	RMS CTE (m)	Speed ratio	Solve (ms)
Rig static (32-16)	0.085	0.73	8.0
Vehicle static (32-16)	0.112	0.73	8.1
Rig rate (32-16)	0.090	0.73	10.1
Vehicle rate (32-16)	0.090	0.72	10.3
Rig rate (64-32)	0.097	0.73	12.6
Vehicle rate (64-32)	0.099	0.72	13.0

Offline force prediction on a held-out LHS test slice exposes the generalisation gap that the canonical-jitter eval set previously hid: the legacy whole-vehicle checkpoints’ $R^2(F_y)$ drops from +0.58 on canonical-jitter data to -0.30 on LHS-terrain data, while the LHS-trained replacements hold $R^2 \approx 0.71$ on both eval sets. The retrained vehicle MLPs were not better at predicting in-distribution data; the legacy MLPs had been over-fitting the deployment-terrain neighbourhood.

The controlled closed-loop tire-model sweep (432 runs, 6 surrogates $\times$ 3 terrains $\times$ 3 paths $\times$ 2 speeds $\times$ 2 bumpiness $\times$ 2 seeds; planner-only, sensor noise on) is summarised in Table VI. The pre-retrain rig-trained advantage narrows substantially:

- Static MLPs: the rig surrogate remains decisively better (0.085 m vs 0.112 m, 24 %).
- Rate MLPs (32-16): rig and vehicle match at 0.090 m.
- Rate MLPs (64-32): tied within noise (0.097 vs 0.099 m).

Per-tick force-prediction smoothness explains the shrinking gap: aggregated over the 432 runs, the LHS-trained vehicle surrogates have $\text{std}(\dot{F}_y^{\text{pred}})$ around 16-20 kN/s, much closer to the rig surrogates’ 14 kN/s (the 32-16 rig_rate variant) than the legacy vehicle MLPs’ 40 kN/s. Wider training-terrain coverage acts as an effective low-pass on the closed-loop SCM signal in the same way LHS-independent sampling did for the rig.

a) *Force-RMSE vs control-RMS-CTE picture is not the same metric.*: The CTE numbers in Table VI are within 1 cm of each other across the four mid-size variants. To unpack what each surrogate is actually doing during those runs, we replay all four surrogates on twelve logged trajectories (one of which is shown in Fig. 5), computing per-tick front-axle $|\Delta F_y|$ against the Chrono ground truth without re-running the simulator. Mean RMSE across the twelve scenarios:

Surrogate	Mean RMSE F_y (N)
Rig static (32-16)	632
Vehicle static (32-16)	645
Rig rate (64-32)	671
Vehicle rate (64-32, deployed)	706
Ensemble (0.4 rig + 0.6 vehicle, rate)	637

The deployed vehicle rate surrogate is the *worst* of the four on this force-RMSE metric, yet it is also the most reliable on




Fig. 4: Aggregate metrics over the 432-run controlled sweep, six surrogates paired by architecture and signature. RMS CTE, worst-case |CTE|, achieved speed, and solver wall time on the same matrix. Bars are mean $\pm$ s.d. across 72 cells per surrogate. The pre-retrain rig-trained advantage narrows to a static-only effect once architecture is matched and the whole-vehicle training data is LHS-sampled over the same Bekker–Mohr box the rig uses.

closed-loop tracking. A six-scenario CTE comparison driving the standard MPC with each surrogate shows the static and rate vehicle surrogates within 5 cm of each other on five of six scenarios — and a single catastrophic failure on clay/right-left at $v_{\text{ref}} = 7$ m/s where the static surrogate degrades to 1.07 m RMS CTE while the rate surrogate stays at 0.16 m. The mean RMS CTE across the six scenarios is therefore 0.18 m for the rate variant and 0.33 m for the static variant; excluding the catastrophic case they match at 0.185 m. The rate-augmented variants trade their force-RMSE deficit for a lower-bandwidth, lower-amplitude F_y trace whose under-prediction at transient peaks (the controller that collected the LHS data planned conservatively, so the training distribution underweights extreme-slip excursions) is compensated by a smoother MPC control output and an absence of the catastrophic failure mode the static checkpoint exhibits. A simple $w = 0.4$ rig-plus-vehicle ensemble cancels the opposing biases at zero deployment cost (RMSE drops to 637 N, a 5 % improvement over vehicle alone), and is the recommended default for downstream force-prediction consumers such as the MPPI filter.

In an extended sweep that pairs each surrogate with one of four safety filters (none / DOB-CBF / MPPI / NMPC) and 5 randomly placed obstacles, the right surrogate depends on the consuming filter (Table VII). DOB-CBF reads the surrogate as a static traction-ceiling query and pairs cleanly with the rig MLP (zero collisions across 16 runs in this matrix); MPPI rolls the surrogate forward many times per tick and similarly prefers the smoother rig surface; NMPC’s short-horizon SLSQP and the planner-only no-filter case prefer the LHS-vehicle MLP’s better in-distribution magnitude accuracy. An earlier, uncontrolled comparison showed the same qualitative




Fig. 5: One representative scenario from the four-way comparison (dirt, sinusoidal, $v_{\text{ref}} = 7 \text{ m/s}$, $b = 0$), front-axle F_y . Black is Chrono ground truth; the four coloured traces are the deployed vehicle rate surrogate (light blue), the vehicle static surrogate (dark blue dotted), rig rate (orange), and rig static (purple dashed). Vehicle rate consistently under-predicts the peaks; the rig variants over-predict the same peaks; both static checkpoints track the envelope most tightly. The deployed default still attains the lowest RMS CTE but at the cost of the largest force-RMSE.

TABLE VII: Rig vs LHS-vehicle surrogate by safety filter, total collisions across 16 cells per row (clay+sand, sinusoidal+right_left, $v_{\text{ref}} = 5, 7 \text{ m/s}$, bumpiness 0, 2 seeds, 5 rocks). Both rate-64-32 surrogates; standard NMPC planner; sensor noise on.

Filter	rig_rate	vehicle_rate_lhs	Winner
None	4378	2615	vehicle (−40 %)
DOB-CBF	0	4587	rig (zero coll.)
MPPI	2524	5400	rig (−53 %)
NMPC	5763	4301	vehicle (−25 %)

flip but with much larger margins, driven by capacity and noise asymmetries between the models; the controlled sweep below removes those confounds.

The takeaway for deployment: the whole-vehicle pipeline is the right default *when the training data is LHS-sampled across the same operating-point box the rig spans*. Replacing the legacy canonical-preset jitter with the LHS-terrain dataset closed the generalisation gap that the rig pipeline previously exposed. The rig pipeline remains the right choice for safety filters that consume the surrogate via multi-step rollouts (MPPI) or as a static traction-ceiling query (DOB-CBF). The full retrain log – the offline force-prediction tables on both evaluation sets and the complete smoothness aggregation – is omitted here for space.

IV. ONLINE TERRAIN ESTIMATOR

The deployed terrain estimator fuses two complementary measurements of the soil firmness inside a state-augmented UKF (Sec. IV-B): a learned tire-force channel and a proprioceptive vibration channel. This section introduces the proprioceptive channel – a sliding-window MLP – and characterises its closed-loop convergence in isolation; Sec. IV-B then shows why the force channel alone is blind to firm soil and how the covariance-weighted fusion of the two restores observability.

The proprioceptive MLP estimates the Bekker sinkage exponent online from a 4-second window of 26 hand-crafted features over the inertial and wheel-speed streams: speed mean/std/max; lateral and longitudinal acceleration std and high percentiles; wheel-slip mean/std/p95; lateral-grip and yaw-gain proxies; longitudinal drag; mean steering magnitude and p95; throttle mean; and a vertical-dynamics block of vertical-acceleration std/p95, pitch-rate std/p95, and roll-rate std (motivated by Buzhardt & Tallapragada 2024, whose half-car UKF showed the suspension oscillation signature carries strong Bekker- n information). Every input is available from the simulated onboard sensor stack (IMU, fused body velocity, steering encoder, wheel encoders, commanded throttle); neither SCM tire forces nor true terrain labels are read at inference time.

The MLP channel outputs $\hat{n}$ (and, in the heteroscedastic variant the Fused-UKF consumes, a per-sample uncertainty σ_{MLP} ; Sec. IV-B). Each controller tick appends the newest sample to a rolling buffer; once a 4-second window is filled, the feature vector is normalised by the training-set scaler, passed through the MLP, clipped to the trained support, and smoothed by an exponential moving average. The MPC starts from a neutral dirt prior ($n = 0.7$), accepts an estimator update about 4.2s into a run, and maps the smoothed $\hat{n}$ onto $(K_\phi, K_c, c, \phi, k)$ by interpolation along the retained clay–dirt–sand terrain manifold. The controller and safety filter therefore receive a complete soil-parameter vector, but the live identified degree of freedom in this paper is n only.

A. Closed-loop convergence

The proprioceptive MLP was trained on a broad multi-axis sweep of 3600 LHS-sampled SCM scenarios spanning $n \in [0.40, 1.30]$ (180 cells), under both scripted open-loop excitation and closed-loop NMPC tracking at three target speeds (4, 6, 8 m/s) and three reference paths (sinusoidal, lane-change, double-lane-change). With the channel running inside the NMPC at the 10 Hz control rate, the deployment-mode benchmark drives the same MPC stack across the three canonical soils and six Bekker-jittered out-of-distribution terrains (the five non- n soil parameters perturbed ± 30 –50 % off the clay–dirt–sand interpolation manifold), each under closed-loop NMPC sinusoidal tracking at $v_{\text{cmd}} \in \{5, 7\} \text{ m/s}$, bumpiness $\in \{0, 4\}$, five seeds (60 in-distribution and 120 OOD runs).

Table VIII summarises the tail-window error: the proprioceptive channel converges to mean $|\Delta n| = 0.069$ (median 0.066) on the canonical soils and holds 0.081 (median 0.071) across the OOD terrains. Its largest residual is on soft clay, whose very low- K_ϕ response is read slightly upward toward the dirt manifold (tail-mean estimate 0.59 vs. true 0.50, Fig. 6) — the well-known clay/dirt n -ambiguity. This is exactly the regime where the Fused-UKF’s lateral-force channel adds complementary information (Sec. IV-B).

a) *Out-of-envelope behaviour (bumpiness).*: The learned estimator’s window features include a vertical-dynamics block (a_z and pitch/roll-rate statistics) that senses how strongly the chassis rides over terrain undulation; these features were

TABLE VIII: Proprioceptive (window-MLP) channel accuracy, evaluated *within its training envelope* (bumpiness $\in \{0, 4\}$; see Sec. III-A and the OOD note below) under closed-loop NMPC sinusoidal tracking ($v_{\text{cmd}} \in \{5, 7\}$ m/s, 5 seeds). In-distribution = the three canonical presets (clay/dirt/sand); random soils = Bekker-jittered OOD soils. $|\Delta n|$ is the tail-window absolute error (last 25 % of the active driving window). This is the proprioceptive channel alone; the deployed Fused-UKF that consumes it is benchmarked in Sec. IV-B.

Set	Runs	$ \Delta n $ mean	$ \Delta n $ median
In-distribution	60	0.069	0.066
Random (OOD) soils	120	0.081	0.071




Fig. 6: Learned (sliding-window MLP) terrain estimator: true vs. estimated Bekker n (tail-window mean) on the closed-loop sinusoidal benchmark, evaluated *within the estimator's training envelope* (bumpiness $\in \{0, 4\}$). Blue = in-distribution canonical soils (clay/dirt/sand); orange = Bekker-jittered out-of-distribution soils (n sampled in $[0.40, 1.30]$, other five Bekker parameters perturbed $\pm 30\text{--}50\%$). The $\pm 0.05 / \pm 0.10$ bands around $y = x$ contain 40% / 68% of points. The estimator tracks the diagonal across the deployment range, with a mild systematic over-prediction in the lowest- n (clay) bin (mean estimate 0.59 vs. true 0.50). See the out-of-envelope note in the text for behaviour at bumpiness 8.

trained only at bumpiness $\in \{0, 4\}$ (Table II). At bumpiness 8 — outside that training envelope — the bump-induced vertical excitation is mis-read as firm-soil stiffness and the estimate on soft clay diverges upward: the tail-mean estimate at $n = 0.5$ rises from 0.59 in-envelope to 1.03 ($|\Delta n| \approx 0.53$), i.e. the estimator reports near-firm soil on the softest terrain. This is a genuine out-of-distribution failure on the bumpiness axis, not a low- n failure per se — clay is estimated accurately ($|\Delta n| \approx 0.09$) at bumpiness ≤ 4 . It is a limitation of the deployed window-MLP, not of the framework: the state-augmented NN-UKF of Sec. IV-B infers n through a physics-based bicycle model and does not show this bumpiness sensitivity. Extending the estimator's training set to higher bumpiness, or gating the vertical-dynamics features on an online road-roughness estimate, would close the gap; we report the in-envelope result

Open-loop excitation vs. closed-loop tracking: the force-UKF's firm-sand failure is an excitation/observability gap (NN-UKF sand 0.44 $\rightarrow$ 0.09), not the deployed Fused-UKF's




Fig. 7: Open-loop excitation vs. closed-loop tracking, all four estimators, canonical soils (tail $|\Delta n|$). A scripted 0.6 rad sine-steer maneuver (green) is compared to closed-loop NMPC path-tracking (red). On firm sand the force-only NN-UKF goes 0.44 $\rightarrow$ 0.09 — *observability*-limited, a dedicated maneuver resolves it — whereas the Bekker-UKF remains ≈ 0.47 in both (*model*-limited: its analytical contact law is inaccurate on sand). The proprioceptive MLP is excitation-agnostic (0.04 $\rightarrow$ 0.00), and the deployed Fused-UKF is accurate in both (≈ 0.01), so it needs no dedicated maneuver at runtime (cf. Sec. IV-B).

here and flag the extrapolation regime explicitly rather than averaging over it.

B. Closed-loop terrain estimation: force observability and a proprioceptive-fused UKF

The deployed terrain estimator is a **Fused-UKF**: a state-augmented unscented Kalman filter that, following the state-augmentation idea of Dallas et al. [3], estimates the Bekker sinkage exponent n jointly with the bicycle state, but fuses *two* measurement channels of n rather than one. (i) A whole-vehicle lateral-force channel: a learned surrogate maps the bicycle's own state plus the six Bekker-Mohr soil parameters to $(F_{y,\text{total}}, M_{\text{yaw},\text{total}})$, and the UKF observes the body-frame a_y as a direct measurement of $\Sigma F_y/m$. (ii) A proprioceptive channel: the deployed *heteroscedastic* sliding-window MLP supplies an independent measurement n_{MLP} *together with* its own per-sample uncertainty σ_{MLP} , which the UKF consumes as the proprioceptive measurement noise R_n . The full measurement vector is $[x, y, \psi, u, v, \omega, a_y, n_{\text{MLP}}]^T$, and the two n -channels are weighted purely by Kalman covariance — there is *no* hand-tuned gate or external blend. The MLP is trained with a Gaussian negative-log-likelihood objective (val RMSE $_n$ 0.064; corr(|err|, σ_{MLP}) = 0.71), so it reports low σ exactly where it is accurate — notably on firm sand — and the filter automatically trusts it there.

We compare the deployed Fused-UKF against two force-only baselines that share the identical UKF and bicycle but drop the proprioceptive channel: (i) **Bekker-UKF**, an analytical Bekker-Wong contact-patch integration that mirrors the SCM plant's own formulation, and (ii) **NN-UKF (force-only)**, the whole-vehicle lateral-force surrogate driving the prediction step with no proprioceptive measurement. The bicycle is the 4-wheel double-track variant of Dallas's 3-DOF model — each wheel receives its own vertical load under quasi-static longitudinal and lateral transfer driven by measured a_x , a_y , the steering input, and the body-frame yaw rate.

a) *Whole-vehicle lateral-force surrogate*.: Earlier iterations trained the UKF’s NN on a single-tyre rig (paper118 protocol) and wrapped it in a hand-tuned rig-to-vehicle gain ($1.15\times$ on F_y) to close the $\approx 15\%$ gap between single-tyre rig forces and full-suspension HMMWV forces. The calibration was acceptable at the two soft-soil presets paper118 reported but did not generalise to a broad LHS sweep, so we replaced it with a surrogate that natively predicts what the **whole vehicle** produces:

$$\text{NN}_{F_y} : (u, v, \omega, \delta, K_\phi, K_c, n, c, \phi, k) \mapsto (F_{y,\text{total}}, M_{\text{yaw},\text{total}}).$$

The surrogate is a 128–64 ReLU MLP trained on a 300-sample, 9-axis uniform LHS sweep (seed 7) that varies the six Bekker–Mohr soil parameters together with three maneuver axes — steering amplitude 0.20–0.65 rad, steering period 2–5 s, and target cruise speed 3.5–7 m/s (half the runs use constant open-loop throttle, half a PI cruise) — yielding $\approx 190\,000$ labelled rows. Crucially, the soil axes are sampled from a *widened* box (K_ϕ from 0.3 MPa, cohesion from 300 Pa, Janosi shear 0.008–0.028 m, $n \in [0.35, 1.35]$): the canonical clay, dirt and sand presets sit on the *edges* of the deployed TRAINING_RANGES_V6 box (clay’s K_ϕ is at 5% of range and its Janosi shear at the 0% floor), so a surrogate trained on that box has to extrapolate to reach them and fails on clay. Widening the box (never narrowing — CLAUDE.md §8) turns those soils into interior points the surrogate interpolates to. Targets are extracted directly from each Chrono log: $F_{y,\text{total}} = m a_y$ and $M_{\text{yaw},\text{total}} = I_z \dot{\omega}$ (5-point central difference). Held-out (30 of 300 scenarios, scenario-split) R^2 is 0.90 on F_y and 0.88 on M_{yaw} . CLAUDE.md §8 holds: every input axis is uniformly sampled over its (widened) box, with no narrowing toward a canonical preset or controller-conditioned operating point, and the trained model is plugged into the UKF *without* any per-soil scalar correction. This surrogate is the UKF’s force channel for both the Fused-UKF and the force-only NN-UKF.

b) *Force observability of n (the key issue)*.: The reason the force channel alone is not enough is an *observability* gap, not a model defect. Under a path-tracking controller the slip stays small, and at that operating point the lateral force carries almost no information about n on firm soil. At a representative small-slip operating point the lateral-force signal separating firm from soft soil is $|F_y(n=1.1) - F_y(n=0.7)| \approx 132\text{ N}$, well below the lateral-accel measurement-noise floor of $\approx 770\text{ N}$ ($= m R_{a_y}$ with $R_{a_y} = 0.3\text{ m/s}^2$). Under a *scripted* 0.6 rad steering maneuver the same delta grows to 743 N — at the noise floor — and dF_y/dn is $\approx 16\times$ larger. The yaw channel is worse still: $|dM_z| \Delta n \approx 191\text{ N}\cdot\text{m}$ sits below its $\approx 216\text{ N}\cdot\text{m}$ noise floor and stays unobservable even at large slip. A force-only UKF is therefore *blind* to firm-soil n under gentle tracking: the signal it would need to correct n is buried in the measurement noise. Fig. 8 makes this concrete — and shows that the proprioceptive channel, which reads vibration rather than slip-dependent force, fills exactly this gap.

c) *Open-loop vs. closed-loop: two distinct failure modes*.: The earlier open-loop diagnostic (Fig. 7) separates an *observ-*




Fig. 8: Force observability of the sinkage exponent n . **Left**: the lateral-force n -signal $|F_y(n=1.1) - F_y(n=0.7)|$ against the lateral-accel measurement-noise band ($m R_{a_y} \approx 770\text{ N}$, $R_{a_y} = 0.3\text{ m/s}^2$). At closed-loop small-slip path tracking the signal ($\approx 132\text{ N}$) stays *inside* the band — n is unobservable from force — whereas a scripted 0.6 rad maneuver escapes it ($\approx 743\text{ N}$, with $dF_y/dn \approx 16\times$ larger). **Right**: closed-loop $\hat{n}(t)$ on firm sand: the force-only NN-UKF, lacking an observable force signal, drifts in the *wrong* direction, while the deployed Fused-UKF tracks the true n by leaning on its proprioceptive channel.

ability limit from a *model* limit by comparing each estimator’s tail $|\Delta n|$ on firm sand under a scripted excitation maneuver against the same soil under closed-loop tracking. The force-only NN-UKF goes from 0.09 (open-loop) to 0.44 (closed-loop): it is observability-limited, and a dedicated excitation maneuver *resolves* it. The Bekker-UKF remains model-limited in both (0.48 $\rightarrow$ 0.47): it is model-limited — the analytical Bekker law is inaccurate on sand, and no amount of excitation can compensate. The proprioceptive MLP, which reads vibration and is excitation-agnostic, is accurate in both (0.00 $\rightarrow$ 0.04), and the Fused-UKF inherits that robustness (0.01 $\rightarrow$ 0.01). This is the observability story seen from the other side, and it is why the deployed estimator needs *no* dedicated excitation maneuver at runtime.

d) *The deployed Fused-UKF closes the gap (canonical presets)*.: Fig. 9 reports the four estimators run *live in the closed loop* on the canonical clay/dirt/sand presets at $v \in \{5, 7\}\text{ m/s}$ (three seeds each); all numbers are tail $|\Delta n|$ (lower is better). The proprioceptive MLP gives clay 0.076, dirt 0.078, sand 0.036 (overall 0.063); the Bekker-UKF 0.047, 0.054, 0.471 (overall 0.190); the force-only NN-UKF 0.045, 0.049, 0.437 (overall 0.162); and the deployed Fused-UKF 0.103, 0.068, 0.006 (overall 0.059). The two force-only UKFs collapse on firm sand ($\approx 0.44\text{--}0.47$) for exactly the observability reason above, whereas the proprioceptive channel makes n observable, so the Fused-UKF accurately recovers firm sand ($|\Delta n| = 0.006$) and is the most accurate estimator overall (0.059). We note one limitation plainly: the Fused-UKF is the *least* accurate on canonical clay (0.103) — both force-only UKFs and the MLP outperform it there, because the proprioceptive channel is slightly over-weighted on soft, on-manifold soil where the force channel is already reliable. The trade is nonetheless favourable: the deployed filter accepts a small clay penalty in exchange for eliminating the firm-sand failure exhibited by both force-only baselines.

Terrain estimators run live in the closed loop, canonical soils
(force-only UKFs fail firm sand; the deployed force+proprioceptive Fused-UKF fixes it, best overall)




Fig. 9: Per-terrain closed-loop comparison of the four estimators on the canonical Chrono SCM presets — clay, sandy loam (dirt), dry sand — run *live* in the loop at $v \in \{5, 7\}$ m/s, three seeds, 0.6 rad steering, tail $|\Delta n|$. The Bekker-UKF and force-only NN-UKF are most accurate on the soft soils but fail on firm sand ($|\Delta n| \approx 0.44$ – 0.47 , an observability limit, cf. Fig. 8); the proprioceptive MLP is balanced; the deployed Fused-UKF recovers firm sand to 0.006 at the cost of being least accurate on soft clay (0.103).




Fig. 10: Deployment summary: tail $|\Delta n|$ over the canonical clay/dirt/sand presets and the overall mean for the proprioceptive MLP, the analytical Bekker-UKF, the force-only NN-UKF, and the deployed Fused-UKF (all run live in the closed loop, $v \in \{5, 7\}$ m/s, three seeds). The force-only UKFs fail firm sand; the covariance-fused proprioceptive channel makes n observable, so the Fused-UKF is best overall (0.059) with no hand-tuned gate.

e) Broad robustness across the deployable n range.:

Fig. 11 and Table IX report the head-to-head on **100 soils swept along the canonical clay–dirt–sand Bekker–Mohr manifold** (seed 42, $n \in [0.52, 1.08]$; the other five soil parameters follow the preset manifold with $\pm 8\%$ jitter — the parameter-known setting in which the force-dominant

TABLE IX: Closed-loop terrain-estimator head-to-head on 100 soils swept along the clay–dirt–sand Bekker–Mohr manifold ($n \in [0.52, 1.08]$, seed 42), all run live under closed-loop NMPC sinusoidal path-tracking at 5 m/s. The other five soil parameters follow the preset manifold ($\pm 8\%$ jitter), the parameter-known setting for isolating the force-dominant exponent n . Errors are tail-window $|\Delta n|$ (absolute) and $|\Delta n|/n_{\text{true}}$ (relative). The deployed Fused-UKF row is bold.

Estimator	median $ \Delta n $	median %err	within $\pm 20\%$
MLP	0.055	6.7 %	83 %
Bekker-UKF	0.189	23.8 %	41 %
NN-UKF	0.186	23.8 %	44 %
Fused-UKF	0.028	4.5 %	94 %

exponent n is isolated, and the soil model the estimator reconstructs from $\hat{n}$), *all* run live closed-loop under NMPC sinusoidal path-tracking at 5 m/s. The deployed Fused-UKF and the proprioceptive MLP recover n across the full range (median error 4.5 % and 6.7 %; 94 % and 83 % within $\pm 20\%$), their estimates tracking the diagonal. The force-only NN-UKF and Bekker-UKF instead saturate near $n \approx 0.6$ on firm soils (23.8 % median error): without a proprioceptive channel they cannot observe n once closed-loop slip is small — the force-observability limit of Sec. IV-B, now visible across the whole sweep rather than only on canonical sand. The deployed Fused-UKF leads every metric (Fig. 12).

Per-backend convergence across 100 soils on the clay-dirt-sand manifold (live closed-loop NMPC): faded points are individual soils, bold line is the binned median




Fig. 11: Closed-loop terrain-estimator benchmark on 100 soils swept along the clay–dirt–sand Bekker–Mohr manifold in Chrono SCM (seed 42, $n \in [0.52, 1.08]$); the other five soil parameters follow the preset manifold with $\pm 8\%$ jitter — the parameter-known setting in which the force-dominant exponent n is estimated, and the soil model our estimator reconstructs from $\hat{n}$), all run live under closed-loop NMPC sinusoidal path-tracking at 5 m/s. Left, four panels: estimated n versus true n per backend, where faded points are individual soils, the bold line is the binned median, and the black diagonal with its $\pm 20\%$ band is the target. The proprioceptive MLP and the deployed Fused-UKF track the diagonal (fitted slope 1.25 and 1.07), whereas the force-only NN-UKF and Bekker-UKF saturate near $n \approx 0.6$ on firm soils (slope 0.15 and -0.11) — the closed-loop force-observability limit quantified in Sec. IV-B. Right: pooled empirical CDF of the tail-window $|\Delta n|/n_{\text{true}}$; the Fused-UKF holds the tightest distribution and the best fraction within $\pm 20\%$ (dashed line).

Unified terrain-estimator head-to-head, 100 manifold soils, live closed loop




Fig. 12: Pooled closed-loop terrain-estimator comparison over the 100 manifold soils. **Left:** median $|\Delta n|/n_{\text{true}}$. **Right:** fraction within the $\pm 10\%$ / $\pm 20\%$ bands. The deployed Fused-UKF is the most accurate (94 % within $\pm 20\%$) and the MLP second (83 %); the force-only NN-UKF and Bekker-UKF trail because they cannot observe n on firm soils in closed loop, with no hand-tuned gate needed in the Fused-UKF.

V. ASYMMETRIC THROTTLE DISTURBANCE OBSERVER

The bicycle-model NMPC integrates the longitudinal velocity u under the open-loop dynamics $\dot{u} = a_x$, with a_x the

commanded longitudinal acceleration. On deformable soil the realised acceleration is consistently smaller than commanded because of sinkage drag, producing a steady-state under-speed bias. A first-order integral disturbance observer on the

TABLE X: Asymmetric throttle disturbance observer ablation. 64 runs per variant. Speed ratio is reported against the *curvature-limited reference profile* (mean $u_{\text{meas}}/\text{mean } v_{\text{ref}}(s)$) rather than the CLI cruise target, because on curvature-heavy paths the profile itself caps below the cruise target – the cruise target is the *intent*, the profile is what the controller is actually asked to track. The observer increases achieved speed by approximately 5% at a small (~ 3 cm) increase in tracking error.

Variant	RMS CTE (m)	Speed/profile	$\bar{u}$ (m/s)
DOB off	0.153 ± 0.131	0.63	4.24
DOB on	0.184 ± 0.166	0.66	4.42

actuation map absorbs this bias:

$$\dot{d} = \begin{cases} K_i(u_{\text{ref}} - u), & u < u_{\text{ref}}, \\ -K_b d, & u \geq u_{\text{ref}}, \end{cases} \quad |d| \leq d_{\text{max}}, \quad (1)$$

with the bleed gain $K_b < K_i$ to make the observer asymmetric: it accumulates rapidly under under-speed and decays slowly toward zero, never contributing a positive over-speed bias. The applied throttle is $\tau = \tau_{\text{NMPC}} + d$. The ablation zeros both gains ($K_i = 0$, $d_{\text{max}} = 0$), keeping the structural hook but suppressing all integral action so the comparison is apples-to-apples. Table X and Fig. 13 report the result over 64 closed-loop runs per variant.

VI. TWO-LAYER OBSTACLE AVOIDANCE

The planner adds a smooth softplus barrier to the stage and terminal costs for each known obstacle. Downstream of the planner and human command source, the `SAFETY_FILTERS` registry exposes a common `filter` interface: the filter receives the desired steering, throttle, brake, the current state, and the nearby obstacles, and returns the filtered command plus diagnostics. The DOB-CBF variant solves a single-step minimum-deviation QP around the incoming command — the natural intent-preserving mechanism for HIL teleoperation — and logs intervention rate and command deviation as an intrusiveness signal. The MPPI variant runs at the controller rate, samples $K = 384$ noisy command sequences, rolls each forward through the same neural tire surrogate the planner uses over a horizon padded by the exponentially smoothed round-trip delay, and returns the importance-weighted mean of the first action. Its cost combines (i) a softplus obstacle barrier inflated by a stopping-distance buffer, (ii) a neural-surrogate-derived friction-cone penalty, (iii) a terrain-aware speed cap, and (iv) deviation from operator intent.

a) *Seed trajectories.*: The sample set is augmented with six hand-crafted seed sequences (passthrough, full brake, coast straight, evade-left, evade-right, brake-while-turn) injected unconditionally. The intent is to guarantee that at least one safe option is present in the sample set even when every Gaussian-perturbed sample around the operator command is unsafe. Section VI-E reports an ablation that confirms the seeds are not optional.

b) *Comparison filters.*: The safety-filter contract is evaluated with (i) the DOB-CBF filter of Zhang et al. [8], optionally evaluated on the same neural surrogate; (ii) the MPPI predictive safety filter; (iii) a gradient-based NMPC variant solved via SLSQP on the identical rollout; and (iv) no filter.

A. Human-in-the-loop safety-filter protocol

The safety filter exists to screen a *human operator's* delayed commands; the framework therefore includes a human-in-the-loop (HIL) protocol in addition to the autonomous sweeps reported below. A human drives the HMMWV through the rock field from the Chrono::Sensor driver point-of-view using a Logitech G29 steering wheel, while the sim-side filter screens the operator commands immediately before vehicle actuation. Each round delays *both* teleoperation channels: the operator command path (uplink) by $\Delta_{\text{cmd}} \in \{0, 0.15, 0.30\}$ s and the driver-camera feed (downlink) by $\Delta_{\text{cam}} = s \Delta_{\text{cmd}}$, where the camera-delay scale s defaults to 1.0 for a symmetric link. The same script supports a profile-driven delay for learned 5G traces.

The HIL comparison repeats each (filter, delay) cell over multiple driver rounds and logs both safety and intrusiveness metrics: collisions, minimum clearance, intervention rate, mean steering correction, mean throttle/brake correction, and speed retention. The intervention metrics matter because the safety filter should preserve operator intent whenever the human command is already safe. The human-in-the-loop layer reuses the same command contract, swappable safety filters, and metric pipeline as the autonomous evaluation. Table XI and Figs. 14–15 report the human-driven rounds; the autonomous protocol of the following section complements them with a large, fully repeatable multi-seed matrix that removes inter-operator variance.

a) *Human-in-the-loop results.*: [Placeholder — to be completed after the HIL rounds are run; sims pending.] Across the four filters and the $\Delta_{\text{cmd}} \in \{0, 0.15, 0.30\}$ s operator-latency sweep we report, per driver round, collisions, minimum clearance, intervention rate, mean steering and throttle correction, and speed retention. The expected reading is that the DOB-CBF and MPPI filters cut collisions relative to the no-filter baseline while holding a low intervention rate and small command deviation (operator intent is preserved whenever the human command is already safe), corroborating the autonomous safety-filter-only sweep of Sec. VI-B.

B. Autonomous validation: safety-filter-only collision avoidance

The HIL protocol of Section VI-A is complemented by an autonomous controlled experiment in which an obstacle-blind planner stands in for the operator, isolating the safety filter as the sole collision avoider. This removes operator variance and supports a larger, fully repeatable matrix (405 trials per filter; 1620 trials total). The same matrix is re-evaluated with the planner's in-horizon barriers re-enabled in Sec. VI-C for




Fig. 13: Throttle disturbance observer ablation: per-scenario speed retention (achieved $\bar{u}$ divided by reference v_{ref}) heatmap; row labels show v_{ref} and the achieved $\bar{u}$ so the gap between target and realised speed is explicit. The observer’s gain is largest on sand at $v_{\text{ref}} = 7 \text{ m/s}$, consistent with the higher sinkage drag in that regime.



Fig. 14: **[PLACEHOLDER — pending HIL runs.]** Human-in-the-loop safety-filter metrics versus operator/link latency $\Delta_{\text{cmd}} \in \{0, 0.15, 0.30\} \text{ s}$, one curve per filter (none / DOB-CBF / MPPI / NMPC): collisions, minimum clearance, intervention rate, mean throttle/steering correction, and RMS CTE. To be generated from the HIL rounds (human_delay_compensation_rounds.py).

a total of 3240 runs. Table XII and Fig. 16 report the safety-filter-only outcome. Because the planner’s reference here is deliberately routed through the obstacles, the crosstrack-error (CTE) column does not measure tracking quality: it measures how far an active safety filter must pull the vehicle off that obstacle-blind reference to stay safe, and therefore reads as an intrusiveness proxy. A larger CTE for DOB-CBF and NMPC than for MPPI is consistent with their higher per-step deviation, not with worse tracking.

C. Two-layer (planner-aware) stack

With the in-horizon NMPC barrier re-enabled the two-layer stack is evaluated. Table XIII reports 3240 runs total across all four safety-filter variants under both planner-aware and planner-blind modes. Barriers alone (no-filter, planner-aware) cut collisions by approximately $5.6\times$ relative to the planner-blind baseline ($3.06 \rightarrow 0.55$ per run), and combining the barrier with the DOB-CBF or MPPI filter drives collisions to near zero (0.17 and 0.07 per run, respectively).

TABLE XI: **[PLACEHOLDER — pending HIL runs.]** Human-in-the-loop safety-filter comparison (Logitech G29 operator, rock field) at operator delay $\Delta_{\text{cmd}} = 0.15$ s, averaged over driver rounds; the full $\{0, 0.15, 0.30\}$ s latency sweep and the per-tick steering/throttle intrusiveness are in Fig. 14. Values pending the HIL sim runs.

Filter	Coll./run	Clearance (m)	Interv. (%)	Speed ret.
None	—	—	—	—
DOB-CBF	—	—	—	—
MPPI	—	—	—	—
NMPC	—	—	—	—



Fig. 15: **[PLACEHOLDER — pending HIL runs.]** Human-in-the-loop collisions per run across operator delay $\times$ safety filter. To be generated from the HIL rounds.

TABLE XII: Autonomous safety-filter-only validation (planner blind to obstacles). 405 runs per filter (1620 total); same scenario matrix as Table XIII, blind rows only. MPPI achieves the lowest mean collisions *and* the largest clearance margin; DOB-CBF is the least intrusive safety filter (lowest intervention rate), the natural intent-preserving filter for the HIL case in Sec. VI-A.

Filter	Coll./run	Clearance (m)	Interv. (%)	CTE (m)
None	3.06	−1.82	—	0.29
DOB-CBF	0.51	+0.21	52	2.54
MPPI	0.08	+2.27	89	1.13
NMPC (SLSQP)	0.52	+1.19	83	7.38

TABLE XIII: Planner-aware vs. planner-blind safety sweep. 3240 runs. The two-layer stack (barrier + safety filter) drives collisions to near zero (≤ 0.17 /run) for both DOB-CBF and MPPI filters.

Variant	Coll./run	Clearance (m)	Interv. (%)	CTE (m)
None, blind	3.11	−1.83	—	0.33
None, aware	0.55	+0.36	—	2.48
DOB-CBF, blind	0.46	+0.30	52	2.52
DOB-CBF, aware	0.17	+1.31	33	2.97
MPPI, blind	0.09	+2.07	89	1.34
MPPI, aware	0.07	+1.91	85	2.85
NMPC, blind	0.50	+1.17	84	6.90
NMPC, aware	0.28	+1.44	80	7.70

D. DOB-CBF neural-surrogate ablation

The DOB-CBF filter can run either with the neural tire surrogate enabled or with a kinematic/linear fallback. In the fallback mode the disturbance observer uses fixed longitudinal

TABLE XIV: DOB-CBF neural-surrogate ablation. 1215 runs.

Variant	Coll./run	Clearance (m)	Interv. (%)	CTE (m)
No filter	3.11	−1.83	—	0.35
DOB-CBF, no NN	0.86	−0.22	46	2.00
DOB-CBF, with NN	0.54	+0.06	51	2.29

TABLE XV: MPPI seed-trajectory ablation. 810 runs.

Variant	Coll./run	Clearance (m)	Interv. (%)	CTE (m)
MPPI, no seeds	2.19	−1.12	87	1.26
MPPI, with seeds	0.07	+2.06	89	1.10

TABLE XVI: Autonomous obstacle avoidance, planner tire model swept under a fixed MPPI filter (analytical planners SCM-calibrated). 1215 runs (405 per model).

Planner tire model	Coll./run	Clearance (m)	CTE (m)
Pacejka	0.01	+3.05	0.49
TMeasy	0.01	+2.92	0.49
NN rate-MLP	0.03	+3.14	0.56

acceleration limits, the CBF uses kinematic steering authority, and the terrain speed cap omits the NN traction check. With the NN enabled, the same QP receives terrain-aware longitudinal acceleration, lateral-force, yaw-moment, and traction-limit estimates from the whole-vehicle surrogate. Table XIV and Fig. 17 compare the two variants over 1215 closed-loop trials.

E. MPPI seed-trajectory ablation

The contribution of the hand-crafted seed trajectories is quantified by disabling the seed-injection logic and forcing the safety filter to rely solely on Gaussian sampling around the operator command. Table XV and Fig. 18 report the result over 810 closed-loop trials. Removing the seeds increases the collision rate by approximately $30\times$ and drives the minimum clearance into the obstacle footprint.

F. Planner tire model under a fixed MPPI filter

A separate sweep runs the autonomous obstacle scenario with the MPPI filter always on, varying only the planner’s tire model (the analytical planners use the SCM-calibrated parameters of Sec. III-B). All three tire models avoid the obstacles approximately equally (Table XVI and Fig. 19), indicating that the safety filter dominates the filter-mediated outcome and that the planner-tire choice is largely orthogonal to the safety outcome.

VII. 5G-PROFILE LATENCY ROBUSTNESS

A sequence model (N-HITS) is trained on the public 5G YouTube uplink dataset of Choi et al. [2] and used to generate a synthetic bitrate trace. The trace is mapped through a configurable queue-load model to produce a per-channel latency profile that is applied as an additive scheduled delay on the camera and command channels.

The closed-loop obstacle scenario is then run under the synthetic profile with three filter configurations: Table XVII and Fig. 21 report the result over 1215 trials. Both safety filter




Fig. 16: Autonomous safety-filter-only validation. Mean unique obstacles hit per run, stratified by terrain and safety filter, with whisker error bars showing across-seed standard deviation. The reported sweep covers all three deployment terrains (clay, dirt, sand) across three speeds and three bumpiness levels, 135 runs per (filter, terrain) cell. Aggregate KPIs are in Table XII.




Fig. 17: DOB-CBF neural-surrogate ablation: per-scenario collisions. Aggregate KPIs are in Table XIV.

TABLE XVII: Closed-loop collisions under the learned N-HiTS-5G latency profile. 1215 runs.

Filter	Coll./run	Clearance (m)	Interv. (%)
None	2.43	-1.40	—
DOB-CBF	0.01	+2.51	53
MPPI	0.09	+ 3.26	86

variants reduce collisions by more than 90 % relative to the no-filter baseline (DOB-CBF by 99.7 %, MPPI by 96 %).

VIII. TERRAIN- AND LATENCY-AWARE COLLISION WARNING

The safety filters in §VI-§VII modify the operator’s command stream when a collision is imminent. In some deployment modes (e.g. expert-loop teleoperation, or a safety filter that has been muted for debugging) the operator wants only a *notification* rather than a control override. We add an

independent forward collision warning component that runs in parallel with the rest of the stack and emits a discrete severity signal {GREEN, YELLOW, ORANGE, RED} on every controller tick.

The warning module is exposed through a small factory in line with the rest of the swappable safety layer, so the warning strategy can be selected at construction time. The default strategy is a time-to-collision predictor with two adjustments:

a) *Terrain awareness.*: The required stopping distance $d_{\text{stop}} = v\tau_r + v^2/(2a_b)$ uses a brake-deceleration $a_b(\hat{n})$ that is computed *analytically at init time* by querying the same rig tire surrogate the DOB-CBF and MPC use for traction-budget queries. For every $\hat{n} \in [0.40, 1.30]$ on a 0.05 grid, the surrogate is loaded with the manifold-interpolated Bekker vector at that $\hat{n}$, swept over braking slip ratios $\kappa \in [-0.40, 0]$ at static per-wheel F_z , and the peak $|F_x|$ at front and rear axles is summed to give the total available braking force;




Fig. 18: MPPI seed-trajectory ablation. Removing the seeds eliminates the safety filter’s commitment to evasive maneuvers; the weighted mean then averages over many comparably high-error samples rather than concentrating on a recoverable trajectory.




Fig. 19: Autonomous obstacle avoidance, planner tire model swept under a fixed MPPI filter. Mean unique obstacles hit per run stratified by terrain with across-seed whisker error bars; the three tire models are statistically indistinguishable here because the safety filter, not the planner-tire choice, dominates the safety outcome. Sweep matrix is clay/dirt/sand $\times$ 3 paths $\times$ 3 speeds $\times$ 3 bumpiness $\times$ 5 seeds. Aggregate KPIs are in Table XVI.

$a_b(\hat{n}) = \sum F_{x,\text{peak}}/m_{\text{veh}}$. The resulting table runs from $a_b(0.4) \approx 2.3 \text{ m/s}^2$ (soft, clay-like) to $a_b(1.1) \approx 4.7 \text{ m/s}^2$ (firm, sand-like) — both endpoints noticeably more conservative than the hand-tuned $2.5/6.0 \text{ m/s}^2$ heuristic the implementation previously used. The live $\hat{n}$ from the online terrain estimator (§IV) indexes into this table at runtime, so the warning is more conservative on soils that the vehicle cannot brake hard on.

b) Brake-decel validation.: The analytical $a_b(\hat{n})$ table is validated against actual Chrono SCM behaviour with 27 full-brake stops: three terrains $\times$ three initial speeds $\{3, 5, 7\} \text{ m/s}$ $\times$ three seeds, each scenario cruising to target speed and then applying brake = 1, throttle = 0 until the vehicle is

below 0.2 m/s . Stopping distance and mean decel are extracted from the recorded chassis trajectory and compared to the prediction at the brake-onset speed (Fig. 22). On mean decel, the rig-NN analytical table is within 0.1 m/s^2 on clay, over-predicts dirt by 0.7 m/s^2 (the classical contact-patch saturation gap of §III-D), and over-predicts sand by 1.1 m/s^2 — small enough that the resulting stopping-distance prediction lands within $\pm 0.5 \text{ m}$ of the recorded ground truth on 23 of 27 trials. Aggregated mean $|\Delta d_{\text{stop}}|$ is 0.17 m for the analytical table versus 0.45 m for the hand-tuned linear-interp fallback ($2.6\times$ improvement); the analytical prediction also has a small positive mean bias ($+0.10 \text{ m}$), meaning the warning is biased toward firing slightly earlier than strictly necessary, which is




Fig. 20: Learned N-HiTS 5G uplink profile applied to the camera and control channels (log- x histogram; dashed lines are channel means). The profile is bimodal: a low-latency good-window bulk (control around 10–25 ms, camera around 30–50 ms), a poor-window cluster near 100–200 ms, and discrete outage spikes at 450 ms (control) and 660 ms (camera). Mean one-way latency is approximately 94 ms (control) and 144 ms (camera).

TABLE XVIII: Forward collision warning lead time before impact (RED severity) under terrain $\times$ latency sweep. The vehicle drives blindly at a single 1.2 m rock with constant throttle. Higher latency and softer soil both increase the lead time, as designed.

	lat=0 ms	lat=150 ms	lat=300 ms
clay ($\hat{n}=0.5$)	1.56 s	1.74 s	1.76 s
dirt ($\hat{n}=0.7$)	1.09 s	1.25 s	1.48 s
sand ($\hat{n}=1.1$)	0.68 s	1.00 s	1.30 s

the safe direction.

c) HIL integration.: The warning module is wired through the sim node so any HIL teleoperation round can enable it. Per-tick severity is logged alongside the existing diagnostics, and severity transitions are reported on the sim-node console and, when the Irrlicht visualiser is active, surfaced to the operator as a text banner. When the online terrain estimator is active, the live $\hat{n}$ is forwarded to the warning system on every control message so that the brake-decel estimate adapts to the estimator’s current terrain belief; otherwise the warning falls back to the nominal n of the configured terrain preset. The warning never modifies commands, so it composes freely with any safety filter (none, DOB-CBF, MPPI, NMPC) used in the same round.

d) Latency awareness.: An EMA tracker of recent one-way network delays and a sliding-window jitter estimator inflate the operator reaction time by $\tau_r + \text{RTT} + k\sigma$, where σ is the standard deviation of one-way delays over the last second of received commands. Increasing the latency baseline or the jitter inflates d_{stop} and fires the warning earlier.

The benchmark sweeps three terrains and three one-way

latency settings. Table XVIII reports the time between the first RED warning and the rock impact: on soft clay the warning fires approximately 1.6–1.8 s before impact; on firm sand the same vehicle reaches the rock with about 0.7–1.3 s of lead. The lead time also grows with the configured operator latency on every terrain (clay 1.56 $\rightarrow$ 1.76 s as latency goes 0 $\rightarrow$ 300 ms, dirt 1.09 $\rightarrow$ 1.48, sand 0.68 $\rightarrow$ 1.30), confirming that the warning correctly couples both the terrain-conditioned stopping budget and the latency-conditioned operator-reaction budget.

IX. OPEN-SOURCE BENCHMARKING SUITE

A single invocation of the suite’s top-level driver executes all of the autonomous sub-sweeps that produce the non-HIL results reported in this paper, then merges the resulting figures and CSVs into the publication set. The paper tier completes approximately 13,000 Chrono closed-loop trials on a single 24-core workstation; the human-in-the-loop protocol of Sec. VI-A is run separately because it requires an operator at the wheel.

Reproducibility is enforced through a few architectural choices in the suite itself. Sensor noise is enabled in every trial so no oracle quantity is observable at inference time. A per-trial diagnostic CSV is saved alongside each run for post-hoc inspection. Aggregated KPIs deduplicate on the run key (*variant, terrain, path, speed, bumpiness, seed*), so a re-run cleanly fills only the missing cells without overwriting existing rows. The ZeroMQ publisher retries socket bind with linear backoff to eliminate TIME_WAIT races under rapid run cycling, and the publication step matches result folders by exact timestamp so that closely-named sweep variants are never conflated.

X. DISCUSSION

Two recent threads are directly adjacent to this framework and merit explicit comparison. Onozuka et al. [9] replace a terrain-parameter-dependent NN tire model with a physics-informed structure – a Janosi saturating shear law wrapped around two small networks that supply the force coefficients – and re-fit those coefficients online by stochastic gradient descent on state-derivative residuals. The approach is complementary to ours: they fold soil mechanics into a structured force law where we estimate the soil and re-condition an unstructured surrogate. A direct adaptation of their model into the per-axle interface of our acados solver improved offline force prediction (held-out $R_{F_y}^2$ from 0.35 to 0.59) but underperformed on aggressive transient maneuvers because the static formulation triggered QP failures in our in-horizon NMPC; a faithful deployment requires the dedicated curvilinear-coordinate, wheelspeed-state MPC of [9], which is out of this paper’s scope. Gupta et al. [10] compensate unmodeled dynamics with a reinforcement-learning residual on top of MPC; in a feasibility prototype on the same plant the residual closed less than 8 % of the residual tracking error and only at the largest model mismatch – consistent with our own earlier finding that a learned dynamics residual offered




Fig. 21: 5G-profile latency compensation sweep: per-scenario collisions. Aggregate KPIs are in Table XVII.




Fig. 22: Validation of the warning system's analytical brake-deceleration table against actual Chrono SCM stopping behaviour (27 trials, 3 terrains $\times$ 3 initial speeds $\times$ 3 seeds). Left: mean deceleration over each stop. The rig-NN analytical estimate (orange) matches the Chrono mean (black) closely on clay and slightly over-predicts on dirt and sand; the original linear-interp fallback (grey) under-predicts on clay and over-predicts on sand. Right: predicted vs actual stopping distance with the ± 0.5 m band shaded. Rig-NN points (circles) cluster tighter to $y = x$ than linear-interp ($\times$, scatter); mean $|\Delta d_{\text{stop}}|$ is 0.17 m analytical vs 0.45 m linear-interp.

little benefit on this plant – so this paper does not adopt RL compensation.

The empirical evidence supports each architectural choice. The whole-vehicle neural tire surrogate solves in ~ 14 ms (well within the 100 ms MPC step) and reduces median RMS crosstrack error against the *SCM-calibrated* analytical baselines by 35–43 % in the live-estimator regime (Table IV), separating clearly from them in the tail across the full terrain matrix (Table III), where even the calibrated baselines diverge on off-nominal dirt. The asymmetric throttle disturbance observer increases achieved speed by approximately 5 %

(4.24 $\rightarrow$ 4.42 m/s, 0.63 $\rightarrow$ 0.66 of the curvature-limited profile) at a small (~ 3 cm) tracking cost. The two-layer planner-aware stack drives collisions to near zero ($\leq 0.17/\text{run}$) when paired with either DOB-CBF or MPPI as the downstream safety filter, the MPPI seed trajectories are essential rather than auxiliary, the DOB-CBF filter benefits substantially from re-using the neural surrogate, and both safety filters cut collisions by $> 90\%$ under the learned 5G profile. The forward collision warning closes the advisory gap the override-style filters leave open: its analytical stopping-distance prediction lands within 0.17 m of the actual Chrono stop (2.6 $\times$ better than the prior

Collision-warning timeline (latency = 150 ms); background shading = severity GREEN→YELLOW→ORANGE→RED




Fig. 23: Severity escalation over time for one representative blind-drive run per terrain at 150 ms one-way delay. Background shading is the live severity band (GREEN → YELLOW → ORANGE → RED); curves are the chassis clearance to the rock (solid) and the warning system’s running stopping-distance estimate (dashed). The first RED fires when the clearance curve drops to the stopping-distance curve.




Fig. 24: Forward collision warning lead time before impact in the blind-drive sweep (no MPC, no safety filter, fixed throttle into a single rock). Both the terrain-conditioned brake budget and the latency-conditioned operator-reaction budget enlarge the required stopping distance and therefore advance the first RED warning: soft soil (clay) gets the longest lead, and within every terrain the lead grows monotonically with the configured one-way delay.

hand-tuned fallback), and lead time grows monotonically with both softer soil and longer one-way delay.

The terrain estimator is intentionally scoped to the sinkage exponent n , which is the parameter that transfers cleanly under closed-loop sinusoidal excitation. The HIL protocol of Section VI-A is implemented with a Logitech G29 and delayed command/camera channels; the autonomous sweeps provide the repeatable quantitative evidence, and any session can additionally enable the forward collision warning alongside the chosen filter.

A. Limitations and scope

This study is conducted entirely in simulation, on a single HMMWV plant on Chrono’s Soil Contact Model. We make no sim-to-real transfer claim: the contribution is the modular, latency-aware *architecture* and the relative comparisons

it enables on a high-fidelity, widely-used deformable-terrain plant [4], [7]. Those comparisons — learned surrogate versus analytical tire model, safety filter versus no safety filter, estimator-on versus wrong-prior — are internal to one plant and one harness, so they are unaffected by any absolute sim-to-real offset; and the plant is itself a swap point, so porting to hardware or another terramechanics model is a registration rather than a rewrite. The neural surrogate is trained and evaluated on the same SCM plant, so the analytical baselines are calibrated to that plant’s mean lateral friction with a single global parameter set (Sec. III-B): the comparison is against a fair, SCM-calibrated analytical model rather than an uninformative rigid-road baseline, and the residual gap reflects what a fixed parameterization structurally cannot capture about terrain-varying deformable forces, not a tuning deficit.

The online estimator recovers only the sinkage exponent n and reconstructs the remaining five Bekker–Mohr parameters from $\hat{n}$ along the clay–dirt–sand preset manifold — the parameter-known setting also used by the reference terramechanics estimators (Sec. IV-B). This assumes deployment soils lie near that manifold; soils with large independent excursions in cohesion, friction, or stiffness fall outside the present scope, and n -recovery degrades off the manifold. Estimating the full soil vector online, hardware transfer, and the human-subject teleoperation study the HIL protocol is built for are the principal directions for future work.

XI. CONCLUSION

We presented a modular, latency-aware framework that integrates terrain-adaptive control, online soil estimation, two-layer obstacle avoidance, and a terrain- and latency-aware collision warning around a single deformable-terrain plant. The novelty is the *integration*: where prior work treats terrain adaptation and delay-compensated safety in isolation, here a differentiable SCM tire surrogate, an online n -estimator that re-conditions it, swappable safety filters, and an advisory warning share one plant, one messaging substrate, and one benchmarking harness, so every architectural choice is

measured on the same matrix. Empirically, the surrogate-plus-estimator recovers near-oracle tracking with no prior terrain knowledge — within ≈ 20 mm median RMS crosstrack error of the matched-prior oracle and well below SCM-calibrated analytical baselines; the deployed proprioceptive-fused UKF tracks n across the deployable range at 4.5 % median error; both safety filters cut collisions by more than 90 % under a learned 5G latency profile; and the collision warning predicts stopping distance to 0.17 m. The modular swap points make each of these a replaceable component rather than a fixed pipeline, which is what positions the framework for the hardware-in-the-loop and full-soil-estimation extensions above.

REPRODUCIBILITY

The complete autonomous sweep, including the non-HIL figures and CSV-backed tables in this paper, is reproduced by the following single command in the provided conda environment:

```
python benchmarking/run.py -tier paper
```

The exact result folders backing each figure are catalogued alongside the published figures. The HIL rounds are intentionally excluded from this automated command because they require a human operator; they are run through a separate human-in-the-loop script.

ACKNOWLEDGEMENTS

This work builds on the Chrono::HIL framework [11] and Project Chrono [7], [5]. The 5G traffic profile is generated using the public N-HiTS-5G implementation released with Choi et al. [2].

REFERENCES

- [1] M. G. Bekker, *Introduction to Terrain-Vehicle Systems*. Ann Arbor, MI: University of Michigan Press, 1969.
- [2] Y.-H. Choi *et al.*, “ML-based 5G traffic generation for practical simulations using open datasets,” *IEEE Commun. Mag.*, vol. 61, pp. 130–136, 2023.
- [3] J. Dallas *et al.*, “Terrain adaptive trajectory planning and tracking on deformable terrains,” *IEEE Trans. Veh. Technol.*, vol. 70, no. 11, pp. 11255–11268, 2021.
- [4] R. Krenn and G. Hirzinger, “SCM – a soil contact model for multi-body system simulations,” in *Proc. Int. Soc. for Terrain-Vehicle Systems (ISTVS)*, Bremen, Germany, 2009.
- [5] R. Serban, M. Taylor, D. Negrut, and A. Tasora, “Chrono::Vehicle: template-based ground vehicle modelling and simulation,” *Int. J. Veh. Perf.*, vol. 5, no. 1, pp. 18–39, 2019.
- [6] H. Shibly, K. Iagnemma, and S. Dubowsky, “An equivalent soil mechanics formulation for rigid wheels in deformable terrain,” *J. Terramech.*, vol. 42, no. 1, pp. 1–13, 2005.
- [7] A. Tasora *et al.*, “Chrono: an open source multi-physics dynamics engine,” in *High Performance Computing in Science and Engineering*, pp. 19–49, Springer, 2016.
- [8] H. Zhang *et al.*, “Shared control of teleoperated vehicles with delay-compensated safety filtering,” in *Proc. IEEE Conf. Control Technol. Appl. (CCTA)*, pp. 192–199, 2025.
- [9] Y. Onozuka, J. Dallas, M. Suminaka, and J. Subosits, “Adaptive Model Predictive Control on Unknown Deformable Terrains Using Physics-Informed Learning Tire Models,” in *Proc. IEEE Intelligent Vehicles Symp. (IV)*, 2025, pp. 1640–1647.
- [10] P. Gupta, J. M. Smereka, and Y. Jia, “Reinforcement learning compensated model predictive control for off-road driving on unknown deformable terrain,” *arXiv:2408.09253*, 2024.

- [11] Z. Zhou *et al.*, “A Chrono-based framework for large-scale traffic simulation with human-in-the-loop,” 2023.