


Hard links and Symbolic links — A comparison





Visualized path difference between hard link and symbolic link references

Hard links and symbolic links are two different methods to refer to a file in the hard drive. These methods are part of the filesystem that organizes what file is what and where. A hard link is essentially a synced carbon copy of a file that refers directly to the inode of a file. Symbolic links on the other hand refer directly to the file which refers to the inode, a shortcut. In order to understand how symbolic and hard links work, we will need to go over what are inodes.

What is an inode?

The inode is a database that describes the file/directory attributes such as metadata and the physical location on the hard drive. They are essentially the numerical equivalent of a full address. With an inode, the OS can retrieve information about the

To make Medium work, we log user data. By using Medium, you agree to our Privacy Policy, including cookie policy. G Sign in to medium.com with Google

be moved to a different location on th it automatically. This will be importan

What is a hard link?

A hard link is a direct reference to a fil and not directories. By using a hardling location and the hardlink will still poi pointing to that file. There is no references to the original measures, marginal marginal marginal marginal measures.

Dejun Yang

zzidiv2017@gmail.com

Continue as Dejun

To create your account, Google will share your name, email address, and profile picture with medium.com. See medium.com's privacy policy and terms of

can only refer to files within the same volume otherwise symbolic links will be needed. To make a hard link of a file, you will require the ln command and refer to the source file before naming what the hard link will be named. Here is an example of how a hard link named test 2 will be made.

```
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions/test$ touch test
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
 ell_variables_expansions/test$ ls
                               trusty-64:~/holberton-system_engineering-devops/0x03-s
   1_variables_expansions/test$ In test test2
   grant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
   1_variables_expansions/test$ ls
                                reddit.html
                                                          test2
                                                  test
agrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-spell_variables_expansions/test$
```

First made the test file before making hard link test2


The file test should be completely empty and I will add "Hello" to it via the hard link.

agrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s _variables_expansions/test\$ emacs test2

Typing in Hello into the file test via test2

test2 (END)

Opening test 2 with Hello in it




Now what will happen if we copy over a similar file called test from a different folder into this folder? For this experiment we will change the folder name from 'test' to 'test folder'.

```
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions$ cp test ./testfolder/test
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions$ cd testfolder/
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions/testfolder$ emacs test
 agrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
                                                                            275219 test2~
                                  reddit.html
                                                       275219 test2
 agrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions/testfolder$ emacs test2
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions/testfolder$ cd ..
agrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s/
neľl_variaĎles_expansions$ mv
                                                           testfolder/test/
agrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s/
  11_variables_expansions$ cd testfolder/
 agrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
nell_variables_expansions/testfolder$
 75215 aaa.jpg
                        275179 a.jpg
                                                       275220 test
                                                                            275219 test2~
                                  reddit.html
                                                       275219 test2
```

Here we can see that the cp command does not change the inode value of the original value but mv does. We have copied over a file from the parent directory into 'testfolder' and the inode value has not changed. It is only when you move over a file and replace the file that the inode value changes.


What are symbolic links?

Symbolic links are essentially shortcuts that reference to a file instead of its inode value. This method can be applied to directories and can reference across different hard disks/volumes. Since the symbolic link is referring to the original file and not its



Making a symbolic link. Note the link has an arrow pointing to the original file in its filename

Since the symbolic link is a link that directs to the original file, changing the symbolic link should change the original file.




Changed the link hello_sym

```
Rob
Bob
Hello
hello (END)
```

The change is reflected in the original file

```
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions/testfolder$ ls -i
275215 aaa.jpg 275179 a.jpg 275219 hello~ 275207 reddit.html
275182 aa.jpg 275222 hello 275175 hello_sym
```

A quick Is -i check shows they have different inodes




Moving the original file to a different folder broke the link

```
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions/testfolder$ less hello_sym
hello_sym: No such file or directory
```

Opening the link shows the link is broken


So symbolic links can be seen as a static link to the last known location of the original file. The link should work even if you replace the original file with a different file with the same name.




Made a new file hello with new contents

```
vagrant@vagrant-ubuntu-trusty-64:~/holberton-system_engineering-devops/0x03-s
hell_variables_expansions/testfolder$ ls
aaa.jpg aa.jpg a.jpg hello hello~ hello_sym reddit.html
```

The link is now working again





About Help Legal

Get the Medium app



