

Comments and Corrections

Corrections to “Impact of the Modulation Chirp of a DEMZM on the Transmission of Signals Based on OFDM”

Paulo Almeida, *Student Member, IEEE*, and
Henrique Silva, *Member, IEEE*

In the above letter [1], equations (4) and (5) are incorrect, because the factor γ is missing in the $\cos(\cdot)$ terms. We apologize for this error. The correct equations follow:

$$V_1 = 2 \frac{\gamma \cos(\pi V_{bias}/V_\pi) + \gamma^2 - \alpha \gamma \sin(\pi V_{bias}/V_\pi)}{2\gamma \cos(\pi V_{bias}/V_\pi) + 1 + \gamma^2} m V_\pi \quad (4)$$

$$V_2 = -2 \frac{\gamma \cos(\pi V_{bias}/V_\pi) + 1 + \alpha \gamma \sin(\pi V_{bias}/V_\pi)}{2\gamma \cos(\pi V_{bias}/V_\pi) + 1 + \gamma^2} m V_\pi. \quad (5)$$

This error does not have any impact on the results that have been presented, since the terms changed in equations (4) and (5) are null when the dual-electrode Mach-Zehnder modulator is biased at the quadrature point.

REFERENCES

- [1] P. Almeida and H. Silva, “Impact of the modulation chirp of a DEMZM on the transmission of signals based on OFDM,” *IEEE Photon. Technol. Lett.*, vol. 25, no. 3, pp. 283–286, Feb. 1, 2013.

Manuscript received March 28, 2013; accepted April 8, 2013. Date of current version May 15, 2013. This work was supported in part by the Portuguese Foundation for Science and Technology, through the Ph.D. Grant SFRH/BD/62647/2009.

The authors are with the Department of Electrical and Computer Engineering, Instituto de Telecomunicações, University of Coimbra, Coimbra 3030-290, Portugal (e-mail: palmeida@co.it.pt; hjas@co.it.pt).

Digital Object Identifier 10.1109/LPT.2013.2258008