

---

# Java Network (Socket)


# Contents

---

- ◆ What is Socket
- ◆ Server Sockets and Sockets
- ◆ Datagram Sockets and Packets
- ◆ Client and Server Application


# Socket: Interface for Application Layer

## Echo Program




# Socket Address: IP and Port

**For example: Country and Airport**  
**Air lines: country A airport Q to**  
**country B airport R**





**communication: A host Q port to B host R port**      **1 port: N ports**



# Two types of Data Transportation Services



## 1. Connection oriented

◆ Transmission Control Protocol (TCP) : To obtain reliable, sequenced data exchange.




## 2. Connectionless

◆ User Datagram Protocol (UDP) : To obtain a more efficient, best-effort delivery.



# Socket Call for Connection-Oriented Protocol



# Server Sockets and Sockets

## ◆ ServerSocket Constructor

This class implements server sockets. A server socket waits for requests to come in over the network. It performs some operation based on that request, and then possibly returns a result to the requester.

*ServerSocket(int port) throws IOException*

- Creates a server socket, bound to the specified port.

```
ServerSocket ss = new ServerSocket(port);
```

## ◆ accept() Method

*Socket accept() throws IOException*

- Listens for a connection to be made to this socket and accepts it.

```
Socket s = ss.accept();
```

## ◆ close() Method

*void close() throws IOException*

- Closes this socket.

```
s.close();
```

## ◆ Socket Class

This class implements client sockets (also called just "sockets"). A socket is an endpoint for communication between two machines.

*Socket(String hostName, int port) throws*

*UnknownHostException, IOException*

- Creates a stream socket and connects it to the specified port number at the specified IP address.

```
Socket s = new Socket(server, port);
```

## ◆ getInputStream(), getOutputStream Method

*InputStream getInputStream() throws IOException*

- Returns an input stream for this socket.

*OutputStream getOutputStream() throws IOException*

- Returns an output stream for this socket.

```
OutputStream os = s.getOutputStream();
```

## ◆ close()

*void close() throws IOException*

- Closes this socket.

<http://docs.oracle.com/javase/8/docs/api/java/net/ServerSocket.html>

<http://docs.oracle.com/javase/8/docs/api/java/net/Socket.html>

# Server Sockets and Sockets

```
import java.io.*;
import java.net.*;
import java.util.*;

class ServerSocketDemo {
    public static void main(String args[]) {
        try {

            // Get Port
            int port = Integer.parseInt(args[0]);
            Random random = new Random();
            //Create Server Socket
            ServerSocket ss = new ServerSocket(port);
            //Create Infinite Loop
            while(true) {
                //Accept Incoming Requests
                Socket s = ss.accept();

                //Write Result to Client
                OutputStream os = s.getOutputStream();
                DataOutputStream dos = new
DataOutputStream(os);
                dos.writeInt(random.nextInt());

                //Close socket
                s.close();
            }
        } catch (Exception e) {
            System.out.println("Exception: " + e);
        }
    }
}
```

```
class SocketDemo {
    public static void main(String args[]) {
        try {
            //Get Server and Port
            String server = args[0];
            int port = Integer.parseInt(args[1]);
            //Create socket
            Socket s = new Socket(server, port);
            //Read random number from server
            InputStream is = s.getInputStream();
            DataInputStream dis = new
DataInputStream(is);
            int i = dis.readInt();
            //Display Result
            System.out.println(i);
            //Close Socket
            s.close();
        }
        catch (Exception e) {
            System.out.println("Exception: " + e);
        }
    }
}
```

Running :

```
% java ServerSocketDemo 4321
```



```
% java SocketDemo 127.0.0.1 4321
```




# Run Configuration in Eclipse


right click → run as → run configuration

```
5
6 public class HelloClient {
7
8     public static void main(String args[]) {
9         String message = "Hello: This is my test message";
10
11         // "obj" is the identifier that we'll use to refer
12         // to the remote object that implements the "Hello"
13         // interface
14         Hello obj = null;
15
16         try {
17             obj = (Hello)Naming.lookup("//" + "/HelloServer");
18             message = obj.sayHello();
19         } catch (Exception e) {
20             System.out.println("HelloClient exception: " + e.getMessage());
21             e.printStackTrace();
22         }
23         System.out.println("Message = " + message);
24     } // end of main
25 } // end of HelloClient
26
27
```





Search the program  
you want to run



Input parameters (space  
between parameters)  
→ Apply → run

```
47     } catch (IOException e) {  
48         System.out.println("Error : I/O Error." + e);  
49     }  
50 } // end of while  
51 } // end of main method  
52 } // end of Client Constructor  
53
```

Problems @ Javadoc Declaration Console Coverage  
Server [Java Application] C:\Program Files\Java\jre1.8.0\_144\bin\javaw.exe (2017年12月1日 上午10:27:11)

Initializint Port...  
Listen...

1 Server [Java Application] C:\Program Files\Java\jre1.8.0\_144\bin\javaw.exe  
2 Client [Java Application] C:\Program Files\Java\jre1.8.0\_144\bin\javaw.exe


Switch Application

# Example 2

```
public class SocketServerExample {
    //static ServerSocket variable
    private static ServerSocket server;
    //socket server port on which it will listen
    private static int port = 9876;
    public static void main(String args[])
        throws IOException, ClassNotFoundException{
        //create the socket server object
        server = new ServerSocket(port);
        //keep listens indefinitely until receives 'exit' call or program terminates
        while(true){
            System.out.println("Waiting for the client request");
            //creating socket and waiting for client connection
            Socket socket = server.accept();
            //read from socket to ObjectInputStream object
            ObjectInputStream ois = new ObjectInputStream(socket.getInputStream());
            //convert ObjectInputStream object to String
            String message = (String) ois.readObject();
            System.out.println("Message Received: " + message);
            //create ObjectOutputStream object
            ObjectOutputStream oos = new ObjectOutputStream(socket.getOutputStream());
            //write object to Socket
            oos.writeObject("Hi Client "+message);
            //close resources
            ois.close();
            oos.close();
            socket.close();
            //terminate the server if client sends exit request
            if(message.equalsIgnoreCase("exit")) break;
        }
        System.out.println("Shutting down Socket server!!");
        //close the ServerSocket object
        server.close();
    }
}
```

```
public class SocketClientExample {
    public static void main(String[] args)
        throws UnknownHostException, IOException,
        ClassNotFoundException, InterruptedException{
        /*get the localhost IP address, if server
        is running on some other IP, you need to use that*/
        InetAddress host = InetAddress.getLocalHost();
        Socket socket = null;
        ObjectOutputStream oos = null;
        ObjectInputStream ois = null;
        for(int i=0; i<5;i++){
            //establish socket connection to server
            socket = new Socket(host.getHostName(), 9876);
            //write to socket using ObjectOutputStream
            oos = new ObjectOutputStream(socket.getOutputStream());
            System.out.println("Sending request to Socket Server");
            if(i==4)oos.writeObject("exit");
            else oos.writeObject(""+i);
            //read the server response message
            ois = new ObjectInputStream(socket.getInputStream());
            String message = (String) ois.readObject();
            System.out.println("Message: " + message);
            //close resources
            ois.close();
            oos.close();
            Thread.sleep(100);
        }
    }
}
```

# Socket Call for Connectionless Protocol



# Datagram Sockets and Packets

◆ **UDP does not guarantee reliable, sequenced data exchange, and therefore requires much less overhead.**

## ◆ **DatagramSocket() Method**

*DatagramSocket() throws SocketException*

*DatagramSocket(int port) throws SocketException*

```
DatagramSocket ds = new DatagramSocket(port);
```

## ◆ **send() Method**

*void send(DatagramPacket dp) throws IOException*

```
ds.send(dp);
```

## ◆ **DatagramPacket Constructor**

*DatagramPacket(byte buffer[], int size)*

*DatagramPacket(byte buffer[], int size, InetAddress ia, int port)*

```
DatagramPacket dp = new DatagramPacket(buffer, buffer.length);
```

```
DatagramPacket dp = new DatagramPacket(buffer, buffer.length, ia, port);
```

## ◆ **close() Method**

*void close()*

## ◆ **receive() Method**

*void receive(DatagramPacket dp) throws IOException*

```
ds.receive(dp);
```

# Datagram Sockets and Packets

```
class DatagramReceiver {
    private final static int BUFSIZE = 20;
    public static void main(String args[]) {
        try {
            //Obtain port
            int port = Integer.parseInt(args[0]);

            //Create a DatagramSocket object for the port
            DatagramSocket ds = new DatagramSocket(port);

            //Create a buffer to hold incoming data
            byte buffer[] = new byte[BUFSIZE];

            //Create infinite loop
            while(true) {
                //Create a datagram packet
                DatagramPacket dp =
                    new DatagramPacket(buffer, buffer.length);

                //Receive data
                ds.receive(dp);

                //Get data from the datagram packet
                String str = new String(dp.getData());

                // Display the data
                System.out.println(str);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

```
class DatagramSender {
    public static void main(String args[]) {
        try {
            // Create destination Internet address
            InetAddress ia =
                InetAddress.getByName(args[0]);
            // Obtain destination port
            int port = Integer.parseInt(args[1]);

            // Create a datagram socket
            DatagramSocket ds = new DatagramSocket();

            //Create a datagram packet
            byte buffer[] = args[2].getBytes();
            DatagramPacket dp =
                new DatagramPacket(buffer, buffer.length,
                    ia, port);
            // Send the datagram packet
            ds.send(dp);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

## Running :

```
% java DatagramReceiver 4321
```

```
% java DatagramSender localhost 4321 Message
```



# Example 2

```
public class QuoteServerThread extends Thread {
    protected DatagramSocket socket = null;
    protected BufferedReader in = null;
    protected boolean moreQuotes = true;

    public QuoteServerThread() throws IOException {
        this("QuoteServerThread");
    }

    public QuoteServerThread(String name) throws IOException {
        super(name);
        socket = new DatagramSocket(4445);

        try {
            in = new BufferedReader(new FileReader("one-liners.txt"));
        } catch (FileNotFoundException e) {
            System.err.println("Could not open file. Serving time instead.");
        }
    }

    public void run() {
        while (moreQuotes) {
            try {
                byte[] buf = new byte[256];
                // receive request
                DatagramPacket packet = new DatagramPacket(buf, buf.length);
                socket.receive(packet);
                // figure out response
                String dString = null;
                if (in != null)
                    dString = new Date().toString();
                else
                    dString = getNextQuote();

                buf = dString.getBytes();
                // send the response to the client at "address" and "port"
```

```
                buf = dString.getBytes();
                // send the response to the client at "address" and "port"
                InetAddress address = packet.getAddress();
                int port = packet.getPort();
                packet = new DatagramPacket(buf, buf.length, address, port);
                socket.send(packet);
            } catch (IOException e) {
                e.printStackTrace();
                moreQuotes = false;
            }
        }
        socket.close();
    }

    protected String getNextQuote() {
        String returnValue = null;
        try {
            if ((returnValue = in.readLine()) == null) {
                in.close();
                moreQuotes = false;
                returnValue = "No more quotes. Goodbye.";
            }
        } catch (IOException e) {
            returnValue = "IOException occurred in server.";
        }
        return returnValue;
    }

    public static void main(String[] args) throws IOException {
        new QuoteServerThread().start();
    }
}
```

# Example 2

```
public class QuoteClient {
    public static void main(String[] args) throws IOException {
        if (args.length != 1) {
            System.out.println("Usage: java QuoteClient <hostname>");
            return;
        }
        // get a datagram socket
        DatagramSocket socket = new DatagramSocket();
        // send request
        byte[] buf = new byte[256];
        InetAddress address = InetAddress.getByName(args[0]);
        DatagramPacket packet = new DatagramPacket(buf, buf.length, address, 4445);
        socket.send(packet);
        // get response
        packet = new DatagramPacket(buf, buf.length);
        socket.receive(packet);
        // display response
        String received = new String(packet.getData(), 0, packet.getLength());
        System.out.println("Quote of the Moment: " + received);
        socket.close();
    }
}
```

# Client and Server Application

```
import java.io.*;
import java.net.*;

public class Server
{
    public ServerSocket svrSocket = null;
    public Socket socket = null;
    public InputStream inputStream = null;
    public OutputStream outputStream = null;
    public DataInputStream dataStream = null;
    public PrintStream printStream = null;
    public DataOutputStream dataOutputStream = null;
    public String message;
    public BufferedReader charStream = new
    BufferedReader(new InputStreamReader(System.in));

    public Server() {
        try {
            svrSocket = new ServerSocket(1056);
            System.out.println("\nInitializint Port...");
            System.out.println("\nListen...");
            socket = svrSocket.accept();
            System.out.println("\nConnect to Client!\n");
            inputStream = socket.getInputStream();
            dataStream = new DataInputStream(inputStream);
            outputStream = socket.getOutputStream();
            dataOutputStream = new
            DataOutputStream(outputStream);

            message = dataStream.readUTF();
            System.out.println(message + "\n");
        } catch( UnknownHostException e) {
            System.out.println("Error : Cannot find server." + e);
        }
        catch( IOException e ) {
            System.out.println("Error : I/O Error." + e);
        }
    }
}
```

```
public void readSocket(){
    try {
        message = dataStream.readUTF();
        System.out.println(message + "\n");
        if(message.equals("Exit")){
            System.exit(0);
        }
    }
    catch( UnknownHostException e) {
        System.out.println("Error : Cannot find server." + e);
    }
    catch( IOException e ) {
        System.out.println("Error : I/O Error." + e);
    }
}

public void writeSocket(){
    try {
        String initmsg_r = new String("Enter your message: ");
        dataOutputStream.writeUTF(initmsg_r);
        System.out.print("Enter please for ready... ");
        message = charStream.readLine();
        if (! Message.equals("Exit")) return;
        else {dataOutputStream.writeUTF("Exit");
            System.exit(0); }
    }
    catch( UnknownHostException e) {
        System.out.println("Error : Cannot find server." + e);
    }
    catch( IOException e ) {
        System.out.println("Error : I/O Error." + e);
    }
}
```

# Client and Server Application

```
public static void main(String args[]) {  
    Server svr = new Server();  
    for(;;){  
        svr.writeSocket();  
        svr.readSocket();  
    }  
}  
}  
// End of Server
```

```
import java.net.*;  
import java.io.*;  
  
public class Client {  
  
    public static void main(String args[]) {  
        // Initialize the stream  
        OutputStream outputStream = null;  
        DataOutputStream dataOutputStream = null;  
        InputStream inputStream = null;  
        DataInputStream dataStream = null;  
        BufferedReader charStream = null;  
  
        // Initialize Socket  
        Socket socket = null;  
        String message;  
  
        try {  
            charStream = new BufferedReader(new  
                InputStreamReader(System.in));  
            message = new String("Hi! I am a client");  
            socket = new Socket("127.0.0.1", 1056);
```

```
dataStream = new DataInputStream(inputStream);  
        outputStream = socket.getOutputStream();  
        dataOutputStream = new  
        DataOutputStream(outputStream);  
        dataOutputStream.writeUTF(message);  
    } catch(UnknownHostException e) {  
        System.out.println("Error : Cannot find server." + e);  
    }  
    catch(IOException e) {  
        System.out.println("Error : I/O Error." + e);  
    }  
  
    while(true) {  
        try {  
            inputStream = socket.getInputStream();  
            dataStream = new DataInputStream(inputStream);  
            message = dataStream.readUTF();  
            System.out.print(message);  
            if(message.equals("Exit")){ System.exit(0); }  
            message = charStream.readLine();  
            dataOutputStream.writeUTF(message);  
        } catch(UnknownHostException e) {  
            System.out.println("Error : Cannot find server." + e);  
        }  
        catch(IOException e) {  
            System.out.println("Error : I/O Error." + e);  
        }  
    } // end of while  
} // end of main method  
} // end of Client Constructor
```

# Exercise 1: Echo Program

## Echo program using socket:

- 1) client reads line from standard input (**inFromUser** stream) , and sends to server via socket (**outToServer** stream)
- 2) server reads line from socket
- 3) server converts line to uppercase, sends back to client
- 4) client reads from socket (**inFromServer** stream) , and show the modified line through (**outToUser** stream)

