

修改mysql5.5默认编码(图文步骤修改为utf-8编码)


作者： 字体：[增加 减小] 类型：转载 时间：2013-01-25 我要评论

安装mysql后，启动服务并登陆，使用show variables命令可查看mysql数据库的默认编码;mysql数据库的默认编码并不是utf-8如何修改呢，本文将详细介绍，感兴趣的朋友可以了解下

mysql数据库的默认编码并不是utf-8。

安装mysql后，启动服务并登陆，使用show variables命令可查看mysql数据库的默认编码：

```
mysql> show variables like 'character%';
+-----+-----+
| Variable_name | Value |
+-----+-----+
| character_set_client | utf8 |
| character_set_connection | utf8 |
| character_set_database | latin1 |
| character_set_filesystem | binary |
| character_set_results | utf8 |
| character_set_server | latin1 |
| character_set_system | utf8 |
| character_sets_dir | /usr/share/mysql/charsets/ |
+-----+-----+
8 rows in set (0.00 sec)
```



由上图可见database和server的字符集使用了latin1编码方式，不支持中文，即存储中文时会出现乱码。以下是命令行修改为utf-8编码的过程，以支持中文。

(1)关闭mysql服务

代码如下：

[复制代码](#)

```
service mysql stop
```

(2)修改 /etc/mysql/my.cnf （默认的安装路径）

代码如下：

[复制代码](#)

```
vim /etc/mysql/my.cnf
```

打开my.cnf后，在文件内的[mysqld]下增加如下两行设置：

代码如下：

[复制代码](#)

```
character_set_server=utf8  
init_connect='SET NAMES utf8'
```

(具体如截图所示)：

```
[mysqld]  
#  
# * Basic Settings  
#  
user                = mysql  
pid-file            = /var/run/mysqld/mysqld.pid  
socket              = /var/run/mysqld/mysqld.sock  
character_set_server=utf8  
init_connect='SET NAMES utf8'  
port                = 3306  
basedir             = /usr  
datadir             = /var/lib/mysql  
tmpdir              = /tmp  
lc-messages-dir     = /usr/share/mysql  
skip-external-locking  
  
脚本之家  
WWW.JB51.NET
```

保存退出。

(3) 重新启动mysql服务

代码如下：

[复制代码](#)

```
service mysql start
```

至此，完成修改默认编码，登陆mysql后重新使用show variable like '%character%'获得的输出效果如下：

```
mysql> show variables like '%character%';  
+-----+-----+  
| Variable_name | Value |  
+-----+-----+  
| character_set_client | utf8 |  
| character_set_connection | utf8 |  
| character_set_database | utf8 |  
| character_set_filesystem | binary |  
| character_set_results | utf8 |  
| character_set_server | utf8 |  
| character_set_system | utf8 |  
| character_sets_dir | /usr/share/mysql/charsets/ |  
+-----+-----+  
8 rows in set (0.00 sec)  
  
mysql>   
  
脚本之家  
WWW.JB51.NET
```

注

具体操作和输出情况如下：

```
root@xiaomo:~# service mysql stop
mysql stop/waiting
root@xiaomo:~# vim /etc/mysql/my.cnf
root@xiaomo:~# service mysql start
mysql start/running, process 10547
```

