

Final Exam

Course Name: Web Technology	Date: 06-June-2024
Course Code: IS231	Exam Duration: 2 Hours
Instructor(s): Dr. Neamat El-Tazi & Dr. Laila Esheiba	Total Marks: 60

PLEASE DELIVER THE EXAM PAPER WITH THE BUBBLE SHEET.

For each of the following statements, choose the right answer and copy your answer in the bubble sheet:

- Django is based on which framework?
 - MVC
 - MVVM
 - MVT
 - None of the previous
- For a model to be visible in the admin interface it has to be registered in which file?
 - settings.py
 - admin.py
 - views.py
 - None of the previous
- Which of the following statement(s) is true about the JavaScript?
 - It is a scripting language used to make the website interactive
 - It is an advanced version of Java for Desktop and Mobile application development
 - It is a markup language of Java to develop the webpages
 - All of the above
- To perform programming logic in Django templates, you can use 'template tags', what is a correct syntax to start a 'for' loop?
 - { for x in y }
 - < % for x in y %>
 - {% for x in y %}
 - None of the previous
- What is a correct syntax for creating a Django project?
 - django start my_tennis_club
 - py manage.py start-django my_tennis_club
 - django-admin startproject my_tennis_club
 - None of the previous
- If you have a Django application named members, and a model named Member, what is a correct syntax to import the model?
 - from members.models import Member
 - import Member from members
 - import members.Member
 - None of the previous
- Which is the correct syntax to call an external JavaScript file in the current HTML document?
 - <script src="jsfile.js"></script>
 - <script href=" jsfile.js"></script>
 - <import src=" jsfile.js"></import>
 - <script link=" jsfile.js"></script>
- Which JavaScript method is used to access an HTML element by id?
 - getElementById()
 - getElement(id)
 - getElementById(id)
 - elementById(id)
- Which property is used to define the HTML content to an HTML element with a specific id?
 - innerText
 - innerHTML
 - elementText
 - innerHTML
- When you have done changes in a model in Django, which command has to be executed in order to make the changes take effect in the database?

- a. python manage.py runmigrations
c. python manage.py makemigrations

- b. python manage.py executemigrations
d. None of the previous

11. Which JavaScript method is used to write on browser's console?

- a. console.write()
b. console.output()
c. console.log()
d. console.writeHTML()

12. Which JavaScript method is used to write into an alert box?

- a. window.alertHTML()
b. window.alert()
c. window.alertBox()
d. window.alertContent()

13. In HTML DOM, which of the following properties are read-only?

- a. nodeName
b. nodeValue
c. nodeName and nodeValue
d. None of the previous

14. Which is the correct syntax to declare a constant in JavaScript?

- a. const constant_name;
b. constant_name const;
c. constant_name const = value;
d. const constant_name = value;

15. What will be the output of this code?

```
<script>  
    const VALUE = 10;  
    VALUE = 20;  
</script>
```

- a. 10
b. 20
c. ValueError
d. TypeError

16. Can we use a function as a variable value?

- a. Yes
b. No

17. What will be the value of X?

```
<script>  
    var X=10;  
    function myfunc()  
    {  
        let x=20;  
    }  
    document.write(X);  
</script>
```

- a. 20
b. 10
c. ValueError
d. TypeError

18. What is the output of the following JavaScript code?

```
<script>  
    var a = 10 + 20 + "5";  
    document.getElementById("demo").innerHTML = a;  
</script>
```

- a. 35
b. 305
c. TypeError
d. ValueError

19. What will be the output of the following JavaScript code?

```
<script>  
    var x = 12.34;  
    document.getElementById("test").innerHTML = typeof(x);  
</script>
```

- a. int
b. float
c. long
d. number

20. Which is the correct syntax to access an object property in JavaScript?

- a. objectName.propertyName
b. objectName[propertyName]

- c. `objectName["propertyName"]` d. None of the previous
21. What will be the output of the following JavaScript code?

```
<script>
    var numbers = [1,2,3,4];
    function myfunc(total,value)
    {
        return total+value;
    }
    var sum=numbers.reduce(myfunc,2);
</script>
```

- a. 10
c. 9

- b. 7
d. None of the previous

22. What will be the output of the following JavaScript code?

```
<script>
    var numbers = [170,50,25];
    function myfunc(total,value)
    {
        return total-value;
    }
    var x=numbers.reduce(myfunc);
    document.write(x);
</script>
```

- a. 100
c. 245

- b. 95
d. None of the previous

23. "Expires: Tuesday, 17 Dec 2020 18:30 GMT" is _____ header denoting _____
- a. request, time-based caching
c. request, content-type caching
- b. response, content-based caching
d. response, time-based caching

24. What will be the output of the following JavaScript code?

```
<script>
    const arr = [10, 20, 30];
    let result = 0;
    arr.forEach(myFunction);
    document.write("Result: ", result)
    function myFunction(value, index, array) {
        result += value;
    }
</script>
```

- a. Result: 102030
c. Result: 10,20,30

- b. Result: 60
d. ValueError

25. What will be the output of the following JavaScript code?

```
<script>
    const values = [10, 20, 30];
    const result = values.map(myFunction);
    document.write("Result: ", result);
    function myFunction(value, index, array) {
        return value * value;
    }
</script>
```

- a. Result: 10,20,30
c. Result: 100,400,900

- b. Result: 10*10,20*20,30*30
d. Result: 100400900

26. Which function is used to serialize an object into a JSON string in JavaScript?

- a. `parse()`
c. `stringify()`

- b. `convert()`
d. None of the previous

27. In Python, _____ defines a block of statements.

- a. Block
c. Indentation

- b. Loop
d. None of the previous

28. What will be the output of this JavaScript code?

```
<script>
    var numbers = [10, 20, 30];

    function myFunction(value, index, array) {
        return value > 10;
    }

    var y = numbers.find(myFunction);
    document.write(y);
</script>
```

- a. 20,30
c. 20

- b. [20,30]
d. None of the previous

29. What will be the output of the following JavaScript code?

```
<script>
try {
    const cars = {
        company: "Honda",
        color: "white"
    };
    var x = "color";
    delete cars.company;
    document.write(cars.company);
    document.write(cars[x]);
}
catch (err) {
    document.write(err.message);
}
</script>
```

- a. Hondaundefined
c. undefinedwhite

- b. undefinedcolor
d. TypeError

30. What will be the output of the following JavaScript code?

```
<html>
<body>
<p id="demo"></p>
<script>
let x = 10;
let y = 20;
let text = "x * y";
let result = eval(text);
document.getElementById("demo").innerHTML = result;
</script>
</body>
</html>
```

- a. x*y
c. valueError

- b. "200"
d. None of the previous

31. What will be the output of this JavaScript code?

```
<script>
    var numbers = [10, 20, 30];
    function myFunction(value, index, array) {
        return value > 10;
    }

    var y = numbers.filter(myFunction);
    document.write(typeof y);
</script>
```

- a. array
c. object

- b. number
d. None of the previous

32. What will be the output of this JavaScript code?

```
<script>
    var numbers = [10, 20, 10, 30];
    var y = numbers.lastIndexOf(10);
    var z = numbers.indexOf(30);
    document.write(y+z);
</script>
```


- a. 03
c. 23
33. What will be the output of the following Java Script code snippet?
- ```
function test(...args) {
 document.write(typeof(args));
}
test(12);
```
- b. 3  
d. None of the previous

- a. NaN  
c. object
34. What will be the output of the following JavaScript code?
- ```
var quiz=[1,2,3];  
var result=quiz.concat(6,7,8);  
document.write(result);
```
- b. number
d. array

- a. error
c. 1,2,3,6,7,8
35. What will be the output of the following JavaScript code?
- ```
var a=0;
for(a;a<5;a++);
document.write(a);
```
- b. [1,2,3,6,7,8]  
d. None of the previous

- a. 01234  
c. Error
36. What will be the output of the following python code?
- ```
newtuple=(1,2,3,4)  
(*k)=newtuple  
Print(k)
```
- b. 0
d. None of the previous

- a. 2,3,4
c. 1,2,3
37. What will be the output of the following Python code?
- ```
newtuple=(1,2,3,4)
(x,*k,y)=newtuple
Print(k)
```
- b. [2,3,4]  
d. None of the previous

- a. 2,3  
c. Python Error
38. Which is the correct HTML statement to define the red color of the paragraph text?
- ```
newtuple=(1,2,3,4)  
(x,*k,y)=newtuple  
Print(k)
```
- b. [2,3]
d. None of the previous

- a. `p style="color: #ff0000;">`
c. Both a. and b.
39. Which HTML tag is used to define highlighted text?
- b. `<p style="color: red;">`
d. None of the previous

- a. `<highlight>`
c. `<m>`
40. Which is the correct HTML statement to display H₂O in a paragraph?
- b. `<mark>`
d. None of the previous

- a. `<p>H<sup>2</sup></sup>O</p>`
b. `<p>H<ins>2</ins></ins>O</p>`
c. `<p>H<below>2</below>O</p>`
d. `<p>H<sub>2</sub></sub>O</p>`

41. Which is the correct HTML statement to display HelloHi! in a paragraph?
- a. `<p><del>Hello</del><ins>Hi!</ins></p>`
b. `<p><del>Hello</del><ins>Hi!</ins></p>`
c. `<p><del>Hello</del><mark>Hi!</mark></p>`
d. None of the above

42. Which attribute specifies the path to the image?

- a. href
- b. link
- c. src
- d. All of the above

43. Can we use class name with multiple HTML elements?

- a. Yes
- b. No

44. The ___ property is used in the positioning of the background image.

- a. background-image
- b. background-position
- c. padding
- d. All of the above

45. Which of the following selectors selects the specified elements of type E with a particular class value?

- a. E ~ F
- b. E.class
- c. *
- d. .Class (E)

46. Which of the following selectors selects all elements of E that have the attribute (attr) that ends with a given (value)?

- a. E[attr~=value]
- b. E[attr\$=value]
- c. E[attr*=value]
- d. None of the above

47. Which of the following selectors selects an element that has no children?

- a. :nochild
- b. :empty
- c. :no-child
- d. None of the above

48. What will be the output of the following Python code?

```
b="Hello, World!"  
print(b[-5:-3])
```

- a. orl
- b. or
- c. wo
- d. None of the above

49. What will be the output of the following Python code?

```
thistuple=(1,2,3,3,4,5)  
x=thistuple.index(3)  
print(x)
```

- a. 3
- b. 2
- c. 4
- d. None of the previous

50. If an application is running on Asynchronous Server Gateway Interface (ASGI), then it will handle client requests in a sequential manner?

- a. True
- b. False

51. Can you play audios in HTML?

- a. Yes
- b. No

52. What will be the output of the following Python code?

```
fruits={"apple","banana","cherry"}  
fruits.add("apple")  
x=len(fruits)  
print(x)
```

- a. 4
- b. 3
- c. 2
- d. None of the previous

53. What will be the output of the following Python code?

```
car = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
y=car.keys()  
car["color"]="red"  
print(len(y))
```

- a. 3

b. 6

- c. 4
54. To add items from another set to the current set we use _____ method, while to append items from another list to the current list we use _____ method. d. 8
- Extend(), append()
 - Extend(), update()
 - Update(), extend()
 - Update(), append()
55. To make a copy of a dictionary, we can use _____.
- Copy()
 - dict()
 - a. and b.
 - makecopy()
56. In CSS, "color:red" can be called as _____.
- Selector
 - Declaration
 - Rule
 - Value
57. External CSS style has the highest priority
- True
 - False
58. The _____ HTTP request header specifies information about the software (browser) making the request.
- Referrer
 - User-Agent
 - cookie
 - None of the above
59. What does {{ name }} this mean in Django Templates?
- {{ name }} will be the output.
 - It will be displayed as name in HTML.
 - The name will be replaced with values of Python variable.
 - None of the above.
60. What is the output of the following JavaScript snippet?
- ```

x = "20"
y = 10
document.writeln(x+y,x-y)

```
- 30, 10
  - 30, NAN
  - 2010, NAN
  - 201010
61. Which of the following is the correct way of creating a hyperlink in HTML?
- <a> www.google.com</a>
  - <a href="www.google.com" google /a>
  - <a href="www.google.com"> google </a>
  - <a link="www.google.com" google </a>
62. What is the purpose of using div tags in HTML?
- For creating different styles
  - For creating different sections
  - For adding headings.
  - For adding titles
63. Which of the following is the correct way to add background color in HTML?
- <body color = "green">
  - <body bg-color="green">
  - <body style = "background-color=green">
  - <body style="background-color: green;">
64. If you have the following JavaScript statement: `const f = (a, b) => a + b + 5;`
- f(3,4) will return 75
  - f(4,5) will return 9
  - f(4,5) will return 14
  - Not a correct syntax for an arrow function

65. To multiply an array of numbers (named myNumbers) with 4, the following is a correct syntax to do it:
- myNumbers.map((value)=>value\*4);
  - myNumbers.filter((value)=>value\*4);
  - myNumbers.map(value\*4);
  - myNumbers.filter(value\*4);
66. To select numbers that are less than 10 from an array of numbers (named myNumbers), the following is a correct syntax to do it:
- myNumbers.map((value)=>value<10);
  - myNumbers.filter((value)=>value<10);
  - myNumbers.map(value<10);
  - myNumbers.filter(value<10);
67. var colors = (1:"red", 2:"green", 3:"blue") is one of the ways of defining an array in JavaScript?
- True
  - False
68. In the following statement: myNumbers=[1,2,3]  
x=myNumbers.pop()  
The removed item will be 1
- True
  - False
69. In the following statement: myNumbers=[1,2,3]  
x=myNumbers.pop()  
The removed item will be 3
- True
  - False
70. In Python, the value of [] is False?
- True
  - False
71. In Python, it is possible to use the set() constructor to create a set?
- True
  - False
72. In Python, A set is a collection which is both unordered and indexed?
- True
  - False
73. def f(\*\*person):  
print("Person's name is " + person["name"])  
f(name="Ahmed", age=10)  
The above statement will return:
- Person's name is Ahmed
  - Person's name is Ahmed and Age is 10
  - Error as the function f doesn't take except one argument
  - Error as the function f doesn't take an argument called "name"
74. y=lambda x: x/20  
print(y(100))  
The above statement will return:
- Error as there is no function called y
  - 100/20
  - 5
  - y(100)
75. In the following Python statements:  
if 1<2:  
print("One is less than Two!")  
print("Oae is less than Two!")
- The output will be: One is less than Two! One is less than Two!
  - The output will be: One is less than Two!
  - The output will be: One is less than Two!  
One is less than Two!
  - The output will be an Error
76. The output of the following statement in python is:  
x = "My Lovely Bird!"  
print(x[:7])
- My Love
  - My Lovel
  - ly Bird!
  - y Bird!
77. The output of the following statement in python is:  
x = "My Lovely Bird!"  
print(x[7:])



78. What will be the output of this JavaScript code?

```
const myArr = [1, 2, [3, [4, 5, 6], 7], 8];
const newArr = myArr.flat();
document.writeln(newArr);
```

- a. 1,2,3,[4,5,6],7,8  
c. 1,2,3,4,5,6,7,8

- b. My Love  
d. y Bird!

- b. 1,2,[3,4,5,6],7,8  
d. None of the previous

Based on the following HTML page, answer the following questions:

```
<!DOCTYPE html>
<html>
<head>
</head>
<body>
<h2 id="id1">Hello World</h2>
<p>Welcome</p>
<div>
 <p>Paragraph 1 .</p>
 <p>Paragraph 2 .</p>
 <section><p>Paragraph 3 .</p></section>
</div>
<p>Paragraph 4.</p>
<p>Paragraph 5.</p>
<script>
const my=document.getElementsByTagName("p");
document.getElementById("id1").innerHTML=my.length;
</script>
</body>
</html>
```

79. To get the value of the text node of the h2 element node, you can use document.getElementById("id1").innerHTML which is equivalent to

- a. document.getElementById("id1").text;  
b. document.getElementById("id1").firstChild.nodeValue;  
c. document.getElementById("id1").nodeValue;  
d. none of the above

80. Based on the above html page, the content of h2 element will be presented as

- a. Hello World  
b. Hello World 6  
c. 5  
d. None of the above

81. The number of objects in my variable is

- a. 4  
c. 6  
b. 5  
d. 3

82. By using this CSS selector div > p { color: red}, how many p elements will be styled?

- a. 3  
c. 5  
b. 2  
d. 6

83. By using this CSS selector div ~ p {color: blue}, the number of p elements that will be styled is

- a. 3  
c. 5  
b. 2  
d. 6

84. Using document.getElementById("id1").nodeType will return

- a. 1  
c. Element node  
b. 3  
d. Text node

Based on the following HTML page, answer the following questions

```
<!DOCTYPE html>
<html>
<head>
<style>
a[target=_blank] {
 background-color: yellow;
}
p:first-child {color:red;}
</style>
</head>
<body>

<h2>CSS Selector</h2>
<p>Hello I am Here:</p>
<p>Hello I am Here: Paragraph 2</p>
<p> Hello I am Here: P3</p>
w3schools.com
disney.com
wikipedia.org
</body>
</html>
```

85. In a[target=\_blank], the [target=\_blank] is called
- attribute selector
  - anchor selector
  - pseudo element selector
  - none of the above
86. By using p:firstchild {color:red;} , the number of elements that will be styled
- 1
  - 2
  - 3
  - None of the above
87. To change the background color of all <a> elements to be yellow, you can use
- a[target] {background-color: yellow;}
  - a.all{background-color: yellow;}
  - a[target=\_blank target=\_top] {background-color: yellow;}
  - a {background-color: yellow;}
88. To change the color of <a> elements to yellow when the mouse moves over it, you can use
- a:hover {background-color: yellow;}
  - a: hover {background-color: yellow;}
  - a:link {background-color: yellow;}
  - a:active {background-color: yellow;}
89. href is a/an \_\_\_\_\_ while "\_blank" is a \_\_\_\_\_
- value, attribute
  - link, value
  - attribute, value
  - link, text node
90. The hyperlink <a href="https://w3schools.com"> is a/an \_\_\_\_\_ URL, while <a href="Page2.html"> is an example of a/an \_\_\_\_\_ URL.
- Absolute, relative
  - Relative, absolute
  - Relative, Relative
  - None of the above

*End of Questions*  
*Good luck!*