What is claimed is:

1. A system, comprising:

a vehicle having at least one network zone;

a policy manager circuit structured to interpret a policy comprising an external data routing description, wherein the policy comprises a default policy value;

a configuration circuit structured to configure a gatekeeper interface circuit in response to the external data routing description and an external data service description;

the gatekeeper interface circuit interposed between the at least one network zone and at least one external communication portal selectively couplable to an external device; and

wherein the gatekeeper interface circuit is structured to regulate communications between end points of a first network zone and the at least one external communication portal, and to regulate communications between end points of a second network zone and the at least one external communication portal.

2. The system of claim 1, wherein the policy further comprises a primary policy value, and wherein the configuration circuit is further structured to configure the gatekeeper interface circuit in response to the primary policy value.

3. The system of claim 2, wherein the configuration circuit is further structured to determine whether the primary policy value is present, and to utilize the primary policy value as the policy instead of the default policy value in response to determining the primary policy value is present.

4. The system of claim 2, wherein the policy further comprises a secondary policy value, and wherein the configuration circuit is further structured to configure the gatekeeper interface circuit in response to the secondary policy value.

5. The system of claim 4, wherein the configuration circuit is further structured to determine whether the secondary policy value is present, and to utilize the secondary policy value as the policy instead of either the default policy value or the primary policy value, in response to determining the secondary policy value is present.

6. The system of claim 4, wherein the configuration circuit is further structured to apply the secondary policy value as the policy, and to apply consistent portions of the primary policy value as a further portion of the policy.

7. The system of claim 4, wherein the default policy value comprises a permanent storage policy, and wherein the primary policy value comprises a tool supplied policy.

8. The system of claim 7, wherein the secondary policy value comprises a post-manufacturing policy.

9. The system of claim 8, wherein the policy manager circuit is further structured to interpret the tool supplied policy from a second external device.

10. The system of claim 9, wherein the second external device comprises at least one device selected from the devices consisting of: a service tool, a manufacturing tool, a web based application, and a cloud based application.

11. The system of claim 10, wherein the policy manager circuit is further structured to interpret the post-manufacturing policy from the second external device.

12. The system of claim 10, wherein the policy manager circuit is further structured to interpret the post-manufacturing policy from a third external device.

13. The system of claim 8, wherein the configuration circuit is further structured to determine whether each of the primary policy value and the secondary policy value are present, and to utilize, in order, the secondary policy value, the primary policy value, or the default policy value.

14. The system of claim 8, wherein the policy manager circuit is further structured to interpret the primary policy value from a second external device in response to the default policy value.

15. The system of claim 8, wherein the policy manager circuit is further structured to interpret the secondary policy value from a second external device in response to at least one of the primary policy value or the default policy value.