CLAIMS

1. A toothbrush with a handle (1), at least one cleaning zone (2) and at least one deformable element (3), where the deformable element (3) has a first flexible arm (31) arranged relatively towards the cleaning zone (2) and a second flexible arm (32) arranged relatively away from the cleaning zone (2), where the deformable element (3) can move from a resting position in which the first arm (31) is substantially flat and aligned to the handle (1), to a cleaning position in which the first arm (31) and the cleaning zone (2) adopt a curvature of a surface of a dentition (40), where the arms (31, 32) form a wedge being connected together at one end (33) of the deformable element and distanced from each other at the other end (34) of the deformable element, where the first and second arms (31, 32) are linked by at least two bridges (35, 35′, 35″) which are tiltable with respect to the first and second arms (31, 32) when pressure is applied to the cleaning zone (2), wherein the arms (31, 32) and bridges (35, 35′, 35″) enclose a void space (36, 36′, 36″, 36‴).
2. The toothbrush of claim 1, wherein the arms (31, 32) and the bridges (35) are formed integrally by injection moulding.
3. The toothbrush of claims 1-2, wherein the arms (31, 32) and the bridges (35, 35′, 35″) are made of a thermoplastic elastomer (TPE) material.
4. The toothbrush of claim 3, wherein the TPE material has a Shore D hardness of about 50 to 66, preferably about 54 to 62, more preferably about 56 to 60, most preferably about 58.
5. The toothbrush of any of the preceding claims, wherein the bridges (35, 35′, 35″) have hinges (38) flexibly connecting the bridges (35, 35′, 35″) to the arms (31, 32).
6. The toothbrush of claim 5, wherein the hinges (38) are integral hinges.
7. The toothbrush of claim 6, wherein the integral hinges (38) have a thickness in the longitudinal direction of the toothbrush of about 0.2 to 0.4 mm.
8. The toothbrush of any of the preceding claims, wherein the distance (I‴) between the arms (31, 32) at a proximal end (34) of the deformable element is between about 3mm to 5mm, preferably 3.5 to 4.5mm.
9. The toothbrush of any of the preceding claims, wherein a longitudinal distance (D_2, D_3) between adjacent bridges is between about 5 to 9mm, preferably between 7 to 8mm.
10. The toothbrush of any of the preceding claims, wherein the deformable element (3) is not longer than 150% of the length of the cleaning zone (2), preferably not longer than 130% of the length of the cleaning zone (2).

11. The toothbrush of any of the preceding claims, wherein the deformable element (3) has 2-7 bridges (35, 35′, 35″), preferably 3-5 bridges (35, 35′, 35″), most preferably 3 bridges (35, 35′, 35″).
12. The toothbrush of any of the preceding claims, wherein the handle (1) comprises a polypropylene skeleton and is formed integrally in one piece with the deformable element (3) by injection moulding.
13. The toothbrush of any of the preceding claims, wherein the deformable element (3) consists of a material having an elongation at break of 500 to 800%, preferably 600 to 750%, more preferably 650 to 700%.
14. The toothbrush of any of the preceding claims, wherein an angle (α) between the bridges (35, 35′, 35″) and the arms (31, 32) is around 90° in the resting position, and around 95° to 110°, preferably around 97° to 105° when pressure is applied to the cleaning zone (2).