CLAIMS

1. A vehicle diagnostic processing method, applied to a diagnostic device (50), characterized in that the diagnostic device (50) comprises: a diagnostic communication protocol module (51), a service allocation module (52), a diagnostic event management module (53), and a data communication module (54), and the method comprises:

obtaining (S101), by the diagnostic communication protocol module (51), a diagnostic service request, wherein the diagnostic service request comprises a service request event and a service request type;

performing (S102), by the diagnostic communication protocol module (51), filtering and unpacking processing on the diagnostic service request to obtain a processed diagnostic service request;

uploading (S103), by the service allocation module (52), the processed diagnostic service request to the diagnostic event management module (53) or the data communication module (54) according to a service request type in the processed diagnostic service request; and

upon receiving the processed diagnostic service request, performing (S104), by the diagnostic event management module (53) or the data communication module (54), corresponding service diagnostic processing according to the service request event.

2. The method according to claim 1, wherein the diagnostic device (50) further comprises: a session determination module (55), and the method further comprises:

if determining that the processed diagnostic service request meets a preconfigured filtering condition, taking (S201), by the session determination module (55), the processed diagnostic service request as a target diagnostic service request and reporting (S201) the target diagnostic service request to the service allocation module (52); and

the uploading (S102), by the service allocation module (52), the processed diagnostic service request to the diagnostic event management module (53) or the data communication module (54) according to a service request type in the processed diagnostic service request comprises:

uploading (S202), by the service allocation module (52), the target diagnostic service request to the diagnostic event management module (53) or the data communication module (54) according to the service request type in the target diagnostic service request.

3. The method according to claim 1 or 2, wherein the uploading (S103), by the service allocation module (52), the processed diagnostic service request to the diagnostic event management module (53) or the data communication module (54) according to a service request type in the processed diagnostic service request comprises:

when determining that the service request type is a passive service request type, uploading (S301), by the service allocation module (52), the processed diagnostic service request to the diagnostic event management module (53) matching the passive service request type;

or

when determining that the service request type is an active service request type, uploading (S401), by the service allocation module (52), the processed diagnostic service request to the data communication module (54) matching the active service request type.

4. The method according to any one of claims 1 to 3, wherein the upon receiving the processed diagnostic service request, performing (S104), by the diagnostic event management module (53) or the data communication module (54), corresponding service diagnostic processing according to the service request event comprises:

upon receiving the processed diagnostic service request, reading (S302), by the diagnostic event management module (53), diagnostic information related to the service request event from the diagnostic event management module (53) according to the service request event, and obtaining a fault code corresponding to the diagnostic information.

5. The method according to any one of claims 1 to 3, wherein the upon receiving the processed diagnostic service request, performing (S104), by the diagnostic event management module (53) or the data communication module (54), corresponding service diagnostic processing according to the service request event comprises:

upon receiving the processed diagnostic service request, determining (S402), by the data communication module (54), an operating mode corresponding to the processed diagnostic service request according to a target controller in the processed diagnostic service request; and

when determining that the operating mode corresponding to the processed diagnostic service request is an intra-domain operating mode, sending (S403), by the data communication module (54), the processed diagnostic service request to a local domain controller, to allow the local domain controller to perform a diagnostic operation according to a target diagnostic application corresponding to the service request event and obtain diagnostic information.

6. The method according to claim 5, wherein the method further comprises:

when determining that the operating mode corresponding to the processed diagnostic service request is an inter-domain operating mode, sending (S404), by the data communication module (54), the processed diagnostic service request to an external domain controller, to allow the external domain controller to perform a diagnostic operation according to the target diagnostic application corresponding to the service request event and obtain diagnostic information.

7. A diagnostic device (50), characterized in that the diagnostic device (50) comprises a diagnostic communication protocol module (51), a service allocation module (52), a diagnostic event management module (53), and a data communication module (54);

the diagnostic communication protocol module (51) is configured to obtain a diagnostic service request;

the diagnostic communication protocol module (51) is further configured to perform filtering and unpacking processing on the diagnostic service request to obtain a processed diagnostic service request;

the service allocation module (52) is configured to upload the processed diagnostic service request to the diagnostic event management module (53) or the data communication module (54) according to a service request type in the processed diagnostic service request; and

the diagnostic event management module (53) is configured to, upon receiving the processed diagnostic service request, perform corresponding service diagnostic processing according to a service request event of the processed diagnostic service request;

or

the data communication module (54) is configured to, upon receiving the processed diagnostic service request, perform corresponding service diagnostic processing according to a service request event of the processed diagnostic service request.

8. An electronic device (70), characterized by comprising: a processor (71) and a memory (72) communicatively connected to the processor (71);

wherein the memory stores a computer-executable instruction; and

the processor (71) executes the computer-executable instruction stored in the memory (72) to implement the method according to any one of claims 1 to 6.

9. A vehicle (60), characterized by comprising domain controllers (61, 62) and a diagnostic device (63, 64) disposed in each of the domain controllers, wherein the diagnostic device (63, 64) is configured to implement the method according to any one of claims 1 to 6.

10. A computer-readable storage medium, characterized in that the computer-readable storage medium stores a computer-executable instruction which, when executed by a processor, is used to implement the method according to any one of claims 1 to 6.

11. A computer program product, characterized by comprising a computer program which, when executed by a processor, implements the method according to any one of claims 1 to 6.