CLAIMS:

1. Agitator (20) configured to be used in a suction head (1) that is configured to be applied in a vacuum cleaner and to perform a cleaning action on a surface (2) when the suction head (1) is in an operational cleaning position relative to the surface (2),

wherein the agitator (20) is configured to be rotatably arranged in the suction head (1) and includes a core element (21) and flexible cleaning elements (22) arranged on the core element (21),

wherein an outer portion of each of the cleaning elements (22) is configured to be moved over the surface (2) during a part of each revolution of the agitator (20) when the agitator (20) is arranged in the suction head (1) and the suction head (1) is in the operational cleaning position,

wherein the cleaning elements (22) are arranged along the length of the agitator (20) in a cleaning field (23),

wherein the cleaning field (23) is interrupted by at least one air passage (26) that is configured to enable an airflow between internal edges (23a, 23b) of the cleaning field (23) delimiting the at least one air passage (26), and

wherein outside of the at least one air passage (26), the cleaning elements (22) are arranged at close range relative to each other whereby an airflow between the cleaning elements (22) is disabled or at most enabled to a significantly smaller extent than at the position of the at least one air passage (26),

characterized in that the cleaning field (23) spans a major part of the core element (21) in a peripheral direction around the core element (21).

2. Agitator (20) according to claim 1, wherein either the at least one air passage (26) is free from the cleaning elements (22) or the at least one air passage (26) does include the cleaning elements (22) but at a significantly lower packing density than the cleaning field (23).

3. Agitator (20) according to claim 1 or 2, wherein the at least one air passage includes elements extending from the core element (21) along a shorter radial distance than the cleaning elements (22).

4. Agitator (20) according to any of claims 1-3, wherein the at least one air passage (26) extends in the peripheral direction around the core element (21).

5. Agitator (20) according to claim 4, wherein the at least one air passage (26) extends perpendicular to the longitudinal axis of the core element (21).

6. Agitator (20) according to claim 4 or 5, wherein the at least one air passage (26) spans the entire periphery of the core element (21).

7. Agitator (20) according to any of claims 1-6, wherein the cleaning field (23) spans the entire periphery of the core element (21).

8. Agitator (20) according to any of claims 1-7, wherein the cleaning elements (22) comprise fiber hairs, a linear mass density of the cleaning elements (22) being lower than 300 g per 10 km.

9. Agitator (20) according to any of claims 1-8, wherein the cleaning elements (22) are arranged on the core element (21) in tufts.

10. Agitator (20) according to claim 9, wherein a packing density of the cleaning elements (22) in the cleaning field (23) outside of the at least one air passage (26) is at least 15,000 cleaning elements (22) per area of 1 cm by 1 cm.

11. Agitator (20) according to any of claims 1-10, including at least one agitator element (24) in addition to the cleaning elements (22), wherein the at least one agitator element (24) is significantly less flexible than the cleaning elements (22), and wherein an outer portion of the at least one agitator element (24) is configured to be moved over the surface (2) during a part of each revolution of the agitator (20) when the agitator (20) is arranged in the suction head (1) and the suction head (1) is in the operational cleaning position.

12. Agitator (20) according to claim 11, wherein the at least one agitator element (24) is arranged on at least one strip-shaped body (25), and wherein the at least one strip-shaped body (25) is arranged to spiral around the core element (21) at a position of outer portions of the cleaning elements (22).

13. Suction head (1) configured to be applied in a vacuum cleaner and to perform a cleaning action on a surface (2) when the suction head (1) is in an operational cleaning position relative to the surface (2), the suction head (1) comprising:

a housing (10) including a coupling area (11) configured to enable coupling of the housing (10) to an air suction source of the vacuum cleaner, and

an agitator (20) according to any of claims 1-12,

wherein the agitator (20) is arranged in the housing (10) and the housing (10) is configured to expose a portion of the agitator (20) to the surface (2),

wherein the agitator (20) is rotatable in the housing (10) about a rotation axis (R) extending in the direction of a longitudinal axis of the core element (21),

wherein the agitator (20) is configured to enable an airflow passing the agitator (20) from a position (2a) on the surface (2) upstream of the agitator (20) in a direction towards the coupling area (11) of the housing (10) at the position of the at least one air passage (26) in the cleaning field (23) of the agitator (20) when the suction head (1) is in the operational cleaning position, and

wherein the agitator (20) is configured to disable or at most enable to a significantly smaller extent an airflow passing the agitator (20) from a position (2a) on the surface (2) upstream of the agitator (20) in a direction towards the coupling area (11) of the housing (10) at a position that is outside of the at least one air passage (26) when the suction head (1) is in the operational cleaning position.

14. Vacuum cleaner, comprising an air suction source and a suction head (1) according to claim 13.

15. Vacuum cleaner, comprising an air suction source and an agitator (20) according to any of claims 1-12.