CLAIMS:

1. An apparatus (100) with optical fiber attach capability, the apparatus (100) comprising:

a system on a chip (105);

a photonic integrated circuit (110) with a v-groove in a front side fiber coupling region;

an organic redistribution layer (140) ~~attached to~~communicating with the system on a chip and photonic integrated circuit;

a substrate (135) on which the system on a chip and the photonic integrated circuit are assembled; and

an optical fiber (120) attached to the front side fiber coupling region, wherein a mold compound (130) encapsulates the system on a chip (105), the photonic integrated circuit (110), and the attached optical fiber (120), and wherein the mold compound (130) and the substrate (135) include~~s~~ a cutout at the attachment of the optical fiber (120) to the photonic integrated circuit (110).

2. The apparatus of claim 1, wherein the apparatus (100) is a die-last wafer-level fanout package.

3. The apparatus of claim 1, wherein the attached optical fiber (120) is secured by a glob top (150).

4. The apparatus of claim 1, wherein the mold compound (130) comprises an epoxy material.

5. The apparatus of claim 3, wherein the glob top (150) comprises an epoxy material.

6. The apparatus of claim 1, wherein the organic redistribution layer (140) comprises a plurality of polymer layers.

7. The apparatus of claim 1, wherein the system on a chip (105) and the photonic integrated circuit (110) are attached to the organic redistribution layer (140) with microbumps (145) and.

~~8. The apparatus of claim 7,~~ wherein the microbumps (145) are secured by an underfill (155).

8~~9~~. The apparatus of claim 1, wherein a plurality of bumps (160) is attached to the organic redistribution layer (140).

9~~10~~. The apparatus of claim 8~~9~~, wherein the plurality of bumps (160) comprises a ball grid array.