# SIM340DZ
GSM/GPRS Module

The SIM340DZ is a complete Quad-band GSM/GPRS solution in a SMT module which can be embedded in the customer applications.

Featuring an industry-standard interface, the SIM340DZ delivers GSM/GPRS 850/900/1800/1900MHz performance for voice, SMS, Data, and Fax in a small form factor and with low power consumption. With a tiny configuration of 33mm x 33mm x 3 mm, SIM340DZ can fit almost all the space requirements in your M2M application, especially for slim and compact handset applications.

- Quad - band GSM/GPRS module with a size of 33mmx33mmx3mm
- SMT type suit for customer application
- An embedded Powerful TCP/IP protocol stack
- Based upon mature and field-proven platform, backed up by our support service, from definition to design and production

We make future wireless

General features

- Quad-Band 850/ 900/ 1800/ 1900 MHz
- GPRS multi-slot class 10/8
- GPRS mobile station class B
- Compliant to GSM phase 2/2+
  – Class 4 (2 W @850/ 900 MHz)
  – Class 1 (1 W @ 1800/1900MHz)
- Dimensions: 33* 33 * 3 mm
- Weight: 7.8 g
- Control via AT commands (GSM 07.07 ,07.05 and SIMCOM enhanced AT Commands)
- SIM application toolkit
- Supply voltage range 3.4 ... 4.5 V
- Low power consumption
- Normal operation temperature: -30 °C to +80°C

Specifications for fax

- Group 3, class 1

Specifications for data

- GPRS class 10: max. 85.6 kbps (downlink)
- PBCCH support
- Coding schemes CS 1, 2, 3, 4
- CSD up to 14.4 kbps
- USSD
- Non transparent mode
- PPP-stack

Specifications for SMS via GSM / GPRS

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Drivers

- MUX Driver

More about SIM340DZ module,
Please contact:
Tel:+86 21 32523300
Fax:+86 21 32523301

Specifications for voice

- Tricodec
  – Half rate (HR)
  – Full rate (FR)
  – Enhanced Full rate (EFR)
- Hands-free operation
  （Echo suppression）

Interfaces

- Interface to external SIM 3V/ 1.8V
- Two analog audio interfaces
- RTC backup
- SPI interface
- Serial interface and debug interface
- Antenna pad
- Charge interface
- GPIO

Compatibility

- AT cellular command interface

Approvals

- GCF
- CE
- RoHS
- FCC

Attachment（pin assignment）

Email:simcom@sim.com